

Ciient **Firststar**

TYPE Wireless charging transmitting coil: 8.1 UH

Model NO G43.5*5.3*0.6 double-slot with holes black film with adhesive on both sides and inclined grooves. The total length of the line is 39MM, plus NTC.

Enginrer NO MC133 model - 190 - 0391 - 0 - 00

Date June 23, 2025

For Enginer Departner Only	
Rrvised Cintent	APProved Date
	

Prepared

Checked

Approved

Wan Jimei

Wan Jimei

Liu Chengzhao

Authorixed Signaturure Company Chop		
Enginrer	QC APProved	APProved

一、 Winding Procease:

NO	Winding	guage	umber of windings	direction of winding	Note
1	N1	2UEW-B-0.08*24*2P	11TS	CCW	
2					

二. FEATURES:

1. Test conditions: 25°C,65%RH@100KHz/1V

1.1 Inductance

1.2 L0A=8.1uH±5%

1.3 Q value= 42 MIN

1.4 DCR: 92 mΩ ±5%

1.5 Operating Temperature: -25°C~85°C

2. Test instrument: **Tong hui TH2830**

3. bill of materials


item	materials
WIRE	φ 0.08*24*2P 2UEW-
FERRITE	43.5 * 5.3 * 0.6 L-shaped double-slot, perforated ferrite hard magnetic, positive black film, double-sided adhesive on both sides
GLUE	Water-based white glue
SOLDER	HQ-996/JS-996
Tin	Kanjiro Pure Tin
High temperatur e adhesive	Apply 5MM heat-resistant adhesive tape
	NTC 25@10K ±1% L=80mm 3950K red enamel wire Tin coating length 1-2mm Probe maximum 1.8mm WKT

三. CIRCUIT DIAGRAM



Unit: MM

四. OUTSIDE DIAGRA




Note: The spacing between the outlet positions is 5mm. Use hot glue tape. The width of the inclined slot outlet is 3-5mm. Add NTC.

	A	B	C	D	E	F	G
TD	43.5±0.5	39±1	20.5±0.5	5.3±0.5	39±2	3±1	1.5±0.2

Unit: MM

五. PACKAGE

5.1 Packing pictures:



5.2 Packing Quantity:

Item	Quantity	Material
Box	350 Pcs	345*330*50 mm
Big Carton	1750 Pcs	360*340*280 mm

5.3 The packaging shall be based on the exusting packing plate and the actual delivery package shall prevail .If there is any requirement,we can customize it.

Shenzhen Taichengda Fang Electronic Technology Co., Ltd.

No. 603B, Building 1, 1st, 2nd, 4th and 5th floors, Yuehua Industrial Zone, No. 2, Yuehua Road, Meilin Street, Futian District, Shenzhen City

六、Storage and Use condition

6.1 Storage condition

6.1.1 Recommended keeping conditions: $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$, 70%RH (Max.)

6.1.2 Storage life: Within the limits of six months from being produced.

6.2 Use condition: Use condition limit: $T = -25^{\circ}\text{C} \sim 85^{\circ}\text{C}$, $\text{RH} \leq 90\%$.