Test plot as follows:

DH5_Ant1_Hop



2DH5_Ant1_Hop



3DH5_Ant1_Hop


Spectrum
Ref Level 24.74 dBm Offset 14.74 dB RBW 100 kHz
Att 20 dB SWT 94.8 µs VBW 300 kHz Mode Auto FFT
Count 1000/1000
1Pk View
20 dBm
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
Start 2.4 GHz
691 pts
Stop 2.4835 GHz
Date: 22.MAY.2025 20:53:13

5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data

TestMode	Freq(MHz)	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Hop	0.380	330	0.125	≤0.4	PASS
DH3	Hop	1.628	150	0.244	≤0.4	PASS
DH5	Hop	2.869	60	0.172	≤0.4	PASS
2DH1	Hop	0.388	320	0.124	≤0.4	PASS
2DH3	Hop	1.633	180	0.294	≤0.4	PASS
2DH5	Hop	2.873	120	0.345	≤0.4	PASS
3DH1	Hop	0.388	320	0.124	≤0.4	PASS
3DH3	Hop	1.631	150	0.245	≤0.4	PASS
3DH5	Hop	2.875	100	0.288	≤0.4	PASS

Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

Test plot as follows:

DH1_Ant1_Hop



Date: 22.MAY.2025 20:40:46



Date: 22.MAY.2025 20:40:51

DH3_Ant1_Hop



Date: 22.MAY.2025 20:41:17



Date: 22.MAY.2025 20:41:22

DH5_Ant1_Hop



Date: 22.MAY.2025 20:39:22



Date: 22.MAY.2025 20:39:27

2DH1_Ant1_Hop



Date: 22.MAY.2025 20:50:19



Date: 22.MAY.2025 20:50:24

2DH3_Ant1_Hop



Date: 22.MAY.2025 20:50:46



Date: 22.MAY.2025 20:50:51

2DH5_Ant1_Hop



Date: 22.MAY.2025 20:49:50



Date: 22.MAY.2025 20:49:55

3DH1_Ant1_Hop



Date: 22.MAY.2025 20:58:24



Date: 22.MAY.2025 20:58:30

3DH3_Ant1_Hop



Date: 22.MAY.2025 20:59:46



Date: 22.MAY.2025 20:59:51

3DH5_Ant1_Hop



Date: 22.MAY.2025 20:53:28



Date: 22.MAY.2025 20:53:33

5.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 *Remark: Offset=cable loss+ attenuation factor.*
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

TestMode	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Low	2402	1.10	-41.43	≤-18.9	PASS
	High	2480	1.66	-50.93	≤-18.34	PASS
	Low	Hop_2402	0.60	-42.5	≤-19.4	PASS
	High	Hop_2480	0.81	-51.06	≤-19.19	PASS
2DH5	Low	2402	0.88	-41.43	≤-19.12	PASS
	High	2480	1.48	-51.17	≤-18.52	PASS
	Low	Hop_2402	0.56	-44.29	≤-19.44	PASS
	High	Hop_2480	0.65	-50.64	≤-19.35	PASS
3DH5	Low	2402	1.02	-41.87	≤-18.98	PASS
	High	2480	1.55	-51.03	≤-18.45	PASS
	Low	Hop_2402	0.82	-41.6	≤-19.18	PASS
	High	Hop_2480	0.47	-51.06	≤-19.53	PASS

Test plot as follows:

DH5_Ant1_Low_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.402174 GHz	1.10 dBm		
M2		1	2.4 GHz	-51.75 dBm		
M3		1	2.39 GHz	-55.45 dBm		
M4		1	2.3990217 GHz	-41.43 dBm		

Date: 22.MAY.2025 20:21:27

DH5_Ant1_High_2480



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48001 GHz	1.66 dBm		
M2		1	2.4835 GHz	-53.46 dBm		
M3		1	2.5 GHz	-55.14 dBm		
M4		1	2.503275 GHz	-50.93 dBm		

Date: 22.MAY.2025 20:24:03

DH5_Ant1_Low_Hop_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.404005 GHz	0.60 dBm		
M2		1	2.4 GHz	-45.10 dBm		
M3		1	2.39 GHz	-56.08 dBm		
M4		1	2.3991014 GHz	-42.50 dBm		

Date: 26.MAY.2025 11:36:47

DH5_Ant1_High_Hop_2480



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47689 GHz	0.81 dBm		
M2		1	2.4835 GHz	-54.41 dBm		
M3		1	2.5 GHz	-55.45 dBm		
M4		1	2.507913 GHz	-51.06 dBm		

Date: 26.MAY.2025 11:36:56

2DH5_Ant1_Low_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.402174 GHz	0.88 dBm		
M2		1	2.4 GHz	-51.95 dBm		
M3		1	2.39 GHz	-56.18 dBm		
M4		1	2.3991812 GHz	-41.43 dBm		

Date: 22.MAY.2025 20:25:10

2DH5_Ant1_High_2480