ACCREDITED
TESTING CERT# 3061.01

RF Exposure Evaluation Report

Product	:	Underwater Wireless Microphone Transmitter
Trade mark	:	DIVEVOLK
Model/Type reference	:	WMT
Serial Number	:	N/A
Report Number	:	EED32S80421002
FCC ID	:	2BOFD-WMT
Date of Issue	:	Jun. 02, 2026
Test Standards	:	47 CFR Part 1.1307 47 CFR Part 1.1310 47 CFR Part 2.1093 KDB 447498 D04 Interim General RF Exposure Guidance v01
Test result	:	PASS

Prepared for:

Divevolk (Zhuhai) Intelligence Tech Co., Ltd
17th Floor, Room 229, No. 91, Qinlang Road, Hengqin New District, Zhuhai City

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:	Win Wei	Reviewed by:	Keven Tan
Approved by:	Aaron Ma	Date:	Jun. 02, 2026

CENTRE TESTING INTERNATIONAL GROUP CO.,LTD. Report Seal

Check No.:5306040326

1 Contents

Page

1 CONTENTS 2

2 GENERAL INFORMATION 3

2.1 CLIENT INFORMATION 3
2.2 GENERAL DESCRIPTION OF EUT 3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 3
2.4 TEST LOCATION 4
2.5 DEVIATION FROM STANDARDS 4
2.6 ABNORMALITIES FROM STANDARD CONDITIONS 4
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER 4

3 SAR EVALUATION 5

3.1 RF EXPOSURE COMPLIANCE REQUIREMENT 5
3.1.1 Limits 5
3.1.2 Test Procedure 5
3.1.3 EUT RF Exposure Evaluation 6

2 General Information

2.1 Client Information

Applicant:	Divevolk (Zhuhai) Intelligence Tech Co., Ltd
Address of Applicant:	17th Floor, Room 229, No. 91, Qinlang Road, Hengqin New District, Zhuhai City
Manufacturer:	Divevolk (Zhuhai) Intelligence Tech Co., Ltd
Address of Manufacturer:	17th Floor, Room 229, No. 91, Qinlang Road, Hengqin New District, Zhuhai City
Factory:	Zhongshan Haichu Intelligence Technology Co., Ltd.
Address of Factory:	4th Floor, Area B, Building 3, Jinwan Industrial Park, Shengye Road, Xinxu Village, Sanxiang Town,Zhongshan City

2.2 General Description of EUT

Product Name:	Underwater Wireless Microphone Transmitter
Model No.(EUT):	WMT
Trade Mark:	DIVEVOLK

2.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz	
Modulation Type:	GFSK, π/4DQPSK	
Test Power Grade:	Default	
Test Software of EUT:	FCC_assist_1.0.2.2.exe	
Antenna Type:	PCB Antenna	
Antenna Gain:	-9.91dBi	
Power Supply:	Battery:	DC 3.7V
Sample Received Date:	Mar. 05, 2026	
Sample tested Date:	Mar. 05, 2026 to Mar. 12, 2026	

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China
Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385
No tests were sub-contracted.
FCC Designation No.: CN1164, Test Firm Registration No.: 260439

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).
This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{\text{th}}\,(\text{mW}) = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \le 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \le 40\text{ cm} \end{cases}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\text{ cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{\text{th}}\,(\text{mW}) = ERP_{20\text{ cm}}\,(\text{mW}) = \begin{cases} 2040f & 0.3\text{ GHz} \le f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \le f \le 6\text{ GHz} \end{cases} \qquad \text{(B.1)}$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation

For Stand alone:

Band	Freq. (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
BT	2402	0.5	0.17	-9.91	-11.89	0.06	2.788	0.0232	Pass

Note：

①EIRP=conducted power+antenna gain；

②ERP=EIRP-2.15;

③EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) – 95.23;

④ERP(mW) = 10^(ERP (dBm)/10);

⑤The estimation distance is 0.5cm;

⑥The test data please refer to the report of EED32S80421001 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;

2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;

3. The result(s) shown in this report refer(s) only to the sample(s) tested;

4. Unless otherwise stated,the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;

5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***