# FCC Part 15C Test Report
# FCC ID:2BOIGE-FINDER

| | |
|---|---|
| Applicant: | Shenzhen Xirui Network Technology Co., LTD |
| Address: | Room 401, Huili Building, No. 9 Zhongxin Road, Tao Yuan Community, Dalang Street, Longhua District, Shenzhen City, China |
| Manufacturer: | Shenzhen Xirui Network Technology Co., LTD |
| Address: | Room 401, Huili Building, No. 9 Zhongxin Road, Tao Yuan Community, Dalang Street, Longhua District, Shenzhen City, China |
| EUT: | eirix finder |
| Trade Mark: | N/A |
| Model Number: | E-Finder<br>(Refer to Section 3.1 for serial model.) |
| Date of Receipt: | Oct. 11, 2025 |
| Test Date: | Oct. 11, 2025 to Nov. 11, 2025 |
| Date of Report: | Nov. 11, 2025 |
| Prepared By: | Shenzhen DL Testing Technology Co., Ltd. |
| Address: | 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China. |
| Applicable Standards: | FCC CFR Title 47 Part 15 Subpart C Section 15.247<br>ANSI C63.10:2020 |
| Test Result: | Pass |
| Report Number: | DLE-251104006R |

| | | |
|---|---|---|
| Prepared (Test Engineer): | Dimon Tan | Dimon Tan |
| Reviewer (Supervisor): | Jack Bu | Jack Bu |
| Approved (Manager): | Jade Yang | Jade Yang |

*This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.*

**Table of Contents** **Page**


1.VERSION ..... 4
2. SUMMARY OF TEST RESULTS ..... 5
2.1 TEST FACILITY ..... 6
2.2 MEASUREMENT UNCERTAINTY ..... 6
3. GENERAL INFORMATION ..... 7
3.1 GENERAL DESCRIPTION OF EUT ..... 7
3.2 DESCRIPTION OF TEST MODES ..... 8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED ..... 9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) ..... 9
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS ..... 10
4. EMC EMISSION TEST ..... 11
4.1 CONDUCTED EMISSION MEASUREMENT ..... 11
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS ..... 11
4.1.2 TEST PROCEDURE ..... 11
4.1.3 DEVIATION FROM TEST STANDARD ..... 11
4.1.4 TEST SETUP ..... 12
4.1.5 EUT OPERATING CONDITIONS ..... 12
4.2.1 RADIATED EMISSION LIMITS ..... 13
4.2.2 TEST PROCEDURE ..... 14
4.2.3 DEVIATION FROM TEST STANDARD ..... 14
4.2.4 TEST SETUP ..... 14
4.2.5 EUT OPERATING CONDITIONS ..... 15
BETWEEN 30MHZ – 1GHZ ..... 16
1GHZ~25GHZ ..... 18
5.RADIATED BAND EMISSION MEASUREMENT ..... 20
5.1 TEST REQUIREMENT: ..... 20
5.2 TEST PROCEDURE ..... 20
5.3 DEVIATION FROM TEST STANDARD ..... 20
5.4 TEST SETUP ..... 21
5.5 EUT OPERATING CONDITIONS ..... 21
5.6 TEST RESULT ..... 22
6.POWER SPECTRAL DENSITY TEST ..... 23
6.1 APPLIED PROCEDURES / LIMIT ..... 23
6.2 TEST PROCEDURE ..... 23
6.3 DEVIATION FROM STANDARD ..... 23
6.4 TEST SETUP ..... 23
6.5 EUT OPERATION CONDITIONS ..... 23
6.6 TEST RESULT ..... 24
7. 6DB OCCUPIED BANDWIDTH ..... 26
7.1 APPLIED PROCEDURES / LIMIT ..... 26
7.2 TEST PROCEDURE ..... 26
7.3 DEVIATION FROM STANDARD ..... 26
7.4 TEST SETUP ..... 26
7.5 EUT OPERATION CONDITIONS ..... 26

**Table of Contents** **Page**

7.6 TEST RESULT ..... 27
8.PEAK OUTPUT POWER TEST ..... 29
8.1 APPLIED PROCEDURES / LIMIT ..... 29
8.2 TEST PROCEDURE ..... 29
8.3 DEVIATION FROM STANDARD ..... 29
8.4 TEST SETUP ..... 29
8.5 EUT OPERATION CONDITIONS ..... 29
8.6 TEST RESULT ..... 29
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION ..... 30
9.1 APPLICABLE STANDARD ..... 30
9.2 TEST PROCEDURE ..... 30
9.3 DEVIATION FROM STANDARD ..... 30
9.4 TEST SETUP ..... 30
9.5 EUT OPERATION CONDITIONS ..... 31
10.DUTY CYCLE ..... 33
10.1 APPLIED PROCEDURES / LIMIT ..... 33
10.2 DEVIATION FROM STANDARD ..... 33
10.3 TEST SETUP ..... 33
11.ANTENNA REQUIREMENT ..... 35
12. TEST SETUP PHOTO ..... 36
13. EUT CONSTRUCTIONAL DETAILS ..... 36

## 1.VERSION

| Report No. | Version | Description | Approved |
|---|---|---|---|
| DLE-251104006R | Rev.01 | Initial issue of report | Oct. 21, 2025 |
| | | | |

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C | | | |
|---|---|---|---|
| Standard Section | Test Item | Judgment | Remark |
| FCC part 15.203/15.247 (b)(4) | Antenna requirement | PASS | |
| ANSI C63.10:2020 | Duty cycle | PASS | |
| FCC part 15.207 | AC Power Line Conducted Emission | N/A[1] | |
| FCC part 15.247 (b)(3) | Conducted Peak Output Power | PASS | |
| FCC part 15.247 (a)(2) | 6DB Occupied Bandwidth | PASS | |
| FCC part 15.247 (e) | Power Spectral Density | PASS | |
| FCC part 15.247(d) | Band Edge | PASS | |
| FCC part 15.205/15.209 | Spurious Emission | PASS | |

NOTE:

(1)“N/A” denotes test is not applicable in this Test Report

## 2.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.
Add. : 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China.

FCC Test Firm Registration Number: 854456
Designation Number: CN1307
IC Registered No.: 27485
CAB ID.: CN0118

## 2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|---|---|---|
| 1 | 3m camber Radiated spurious emission(9KHz-30MHz) | U=4.5dB |
| 2 | 3m camber Radiated spurious emission(30MHz-1GHz) | U=4.8dB |
| 3 | 3m chamber Radiated spurious emission(1GHz-6GHz) | U=4.9dB |
| 4 | 3m chamber Radiated spurious emission(6GHz-40GHz) | U=5.0dB |
| 5 | Conducted disturbance | U=3.2dB |
| 6 | RF Band Edge | U=1.68dB |
| 7 | RF power conducted | U=1.86dB |
| 8 | RF conducted Spurious Emission | U=2.2dB |
| 9 | RF Occupied Bandwidth | U=1.8MHz |
| 10 | RF Power Spectral Density | U=1.75dB |
| 11 | humidity uncertainty | U=5.3% |
| 12 | Temperature uncertainty | U=0.59℃ |

## 3. GENERAL INFORMATION

### 3.1 GENERAL DESCRIPTION OF EUT

| | |
|---|---|
| Product Name: | eirix finder |
| Model No.: | E-Finder |
| Serial No.: | E-Finder01, E-Finder02, E-Finder03, E-Finder04, E-Finder05, E-Finder06, E-Finder07, E-Finder08, E-Finder09, E-Finder10, E-Finder11, E-Finder12, E-Finder13, E-Finder14, E-Finder15, E-Finder16, E-Finder17, E-Finder18, E-Finder19, E-Finder20, E-Finder21, E-Finder22, E-Finder23, E-Finder24, E-Finder25, E-Finder26, E-Finder27, E-Finder28, E-Finder29, E-Finder30, E-Tracker, E-Tracker01, E-Tracker02, E-Tracker03, E-Tracker04, E-Tracker05, FC01, FC02, FC03, FC04, FC05, FC06, FC07, FC08, FC09, FC10, FA01, FA02, FA03, FA04, FA05, FA06, FA07, FA08, FA09, FA10, FD01, FD02, FD03, FD04, FD05, FD06, FD07, FD08, FD09, FD10, A1, A2, A3, A4, A5, A6, A7, A8, A9, C1, C2, C3, C4, C5, C6, C7, C8, C9, M1, M2, M3, M4, M5, M6, M7, M8, M9, S1, S2, S3, S4, S5, S6, S7, S8, S9, X0, X1, X2, X3, X4, X5, X6, X7, X8, X9, H1, H2, H3, H4, H5, H6, H7, H8, H9, S1, S2, S3, S4, S5, S6, S7, S8, S9, W1, W2, W3, W4, W5, W6, W7, W8, W9 |
| Model Different: | Only the model name is different. |
| Hardware Version: | N/A |
| Software Version: | N/A |
| Sample(s) Status: | Engineer sample |
| Operation Frequency: | 2402MHz~2480MHz |
| Channel Numbers: | 40 |
| Channel Separation: | 2MHz |
| Modulation Type: | GFSK |
| Antenna Type: | Chip antenna |
| Antenna gain: | 2.48dBi |
| Power supply: | Input: 3.7V⎓ |

| Operation Frequency each of channel | | | | | | | |
|---|---|---|---|---|---|---|---|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1 | 2402 MHz | 11 | 2422 MHz | 21 | 2442 MHz | 31 | 2462 MHz |
| 2 | 2404 MHz | 12 | 2424 MHz | 22 | 2444 MHz | 32 | 2464 MHz |
| 3 | 2406 MHz | 13 | 2426 MHz | 23 | 2446 MHz | 33 | 2466 MHz |
| 4 | 2408 MHz | 14 | 2428 MHz | 24 | 2448 MHz | 34 | 2468 MHz |
| 5 | 2410 MHz | 15 | 2430 MHz | 25 | 2450 MHz | 35 | 2470 MHz |
| 6 | 2412 MHz | 16 | 2432 MHz | 26 | 2452 MHz | 36 | 2472 MHz |
| 7 | 2414 MHz | 17 | 2434 MHz | 27 | 2454 MHz | 37 | 2474 MHz |
| 8 | 2416 MHz | 18 | 2436 MHz | 28 | 2456 MHz | 38 | 2476 MHz |
| 9 | 2418 MHz | 19 | 2438 MHz | 29 | 2458 MHz | 39 | 2478 MHz |
| 10 | 2420 MHz | 20 | 2440 MHz | 30 | 2460 MHz | 40 | 2480 MHz |

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|---|---|
| The lowest channel | 2402MHz |
| The middle channel | 2440MHz |
| The Highest channel | 2480MHz |

3.2 DESCRIPTION OF TEST MODES

| | |
|---|---|
| Transmitting mode | Keep the EUT in continuously transmitting mode |
| Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. | |

| | |
|---|---|
| Test Software | CMD |
| Power level setup | Default |

## 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Emission

Conducted Spurious

## 3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|---|---|---|---|---|---|
| E-1 | eirix finder | N/A | E-Finder | N/A | EUT |
| | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|---|---|---|---|---|
| | | | | |
| | | | | |

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

## 3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

| Item | Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|---|---|---|---|---|---|---|
| 1 | Spectrum Analyzer (9kHz-26.5GHz) | Agilent | E4408B | MY50140780 | Oct. 25, 2025 | Oct. 24, 2026 |
| 2 | Test Receiver (9kHz-7GHz) | R&S | ESRP7 | 101393 | Oct. 25, 2025 | Oct. 24, 2026 |
| 3 | Bilog Antenna (30MHz-1GHz) | R&S | VULB9162 | 00306 | Oct. 25, 2025 | Oct. 24, 2026 |
| 4 | Horn Antenna (1GHz-18GHz) | Schwarzbeck | BBHA9120D | 02139 | Oct. 25, 2025 | Oct. 24, 2026 |
| 5 | Horn Antenna (18GHz-40GHz) | A.H. Systems | SAS-574 | 588 | Oct. 25, 2025 | Oct. 24, 2026 |
| 6 | Amplifier (9KHz-6GHz) | Schwarzbeck | BBV9743B | 00153 | Oct. 25, 2025 | Oct. 24, 2026 |
| 7 | Amplifier (1GHz-18GHz) | EMEC | EM01G8GA | 00270 | Oct. 25, 2025 | Oct. 24, 2026 |
| 8 | Amplifier (18GHz-40GHz) | Quanjuda | DLE-161 | 97 | Oct. 25, 2025 | Oct. 24, 2026 |
| 9 | Loop Antenna (9KHz-30MHz) | Schwarzbeck | FMZB1519B | 00014 | Oct. 25, 2025 | Oct. 24, 2026 |
| 10 | RF cables1 (9kHz-1GHz) | ChengYu | 966 | 004 | Oct. 25, 2025 | Oct. 24, 2026 |
| 11 | RF cables2 (1GHz-40GHz) | ChengYu | 966 | 003 | Oct. 25, 2025 | Oct. 24, 2026 |
| 12 | Antenna connector | Florida RF Labs | N/A | RF 01# | Oct. 25, 2025 | Oct. 24, 2026 |
| 13 | Power probe | KEYSIGHT | U2021XA | MY55210018 | Oct. 25, 2025 | Oct. 24, 2026 |
| 14 | Signal Analyzer 9kHz-26.5GHz | Agilent | N9020A | MY55370280 | Oct. 25, 2025 | Oct. 24, 2026 |
| 15 | Test Receiver 20kHz-40GHz | R&S | ESU 40 | 100376 | Nov. 01, 2024 | Oct. 31, 2025 |
| 16 | D.C. Power Supply | LongWei | PS-305D | 010964729 | Nov. 01, 2024 | Oct. 31, 2025 |
| 17 | Power meter | KEYSIGHT | N1912AP | 926431 | Nov. 01, 2024 | Oct. 31, 2025 |

Conduction Test equipment

| Item | Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|---|---|---|---|---|---|---|
| 1 | 843 Shielded Room | ChengYu | 843 Room | 843 | Nov. 05, 2023 | Nov. 04, 2026 |
| 2 | EMI Receiver | R&S | ESR | 101421 | Oct. 25, 2025 | Oct. 24, 2026 |
| 3 | LISN | R&S | ENV216 | 102417 | Oct. 25, 2025 | Oct. 24, 2026 |
| 4 | 843 Cable 1# | ChengYu | CE Cable | 001 | Oct. 25, 2025 | Oct. 24, 2026 |

Other

| Item | Name | Manufacturer | Model | Software version |
|---|---|---|---|---|
| 1 | EMC Conduction Test System | FALA | EZ_EMC | EMC-CON 3A1.1 |
| 2 | EMC radiation test system | FALA | EZ_EMC | FA-03A2 |
| 3 | RF test system | MAIWEI | MTS8310 | 2.0.0.0 |
| 4 | RF communication test system | MAIWEI | MTS8200 | 2.0.0.0 |

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.207 |
| Test Method: | ANSI C63.10:2020 |
| Test Frequency Range: | 150KHz to 30MHz |
| Receiver setup: | RBW=9KHz, VBW=30KHz, Sweep time=auto |

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits

| FREQUENCY (MHz) | Limit (dBuV) | | Standard |
|---|---|---|---|
| | Quas -peak | Average | |
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 56.00 | 46.00 | FCC |
| 5.0 -30.0 | 60.00 | 50.00 | FCC |

Note:

(1) *Decreases with the logarithm of the frequency.

#### 4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

TEST RESULT

The EUT is powered by the battery only, the test item is not applicable.

## 4.2 RADIATED EMISSION MEASUREMENT

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.209 |
| Test Method: | ANSI C63.10:2020 |
| Test Frequency Range: | 9kHz to 25GHz |
| Test site: | Measurement Distance: 3m |
| Receiver setup: | |

| Frequency | Detector | RBW | VBW | Value |
|---|---|---|---|---|
| 9KHz-150KHz | Quasi-peak | 200Hz | 600Hz | Quasi-peak |
| 150KHz-30MHz | Quasi-peak | 9KHz | 30KHz | Quasi-peak |
| 30MHz-1GHz | Quasi-peak | 100KHz | 300KHz | Quasi-peak |
| Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | Peak | 1MHz | 10Hz | Average |

4.2.1 RADIATED EMISSION LIMITS

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|---|---|---|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

LIMITS OF RADIATED EMISSION MEASUREMENT

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) | |
|---|---|---|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
Note:
Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz




（C）Radiated Emission Test-Up Frequency Above 1GHz




4.2.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

| | | | |
|---|---|---|---|
| Temperature: | 26℃ | Relative Humidity: | 54% |
| Pressure: | 101 kPa | Polarization: | Horizontal |
| Test Voltage: | DC 3V | Test Mode : | TX - 2402MHz |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|---|---|---|---|---|---|---|---|
| 1 | 41.7129 | 28.06 | -13.29 | 14.77 | 40.00 | -25.23 | QP |
| 2 | 54.4515 | 29.08 | -14.04 | 15.04 | 40.00 | -24.96 | QP |
| 3 | 128.1130 | 30.06 | -14.59 | 15.47 | 43.50 | -28.03 | QP |
| 4 | 162.6106 | 28.73 | -13.45 | 15.28 | 43.50 | -28.22 | QP |
| 5 | 570.6100 | 29.93 | -10.03 | 19.90 | 46.00 | -26.10 | QP |
| 6 * | 742.2587 | 32.25 | -7.18 | 25.07 | 46.00 | -20.93 | QP |

| | | | |
|---|---|---|---|
| Temperature: | 26℃ | Relative Humidity: | 54% |
| Pressure: | 101kPa | Polarization: | Vertical |
| Test Voltage: | DC 3V | Test Mode : | TX - 2402MHz |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|---|---|---|---|---|---|---|---|
| 1 | 45.0583 | 29.05 | -13.56 | 15.49 | 40.00 | -24.51 | QP |
| 2 | 85.2980 | 36.80 | -17.92 | 18.88 | 40.00 | -21.12 | QP |
| 3 | 128.1130 | 32.83 | -14.59 | 18.24 | 43.50 | -25.26 | QP |
| 4 | 150.5377 | 28.32 | -13.17 | 15.15 | 43.50 | -28.35 | QP |
| 5 | 580.7026 | 29.40 | -9.81 | 19.59 | 46.00 | -26.41 | QP |
| 6 * | 742.2587 | 33.95 | -7.18 | 26.77 | 46.00 | -19.23 | QP |

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case TX - 2402MHz.

1GHz~25GHz

| Polar (H/V) | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|---|---|---|
| Low Channel:2402MHz | | | | | | | | | |
| V | 4804.00 | 51.29 | 30.55 | 5.77 | 24.66 | 51.17 | 74.00 | -22.83 | PK |
| V | 4804.00 | 43.36 | 30.55 | 5.77 | 24.66 | 43.24 | 54.00 | -10.76 | AV |
| V | 7206.00 | 51.69 | 30.33 | 6.32 | 24.55 | 52.23 | 74.00 | -21.77 | PK |
| V | 7206.00 | 43.25 | 30.33 | 6.32 | 24.55 | 43.79 | 54.00 | -10.21 | AV |
| V | 9608.00 | 51.20 | 30.85 | 7.45 | 24.69 | 52.49 | 74.00 | -21.51 | PK |
| V | 9608.00 | 43.79 | 30.85 | 7.45 | 24.69 | 45.08 | 54.00 | -8.92 | AV |
| V | 12010.00 | 53.37 | 31.02 | 8.99 | 25.57 | 56.91 | 74.00 | -17.09 | PK |
| V | 12010.00 | 43.90 | 31.02 | 8.99 | 25.57 | 47.44 | 54.00 | -6.56 | AV |
| H | 4804.00 | 53.15 | 30.55 | 5.77 | 24.66 | 53.03 | 74.00 | -20.97 | PK |
| H | 4804.00 | 43.76 | 30.55 | 5.77 | 24.66 | 43.64 | 54.00 | -10.36 | AV |
| H | 7206.00 | 54.21 | 30.33 | 6.32 | 24.55 | 54.75 | 74.00 | -19.25 | PK |
| H | 7206.00 | 43.36 | 30.33 | 6.32 | 24.55 | 43.90 | 54.00 | -10.10 | AV |
| H | 9608.00 | 53.70 | 30.85 | 7.45 | 24.69 | 54.99 | 74.00 | -19.01 | PK |
| H | 9608.00 | 43.48 | 30.85 | 7.45 | 24.69 | 44.77 | 54.00 | -9.23 | AV |
| H | 12010.00 | 51.97 | 31.02 | 8.99 | 25.57 | 55.51 | 74.00 | -18.49 | PK |
| H | 12010.00 | 43.10 | 31.02 | 8.99 | 25.57 | 46.64 | 54.00 | -7.36 | AV |

| Polar (H/V) | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|---|---|---|
| Middle Channel:2440MHz | | | | | | | | | |
| V | 4880.00 | 54.31 | 30.55 | 5.77 | 24.66 | 54.19 | 74.00 | -19.81 | PK |
| V | 4880.00 | 43.74 | 30.55 | 5.77 | 24.66 | 43.62 | 54.00 | -10.38 | AV |
| V | 7320.00 | 51.75 | 30.33 | 6.32 | 24.55 | 52.29 | 74.00 | -21.71 | PK |
| V | 7320.00 | 43.11 | 30.33 | 6.32 | 24.55 | 43.65 | 54.00 | -10.35 | AV |
| V | 9760.00 | 50.28 | 30.85 | 7.45 | 24.69 | 51.57 | 74.00 | -22.43 | PK |
| V | 9760.00 | 43.94 | 30.85 | 7.45 | 24.69 | 45.23 | 54.00 | -8.77 | AV |
| V | 12200.00 | 51.07 | 31.02 | 8.99 | 25.57 | 54.61 | 74.00 | -19.39 | PK |
| V | 12200.00 | 43.51 | 31.02 | 8.99 | 25.57 | 47.05 | 54.00 | -6.95 | AV |
| H | 4880.00 | 53.16 | 30.55 | 5.77 | 24.66 | 53.04 | 74.00 | -20.96 | PK |
| H | 4880.00 | 43.76 | 30.55 | 5.77 | 24.66 | 43.64 | 54.00 | -10.36 | AV |
| H | 7320.00 | 50.22 | 30.33 | 6.32 | 24.55 | 50.76 | 74.00 | -23.24 | PK |
| H | 7320.00 | 43.57 | 30.33 | 6.32 | 24.55 | 44.11 | 54.00 | -9.89 | AV |
| H | 9760.00 | 51.18 | 30.85 | 7.45 | 24.69 | 52.47 | 74.00 | -21.53 | PK |
| H | 9760.00 | 43.33 | 30.85 | 7.45 | 24.69 | 44.62 | 54.00 | -9.38 | AV |
| H | 12200.00 | 52.73 | 31.02 | 8.99 | 25.57 | 56.27 | 74.00 | -17.73 | PK |
| H | 12200.00 | 43.47 | 31.02 | 8.99 | 25.57 | 47.01 | 54.00 | -6.99 | AV |

| Polar (H/V) | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|---|---|---|
| High Channel:2480MHz | | | | | | | | | |
| V | 4960.00 | 54.30 | 30.55 | 5.77 | 24.66 | 54.18 | 74.00 | -19.82 | PK |
| V | 4960.00 | 43.60 | 30.55 | 5.77 | 24.66 | 43.48 | 54.00 | -10.52 | AV |
| V | 7440.00 | 52.38 | 30.33 | 6.32 | 24.55 | 52.92 | 74.00 | -21.08 | PK |
| V | 7440.00 | 43.78 | 30.33 | 6.32 | 24.55 | 44.32 | 54.00 | -9.68 | AV |
| V | 9920.00 | 54.11 | 30.85 | 7.45 | 24.69 | 55.40 | 74.00 | -18.60 | PK |
| V | 9920.00 | 43.59 | 30.85 | 7.45 | 24.69 | 44.88 | 54.00 | -9.12 | AV |
| V | 12400.00 | 51.30 | 31.02 | 8.99 | 25.57 | 54.84 | 74.00 | -19.16 | PK |
| V | 12400.00 | 43.01 | 31.02 | 8.99 | 25.57 | 46.55 | 54.00 | -7.45 | AV |
| H | 4960.00 | 51.86 | 30.55 | 5.77 | 24.66 | 51.74 | 74.00 | -22.26 | PK |
| H | 4960.00 | 43.83 | 30.55 | 5.77 | 24.66 | 43.71 | 54.00 | -10.29 | AV |
| H | 7440.00 | 52.52 | 30.33 | 6.32 | 24.55 | 53.06 | 74.00 | -20.94 | PK |
| H | 7440.00 | 43.07 | 30.33 | 6.32 | 24.55 | 43.61 | 54.00 | -10.39 | AV |
| H | 9920.00 | 53.86 | 30.85 | 7.45 | 24.69 | 55.15 | 74.00 | -18.85 | PK |
| H | 9920.00 | 43.81 | 30.85 | 7.45 | 24.69 | 45.10 | 54.00 | -8.90 | AV |
| H | 12400.00 | 53.21 | 31.02 | 8.99 | 25.57 | 56.75 | 74.00 | -17.25 | PK |
| H | 12400.00 | 43.87 | 31.02 | 8.99 | 25.57 | 47.41 | 54.00 | -6.59 | AV |

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

## 5.RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.209 and 15.205 |
| Test Method: | ANSI C63.10:2020 |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2390MHz to 2500MHz) data was showed. |
| Test site: | Measurement Distance: 3m |
| Receiver setup: | |

| Frequency | Detector | RBW | VBW | Value |
|---|---|---|---|---|
| Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | Average | 1MHz | 3MHz | Average |

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) | |
|---|---|---|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz




5.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

5.6 TEST RESULT

| | Polar (H/V) | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB/m) | Emission level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector Type | Result |
|---|---|---|---|---|---|---|---|---|---|---|---|
| GFSK | Low Channel: 2402MHz | | | | | | | | | | |
| | H | 2390.00 | 53.98 | 30.22 | 4.85 | 23.98 | 52.59 | 74.00 | -21.41 | PK | PASS |
| | H | 2390.00 | 44.91 | 30.22 | 4.85 | 23.98 | 43.52 | 54.00 | -10.48 | AV | PASS |
| | H | 2400.00 | 53.58 | 30.22 | 4.85 | 23.98 | 52.19 | 74.00 | -21.81 | PK | PASS |
| | H | 2400.00 | 44.45 | 30.22 | 4.85 | 23.98 | 43.06 | 54.00 | -10.94 | AV | PASS |
| | V | 2390.00 | 54.36 | 30.22 | 4.85 | 23.98 | 52.97 | 74.00 | -21.03 | PK | PASS |
| | V | 2390.00 | 44.57 | 30.22 | 4.85 | 23.98 | 43.18 | 54.00 | -10.82 | AV | PASS |
| | V | 2400.00 | 53.35 | 30.22 | 4.85 | 23.98 | 51.96 | 74.00 | -22.04 | PK | PASS |
| | V | 2400.00 | 44.81 | 30.22 | 4.85 | 23.98 | 43.42 | 54.00 | -10.58 | AV | PASS |
| | High Channel: 2480MHz | | | | | | | | | | |
| | H | 2483.50 | 54.55 | 30.22 | 4.85 | 23.98 | 53.16 | 74.00 | -20.84 | PK | PASS |
| | H | 2483.50 | 44.04 | 30.22 | 4.85 | 23.98 | 42.65 | 54.00 | -11.35 | AV | PASS |
| | H | 2500.00 | 54.27 | 30.22 | 4.85 | 23.98 | 52.88 | 74.00 | -21.12 | PK | PASS |
| | H | 2500.00 | 44.56 | 30.22 | 4.85 | 23.98 | 43.17 | 54.00 | -10.83 | AV | PASS |
| | V | 2483.50 | 53.53 | 30.22 | 4.85 | 23.98 | 52.14 | 74.00 | -21.86 | PK | PASS |
| | V | 2483.50 | 44.94 | 30.22 | 4.85 | 23.98 | 43.55 | 54.00 | -10.45 | AV | PASS |
| | V | 2500.00 | 54.87 | 30.22 | 4.85 | 23.98 | 53.48 | 74.00 | -20.52 | PK | PASS |
| | V | 2500.00 | 44.67 | 30.22 | 4.85 | 23.98 | 43.28 | 54.00 | -10.72 | AV | PASS |

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

## 6.POWER SPECTRAL DENSITY TEST

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (e) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v05r02 |

### 6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---|---|---|---|---|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247 | Power Spectral Density | 8dBm/3kHz | 2400-2483.5 | PASS |

### 6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 6.3 DEVIATION FROM STANDARD

No deviation.

### 6.4 TEST SETUP




### 6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 6.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

| | | | |
|---|---|---|---|
| Temperature : | 26℃ | Relative Humidity : | 54% |
| Test Mode : | GFSK | Test Voltage : | DC 3V |

| Frequency | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
|---|---|---|---|
| 2402 MHz | -16.56 | 8 | PASS |
| 2440 MHz | -17.44 | 8 | PASS |
| 2480 MHz | -16.68 | 8 | PASS |

CH01



CH20


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.440000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
05:26:41 PM Nov 11, 2025
Ref Offset 2.89 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.439 978 1 GHz
-17.443 dBm
Center 2.4400000 GHz
#Res BW 3.0 kHz
#VBW 10 kHz
Span 994.2 kHz
Sweep 104.9 ms (1001 pts)

CH40


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
05:27:54 PM Nov 11, 2025
Ref Offset 2.93 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.479 977 7 GHz
-16.682 dBm
Center 2.4800000 GHz
#Res BW 3.0 kHz
#VBW 10 kHz
Span 969.9 kHz
Sweep 102.3 ms (1001 pts)

## 7. 6DB OCCUPIED BANDWIDTH

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v05r02 |

### 7.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---|---|---|---|---|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(a)(2) | Bandwidth | >= 500KHz (6dB Occupied Bandwidth) | 2400-2483.5 | PASS |

### 7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP




### 7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 7.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

| | | | |
|---|---|---|---|
| Temperature : | 26℃ | Relative Humidity : | 54% |
| Test Mode : | GFSK | Test Voltage : | DC 3.7V |

| Test channel | 6dB Occupied Bandwidth (MHz) | Limit(KHz) | Result |
|---|---|---|---|
| Lowest | 0.6705 | >500 | Pass |
| Middle | 0.6628 | | |
| Highest | 0.6466 | | |

CH 01



CH20


Keysight Spectrum Analyzer - Occupied BW
Center Freq 2.440000000 GHz
Center Freq: 2.440000000 GHz
Trig: Free Run
#Atten: 30 dB
Avg|Hold: 100/100
Radio Std: None
Radio Device: BTS
05:26:26 PM Nov 11, 2025
#IFGain:Low
Ref Offset 2.89 dB
10 dB/div
Ref 22.89 dBm
Mkr3 2.4403377 GHz
-9.0800 dBm
Center 2.44 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 2 MHz
Sweep 1.333 ms
Occupied Bandwidth
1.0305 MHz
Total Power 2.96 dBm
Transmit Freq Error 6.327 kHz
% of OBW Power 99.00 %
x dB Bandwidth 662.8 kHz
x dB -6.00 dB
MSG
STATUS

CH40


Keysight Spectrum Analyzer - Occupied BW
Center Freq 2.480000000 GHz
Center Freq: 2.480000000 GHz
Trig: Free Run
#Atten: 30 dB
Avg|Hold: 100/100
Radio Std: None
Radio Device: BTS
05:27:39 PM Nov 11, 2025
#IFGain:Low
Ref Offset 2.93 dB
10 dB/div
Ref 22.93 dBm
Mkr3 2.4803285 GHz
-8.5671 dBm
Center 2.48 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 2 MHz
Sweep 1.333 ms
Occupied Bandwidth
1.0374 MHz
Total Power 3.64 dBm
Transmit Freq Error 5.217 kHz
% of OBW Power 99.00 %
x dB Bandwidth 646.6 kHz
x dB -6.00 dB
MSG
STATUS

## 8.PEAK OUTPUT POWER TEST

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v05r02 |

8.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---|---|---|---|---|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(b)(3) | Peak Output Power | 1 watt or 30dBm | 2400-2483.5 | PASS |

8.2 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP




8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 8.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

| | | | |
|---|---|---|---|
| Temperature： | 26℃ | Relative Humidity： | 54% |
| Test Mode ： | GFSK | Test Voltage ： | DC 3.7V |

| Test channel | Peak Output Power (dBm) | Limit(dBm) | Result |
|---|---|---|---|
| Lowest | -1.30 | 30.00 | Pass |
| Middle | -2.17 | | |
| Highest | -1.33 | | |

## 9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (d) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v05r02 |

### 9.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 9.2 TEST PROCEDURE

A. Reference level measurement, establish a reference level by using the following procedure:
a) Set instrument center frequency to FHSS channel center frequency.
b) Set the span to ≥ 1.5 times the 20dB bandwidth.
c) Set the RBW = 100 kHz.
d) Set the VBW ≥ [3 × RBW].
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum PSD level.
Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

B.Emission level measurement, establish an emission level by using the following procedure:
a) Set the center frequency and span to encompass frequency range to be measured.
b) Set the RBW = 100 kHz.
c) Set the VBW ≥ [3 × RBW].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.
Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

### 9.3 DEVIATION FROM STANDARD

No deviation.

### 9.4 TEST SETUP



## 9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 9.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 9.6 TEST RESULTS

Band Edge, Left Side







Band Edge, Right Side






Conducted spurious emissions:

Lowest channel







Middle channel







Highest channel






## 10.DUTY CYCLE

| Test Method: | ANSI C63.10:2020 |
|---|---|

### 10.1 APPLIED PROCEDURES / LIMIT

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.

b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

1) Set the center frequency of the instrument to the center frequency of the transmission.

2) Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

3) Set VBW ≥ RBW. Set detector = peak or average.

4) The zero-span measurement method shall not be used unless both RBW and VBW are > 50/*T* and the number of sweep points across duration *T* exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7$ µs.)

### 10.2 DEVIATION FROM STANDARD

No deviation.

### 10.3 TEST SETUP



## 10.4 TEST RESULTS

| Frequency (MHz) | Duty Cycle (%) | Result |
|---|---|---|
| 2402 | 67.12 | Pass |




Note: All channel have been tested, and the report only reflects the worst case data.

Duty Cycle = Ton /Total*100%

Duty Cycle Correction Factor = 10log (1/Duty Cycle)

## 11.ANTENNA REQUIREMENT

| Standard requirement: | FCC Part15 C Section 15.203 /247(b)(4) |
|---|---|
| 15.203 requirement:<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.<br>15.247(b)(4) requirement:<br>(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi. | |
| EUT Antenna: | |
| The antenna is Chip Antenna, the best case gain of the antennas is 2.48 dBi, reference to the appendix II for details | |

## 12. TEST SETUP PHOTO

Reference to the appendix I for details.

## 13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

**※※※※※ END OF REPORT ※※※※※**