

FCC TEST REPORT

FCC ID: 2B00H-VK-ST

Report No. : SSP25030090-1E

Applicant : Shenzhen Fanying Zhilian Technology Co., LTD

Product Name : Signal Transmitter

Model Name : VK-ST

Test Standard : FCC Part 15.247

Date of Issue : 2025-04-09



Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Shenzhen Fanying Zhilian Technology Co., LTD 13rd Floor Building 9, Shenzhen Bay Science and Technology Ecological Park, Nanshan District, Shenzhen China
Manufacturer:	Shenzhen Fanying Zhilian Technology Co., LTD 13rd Floor Building 9, Shenzhen Bay Science and Technology Ecological Park, Nanshan District, Shenzhen China
Product Name:	Signal Transmitter
Brand Name:	Vakiav
Main Model:	VK-ST
Series Models:	-
Test Standard:	FCC Part 15 Subpart C KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.4-2014 ANSI C63.10-2013
Date of Test	2025-03-13 to 2025-04-09
Test Result:	PASS
Tested By	<u>Colin Chen</u> (Colin Chen)
Reviewed By:	<u>Lieber Ouyang</u> (Lieber Ouyang)
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.	



CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	9
2. Summary of Test Results	10
3. Antenna Requirement.....	11
3.1 Standard and Limit.....	11
3.2 Test Result.....	11
4. Conducted Emissions	12
4.1 Standard and Limit.....	12
4.2 Test Procedure.....	12
4.3 Test Data and Results	13
5. Radiated Emissions	16
5.1 Standard and Limit.....	16
5.2 Test Procedure.....	16
5.3 Test Data and Results	18
6. Maximum Peak Conducted Output Power	22
6.1 Standard and Limit.....	22
6.2 Test Procedure.....	22
6.3 Test Data and Results	22
7. Occupied Bandwidth	26
7.1 Standard and Limit.....	26
7.2 Test Procedure.....	26
7.3 Test Data and Results	26
8. Maximum Power Spectral Density	32
8.1 Standard and Limit.....	32
8.2 Test Procedure.....	32
8.3 Test Data and Results	32
9. Band-edge Emission(Conducted).....	36
9.1 Standard and Limit.....	36
9.2 Test Procedure.....	36
9.3 Test Data and Results	36
10. Conducted RF Spurious Emissions.....	40
10.1 Standard and Limit.....	40
10.2 Test Procedure.....	40
10.3 Test Data and Results	40

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-04-09	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Signal Transmitter
Trade Name:	Vakiav
Main Model:	VK-ST
Series Models:	-
Rated Voltage:	DC 5V by adapter
Power Adapter:	-
Battery:	-
Test Sample No:	SSP25030090-1
Hardware Version:	LARK_BRIDGE_V2-20241210
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	

Wireless Specification	
Wireless Standard:	802.11ah
Operating Frequency:	905~926MHz
RF Output Power:	12.29dBm (Conducted)
Number of Channel:	11/6/3
Channel Separation:	3MHz
Modulation:	OFDM
Antenna Gain:	0.26dBi
Type of Antenna:	PCB Antenna
Type of Device:	☐ Portable Device ☒ Mobile Device ☐ Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	802.11ah (2M Channel Bandwidth)	905MHz/915MHz/925MHz	
TM2	802.11ah (4M Channel Bandwidth)	906MHz/914MHz/926MHz	
TM3	802.11ah (8M Channel Bandwidth)	908MHz/916MHz/924MHz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
USB Cable	100	Unshielded	Without Ferrite
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Adapter	Huawei	HW-100225C00	HC78E2N6A23645

List of Channels (2M Channel Bandwidth)							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	905	04	911	07	917	10	923
02	907	05	913	08	919	11	925
03	909	06	915	09	921	--	--
List of Channels (4M Channel Bandwidth)							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	906	03	914	05	922	--	--
02	910	04	918	06	926	--	--
List of Channels (8M Channel Bandwidth)							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	908	02	916	03	924	--	--

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No.:	583813
FCC Designation No.:	CN1373
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Test Cable	N/A	Cable 5	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Attenuator	QUANJUDA	6dB	220731	2024-08-07	2025-08-06
Test Cable	N/A	Cable 1	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 2	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 3	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 4	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 8	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 9	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06
RF Test Software	MWRFTTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThinkPad E15 Gen 3	SPPOZ22485	N/A	N/A

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB
Power Spectrum Density	9kHz ~ 26GHz	±0.62 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(b)(3)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.247(a)(2)	Occupied Bandwidth	Passed
FCC Part 15.247(e)	Maximum Power Spectral Density	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an PCB antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.


4.3 Test Data and Results

All of the 802.11ah modes have been tested, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case 802.11ah(2M)_905MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions


Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.1725	46.04	9.23	55.27	64.84	-9.57	QP	P	
2	0.1725	26.06	9.23	35.29	54.84	-19.55	AVG	P	
3	0.3975	35.35	9.38	44.73	57.91	-13.18	QP	P	
4	0.3975	17.19	9.38	26.57	47.91	-21.34	AVG	P	
5	0.9195	28.14	9.38	37.52	56.00	-18.48	QP	P	
6	0.9195	13.21	9.38	22.59	46.00	-23.41	AVG	P	
7	2.7825	17.87	9.49	27.36	56.00	-28.64	QP	P	
8	2.7825	3.19	9.49	12.68	46.00	-33.32	AVG	P	
9	8.2725	16.98	9.56	26.54	60.00	-33.46	QP	P	
10	8.2725	1.20	9.56	10.76	50.00	-39.24	AVG	P	
11	20.3595	24.64	10.00	34.64	60.00	-25.36	QP	P	
12	20.3595	6.32	10.00	16.32	50.00	-33.68	AVG	P	

Test Plots and Data of Conducted Emissions

Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Power Line:	Live
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2040	43.76	9.40	53.16	63.45	-10.29	QP	P	
2	0.2040	24.67	9.40	34.07	53.45	-19.38	AVG	P	
3	0.4020	35.73	9.57	45.30	57.81	-12.51	QP	P	
4	0.4020	18.12	9.57	27.69	47.81	-20.12	AVG	P	
5 *	0.9060	37.20	9.56	46.76	56.00	-9.24	QP	P	
6	0.9060	20.92	9.56	30.48	46.00	-15.52	AVG	P	
7	2.1255	23.23	9.66	32.89	56.00	-23.11	QP	P	
8	2.1255	6.62	9.66	16.28	46.00	-29.72	AVG	P	
9	7.4265	21.53	9.77	31.30	60.00	-28.70	QP	P	
10	7.4265	4.99	9.77	14.76	50.00	-35.24	AVG	P	
11	14.8875	33.40	9.72	43.12	60.00	-16.88	QP	P	
12	14.8875	12.89	9.72	22.61	50.00	-27.39	AVG	P	

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of Emission (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3
Note: The more stringent limit applies at transition frequencies.		

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.


5.3 Test Data and Results

All of the 802.11ah modes have been tested, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case 802.11ah(2M)_905MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)


Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Antenna Polarization:	Horizontal
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	53.3179	38.77	-8.93	29.84	40.00	-10.16	QP	100	360	P	
2	155.3644	38.61	-7.80	30.81	43.50	-12.69	QP	199	102	P	
3	333.6867	39.04	-7.19	31.85	46.00	-14.15	QP	199	348	P	
4	550.9480	40.61	-2.73	37.88	46.00	-8.12	QP	199	276	P	
5 !	839.8746	39.45	1.54	40.99	46.00	-5.01	QP	100	52	P	
6 *	905.0000	101.37	2.66	104.03	-	-	peak	100	321	P	

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Antenna Polarization:	Vertical
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	50.0566	38.08	-8.41	29.67	40.00	-10.33	QP	100	91	P	
2	65.8031	37.71	-10.96	26.75	40.00	-13.25	QP	100	348	P	
3	145.3506	38.64	-7.96	30.68	43.50	-12.82	QP	100	50	P	
4	454.3100	39.02	-4.40	34.62	46.00	-11.38	QP	100	101	P	
5	760.7036	38.36	1.01	39.37	46.00	-6.63	QP	100	143	P	
6 *	905.0000	90.67	2.66	93.33	-	-	peak	100	65	P	

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (802.11ah_2M_905MHz)							
1810	77.75	-23.76	53.99	74	-20.01	H	PK
1810	62.98	-23.76	39.22	54	-14.78	H	AV
2715	65.44	-19.39	46.05	74	-27.95	H	PK
2715	49.1	-19.39	29.71	54	-24.29	H	AV
1810	77.17	-23.76	53.41	74	-20.59	V	PK
1810	60.12	-23.76	36.36	54	-17.64	V	AV
2715	62.69	-19.39	43.3	74	-30.7	V	PK
2715	49.44	-19.39	30.05	54	-23.95	V	AV
Middle Channel (802.11ah_2M_915MHz)							
1830	77.03	-23.64	53.39	74	-20.61	H	PK
1830	59.08	-23.64	35.44	54	-18.56	H	AV
2745	62.76	-19.29	43.47	74	-30.53	H	PK
2745	50.16	-19.29	30.87	54	-23.13	H	AV
1830	73.05	-23.64	49.41	74	-24.59	V	PK
1830	59.08	-23.64	35.44	54	-18.56	V	AV
2745	64.35	-19.29	45.06	74	-28.94	V	PK
2745	45.35	-19.29	26.06	54	-27.94	V	AV
Highest Channel (802.11ah_2M_925MHz)							
1850	74.95	-23.53	51.42	74	-22.58	H	PK
1850	59.68	-23.53	36.15	54	-17.85	H	AV
2775	65.27	-19.14	46.13	74	-27.87	H	PK
2775	45.63	-19.14	26.49	54	-27.51	H	AV
1850	74.04	-23.53	50.51	74	-23.49	V	PK
1850	57.61	-23.53	34.08	54	-19.92	V	AV
2775	63.6	-19.14	44.46	74	-29.54	V	PK
2775	48.69	-19.14	29.55	54	-24.45	V	AV

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported. The EUT was tested at 3 orthogonal positions, and three modes 802.11ah_2M, 4M and 8M, only worst-case 802.11ah_2M, X-axis data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

6. Maximum Peak Conducted Output Power

6.1 Standard and Limit

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

6.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 8MHz, VBW = 8MHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat the above procedures until all frequencies measured were complete.




Test Setup Block Diagram

6.3 Test Data and Results

Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
802.11ah_2M	905	10.48	30	Pass
	915	10.77	30	Pass
	925	10.61	30	Pass
802.11ah_4M	906	12.29	30	Pass
	914	11.71	30	Pass
	926	12.06	30	Pass
802.11ah_8M	908	11.85	30	Pass
	916	11.61	30	Pass
	924	11.84	30	Pass


802.11ah_2M

905MHz




802.11ah_4M


906MHz




915MHz




914MHz



925MHz




926MHz




802.11ah_8M


908MHz



916MHz



924MHz



7. Occupied Bandwidth


7.1 Standard and Limit

According to 15.247(a)(2), Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

7.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) 6dB: Set RBW = 100kHz, VBW $\geq [3 \times \text{RBW}]$, Sweep = Auto.
99%: Set RBW = 1%~5% of 99% bandwidth, VBW $\geq [3 \times \text{RBW}]$, Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 6dB from the reference level.
Record the frequency difference as the emission bandwidth.
- 6) Repeat the above procedures until all frequencies measured were complete.




Test Setup Block Diagram

7.3 Test Data and Results


Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	6dB BW Limit (MHz)	Test Result
802.11ah_2M	905	1.773	1.772	0.5	Pass
	915	1.757	1.767	0.5	Pass
	925	1.766	1.773	0.5	Pass
802.11ah_4M	906	3.677	3.625	0.5	Pass
	914	3.628	3.632	0.5	Pass
	926	3.663	3.637	0.5	Pass
802.11ah_8M	908	7.631	7.558	0.5	Pass
	916	7.545	7.545	0.5	Pass
	924	7.565	7.543	0.5	Pass

6dB Bandwidth:



802.11ah_8M


908MHz




916MHz



924MHz




99% Bandwidth:




802.11ah_8M


908MHz



916MHz



924MHz




8. Maximum Power Spectral Density

8.1 Standard and Limit

According to FCC 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

8.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 3kHz, VBW = 10kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat above procedures until all frequencies measured were complete.




Test Setup Block Diagram

8.3 Test Data and Results

Test Mode	Test Channel MHz	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Test Result
802.11ah_2M	905	-15.6	8	Pass
	915	-15.48	8	Pass
	925	-14.71	8	Pass
802.11ah_4M	906	-18.21	8	Pass
	914	-18.04	8	Pass
	926	-17.93	8	Pass
802.11ah_8M	908	-20.73	8	Pass
	916	-20.34	8	Pass
	924	-20.46	8	Pass


802.11ah_2M

905MHz




802.11ah_4M


906MHz




915MHz




914MHz



925MHz




926MHz




802.11ah_8M


908MHz



916MHz



924MHz



9. Band-edge Emission(Conducted)

9.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

9.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.10.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Set a convenient frequency span including 100 kHz bandwidth from band edge.
- 6) Measure the emission and marking the edge frequency.
- 7) Repeat above procedures until all frequencies measured were complete.




Test Setup Block Diagram

9.3 Test Data and Results


Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
802.11ah_2M	Lowest	905	-36.8	-20	Pass
	Highest	925	-38.3	-20	Pass
802.11ah_4M	Lowest	906	-37.44	-20	Pass
	Highest	926	-38.04	-20	Pass
802.11ah_8M	Lowest	908	-36.27	-20	Pass
	Highest	924	-39.1	-20	Pass

802.11ah_2M Lowest

Reference Power




Band-edge Emission




802.11ah_2M Highest

Reference Power




Band-edge Emission




802.11ah_4M Lowest

Reference Power




Band-edge Emission




802.11ah_4M Highest

Reference Power




Band-edge Emission




802.11ah_8M Lowest

Reference Power




Band-edge Emission




802.11ah_8M Highest

Reference Power



Band-edge Emission



10. Conducted RF Spurious Emissions

10.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

10.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.7.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Measure the spurious emissions with frequency range from 9kHz to 26.5GHz.
- 6) Repeat above procedures until all measured frequencies were complete.



Test Setup Block Diagram

10.3 Test Data and Results


Note: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions measurement data.

802.11ah_2M Lowest

Reference Power




Spurious Emissions




802.11ah_2M Middle

Reference Power




Spurious Emissions




802.11ah_2M Highest

Reference Power




Spurious Emissions




802.11ah_4M Lowest

Reference Power




Spurious Emissions




802.11ah_4M Middle

Reference Power




Spurious Emissions




802.11ah_4M Highest

Reference Power




Spurious Emissions




802.11ah_8M Lowest

Reference Power




Spurious Emissions




802.11ah_8M Middle

Reference Power




Spurious Emissions




802.11ah_8M Highest

Reference Power



Spurious Emissions



***** END OF REPORT *****