



FCC ID:2BOR5-990-1001

Product Name:	Holder
Product Model No.:	990-1001
Model Difference:	/
Transmitting mode:	Keep the EUT in continuously wireless charging mode
Operation Frequency:	111-145KHz, 360KHz
Power supply:	Input: 9 V  2.22 A, 5 V  3 A Output: 5W/ 7.5W/ 15W

Test Modes:	
Mode 1	AC Adapter+Wireless charging load(5W): 360KHz
Mode 2	AC Adapter+Wireless charging load(7.5W): 360KHz
Mode 3	AC Adapter+Wireless charging load(15W): 360KHz
Mode 4	AC Adapter+Wireless charging load(5W): 111-145KHz
Mode 5	AC Adapter+Wireless charging load(7.5W): 111-145KHz
Mode 6	AC Adapter+Wireless charging load(15W): 111-145KHz
Mode 7	Standby mode
Remark: All full load, half load, and no-load tests have been conducted in each mode, only the worst-case was recorded in the report. Mode 1 full load is the worst mode.	

Auxiliary equipment					
Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Mobile phone	Apple Inc.	iPhone 15 Pro	/	AE
E-2	AC Adapter	Xiaomi	MDY-12-ED	/	AE

1 Measuring Standard

KDB 680106 D01 Wireless Power Transfer v04

2 Requirements

According to the item 5 of KDB 680106 D01 v04:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

Requirements of section 3 of KDB 680106 D01	Yes/ No	Description
Mobile Device and Portable Device Configurations	Yes	Mobile Device
Equipment Authorization Procedures for Devices Operating at Frequencies Below 4 MHz	Yes	The device operate in the frequency range 111-145KHz, 360KHz
RF Exposure compliance may be ensured only for a minimum conditions at smaller distances can still be considered unlikely.separation distance that is greater than 20 cm, while use	Yes	The EUT H-field and E-field strengths at 20 cm surrounding the device.

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)


Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 P=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

3 Test Setup

For mobile exposure conditions:



4 Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (20 cm from all sides and 20 cm from the top) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v04.

Remark: The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

5 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	H-field	$\pm 0.7\text{dB}$
2	E-field	$\pm 1.06\text{dB}$

Decision Rule

- ☒ Uncertainty is not included
- ☐ Uncertainty is included



6 Test Instruments list

Test Equipment	Manufacturer	Model No.	SN.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
Exposure Level Tester	Narda	ELT-400	180ZX10220	Sep. 29, 2024	Sep. 28, 2025
Magnetic field probe 100cm2	Narda	ELT probe 100cm2	M0675	Sep. 29, 2024	Sep. 28, 2025

7 Test Result

We have evaluated mode 1 to mode 7 and the worst mode 1 is showed in this report.

Frequ ency Rang e (MHz)	Test Posi tion A (uT)	Test Posi tion A (A/m)	Test Posi tion B (uT)	Test Posi tion B (A/m)	Test Posi tion C (uT)	Test Posi tion C (A/m)	Test Posi tion D (uT)	Test Posi tion D (A/m)	Test Posi tion E (uT)	Test Posi tion E (A/m)	Test Posi tion E (uT)	Test Posi tion E (A/m)	50% Limits (A/m)	Limits (A/m)	Test result
0.360	0.46	0.37	0.35	0.28	0.66	0.53	0.45	0.36	0.28	0.22	0.39	0.31	0.815	1.63	PASS

Note: Calculation: A/m=uT/1.25

7. Test Set-up Photo

