Certificate #7130.01

FCC Radio Test Report

FCC ID: 2BOS5AP9720

This report concerns: Original Grant

Project No.	:	2502C254
Equipment	:	Wireless LAN Access Point
Brand Name	:	Aicheng
Test Model	:	AP9720
Series Model	:	N/A
Applicant	:	Zhejiang Aicheng Technology Development Co., Ltd.
Address	:	Room 427,4th Floor,Building 3,No.969 Wenyixi West Rd,Wuchang Street,Yuhang Disct Hangzhou City, Zhejiang Province, China.
Manufacturer	:	Zhejiang Aicheng Technology Development Co., Ltd.
Address	:	Room 427, 4th Floor, Building 3, No. 969 Wenyixi West Road, Wuchang Street, Yuhang District, Hangzhou City, Zhejiang Province, China.
Factory	:	Joy Technology (ShenZhen) Corporation
Address	:	HengKeng Ind., Shangpai, Shangwu,Aiqun Rd., Shiyan Town,Shenzhen 518108 China
Date of Receipt	:	Apr. 02, 2025
Date of Test	:	Apr. 07, 2025 ~ Jun. 23, 2025
Issued Date	:	Jul. 09, 2025
Report Version	:	R00
Test Sample	:	Engineering Sample No.: DG20250402120 for conducted, DG20250402121 for radiated.
Standard(s)	:	FCC CFR Title 47, Part 15, Subpart C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. (Dongguan)

Prepared by : Evan Yang

Evan Yang

Approved by : Chay . Cai

Chay Cai

No.3, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.
Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. BTL assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by BTL.

The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the ISO/IEC 17025: 2017 requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.
Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents Page

REVISION HISTORY 6

1 . APPLICABLE STANDARDS 7

2 . SUMMARY OF TEST RESULTS 7

2.1 TEST FACILITY 8

2.2 MEASUREMENT UNCERTAINTY 8

2.3 TEST ENVIRONMENT CONDITIONS 9

3 . GENERAL INFORMATION 10

3.1 GENERAL DESCRIPTION OF EUT 10

3.2 DESCRIPTION OF TEST MODES 12

3.3 PARAMETERS OF TEST SOFTWARE 12

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 13

3.5 SUPPORT UNITS 14

3.6 CUSTOMER INFORMATION DESCRIPTION 15

4 . AC POWER LINE CONDUCTED EMISSIONS 16

4.1 LIMIT 16

4.2 TEST PROCEDURE 16

4.3 DEVIATION FROM TEST STANDARD 16

4.4 TEST SETUP 17

4.5 EUT OPERATING CONDITIONS 17

4.6 TEST RESULTS 17

5 . RADIATED EMISSIONS 18

5.1 LIMIT 18

5.2 TEST PROCEDURE 19

5.3 DEVIATION FROM TEST STANDARD 20

5.4 TEST SETUP 20

5.5 EUT OPERATING CONDITIONS 22

5.6 TEST RESULT - 9 KHZ TO 30 MHZ 22

5.7 TEST RESULT - 30 MHZ TO 1000 MHZ 22

5.8 TEST RESULT - ABOVE 1000 MHZ 22

6 . BANDWIDTH 23

6.1 LIMIT 23

6.2 TEST PROCEDURE 23

Table of Contents Page

6.3 DEVIATION FROM STANDARD 23
6.4 TEST SETUP 23
6.5 EUT OPERATION CONDITIONS 23
6.6 TEST RESULTS 23
7 . MAXIMUM OUTPUT POWER 24
7.1 LIMIT 24
7.2 TEST PROCEDURE 24
7.3 DEVIATION FROM STANDARD 24
7.4 TEST SETUP 24
7.5 EUT OPERATION CONDITIONS 24
7.6 TEST RESULTS 24
8 . CONDUCTED SPURIOUS EMISSION 25
8.1 LIMIT 25
8.2 TEST PROCEDURE 25
8.3 DEVIATION FROM STANDARD 26
8.4 TEST SETUP 26
8.5 EUT OPERATION CONDITIONS 26
8.6 TEST RESULTS 26
9 . POWER SPECTRAL DENSITY 27
9.1 LIMIT 27
9.2 TEST PROCEDURE 27
9.3 DEVIATION FROM STANDARD 27
9.4 TEST SETUP 27
9.5 EUT OPERATION CONDITIONS 27
9.6 TEST RESULTS 27
10 . MEASUREMENT INSTRUMENTS LIST 28
11 . EUT TEST PHOTO 30
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS 36
APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ 39
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ 44
APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ 47
APPENDIX E - BANDWIDTH 55

Table of Contents Page

APPENDIX F - MAXIMUM OUTPUT POWER	**57**
APPENDIX G - CONDUCTED SPURIOUS EMISSION	**59**
APPENDIX H - POWER SPECTRAL DENSITY	**61**

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-1-2502C254	R00	Original Report.	Jul. 09, 2025	Valid

1. APPLICABLE STANDARDS

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:
ANSI C63.10-2013
The following reference test guidance is not within the scope of accreditation of A2LA:
KDB 558074 D01 15.247 Meas Guidance v05r02

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	**Test Item**	**Test Result**	**Judgment**	**Remark**
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	------
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	------
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	------
15.247(b)(3)	Maximum Output Power	APPENDIX F	PASS	------
15.247(d)	Conducted Spurious Emission	APPENDIX G	PASS	------
15.247(e)	Power Spectral Density	APPENDIX H	PASS	------
15.203	Antenna Requirement	------	PASS	**Note(2)**

Note:
(1) “N/A” denotes test is not applicable to this device.
(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

2.1 TEST FACILITY

For radiated emissions 1GHz-18GHz:
The test facilities used to collect the test data in this report is at the location of Room 102 & 702, Building A3, No.9, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.

For others:
The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.
BTL's Registration Number for FCC: 747969
BTL's Designation Number for FCC: CN1377

2.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95.45% confidence level (based on a coverage factor (k=2))
The BTL measurement uncertainty as below table:

A. AC power line conducted emissions Measurement:

Test Site	Method	Measurement Frequency Range	*U*,(dB)
DG-C02	CISPR	150kHz ~ 30MHz	2.88

B. Radiated emissions Measurement:

Test Site	Method	Measurement Frequency Range	*U*,(dB)
DG-CB03	CISPR	9kHz ~ 30MHz	2.36

Test Site	Method	Measurement Frequency Range	Ant. H / V	*U*,(dB)
DG-CB03 (3m)	CISPR	30MHz ~ 200MHz	V	4.40
		30MHz ~ 200MHz	H	3.62
		200MHz ~ 1,000MHz	V	4.58
		200MHz ~ 1,000MHz	H	3.98

Test Site	Method	Measurement Frequency Range	*U*,(dB)
DG-CB18 (3m)	CISPR	1GHz ~ 6GHz	4.48
		6GHz ~ 18GHz	3.88

Test Site	Method	Measurement Frequency Range	*U*,(dB)
DG-CB03 (1m)	CISPR	18 ~ 26.5 GHz	3.36

C. Other Measurement:

Test Item	Uncertainty
Bandwidth	0.90 %
Maximum Output Power	1.3 dB
Conducted Spurious Emission	1.9 dB
Power Spectral Density	1.4 dB
Temperature	0.8 °C
Humidity	2.2 %

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

2.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By	Test Date
AC Power Line Conducted Emissions	23°C	55%	AC 120V/60Hz	Hayden Chen	May 23, 2025
Radiated Emissions -9 kHz to 30 MHz	25°C	63%	AC 120V/60Hz	Hayden Chen	Apr. 29, 2025
Radiated Emissions -30 MHz to 1000 MHz	23°C	52%	AC 120V/60Hz	Calvin Wen	May 14, 2025
Radiated Emissions -Above 1GHz-18GHz	25°C	45%	AC 120V/60Hz	Allen Tong	Jun. 05, 2025
Radiated Emissions -Above 18GHz	21°C	51%	AC 120V/60Hz	Calvin Wen	Apr. 27, 2025
Bandwidth	23°C	52%	PoE 48V	Newnar Wang	Jun. 03, 2025
Maximum Output Power	23°C	52%	PoE 48V	Newnar Wang	Jun. 03, 2025
Conducted Spurious Emission	23°C	52%	PoE 48V	Newnar Wang	Jun. 03, 2025
Power Spectral Density	23°C	52%	PoE 48V	Newnar Wang	Jun. 03, 2025

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless LAN Access Point
Brand Name	Aicheng
Test Model	AP9720
Series Model	N/A
Model Difference(s)	N/A
Hardware Version	R02
Software Version	2.0.88-R-20250320.1606
Power Source	DC Voltage supplied from DC adapter (support unit) or supplied from PoE port.
Power Rating	PoE 48V ⎓ 0.5A or DC 12V ⎓ 2A
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Type	GFSK
Bit Rate of Transmitter	1Mbps
Max. Output Power	1Mbps: 5.82 dBm (0.0038 W)

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

3. Table for Filed Antenna:

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	Angeei	MD246001-01	PIFA	IPEX	4.5

3.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39
Mode 2	TX Mode_1Mbps Channel 00

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 2	TX Mode_1Mbps Channel 00

Radiated emissions test - Below 1GHz & Above 18 GHz	
Final Test Mode	Description
Mode 2	TX Mode_1Mbps Channel 00

Radiated emissions test - 1 GHz - 18 GHz	
Final Test Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39

Conducted test	
Final Test Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39

Note:

(1) For radiated emission above 1 GHz test, the spurious points of 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.
(2) For AC power line conducted emissions and radiated emissions below 1 GHz test, the 1Mbps Channel 00 is found to be the worst case and recorded.
(3) For radiated emission Harmonic 18-26.5GHz test, only tested the worst case and recorded.
(4) For radiated emission above 1 GHz test, the polarization of Vertical and Horizontal are evaluated, the worst case is Vertical and recorded.

3.3 PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	IPOP_V4.0		
Frequency (MHz)	2402	2440	2480
1Mbps	7	7	7

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

For AC power line conducted emissions test



For Radiated emissions test - Below 1GHz & Above 18 GHz



For Radiated emissions test 1 GHz - 18 GHz



3.5 SUPPORT UNITS

For AC power line conducted emissions test

Item	Equipment	Brand	Model No.	Series No.
A	POE	tp-link	POE4824G	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
2	RJ45 Cable	NO	NO	1.5m
3	AC Cable	NO	NO	1.5m

For Radiated emissions test - Below 1GHz & Above 18 GHz

Item	Equipment	Brand	Model No.	Series No.
A	Notebook	Honor	14SER5 3500	N/A
B	POE	tp-link	POE4824G	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	RJ45 Cable	NO	NO	10m
2	RJ45 Cable	NO	NO	1m
3	AC Cable	NO	NO	1.5m

For Radiated emissions test 1 GHz - 18 GHz

Item	Equipment	Brand	Model No.	Series No.
A	Notebook	Honor	14SER5 3500	N/A
B	POE	tp-link	POE4824G	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	RJ45 Cable	NO	NO	1.5m
2	RJ45 Cable	NO	NO	1m
3	AC Cable	NO	NO	1.5m

3.6 CUSTOMER INFORMATION DESCRIPTION

1) The antenna gain is provided by the manufacturer.
2) Except for AC power line conducted emissions and radiated emissions, the results of all test items include cable losses. All cable losses are provided by the testing laboratory.

4. AC POWER LINE CONDUCTED EMISSIONS

4.1 LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

Note:

(1) The tighter limit applies at the band edges.
(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
(3) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor
Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor (if use)
Margin Level = Measurement Value - Limit Value

4.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.3 DEVIATION FROM TEST STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.6 TEST RESULTS

Please refer to the APPENDIX A.

Remark:

(1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform.In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.

(2) Measuring frequency range from 150 kHz to 30 MHz.

5. RADIATED EMISSIONS

5.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	Band edge/ Harmonic at 3m (dBµV/m)		Harmonic at 1m (dBµV/m)	
	Peak	Average	Peak	Average
Above 1000	74	54	83.5 (Note 5)	63.5 (Note 5)

Note:

(1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

(4) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor
Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
Margin Level = Measurement Value - Limit Value

(5)

$$FS_{\text{limit}} = FS_{\max} - 20\log\left(\frac{d_{\text{limit}}}{d_{\text{measure}}}\right)$$

20log ($d_{limit}/d_{measure}$)=20log (3/1)=9.5 dB.
FS_{limit}: Harmonic at 3m Peak and Average limit.
FS_{max}: Harmonic at 1m Peak and Average Maximum value.
d_{limit}: Harmonic at 3m test distance.
$d_{measure}$: Harmonic Actual test distance.

5.2 TEST PROCEDURE

a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
b. The measuring distance of 3 m or 1m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~26.5 GHz for PK/AVG detector

5.3 DEVIATION FROM TEST STANDARD

No deviation.

5.4 TEST SETUP

9 kHz to 30 MHz



30 MHz to 1 GHz



Above 1 GHz
Band edge & Harmonic(1 GHz to 18 GHz)



Harmonic(18 GHz to 26.5 GHz)



5.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULT - 9 kHz TO 30 MHz

Please refer to the APPENDIX B.

Remark:

(1) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
(2) Limit line = specific limits (dBuV) + distance extrapolation factor.

5.7 TEST RESULT - 30 MHz TO 1000 MHz

Please refer to the APPENDIX C.

5.8 TEST RESULT - ABOVE 1000 MHz

Please refer to the APPENDIX D.

Remark:

(1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

6. BANDWIDTH

6.1 LIMIT

Section	Test Item	Limit
FCC 15.247(a)(2)	6 dB Bandwidth	>= 500 kHz
	99% Emission Bandwidth	-

6.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

Spectrum Parameters	Setting
Span	> Measurement Bandwidth
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For 99% Emission Bandwidth:

Spectrum Parameters	Setting
Span	Between 1.5 times and 5.0 times the OBW
RBW	30 kHz
VBW	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

Please refer to the APPENDIX E.

7. MAXIMUM OUTPUT POWER

7.1 LIMIT

Section	Test Item	Limit
FCC 15.247(b)(3)	Maximum Output Power	1.0000 watt or 30.00 dBm

7.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span	≥ 3×RBW
RBW	3 MHz
VBW	3 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX F.

8. CONDUCTED SPURIOUS EMISSION

8.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

8.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. The following table is the setting of the spectrum analyzer:

For Reference Level:

Spectrum Parameters	Setting
Span	≥ 1.5 times the bandwidth.
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For Emission Level - Band edge:

Spectrum Parameters	Setting
Start Frequency	2300 MHz
Stop Frequency	2690 MHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For Emission Level - Harmonic:

Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS

Please refer to the APPENDIX G.

9. POWER SPECTRAL DENSITY

9.1 LIMIT

Section	Test Item	Limit
FCC 15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

9.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span	1.5 times the DTS bandwidth
RBW	3 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

9.6 TEST RESULTS

Please refer to the APPENDIX H.

10. MEASUREMENT INSTRUMENTS LIST

AC Power Line Conducted Emissions					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI TEST RECEIVER	R&S	ESCI	100382	Dec. 06, 2025
2	TWO-LINE V-NETWORK	R&S	ENV216	101447	Dec. 06, 2025
3	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
4	Cable	N/A	SFT205-NMNM-9M -001	9M	Nov. 11, 2025
5	643 Shield Room	ETS	6*4*3	N/A	N/A

Radiated Emissions - 9 kHz to 30 MHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Active Loop Antenna	Schwarzbeck	FMZB 1513-60	00025	Mar. 01, 2026
2	Receiver	Agilent	N9038A	MY52130039	Jan. 10, 2026
3	Cable	RegalWay	LMR400-NMNM-6 m	N/A	Apr. 26, 2026
4	Cable	RegalWay	LMR400-NMRANM -3.5m	N/A	Apr. 26, 2026
5	966 Chamber room	CM	9*6*6	N/A	May 16, 2025

Radiated Emissions - 30 MHz to 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	01462	Dec. 14, 2025
2	Attenuator	EMC INSTRUMENT	EMCI-N-6-06	AT-06009	Dec. 14, 2025
3	Preamplifier	EMC INSTRUMENT	EMC001330	980998	May 31, 2025
4	Cable	RegalWay	LMR400-NMNM-12 .5m	N/A	Jun. 06, 2025
5	Cable	RegalWay	LMR400-NMNM-3 m	N/A	Jun. 06, 2025
6	Cable	RegalWay	LMR400-NMNM-0. 5m	N/A	Jun. 06, 2025
7	Receiver	Agilent	N9038A	MY52130039	Jan. 10, 2026
8	Positioning Controller	MF	MF-7802	N/A	N/A
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
10	966 Chamber room	CM	9*6*6	N/A	May 09, 2026

Radiated Emissions - 1 GHz - 18 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Multi-Device Controller	ETS-Lindgren	N/A	N/A	N/A
2	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
3	MXA Signal Analyzer	KEYSIGHT	N9020B	MY63430227	Oct. 29, 2025
4	Cable	RegalWay	RWLP50-4.0A-SMSM-1.3M	N/A	Apr. 06, 2026
5	Cable	RegalWay	RWLP50-2.6A-3.5M2.92MRA-3M	N/A	Apr. 06, 2026
6	Cable	RegalWay	RWLP50-4.0A-SMSM-9M	N/A	Apr. 06, 2026
7	966 Chamber room	ETS	RFD-100(SVSWR)	Q2179	Jan. 07, 2026
8	Double Ridged Horn Antenna	EMC INSTRUMENT	DRH18-E	210509A18ES	Aug. 28, 2025
9	Preamplifier	EMC INSTRUMENT	EMC118A45SE	981001	May 28, 2026
10	Filter	STI	STI15-9912	N/A	Oct. 29, 2025
11	Attenuator	Talent Microwave	TA10A2-S-18	N/A	N/A

Radiated Emissions - Above 18 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Preamplifier	EMC INSTRUMENT	EMC184045SE	980905	Oct. 29, 2025
2	Cable	RegalWay	RWLP50-2.6A-2.92M2.92M-1.1M	N/A	Jul. 25, 2025
3	Cable	Tonscend	HF160-KMKM-3M	N/A	Jul. 25, 2025
4	Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	1227	Oct. 20, 2025
5	966 Chamber room	CM	9*6*6	N/A	May 10, 2026
6	Positioning Controller	MF	MF-7802	N/A	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	EXA Spectrum Analyzer	Keysight	N9010A	MY55150209	Aug. 20, 2025
9	Preamplifier	EMC INSTRUMENT	EMC184045SE	980905	Oct. 29, 2025
10	Cable	RegalWay	RWLP50-2.6A-2.92M2.92M-1.1M	N/A	Jul. 25, 2025
11	Cable	Tonscend	HF160-KMKM-3M	N/A	Jul. 25, 2025

Bandwidth & Maximum Output Power & Power Spectral Density & Conducted Spurious Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	FSV Signal & Spectrum Analyzer	R&S	FSV3044	101682	Oct. 17, 2025
2	CTA	BTL	CTA	N/A	N/A
3	Isolation attenuator	Z-Link	ASMA-16-18-2W	N/A	N/A

Remark: “N/A” denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

11. EUT TEST PHOTO

AC Power Line Conducted Emissions Test Photos

Radiated Emissions Test Photos

9 kHz to 30 MHz





Radiated Emissions Test Photos

30 MHz to 1000 MHz





Radiated Emissions Test Photos

Band edge & Harmonic(1 GHz to 18 GHz)





Radiated Emissions Test Photos

Harmonic(18 GHz to 26.5 GHz)



Conducted Test Photos





APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

Test Mode	TX Mode Channel 00_1Mbps	Phase	Line



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1508	44.44	9.90	54.34	65.96	-11.62	QP	
2	0.1508	34.50	9.90	44.40	55.96	-11.56	AVG	
3	0.2060	39.79	9.90	49.69	63.37	-13.68	QP	
4	0.2060	29.80	9.90	39.70	53.37	-13.67	AVG	
5	0.2700	34.35	9.91	44.26	61.12	-16.86	QP	
6	0.2700	24.60	9.91	34.51	51.12	-16.61	AVG	
7	0.4180	28.43	9.94	38.37	57.49	-19.12	QP	
8	0.4180	18.50	9.94	28.44	47.49	-19.05	AVG	
9	20.1660	31.21	15.18	46.39	60.00	-13.61	QP	
10	20.1660	21.30	15.18	36.48	50.00	-13.52	AVG	
11 *	24.6700	35.04	15.55	50.59	60.00	-9.41	QP	
12	24.6700	22.41	15.55	37.96	50.00	-12.04	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode Channel 00_1Mbps	Phase	Neutral



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1580	44.45	9.97	54.42	65.57	-11.15	QP	
2	0.1580	35.11	9.97	45.08	55.57	-10.49	AVG	
3	0.2060	39.89	9.97	49.86	63.37	-13.51	QP	
4	0.2060	29.80	9.97	39.77	53.37	-13.60	AVG	
5	0.3150	31.09	9.98	41.07	59.84	-18.77	QP	
6	0.3150	21.10	9.98	31.08	49.84	-18.76	AVG	
7	0.3660	30.91	9.99	40.90	58.59	-17.69	QP	
8	0.3660	21.10	9.99	31.09	48.59	-17.50	AVG	
9	0.4140	28.51	10.01	38.52	57.57	-19.05	QP	
10	0.4140	18.89	10.01	28.90	47.57	-18.67	AVG	
11 *	24.6460	35.52	15.51	51.03	60.00	-8.97	QP	
12	24.6460	22.70	15.51	38.21	50.00	-11.79	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ

Test Mode	TX Mode Channel 00_1Mbps	Polarization	Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	0.028	59.32	21.21	80.53	118.72	-38.19	AVG	
2		0.055	48.32	21.34	69.66	112.85	-43.19	AVG	
3		0.121	37.14	21.31	58.45	105.94	-47.49	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode Channel 00_1Mbps	Polarization	Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	1.553	21.32	21.21	42.53	63.78	-21.25	QP	
2		6.538	14.32	21.48	35.80	69.54	-33.74	QP	
3		25.075	14.20	22.06	36.26	69.54	-33.28	QP	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode Channel 00_1Mbps	Polarization	Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	0.032	59.32	21.25	80.57	117.56	-36.99	AVG	
2		0.056	47.21	21.34	68.55	112.72	-44.17	AVG	
3		0.122	36.21	21.31	57.52	105.85	-48.33	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode Channel 00_1Mbps	Polarization	Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	0.687	31.04	21.16	52.20	70.86	-18.66	QP	
2		1.971	19.25	21.21	40.46	69.54	-29.08	QP	
3		25.373	14.77	22.06	36.83	69.54	-32.71	QP	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

Test Mode	TX Mode Channel 00_1Mbps	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	35.8200	49.84	-12.31	37.53	40.00	-2.47	Peak	
2	50.3700	44.88	-11.31	33.57	40.00	-6.43	Peak	
3	75.5899	45.02	-14.39	30.63	40.00	-9.37	Peak	
4	125.0600	41.44	-13.03	28.41	43.52	-15.11	Peak	
5	174.5300	44.54	-11.91	32.63	43.52	-10.89	Peak	
6	418.9700	38.24	-7.50	30.74	46.02	-15.28	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode Channel 00_1Mbps	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	33.8800	42.57	-12.51	30.06	40.00	-9.94	Peak	
2	176.4700	38.59	-12.10	26.49	43.52	-17.03	Peak	
3	425.7600	36.93	-7.30	29.63	46.02	-16.39	Peak	
4	534.4000	38.83	-5.19	33.64	46.02	-12.38	Peak	
5	637.2199	37.82	-2.84	34.98	46.02	-11.04	Peak	
6 *	835.1000	37.58	-0.60	36.98	46.02	-9.04	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ

Test Mode	TX 2402 MHz_CH00_1Mbps	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2357.1000	43.98	8.46	52.44	74.00	-21.56	Peak	
2	2357.1000	35.82	8.46	44.28	54.00	-9.72	AVG	
3	2390.0000	40.56	8.55	49.11	74.00	-24.89	Peak	
4	2390.0000	29.31	8.55	37.86	54.00	-16.14	AVG	
5 *	2402.0000	94.14	8.58	102.72	54.00	48.72	AVG	No Limit
6	2402.3000	96.07	8.58	104.65	74.00	30.65	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2402 MHz_CH00_1Mbps	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	7205.9800	32.42	8.49	40.91	54.00	-13.09	AVG	
2	7206.7200	41.30	8.49	49.79	74.00	-24.21	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2440 MHz_CH19_1Mbps	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	7319.6000	41.54	8.62	50.16	74.00	-23.84	Peak	
2 *	7319.9400	33.50	8.62	42.12	54.00	-11.88	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2480 MHz_CH39_1Mbps	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2479.8000	93.27	8.78	102.05	74.00	28.05	Peak	No Limit
2 *	2480.0000	91.28	8.78	100.06	54.00	46.06	AVG	No Limit
3	2483.5000	50.31	8.79	59.10	74.00	-14.90	Peak	
4	2483.5000	33.01	8.79	41.80	54.00	-12.20	AVG	
5	2524.7000	42.46	8.92	51.38	74.00	-22.62	Peak	
6	2524.7000	35.00	8.92	43.92	54.00	-10.08	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2480 MHz_CH39_1Mbps	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	7439.7600	32.41	8.76	41.17	54.00	-12.83	AVG	
2	7440.6600	41.08	8.76	49.84	74.00	-24.16	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2402 MHz_CH00_1Mbps	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	25199.5000	49.72	2.43	52.15	83.50	-31.35	Peak	
2 *	25199.5000	40.31	2.43	42.74	63.50	-20.76	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2402 MHz_CH00_1Mbps	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	25658.5000	49.32	2.33	51.65	83.50	-31.85	Peak	
2 *	25658.5000	42.31	2.33	44.64	63.50	-18.86	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX E - BANDWIDTH

Test Mode	TX Mode_1Mbps

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6 dB Bandwidth Min. Limit (MHz)	Test Result
00	2402	0.696	1.050	0.5	Pass
19	2440	0.700	1.058	0.5	Pass
39	2480	0.696	1.057	0.5	Pass

CH00 **CH19** **CH39**

6 dB Bandwidth







99 % Occupied Bandwidth







APPENDIX F - MAXIMUM OUTPUT POWER

Test Mode	TX Mode_1Mbps

Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	5.82	0.0038	30.00	1.0000	Pass
2440	5.61	0.0036	30.00	1.0000	Pass
2480	5.37	0.0034	30.00	1.0000	Pass

Note: Output power = Measure result + Cable loss

CH00



CH19



CH39



APPENDIX G - CONDUCTED SPURIOUS EMISSION

Test Mode	TX Mode_1Mbps

Reference Level-CH00



Reference Level-CH19



Reference Level-CH39



Bandedge-CH00



Bandedge-CH39



Harmonic-CH00



Harmonic-CH19



Harmonic-CH39



APPENDIX H - POWER SPECTRAL DENSITY

Test Mode	TX Mode_1Mbps

Channel	Frequency (MHz)	Power Spectral Density (dBm/3 kHz)	Max. Limit (dBm/3 kHz)	Test Result
00	2402	-9.52	8.00	Pass
19	2440	-9.75	8.00	Pass
39	2480	-10.07	8.00	Pass

CH00



CH19



CH39



End of Test Report