FCC TEST REPORT

For

Guangzhou SICI Technical Co., LTD

Solid-State Wireless Power Bank with Foldable Stand

Test Model: S101

Prepared for	:	Guangzhou SICI Technical Co., LTD
Address	:	5th Floor, No7-8 XinXin Road, Yongning Street, Zengcheng District, Guangzhou, 511356, Guangdong, China
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	November 24, 2025
Number of tested samples	:	2
Sample No.	:	A251124034-1(Engineer sample), A251124034-2(Normal sample)
Date of Test	:	November 24, 2025 ~ December 12, 2025
Date of Report	:	December 15, 2025

FCC TEST REPORT
KDB 680106 D01 Wireless Power Transfer v04

Report Reference No.	**:**	**LCSA09015163EB**
Date of Issue.....	:	December 15, 2025
Testing Laboratory Name.....	**:**	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address.....	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Testing Location/ Procedure.....	:	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name.....	**:**	**Guangzhou SICI Technical Co., LTD**
Address.....	:	5th Floor, No7-8 XinXin Road, Yongning Street, Zengcheng District, Guangzhou, 511356, Guangdong, China
Test Specification		
Standard.....	:	FCC CFR 47 PART 1, § 1.1310 KDB 680106 D01 Wireless Power Transfer v04
Test Report Form No.....	**:**	LCSEMC-1.0
TRF Originator.....	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	:	Dated 2023-12

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description.....	**:**	**Solid-State Wireless Power Bank with Foldable Stand**
Trade Mark.....	:	N/A
Test Model.....	:	S101
Ratings.....	:	Please Refer to Page 6
Result	:	**PASS**

Compiled by:	**Supervised by:**	**Approved by:**
Nick Peng	Kevin Huang	Gavin Liang
Nick Peng/ Administrators	Kevin Huang/ RF Manager	Gavin Liang/ Manager

ISED -- TEST REPORT

Test Report No. : **LCSA09015163EB**	December 15, 2025 Date of issue

Test Model.....	: S101
EUT.....	: Solid-State Wireless Power Bank with Foldable Stand
Applicant.....	**: Guangzhou SICI Technical Co., LTD**
Address.....	: 5th Floor, No7-8 XinXin Road, Yongning Street, Zengcheng District, Guangzhou, 511356, Guangdong, China
Telephone.....	:
Fax.....	:
Manufacturer.....	**: Guangzhou SICI Technical Co., LTD**
Address.....	: 5th Floor, No7-8 XinXin Road, Yongning Street, Zengcheng District, Guangzhou, 511356, Guangdong, China
Telephone.....	:
Fax.....	:
Factory.....	**: Guangzhou SICI Technical Co., LTD**
Address.....	: 5th Floor, No7-8 XinXin Road, Yongning Street, Zengcheng District, Guangzhou, 511356, Guangdong, China
Telephone.....	:
Fax.....	:

Test Result	**PASS**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	December 15, 2025	Initial Issue	--

TABLE OF CONTENTS

1. GENERAL INFORMATION 6
1.1. DESCRIPTION OF DEVICE (EUT) 6
1.2. SUPPORT EQUIPMENT LIST 6
1.3 EXTERNAL I/O CABLE 6
1.4. DESCRIPTION OF TEST FACILITY 6
1.5. TEST EQUIPMENT 7
1.6. MEASUREMENT UNCERTAINTY 7
1.7. DESCRIPTION OF TEST MODES 7
1.8. COIL DESCRIPTION 8
1.10. COIL SPECIFICATIONS 8
1.11. DUTY CYCLE 8
2. TEST METHODOLOGY 10
2.1. REFERENCE EVALUATION METHOD 10
2.2. LIMIT 10
2.3. TEST SETUP DIAGRAM 10
2.4. MEASUREMENT PROCEDURE 11
2.5. EQUIPMENT APPROVAL CONSIDERATIONS OF KDB 680106 D01V04 12
3. TEST RESULTS 13
3.3 CONCLUSION 16
4. TEST SETUP PHOTOS 17

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Solid-State Wireless Power Bank with Foldable Stand
Test Model	:	S101
Ratings	:	Battery Capacity: 5000mAh / 3.85V / 19.25Wh USB-C Input: 5V⎓3A / 9V⎓2A USB-C Output: 5V⎓3A / 9V⎓2.22A / 12V⎓1.67A Wireless Output: 5W / 7.5W / 10W / 15W Wireless +USB-C Output: 5V⎓3A (15W max.)
Hardware Version	:	/
Software Version	:	/
Wireless Charging	:	
Operating Frequency	:	110.0-205.0KHz, 300.0-360.0KHz
Modulation Type	:	ASK
Antenna Type	:	Coil Antenna

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

1.2. Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN TIANYIN ELE CTRONICS CO., LTD	Power Adapter	TPA-46050200UU	--	FCC
Samsung	Mobile phone	Galaxy S25	--	FCC

Note: Auxiliary equipment is provided by the laboratory.

1.3 External I/O Cable

I/O Port Description	Quantity	Cable
Type-C USB Port	1	N/A

1.4. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Test Equipment

Equipment	Manufacturer	Model	Serial no.	Calibrated date	Calibrated Due
Exposure Level Tester	Narda	ELT-400	N-0713	2025-11-10	2026-11-09
B-Field Probe	Narda	100cm²	M-1154	2025-09-27	2026-09-26

Exposure Level Tester ELT-400 detailed parameters are as follows:

Common parameter	
Operating temperature	-10 °C ~ +50 °C
Operation humidity	< 95 % (30 °C) or < 29 g/m³
Weight	910 g
Size	180 mm x 100 mm x 55 mm(Main engine) / 290 mm x 125 mm Ø (Probe)
Display	LCD backlit display, 4 refresh rates per second
Battery	Nimh battery (4 x Mignon, AA), rechargeable
Operating time, typical	12 h
Power supply	100 ~240 V AC / 47 ~ 63 Hz
Charging time, typical	2 hours
Recommended calibration cycle	24 months
Country of origin	Germany

1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Field Strength Uncertainty	:	1Hz~400KHz	1%	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

Equipment under test was operated during the measurement under the following conditions:

☒ Charging and communication mode

Test Modes		
Mode 1	AC/DC Adapter (9V/2A) + EUT + Mobile phone (Battery Status: <1%)	Record
Mode 2	AC/DC Adapter (9V/2A) + EUT + Mobile phone (Battery Status: <50%)	Record
Mode 3	AC/DC Adapter (9V/2A) + EUT + Mobile phone (Battery Status: 100%)	Record
Mode 4	AC/DC Adapter (5V/3A) + EUT + Mobile phone (Battery Status: <1%)	Pre-tested
Mode 5	AC/DC Adapter (5V/3A) + EUT + Mobile phone (Battery Status: <50%)	Pre-tested
Mode 6	AC/DC Adapter (5V/3A) + EUT + Mobile phone (Battery Status: 100%)	Pre-tested
Note: All test modes were pre-tested for ac and dc mode, but we only recorded the worst case in this report for ac mode.		

1.8. Coil Description

Config.	Mode	Descriptions
1	Standby (Flatbed Position) @111.2kHz, 300-360KHz	EUT Alone powered by AC/DC adapter
2	Operating (Flatbed Position) (Phone @111.2KHz, 300-360KHz ~10%, 20~50%, and >75% Power Charging)	EUT with lightning to AC/DC Adapter & Wireless Charging to WPT Client. 15W: Direct Contact 15W: 2mm Airgap, 2mm Shift Top as Worst-Case Position

1.9. Coil Size



A	5.30±0.2
B	20.5±0.5
C	39±1
D	43.5±0.5
E	1.5±1
F	50±2
G	1.2±0.2
H	0.6±0.05
J	
K	
L	
M	
N	

(Unit: mm)

1.10. Coil Specifications

Item	Parameter
Input inductance:	Transmitter 1: 6.5 μH±10%
Material of enclosure(s):	Multiple strands of enamelled wire
Number of turns:	Transmitter 1: 10 turns

1.11. Duty Cycle

Mode	ON Time (ms)	Period (ms)	Duty Cycle (%)
Operating (110.0-205.0kHz)	/	/	100
Operating (300.0-360.0kHz)	/	/	100



(110.0-205.0kHz)



(300.0-360.0kHz)

2. TEST METHODOLOGY

2.1. Reference Evaluation Method

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 680106 D01 RF Exposure Wireless Charging Apps v04: RF Exposure Considerations for Low Power Consumer Wireless Power Transfer Applications

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1093: Radiofrequency radiation exposure evaluation: portable devices

FCC CFR 47 part 18.107: Indusial, Scientific, and Medical Equipment

April 2024 TCBC Workshop: Part 18 Wireless Power Transfer Devices: Clarifications on KDB 680106v04 and ECR Processes

2.2. Limit

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	**614**	**1.63**	***(100)**	**≤6**
3.0-30	**1842/f**	**4.89/f**	***(900/f2)**	**<6**
30-300	**61.4**	**0.163**	**1.0**	**<6**
300-1500	**/**	**/**	**f/300**	**<6**
1500-100000	**/**	**/**	**5**	**<6**
mits fo(ii) Lir General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f^2)	<30
30-300	27.5	0.073	0.2	<30
300-1500	/	/	f/1500	<30
1500-100000	/	/	1.0	<30

f = frequency in MHz
* = Plane-wave equivalent power density
Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.
Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

2.3. Test Setup Diagram

Mobile Exposure Conditions



Note: The distance of the points A/B/C/D/E is 20cm.

Portable Exposure Conditions:



Note: The distance of the points A/B/C/D/E/F is 0,2,4,6,8,10,12,14,16,18, 20cm.
The values tested by the probe are X, Y, and Z on three axes perpendicular to the edge of the device. Top and bottom side coincident with the axis(Y) of the main coil.

2.4. Measurement Procedure

Mobile Exposure Conditions

a. The RF exposure test was performed in anechoic chamber.

b. E and H-field measurements should be made with the center of the probe at 20 cm surrounding the EUT and 20 cm above the top surface of the primary/client pair.

c. The highest emission level was recorded and compared with limit.

d. The EUT was measured according to the KDB 680106 D01 Wireless Power Transfer v04.

Portable Exposure Conditions

a. The RF exposure test was performed in anechoic chamber.

b. Perform H-field measurements for each edge/top surface of the host/client pair at every 2 cm, starting from as close as possible out to 20 cm

c. The highest emission level was recorded and compared with limit.

d. The EUT was measured according to the KDB 680106 D01 Wireless Power Transfer v04.

2.5. Equipment Approval Considerations of KDB 680106 D01v04

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operates in the frequency range 110.0-205.0kHz, 300.0-360.0kHz
The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.	Yes	The maximum output power of each primary coil is 15W.
A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)	Yes	Client device is placed directly in contact with the transmitter.
Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).	No	Mixed mobile and portable exposure conditions
The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.	Yes	The E-field and H-field strengths from all simultaneous transmitting coils are demonstrated to less than 50% of the MPE limit.
For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested	Yes	Only one radiating structure and tested at maximum Output Power

3. TEST RESULTS

For portable exposure condition

(1). The portable test modes have covered the considerations of the mobile test, only record the test data of the portable conditions in this report.

(2) Operating modes with client device (1 %, 50%, 99% battery status of client device) have been test, only show the data of worst case of 1% battery status of client device.

(3) Test performed with all the radiating structures operating at maximum power at the same time.

(4) H-field measurements are taken along all three axes the device from 0cm~20cm in 2cm minimum increment for each edge surface of the host/client pair. If the center of the probe sensing element is more than 5mm from the probe outer edge, the field strengths need to be estimated for the positions that are not reachable.

(5) Validation of Field Estimates

(a) If R is the probe radius and the probe tip is in contact with the coil, then the probe center is R cm from the coil surface as bellowing picture



(b) The probe then is measuring the field correctly at R cm from the surface, and only estimating the field at the 0 cm point of contact with the coil surface.

(c) The validation requires showing that the model used to estimate the field provides data within 30% accuracy for at least the two, 2-cm-spaced closest points to where the estimates were made.

(d) If there is only one estimated value, then a single validation point is sufficient.

(e) Validation Example for 4 cm Probe Radius as following

Step 1



Step 2



Step 3



Description of the Validation Example for 4 cm Probe Radius

- Assume that R=4 cm. The field at 0 cm can only be estimated, but the field at 4 cm is measured exactly (at the center of the probe).
- Move the probe at 2 cm from the surface. The field at 2 cm can still only be estimated, but the field at 6 cm is measured exactly.
- Compare the estimates with the values at the same positions where the field was measured exactly (i.e., 4 cm and 6 cm)
- The difference between measurements and estimates needs to be no more than 30%.
- That validation of the estimates needs to be for the two closest points to the coil, but at least 2 cm apart (in this case they are). This is to avoid a validation at, say 2 cm and another one at 2.1 cm, that is essentially a repetition

(6) According to Calibration information and specification about ETL-400 Probe (the B-Field Probe size is 100cm^2, the probe radius is 6.25cm), The Probe ETL-400 Probe's sensitive elements center is located in

the probe's center, and the distance from the sensitive elements center to the tip of probe is 6.25cm.

(7) The actual 0cm, 2cm, 4cm and 6cm field strengths need to be estimated for the positions that are not reachable via numerical calculation.

(8) For validation purposes: If the value to show a 30% agreement between the mode and the probe measurements for the two closest points to the device surface, and with 2cm increments. Then this extrapolation method is reasonable.

(9) Validation E-Field and H-Field as bellowing;

Validation Mode: TM1 Unit: Agreement(%); H-Field(A/m)							
	Top	Bottom	Left	Right	Front	Back	Conclusion
Estimated Distance: 6.25 cm	0.4502	0.5162	0.3905	0.4426	0.3502	0.4833	PASS
Measured Distance: 6.25 cm	0.3654	0.4567	0.3698	0.4136	0.3024	0.4489	
contrast(%)	23.21	13.03	5.60	7.01	15.81	7.66	
Estimated Distance: 8 cm	0.2833	0.2451	0.2506	0.1861	0.3924	0.2312	PASS
Measured Distance: 8 cm	0.2579	0.2325	0.2223	0.1704	0.3395	0.2071	
contrast(%)	9.85	5.42	12.73	9.21	15.58	11.64	
Estimated Distance: 10 cm	0.0823	0.5619	0.1517	0.1362	0.1908	0.1013	PASS
Measured Distance: 10 cm	0.0796	0.4475	0.1300	0.1188	0.1862	0.0838	
contrast(%)	3.39	25.56	24.38	14.65	2.47	20.88	

Validation Mode: TM1 Unit: Agreement(%); E-Field(V/m)							
	Top	Bottom	Left	Right	Front	Back	Conclusion
Estimated Distance: 6.25 cm	30.5212	29.3305	28.9607	25.7596	25.2672	24.0573	PASS
Measured Distance: 6.25 cm	28.9068	26.7656	27.7054	23.6979	22.7969	22.4928	
contrast(%)	5.58	9.58	4.53	8.70	10.97	6.96	
Estimated Distance: 8 cm	28.2185	26.5362	25.9925	22.1924	21.4328	21.2608	PASS
Measured Distance: 8 cm	24.4714	23.0625	23.6158	20.7382	19.3955	19.2320	
contrast(%)	15.31	15.06	10.06	7.01	10.50	10.55	
Estimated Distance: 10 cm	25.6145	23.3892	24.2359	20.8607	20.0213	18.1745	PASS
Measured Distance: 10 cm	22.3092	21.2028	21.6696	17.6294	16.1639	16.3480	
contrast(%)	14.82	10.31	11.84	18.33	23.86	11.17	

Note 1: The compliance location as probe tip;
Note 2: The format of difference is;
The E Validation Difference = $(E_{Estimated\ Distance} - E_{Measured\ Distance})/ E_{Measured\ Distance}$ *100%
The H Validation Difference = $(H_{Estimated\ Distance} - H_{Measured\ Distance})/ H_{Measured\ Distance}$ *100%

H-Field and E-Field Emission level with a combination of measured and estimated results.

Test condition: Mode 1

Distance(cm)	H-Field Result(A/m)							Limit(A/m)
	Type	Top	Bottom	Left	Right	Front	Back	
0	Estimate	0.7413	0.7871	0.5618	0.3223	0.5708	0.4001	1.63
2	Estimate	0.7271	0.4949	0.5416	0.4701	0.5295	0.4375	1.63
4	Estimate	0.5106	0.6097	0.5706	0.6357	0.5198	0.4235	1.63
6	Measured	0.3654	0.4567	0.3698	0.4136	0.3024	0.4489	1.63
8	Measured	0.2579	0.2325	0.2223	0.1704	0.3395	0.2071	1.63
10	Measured	0.0796	0.4475	0.1300	0.1188	0.1862	0.0838	1.63
12	Measured	0.1461	0.1783	0.1689	0.1032	0.2140	0.1384	1.63
14	Measured	0.1813	0.1492	0.1033	0.1787	0.0959	0.1769	1.63
16	Measured	0.1077	0.1043	0.1849	0.1478	0.2030	0.2815	1.63
18	Measured	0.0740	0.0525	0.0943	0.0553	0.1781	0.1658	1.63
20	Measured	0.1102	0.1321	0.1097	0.1478	0.1990	0.1351	1.63

Distance(cm)	E-Field Result(V/m)							Limit(V/m)
	Type	Top	Bottom	Left	Right	Front	Back	
0	Estimate	37.6793	36.2219	36.2836	32.1055	31.6564	31.3867	613
2	Estimate	34.4504	34.1512	33.7675	30.7961	29.6576	29.1602	613
4	Estimate	31.2986	30.6820	31.0206	27.7505	27.0489	26.5807	613
6	Measured	28.9068	26.7656	27.7054	23.6979	22.7969	22.4928	613
8	Measured	24.4714	23.0625	23.6158	20.7382	19.3955	19.2320	613
10	Measured	22.3092	21.2028	21.6696	17.6294	16.1639	16.3480	613
12	Measured	20.1600	19.1399	19.6481	15.4266	13.5944	13.3224	613
14	Measured	17.2368	16.8365	16.9515	13.1616	11.5428	11.3434	613
16	Measured	15.8012	14.7960	15.4279	10.1141	9.2812	9.1567	613
18	Measured	12.5680	11.4861	12.1984	8.4722	7.4902	7.2267	613
20	Measured	7.6114	7.2564	7.4895	5.3383	4.2815	3.7863	613

3.3 Conclusion

A minimum safety distance of 0 cm to the antenna is required when the device is charging a smart phone for portable exposure. The detected emissions are below the limitations according FCC KDB 680106.

4. TEST SETUP PHOTOS

(The separation distance from the geometric center of the probe to the edge of the device is 6.25cm)



0cm-Left



0cm-Right



0cm-Top



0cm-Bottom



0cm-Front

0cm-Back



20cm-Left



20cm-Right



20cm-Top



20cm-Bottom



20cm-Front



20cm-Back

----------THE END OF REPORT----------