

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	ConnectLab S.r.l.
Address:	Viale Coni Zugna, 71 20144 Milano (MI) ITALY

Manufacturer or Supplier:	ConnectLab S.r.l.
Address:	Viale Coni Zugna, 71 20144 Milano (MI) ITALY
Product:	AT&T amiGO Tracker
Brand Name:	DOTS
Model Name:	DOTS01A
FCC ID:	2BOZB-DOTS01A
Date of tests:	Jun. 13, 2025 ~ Jul. 11, 2025

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2020**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Jul. 11, 2025	Date: Jul. 11, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1. SUMMARY OF TEST RESULTS.....	6
1.1 MEASUREMENT UNCERTAINTY	7
2 GENERAL INFORMATION	8
2.2 GENERAL DESCRIPTION OF EUT	8
2.3 DESCRIPTION OF TEST MODES	10
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	11
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
2.4 DUTY CYCLE OF TEST SIGNAL	15
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
2.6 DESCRIPTION OF SUPPORT UNITS	16
3 TEST TYPES AND RESULTS.....	17
3.1 CONDUCTED EMISSION MEASUREMENT	17
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	17
3.1.2 TEST INSTRUMENTS.....	18
3.1.3 TEST PROCEDURES	19
3.1.4 DEVIATION FROM TEST STANDARD	19
3.1.5 TEST SETUP	20
3.1.6 EUT OPERATING CONDITIONS	20
3.1.7 TEST RESULTS	21
3.2 RADIATED EMISSION MEASUREMENT	23
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	23
3.2.2 TEST INSTRUMENTS.....	24
3.2.3 TEST PROCEDURES	25
3.2.4 DEVIATION FROM TEST STANDARD	25
3.2.5 TEST SETUP	26
3.2.6 EUT OPERATING CONDITIONS	27
3.2.7 TEST RESULTS	28
3.3 6 DB BANDWIDTH MEASUREMENT	70
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	70
3.3.2 TEST INSTRUMENTS.....	70
3.3.3 TEST PROCEDURE.....	71
3.3.4 DEVIATION FROM TEST STANDARD	72
3.3.5 TEST SETUP	72
3.3.6 EUT OPERATING CONDITIONS	72
3.3.7 TEST RESULTS	72
3.4 CONDUCTED OUTPUT POWER	73



3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	73
3.4.2	TEST SETUP	73
3.4.3	TEST INSTRUMENTS.....	73
3.4.4	TEST PROCEDURES	73
3.4.5	DEVIATION FROM TEST STANDARD	73
3.4.6	EUT OPERATING CONDITIONS	73
3.4.7	TEST RESULTS	74
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	74
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	75
3.5	POWER SPECTRAL DENSITY MEASUREMENT	76
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	76
3.5.2	TEST SETUP	76
3.5.3	TEST INSTRUMENTS.....	76
3.5.4	TEST PROCEDURE.....	76
3.5.5	DEVIATION FROM TEST STANDARD	76
3.5.6	EUT OPERATING CONDITION	76
3.5.7	TEST RESULTS	77
3.6	OUT OF BAND EMISSION MEASUREMENT	78
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	78
3.6.2	TEST SETUP	78
3.6.3	TEST INSTRUMENTS.....	78
3.6.4	TEST PROCEDURE.....	78
3.6.5	DEVIATION FROM TEST STANDARD	79
3.6.6	EUT OPERATING CONDITION	79
3.6.7	TEST RESULTS	79
3.7	ANTENNA REQUIREMENTS	80
3.7.1	STANDARD APPLICABLE	80
3.7.2	ANTENNA CONNECTED CONSTRUCTION	80
3.7.3	ANTENNA GAIN	80
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	81
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	82
6	APPENDIX A:BLE.....	83
	DTS BANDWIDTH	83
	TEST RESULT	83
	TEST GRAPHS.....	83
	OCCUPIED CHANNEL BANDWIDTH	90
	TEST RESULT	90



TEST GRAPHS.....	90
MAXIMUM CONDUCTED OUTPUT POWER	97
TEST RESULT PEAK	97
MAXIMUM POWER SPECTRAL DENSITY	98
TEST RESULT	98
TEST GRAPHS.....	99
BAND EDGE MEASUREMENTS	105
TEST RESULT	105
TEST GRAPHS.....	105
CONDUCTED SPURIOUS EMISSION.....	110
TEST RESULT	110
TEST GRAPHS.....	111
DUTY CYCLE	129
TEST RESULT	129
TEST GRAPHS.....	129



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QSU2505080113RF01	Original release	Jul. 11, 2025



1. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	TEST LAB*
15.207	AC Power Conducted Emission	Compliance	A
15.205 15.209	Radiated Emissions	Compliance	A
15.247(d)	Out of band Emission Measurement	Compliance	A
15.247(a)(2)	6dB bandwidth	Compliance	A
15.247(b)	Conducted Output power	Compliance	A
15.247(e)	Power Spectral Density	Compliance	A
15.203	Antenna Requirement	Compliance	A

Note : Except RSE and AC Power Conducted Emission, other data please refer to Appendix A.

*Test Lab Information Reference

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



2 GENERAL INFORMATION

2.2 GENERAL DESCRIPTION OF EUT

PRODUCT*	AT&T amiGO Tracker	
BRAND NAME*	DOTS	
MODEL NAME*	DOTS01A	
NOMINAL VOLTAGE*	3.8V	
MODULATION *	BLE	GFSK
TRANSMISSION RATE*	BT_LE: 0.125 Mbps /0.5 Mbps /1 Mbps/2 Mbps	
OPERATING FREQUENCY	2402-2480MHz for BT-LE(GFSK)	
MAX. OUTPUT POWER	BT-LE: 4.49mW (Maximum)	
ANTENNA GAIN*	BLE	0.2dBi
ANTENNA TYPE*	BLE	PIFA
HW VERSION*	1.0	
SW VERSION*	0.0.8-5.0.7	
I/O PORTS*	Refer to user's manual	
CABLE SUPPLIED*	N/A	

NOTE:

- *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
BT_LE(1MHz)	1TX/1RX
BT_LE(2MHz)	1TX/1RX
BT_LE(S2)	1TX/1RX
BT_LE(S8)	1TX/1RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



6. List of Accessory:

ACCESSORIES	Brand	Model	Manufacturer	SPECIFICATION
Battery	EVERPOWER TECHNOLOGY	HT562134K	EVERPOWER TECHNOLOGY CO., LTD.	Power Rating: 3.7 Vdc, 450 mAh Type:Rechargeable Li-ion Polymer
USB Cable 1	Zhengyu Electronic	C362- 250401-002	Zhengyu Electronic Co., Ltd	Signal Line:0.1 meter, non-shielded cable, with w/o ferrite core



2.3 DESCRIPTION OF TEST MODES

11 Channels are provided for 802.11b, 802.11g and 802.11n20 (HT20),802.11ax20 (HE20):

802.11b/802.11g/802.11n20 (HT20)/802.11ax20 (HE20)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

802.11n40 (HT40)/ 802.11ax40 (HE40)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

BT-LE							
CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	19	GFSK	0.125

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

POWER LINE CONDUCTED EMISSION TEST

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n20	1 to 11	6	OFDM	MCS0



BANDEDGE MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

TEST CONDITION			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 3.6V/3.8V/4.2V By Battery	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC 3.6V/3.8V/4.2V By Battery	Hanwen Xu
PLC	25deg. C, 52%RH	DC 3.6V/3.8V/4.2V By Battery	Hanwen Xu
APCM	25deg. C, 60%RH	DC 3.6V/3.8V/4.2V By Battery	Hanwen Xu

2.4 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix A Of this test report..

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.



2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	Adapter	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	USB Line: Unshielded, Detachable, 1.0m;



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Feb.24,24	Feb.23,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Feb.16,24	Feb.15,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.28,23	Apr.27,24
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.27,24	Apr.26,26
CABLE	Rohde&Schwarz	W601	N/A	Apr.28,23	Apr.27,24
CABLE	Rohde&Schwarz	W601	N/A	Apr.27,24	Apr.26,26

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12/24 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA										
Frequency Range	150KHz ~ 30MHz		Detector Function & Resolution Bandwidth		Quasi-Peak (QP) / Average (AV), 9 kHz					
Input Power	120Vac, 60Hz		Environmental Conditions		26deg. C, 51%RH					
Tested By	Hanwen Xu									

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.173	41.65	64.84	23.19	26.49	54.84	28.35	12.31	L1	9.000
1	0.515	38.66	56.00	17.34	29.03	46.00	16.97	11.75	L1	9.000
1	1.572	27.75	56.00	28.25	16.42	46.00	29.58	11.75	L1	9.000
1	4.128	26.78	56.00	29.22	15.99	46.00	30.01	11.78	L1	9.000
1	7.818	33.39	60.00	26.61	24.20	50.00	25.80	11.81	L1	9.000
1	19.077	27.58	60.00	32.42	18.52	50.00	31.48	11.87	L1	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Limit value -Emission level

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.

Level in dBμV

70

67.5

65

62.5

60

57.5

55

52.5

50

47.5

45

42.5

40

37.5

35

32.5

30

27.5

25

22.5

20

17.5

15

12.5

10

7.5

5

2.5

0

150 k

200 k

300 k

400 k

500 k

600 k

800 k

1 M

2 M

3 M

4 M

5 M

6 M

7 M

8 M

10 M

20 M

30 M

Frequency in Hz

AVG Level @Spectrum Overview

PK+ Level @Spectrum Overview

AVG Limit @FCC Part 15 Voltage Mains Class B

QPK Limit @FCC Part 15 Voltage Mains Class B

◇ CAV Level @Final Results


◇ QPK Level @Final Results



Frequency Range		150KHz ~ 30MHz			Detector Function & Resolution Bandwidth			Quasi-Peak (QP) / Average (AV), 9 kHz		
Input Power		120Vac, 60Hz			Environmental Conditions			26deg. C, 51%RH		
Tested By		Hanwen Xu								
Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.173	40.86	64.84	23.98	26.41	54.84	28.43	12.21	N	9.000
1	0.519	39.01	56.00	16.99	30.68	46.00	15.32	12.78	N	9.000
1	1.937	26.52	56.00	29.48	17.10	46.00	28.90	12.74	N	9.000
1	4.493	23.90	56.00	32.10	15.34	46.00	30.66	12.76	N	9.000
1	8.007	31.35	60.00	28.65	23.33	50.00	26.67	12.78	N	9.000
1	18.641	26.76	60.00	33.24	13.64	50.00	36.36	12.84	N	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



**3.2 RADIATED EMISSION MEASUREMENT****3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT**

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,24	Aug.28,26
Pre-Amplifier	R&S	SCU08F1	101028	Sep.15,24	Sep.14,26
Signal Generator	R&S	SMB100A	182185	Feb.15,24	Feb.14,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Feb.24,24	Feb.23,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.27,24	Feb.26,26
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.21,24	Aug.20,26
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Feb.22,24	Feb.21,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.21,24	Aug.20,26
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,24	Feb.21,26
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.26,24	Jun.25,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.30,24	Aug.29,26
Hygrothermograph	DELI	20210528	SZ014	Sep.05,24	Sep.04,26
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.28,23	Apr.27,24
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,26
CABLE	R&S	W12.14	N/A	Apr.28,23	Apr.27,24
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.26,26

NOTE:

1. The calibration interval of the above test instruments is 12/ 24 / 36 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation




3.2.5 TEST SETUP


<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).


3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA






CHANNEL		TX Channel 19			DETECTOR FUNCTION		Quasi-Peak (QP)		
FREQUENCY RANGE		30MHz ~ 1GHz							
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	43.968	31.20	40.00	8.80	-10.23	V	136.7	1.00	120.000
1	87.861	20.04	40.00	19.96	-12.95	V	136.7	1.00	120.000
1	176.276	15.79	43.50	27.71	-12.44	V	359.1	1.00	120.000
1	240.102	22.83	46.00	23.17	-9.05	V	78.6	2.00	120.000
1	326.093	21.03	46.00	24.97	-5.82	V	221	2.00	120.000
1	507.192	20.67	46.00	25.33	-2.98	V	4.9	1.00	120.000

REMARKS:


1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level



ABOVE 1GHz TEST DATA

Note:


1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.
2. All other emissions were greater than 20dB below the limit was not recorded





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,389.000	42.45	54.00	11.55	37.08	H	359.1	1.00
5	2,390.000	42.45	54.00	11.55	37.10	H	85.6	1.00
5	2,402.000	91.75			37.26	H	144.2	2.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,318.000	57.92	74.00	16.08	36.94	V	37.8	1.00
5	2,390.000	56.46	74.00	17.54	37.10	V	100	2.00
5	2,402.000	89.35			37.26	V	232.7	2.00





REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2402MHz: Fundamental frequency.






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,880.000	49.90	74.00	24.10	39.23	54.00	14.77	14.77	V	34.3	2.00
2	7,320.000	55.22	74.00	18.78	44.89	54.00	9.11	21.11	V	34.3	2.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2440MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,479.980	93.07			37.87	H	83.2	1.00
6	2,483.500	43.47	54.00	10.53	37.88	H	98.8	2.00
6	2,499.560	43.44	54.00	10.56	37.91	H	83.2	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,479.980	89.38			37.87	V	231.5	2.00
6	2,483.500	57.72	74.00	16.28	37.88	V	304.3	1.00
6	2,500.000	58.83	74.00	15.17	37.91	V	100	2.00





REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2480MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,389.500	42.40	54.00	11.60	37.09	H	174	1.00
5	2,390.000	42.44	54.00	11.56	37.10	H	140.6	2.00
5	2,404.000	93.40			37.29	H	140.6	2.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,338.500	57.69	74.00	16.31	36.90	V	355	2.00
5	2,390.000	56.89	74.00	17.11	37.10	V	359	2.00
5	2,404.500	89.43			37.30	V	275.7	2.00





REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2404MHz: Fundamental frequency.






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,880.000	51.09	74.00	22.91	39.16	54.00	14.84	14.77	V	1	2.00
2	7,320.000	56.37	74.00	17.63	44.69	54.00	9.31	21.11	V	359	2.00



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor.
2. Margin value = Limit value–Emission level.
3. 2440MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,477.920	94.31			37.87	H	175.2	1.00
6	2,483.500	43.60	54.00	10.40	37.88	H	175.2	1.00
6	2,484.400	43.59	54.00	10.41	37.88	H	175.2	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,477.920	91.42			37.87	V	85.6	1.00
6	2,483.500	58.36	74.00	15.64	37.88	V	348.6	1.00
6	2,496.880	58.78	74.00	15.22	37.91	V	184.8	2.00





REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamplifier Factor
2. Margin value = Limit value–Emission level.
3. 2478MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,387.000	42.49	54.00	11.51	37.06	H	355	2.00
5	2,390.000	42.49	54.00	11.51	37.10	H	262.4	1.00
5	2,402.000	76.66			37.26	H	128.6	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,348.500	57.88	74.00	16.12	36.88	V	321.1	2.00
5	2,390.000	56.20	74.00	17.80	37.10	V	188.4	2.00
5	2,402.500	89.78			37.27	V	232.7	2.00





REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2402MHz: Fundamental frequency.