Appendix B

RF Test Data for BT (BLE) (Conducted Measurement)

Product Name: Pet Smart Feeders

Trade Mark: Star pack

Test Model: WSQ11

Environmental Conditions

Temperature:	24.6° C
Relative Humidity:	52.4%
ATM Pressure:	100.0 kPa
Test Engineer:	Emiya lin
Supervised by:	Simba Haung

Contents

Page

COVER PAGE

1 Duty Cycle 3
1.1 Test Result 3
1.2 Test Graphs 4
2 Maximum Conducted Output Power 6
2.1 Test Result 6
2.2 Test Graphs 7
3 -6dB Bandwidth 9
3.1 Test Result 9
3.2 Test Graphs 10
4 Maximum Power Spectral Density Level 12
4.1 Test Result 12
4.2 Test Graphs 13
5 Band Edge 15
5.1 Test Result 15
5.2 Test Graphs 16
6 Conducted RF Spurious Emission 18
6.1 Test Result 18
6.2 Test Graphs 19
7 Restrict Band 22
7.1 Test Result 22
7.2 Test Graphs 23

1 Duty Cycle

1.1 Test Result

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor	1/T (kHz)
BLE 1M	2402	64	1.94	2.56
BLE 1M	2440	64.33	1.92	2.56
BLE 1M	2480	63.99	1.94	2.56

1.2 Test Graphs

Test Graphs

BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



2 Maximum Conducted Output Power

2.1 Test Result

Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
BLE 1M	2402	1.75	30	Pass
BLE 1M	2440	2.35	30	Pass
BLE 1M	2480	1.82	30	Pass

2.2 Test Graphs

Test Graphs
BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



3 -6dB Bandwidth

3.1 Test Result

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
BLE 1M	2402	0.671	0.5	Pass
BLE 1M	2440	0.702	0.5	Pass
BLE 1M	2480	0.668	0.5	Pass

3.2 Test Graphs

Test Graphs

BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4799704 GHz	1.65 dBm		
M2		1	2.479635 GHz	-4.32 dBm		
M3		1	2.480303 GHz	-4.33 dBm		

4 Maximum Power Spectral Density Level

4.1 Test Result

Mode	Frequency (MHz)	Conducted PSD (dBm/3-100kHz)	Limit (dBm/3kHz)	Verdict
BLE 1M	2402	-13.62	≤8	Pass
BLE 1M	2440	-13.09	≤8	Pass
BLE 1M	2480	-14.06	≤8	Pass

4.2 Test Graphs

Test Graphs
BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



5 Band Edge

5.1 Test Result

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-57.58	-20	Pass
BLE 1M	2480	-48.05	-20	Pass

5.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Ref



BLE 1M 2402MHz Emission



BLE 1M 2480MHz Ref



BLE 1M 2480MHz Emission



6 Conducted RF Spurious Emission

6.1 Test Result

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-45.04	-20	Pass
BLE 1M	2440	-45.19	-20	Pass
BLE 1M	2480	-44.32	-20	Pass

6.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Ref



BLE 1M 2402MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.397 GHz	-1.52 dBm		
M2		1	19.7502 GHz	-43.56 dBm		
M3		1	4.7946 GHz	-53.11 dBm		
M4		1	7.0181 GHz	-50.08 dBm		
M5		1	9.5857 GHz	-49.55 dBm		

BLE 1M 2440MHz Ref



BLE 1M 2440MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45 GHz	0.20 dBm		
M2		1	19.3531 GHz	-42.95 dBm		
M3		1	4.9269 GHz	-53.31 dBm		
M4		1	7.2828 GHz	-49.74 dBm		
M5		1	9.8768 GHz	-48.51 dBm		

BLE 1M 2480MHz Ref



BLE 1M 2480MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.476 GHz	0.11 dBm		
M2		1	20.0943 GHz	-42.86 dBm		
M3		1	4.9534 GHz	-53.11 dBm		
M4		1	7.5739 GHz	-49.01 dBm		
M5		1	9.9298 GHz	-48.75 dBm		

7 Restrict Band

7.1 Test Result

Mode	Frequency (MHz)	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
BLE 1M	2402	2310	-51.59	2	-	45.67	Peak	74	Pass
BLE 1M	2402	2310	-55.69	2	1.94	43.51	Average	54	Pass
BLE 1M	2402	2342.064	-45.38	2	-	51.88	Peak	74	Pass
BLE 1M	2402	2340.528	-54.47	2	1.94	44.73	Average	54	Pass
BLE 1M	2402	2390	-50.14	2	-	47.12	Peak	74	Pass
BLE 1M	2402	2390	-56.85	2	1.94	42.35	Average	54	Pass
BLE 1M	2480	2483.5	-49.4	2	-	47.86	Peak	74	Pass
BLE 1M	2480	2483.5	-55.48	2	1.94	43.72	Average	54	Pass
BLE 1M	2480	2487.376	-45.86	2	-	51.4	Peak	74	Pass
BLE 1M	2480	2487.496	-54.97	2	1.94	44.23	Average	54	Pass
BLE 1M	2480	2500	-48.4	2	-	48.86	Peak	74	Pass
BLE 1M	2480	2500	-56.75	2	1.94	42.45	Average	54	Pass

7.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Peak



BLE 1M 2402MHz Average



BLE 1M 2480MHz Peak



BLE 1M 2480MHz Average



---The End---