Test Report

Applicant	:	Shenzhen Rurun Digital Technology Co., Ltd.
Address	:	2/F Jihe Comm Shenjing Ind Zone Huaqing Ave Qinghua Comm Longhua Dist Shenzhen Guangdong CHINA
Product Name	:	Audio stand
Brand Mark	:	MAGIC JOHN
Model	:	X7
FCC ID	:	2BP3U-MAGICJOHNX7
Report Number	:	BLA-EMC-202506-A4402
Date of Receipt	:	June 11, 2025
Date of Test	:	June 11, 2025 to June 19, 2025
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Compiled by: Hugh **Review by:** Xavier **Approved by:** Blue Zheng

Issued Date: June 19, 2025

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

BlueAsia of Technical Services(Shenzhen) Co., Ltd. BLA

The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information 5

1.1 General information 5

1.2 General description of EUT 5

2 Test summary 6

3 Test Configuration 7

3.1 Test mode 7

3.2 Operation Frequency each of channel 8

3.3 Test channel 8

3.4 Auxiliary equipment 8

3.5 Test environment 8

4 Laboratory information 9

4.1 Laboratory and accreditations 9

4.2 Measurement uncertainty 9

5 Test equipment 10

6 Test result 12

6.1 Antenna requirement 12

6.2 Conducted emissions at AC power line (150 kHz-30 MHz) 13

6.3 Conducted peak output Power 17

6.4 Minimum 6dB bandwidth 18

6.5 Power spectrum density 19

6.6 Conducted Band Edges Measurement 20

6.7 Conducted spurious emissions 22

6.8 Radiated spurious emissions 24

6.9 Radiated emissions which fall in the restricted bands 35

7 Appendix A 42

7.1 Duty Cycle 42

7.2 Maximum Conducted Output Power 46

7.3 -6dB Bandwidth 50

7.4 Occupied Channel Bandwidth 54

7.5 Maximum Power Spectral Density Level 58

BlueAsia

7.6 Band Edge 62
7.7 Conducted RF Spurious Emission 67

Appendix B: photographs of test setup 74

Appendix C: photographs of EUT 76

BlueAsia

Revise Record

Version No.	Date	Description
01	June 19, 2025	Original

BlueAsia

1 General information

1.1 General information

Applicant	Shenzhen Rurun Digital Technology Co., Ltd.
Address	2/F Jihe Comm Shenjing Ind Zone Huaqing Ave Qinghua Comm Longhua Dist Shenzhen Guangdong CHINA
Manufacturer	Shenzhen Rurun Digital Technology Co., Ltd.
Address	2/F Jihe Comm Shenjing Ind Zone Huaqing Ave Qinghua Comm Longhua Dist Shenzhen Guangdong CHINA
Factory	Shenzhen Rurun Digital Technology Co., Ltd.
Address	2/F Jihe Comm Shenjing Ind Zone Huaqing Ave Qinghua Comm Longhua Dist Shenzhen Guangdong CHINA

1.2 General description of EUT

Product name	Audio stand
Model no.	X7
Series model	N/A
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Rate data:	1Mbps; 2Mbps
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB antenna
Antenna Gain:	-0.58dBi(Provided by customer)
Power supply or adapter information	DC3.7V by battery
Hardware Version	V1.0
Software Version	V1.0
Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.	

BlueAsia

2 Test summary

No.	Test item	FCC standard	Test Method(Clause)	Result
1	Antenna Requirement	§15.203	N/A	Pass
2	Conducted Emissions at AC Power Line (150kHz-30MHz)	§15.207	ANSI C63.10-2013 Clause 6.2	Pass
3	Conducted Peak Output Power	§15.247(b)(3)	ANSI C63.10-2013 Clause 7.8.5	Pass
4	Minimum 6dB Bandwidth	§15.247a(2)	ANSI C63.10-2013 Clause 11.8.1	Pass
5	Power Spectrum Density	§15.247(d)	ANSI C63.10-2013 Clause 11.10.2	Pass
6	Conducted Band Edges Measurement	§15.247(d)	ANSI C63.10-2013 Clause 11.13	Pass
7	Conducted Spurious Emissions	§15.247(d)	ANSI C63.10-2013 Clause 11.11	Pass
8	Radiated Spurious Emissions	§15.209 §15.247(d)	ANSI C63.10-2013 Clause 6.4,6.5,6.6	Pass
9	Radiated Emissions which fall in the restricted bands	§15.209 §15.247(d)	ANSI C63.10-2013 Clause 11.12	Pass

BlueAsia

3 Test Configuration

3.1 Test mode

Test Mode [Note 1]	Description
TX	Keep the EUT in continuously transmitting with modulation mode.
RX	Keep the EUT in receiving mode
TX Low channel	Keep the EUT in continuously transmitting mode in low channel
TX middle channel	Keep the EUT in continuously transmitting mode in middle channel
TX high channel	Keep the EUT in continuously transmitting mode in high channel

Note 1: The EUT was configured to measure its highest possible emission and/or immunity level. The test modes were adapted according to the operation manual for use; the EUT was operated in the engineering mode [Note 2] to fix the TX or Rx frequency that was for the purpose of the measurements.

Note 2: Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

Power level setup in software			
Test Software Name	Fcc_Assist_1.0.2.2		
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	CH00	2402	TX level: default
	CH20	2442	
	CH40	2480	

Run Software



3.2 Operation Frequency each of channel

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	31	2462
1	2404	11	2424	21	2444	32	2464
2	2406	12	2426	22	2446	33	2466
3	2408	13	2428	23	2448	34	2468
4	2410	14	2430	23	2450	35	2470
5	2412	15	2432	24	2452	36	2472
6	2414	16	2434	25	2454	37	2474
7	2416	17	2436	26	2456	38	2476
8	2418	18	2438	29	2458	39	2478
9	2420	19	2440	30	2460	40	2480

3.3 Test channel

Channel	Frequency (MHz)
The lowest channel	2402
The middle channel	2442
The Highest channel	2480

3.4 Auxiliary equipment

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	Lenovo	E460C	N/A	From lab (No.BLA-ZC-BS-2022005)

Note:
"--" mean no any auxiliary device during testing.

3.5 Test environment

Environment	Temperature	Voltage
Normal	25°C	DC 3.7V

4 Laboratory information

4.1 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Address:	Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
CNAS accredited No.:	L9788
A2LA Cert. No.:	5071.01
FCC Designation No.:	CN1252
ISED CAB identifier No.:	CN0028
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

4.2 Measurement uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

Parameter	Expanded Uncertainty
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %

BlueAsia

5 Test equipment

Radiated Spurious Emissions (Below 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-002-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-002-02	Control room	966 control room	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-009	EMI receiver	ESR7	R&S	101199	2024/08/08	2025/08/07
BLA-EMC-043	Loop antenna	FMZB1519B	Schwarzbeck	00102	2024/06/29	2026/06/28
BLA-EMC-065	Broadband antenna	VULB9168	Schwarzbeck	01065P	2024/06/29	2026/06/27
BLA-XC-01	Coaxial Cable	N/A	BlueAsia	V01	N/A	N/A
BLA-XC-02	Coaxial Cable	N/A	BlueAsia	V02	N/A	N/A

Radiated Spurious Emissions (Above 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-001-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2023/11/16	2026/11/15
BLA-EMC-001-02	Control Room	966 control room	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-008	Spectrum	FSP40	R&S	100817	2024/08/08	2025/08/07
BLA-EMC-012	Broadband antenna	VULB9168	Schwarzbeck	00836 P:00227	2022/10/12	2025/10/11
BLA-EMC-013	Horn Antenna	BBHA9120D	Schwarzbeck	01892	2024/06/29	2026/06/28
BLA-EMC-014	Amplifier	PA_000318G-45	SKET	PA201804 3003	2024/08/08	2025/08/07
BLA-EMC-046	Filter bank	2.4G/5G Filter bank	SKET	N/A	2024/06/28	2025/06/27
BLA-EMC-061	Receiver	ESPI7	R&S	101477	2024/06/28	2025/06/27
BLA-EMC-066	Amplifier	LNPA_30M01 G-30	SKET	SK202106 0801	2024/06/28	2025/06/27
BLA-EMC-086	Amplifier	LNPA_18G40 G-50dB	SKET	SK202207 1301	2024/06/28	2025/06/27
BLA-EMC-087	Horn Antenna	BBHA 9170	Schwarzbeck	1106	2024/06/29	2026/06/28
BLA-XC-03	Coaxial Cable	N/A	BlueAsia	V03	N/A	N/A
BLA-XC-04	Coaxial Cable	N/A	BlueAsia	V04	N/A	N/A

BlueAsia

Conducted Emissions

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-003-001	Shield room	8*3*3	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-009	EMI receiver	ESR7	R&S	101199	2024/08/08	2025/08/07
BLA-EMC-011	LISN	ENV216	R&S	101372	2024/08/08	2025/08/07
BLA-EMC-033	Impedance transformer	DC-2GHz	DFXP	N/A	2024/06/28	2025/06/27
BLA-EMC-041	LISN	AT166-2	ATTEN	AKK1806000003	2024/08/08	2025/08/07
BLA-EMC-045	Impedance stable network	ISNT8-cat 6	TESEQ	53580	2024/08/08	2025/08/07
BLA-EMC-095	Single-channel vehicle artificial power network	NNBM 8124	Schwarzbeck	01045	2024/06/28	2025/06/27
BLA-EMC-096	Single-channel vehicle artificial power network	NNBM 8124	Schwarzbeck	01075	2024/06/28	2025/06/27
BLA-XC-05	Coaxial Cable	N/A	BlueAsia	V05	N/A	N/A

RF conducted

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-003-003	Shield room	5*3*3	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-016	Signal Generator	N5182A	Agilent	MY52420567	2024/06/28	2025/06/27
BLA-EMC-038	Spectrum	N9020A	Agilent	MY49100060	2024/08/08	2025/08/07
BLA-EMC-042	Power sensor	RPR3006W	DARE	14I00889SN042	2024/08/08	2025/08/07
BLA-EMC-044	Radio communication tester	CMW500	R&S	132429	2024/08/08	2025/08/07
BLA-EMC-064	Signal Generator	N5182B	KEYSIGHT	MY58108892	2024/06/28	2025/06/27
BLA-EMC-079	Spectrum	N9020A	Agilent	MY54420161	2024/08/08	2025/08/07
BLA-EMC-088	Audio Analyzer	ATS-1	Audio Precision	ATS141094	2024/06/28	2025/06/27

Test software

Software No.	Software Name	Manufacture	Software version	Test site
BLA-EMC-S001	EZ-EMC	EZ	EEMC-3A1+	RE(Below 1GHz)
BLA-EMC-S002	EZ-EMC	EZ	EEMC-3A1+	RE(Above 1GHz)
BLA-EMC-S003	EZ-EMC	EZ	EEMC-3A1+	CE
BLA-EMC-S010	MTS 8310	MW	2.0.0.0	RF

BlueAsia

6 Test result

6.1 Antenna requirement

Test Standard	47 CFR Part 15, Subpart C 15.203
Test Method	N/A

6.1.1 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of a so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -0.58 dBi.

BlueAsia

6.2 Conducted emissions at AC power line (150 kHz-30 MHz)

Test Standard	47 CFR Part 15, Subpart C 15.207
Test Method	ANSI C63.10-2013 Clause 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.2.1 Limit

Frequency of emission(MHz)	**Conducted limit(dBμV)**	
	Quasi-peak	**Average**
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

6.2.2 Test setup



Description of test setup connection:

a) *Connect the control PC to the receiver through a USB to GPIB cable;*

b) *The receiver is connected to the LISN through a coaxial line;*

c) *Connect the power port of LISN to the EUT.*

6.2.3 Procedure

1) The mains terminal disturbance voltage test was conducted in a shielded room.

2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

6.2.4 Test data

[Test mode: TX]; [Line: Line];[Power:AC120V/60Hz]



Site		Phase:	*L1*	Temperature:	(C)
Limit:	FCC Class B Conduction(QP)	Power:		Humidity:	%RH
EUT:	Wireless Speaker	Distance:	RBW: 9 KHz		
M/N:	X7		VBW: 30 KHz	Sweep Time: 100 ms	
Mode:	BLE-TX				
Note:					

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	cm	degree	Comment
1		0.2700	29.20	9.86	39.06	61.12	-22.06	QP			
2		0.2700	21.40	9.86	31.26	51.12	-19.86	AVG			
3		0.5060	38.52	9.83	48.35	56.00	-7.65	QP			
4	*	0.5060	28.82	9.83	38.65	46.00	-7.35	AVG			
5		0.9380	30.59	9.73	40.32	56.00	-15.68	QP			
6		0.9380	20.73	9.73	30.46	46.00	-15.54	AVG			
7		1.3700	28.36	9.84	38.20	56.00	-17.80	QP			
8		1.3700	18.96	9.84	28.80	46.00	-17.20	AVG			
9		2.5380	27.65	9.98	37.63	56.00	-18.37	QP			
10		2.5380	20.00	9.98	29.98	46.00	-16.02	AVG			
11		4.7660	25.61	10.17	35.78	56.00	-20.22	QP			
12		4.7660	17.56	10.17	27.73	46.00	-18.27	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESPI_1 Spectrum Analyzer: ESPI

Test Result: Pass

[Test mode: TX]; [Line: Neutral];[Power:AC120V/60Hz]

Conducted Emission Measurement

Project No.: CE Data :#5 2025/06/13



Site		Phase:	N	Temperature:	(C)
Limit:	FCC Class B Conduction(QP)	Power:		Humidity:	%RH
EUT:	Wireless Speaker	Distance:	RBW: 9 KHz		
M/N:	X7		VBW: 30 KHz	Sweep Time: 100 ms	
Mode:	BLE-TX				
Note:					

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	cm	degree	Comment
1		0.2580	25.77	9.77	35.54	61.50	-25.96	QP			
2		0.2580	20.51	9.77	30.28	51.50	-21.22	AVG			
3		0.5060	36.08	9.79	45.87	56.00	-10.13	QP			
4	*	0.5060	30.21	9.79	40.00	46.00	-6.00	AVG			
5		0.8380	29.13	9.66	38.79	56.00	-17.21	QP			
6		0.8380	23.54	9.66	33.20	46.00	-12.80	AVG			
7		1.9140	25.31	9.82	35.13	56.00	-20.87	QP			
8		1.9140	18.83	9.82	28.65	46.00	-17.35	AVG			
9		3.1580	22.68	9.96	32.64	56.00	-23.36	QP			
10		3.1580	17.28	9.96	27.24	46.00	-18.76	AVG			
11		5.3140	21.35	10.14	31.49	60.00	-28.51	QP			
12		5.3140	15.09	10.14	25.23	50.00	-24.77	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESPI_1 Spectrum Analyzer: ESPI

Test Result: Pass

6.3 Conducted peak output Power

Test Standard	47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method	ANSI C63.10-2013 Clause 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.3.1 Limit

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

6.3.2 Test setup



6.3.3 Test data

Pass: Please refer to appendix A for details

6.4 Minimum 6dB bandwidth

Test Standard	47 CFR Part 15, Subpart C 15.247a(2)
Test Method	ANSI C63.10-2013 Clause 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.4.1 Limit

≥500 kHz

6.4.2 Test setup



6.4.3 Test data

Pass: Please refer to appendix A for details

6.5 Power spectrum density

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.5.1 Limit

≤8dBm in any 3 kHz band during any time interval of continuous transmission

6.5.2 Test setup



6.5.3 Test data

Pass: Please refer to appendix A for details

6.6 Conducted Band Edges Measurement

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 11.13
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.
If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.
Attenuation below the general limits specified in §15.209(a) is not required.
In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.6.2 Test setup



6.6.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.7 Conducted spurious emissions

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.7.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.
If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.
Attenuation below the general limits specified in §15.209(a) is not required.
In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.7.2 Test setup



6.7.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.8 Radiated spurious emissions

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.8.1 Limit

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

6.8.2 Test setup

Below 1GHz：



30MHz-1GHz：



Above 1GHz：



6.8.3 Procedure

a) For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b) For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

c) The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

d) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

e) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

f) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

g) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h) Test the EUT in the lowest channel, the middle channel, the highest channel.

i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.

j) Repeat above procedures until all frequencies measured was complete.

Note 1: Scan from 9 kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.

Note 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Note 3: The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Level (dBuV) = Reading (dBuV) + Factor (dB/m)

6.8.4 Test data

Below 1GHz

[Test mode: TX]; [Polarity: Horizontal]



Site
Limit: FCC Part15 Class B
EUT: Wireless Speaker
M/N: X7
Mode: BLE-TX
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	50.7636	-1.53	19.82	18.29	40.00	-21.71	QP	P	
2	161.4740	-1.61	20.37	18.76	43.50	-24.74	QP	P	
3	273.2340	-2.56	18.95	16.39	46.00	-29.61	QP	P	
4	400.4318	-0.95	23.17	22.22	46.00	-23.78	QP	P	
5	729.3582	0.29	29.00	29.29	46.00	-16.71	QP	P	
6 *	922.5157	0.26	31.37	31.63	46.00	-14.37	QP	P	

Test Result: Pass

[Test mode: TX]; [Polarity: Vertical]



Site
Limit: FCC Part15 Class B
EUT: Wireless Speaker
M/N: X7
Mode: BLE-TX
Note:

Polarization: ***Vertical***
Power:

Temperature: (C)
Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	50.9419	-0.71	19.82	19.11	40.00	-20.89	QP	P	
2	158.6677	-0.55	20.51	19.96	43.50	-23.54	QP	P	
3	286.9823	-1.31	19.57	18.26	46.00	-27.74	QP	P	
4	379.9141	-1.61	22.47	20.86	46.00	-25.14	QP	P	
5	625.0780	-0.18	27.72	27.54	46.00	-18.46	QP	P	
6 *	875.2469	1.00	30.58	31.58	46.00	-14.42	QP	P	

*:Maximum data x:Over limit !:over margin

Test Result: Pass

Above 1GHz:

Remark: During the test, pre-scan the BLE1M/BLE2M mode, and found the BLE1M mode which it is worse case.

[Test mode: TX low channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: REH Data :#13 2025/6/17

Site
Limit: FCC Part15 (PK)
EUT: Wireless Speaker
M/N: X7
Mode: BLE-TX-2402
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5641.250	39.31	7.83	47.14	74.00	-26.86	peak	
2		6745.750	37.66	9.08	46.74	74.00	-27.26	peak	
3		7967.750	38.46	11.41	49.87	74.00	-24.13	peak	
4		8931.250	38.76	12.19	50.95	74.00	-23.05	peak	
5		10529.25	37.26	13.71	50.97	74.00	-23.03	peak	
6	*	11622.00	37.56	14.48	52.04	74.00	-21.96	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESR_1 Spectrum Analyzer: FSP40

Test Result: Pass

[Test mode: TX low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Speaker
M/N: X7
Mode: BLE-TX-2402
Note:

Polarization: ***Vertical***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5488.500	39.17	8.42	47.59	74.00	-26.41	peak	
2		6522.500	39.20	8.45	47.65	74.00	-26.35	peak	
3		7967.750	38.46	11.41	49.87	74.00	-24.13	peak	
4		8907.750	37.05	12.57	49.62	74.00	-24.38	peak	
5		9953.500	36.83	13.22	50.05	74.00	-23.95	peak	
6	*	11375.25	36.61	13.99	50.60	74.00	-23.40	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESR_1 Spectrum Analyzer: FSP40

Test Result: Pass