Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

47 CFR Part 15, Subpart C 15.247

Report Reference No......: **CTL2505142051-WF**

Compiled by: (position+printed name+signature)	Happy Guo (File administrators)	Happy Guo
Tested by: (position+printed name+signature)	Lynn Tang (Test Engineer)	Lynn Tang
Approved by: (position+printed name+signature)	Ivan Xie (Manager)	Ivan Xie

Product Name..... :	Smart Luggage
Model/Type reference.....:	ES07X
List Model(s) .....:	ES06
Trade Mark..... :	BEKE
FCC ID..... :	**2BP4K-ES**
Applicant's name..... :	**Guangzhou Pinshun Medical Robot Co., Ltd**
Address of applicant.....:	Room 602, Building A, No. 17, Xicheng MiddleStreet,Huangpu District, Guangzhou City, China
Test Firm.....:	**Shenzhen CTL Testing Technology Co., Ltd.**
Address of Test Firm.....:	Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055
Test specification.....:	
Standard.....:	**47 CFR Part 15, Subpart C 15.247:** Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.
TRF Originator.....:	Shenzhen CTL Testing Technology Co., Ltd.
Master TRF..... :	Dated 2011-01
Date of receipt of test item..... :	June 4, 2025
Date of Test Date.....:	June 4, 2025-June 18, 2025
Date of Issue.....:	June 19, 2025
Result..... :	**Pass**

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2505142051-WF	June 19, 2025 Date of issue

Equipment under Test	:	Smart Luggage
Sample No	:	CTL2505142051
Model /Type	:	ES07X
Listed Models	:	ES06
Applicant	:	**Guangzhou Pinshun Medical Robot Co., Ltd**
Address	:	Room 602, Building A, No. 17, Xicheng MiddleStreet,Huangpu District, Guangzhou City, China
Manufacturer	:	**Guangzhou Pinshun Medical Robot Co., Ltd**
Address	:	Room 602, Building A, No. 17, Xicheng MiddleStreet,Huangpu District, Guangzhou City, China

Test result	**Pass ***

* In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

** Modified History **

Revisions	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	June 19, 2025	CTL2505142051-WF	Tracy Qi

Table of Contents Page

1. SUMMARY 5

1.1. TEST STANDARDS 5
1.2. TEST DESCRIPTION 5
1.3. TEST FACILITY 6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY 6
1.5. AUXILIARY EQUIPMENT INFORMATION 7

2. GENERAL INFORMATION 8

2.1. ENVIRONMENTAL CONDITIONS 8
2.2. GENERAL DESCRIPTION OF EUT 8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY 9
2.4. EQUIPMENTS USED DURING THE TEST 10
2.5. RELATED SUBMITTAL(S) / GRANT (S) 10
2.6. MODIFICATIONS 10

3. TEST CONDITIONS AND RESULTS 11

3.1. CONDUCTED EMISSIONS TEST 11
3.2. RADIATED EMISSIONS AND BAND EDGE 14
3.3. MAXIMUM CONDUCTED OUTPUT POWER 24
3.4. POWER SPECTRAL DENSITY 25
3.5. 6DB BANDWIDTH 26
3.6. OUT-OF-BAND EMISSIONS 27
3.7. ANTENNA REQUIREMENT 28

4. TEST SETUP PHOTOS OF THE EUT 29

5. PHOTOS OF THE EUT 31

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:
47 CFR Part 15, Subpart C 15.247 Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

ANSI C63.10: 2013: American National Standard for Testing Unlicensed Wireless Devices

KDB 558074 D01 v05r02: KDB558074 D01 15.247 Meas Guidance v05r02

1.2. Test Description

47 CFR Part 15, Subpart C 15.247		
47 CFR Part 15, Subpart C 15.207	AC Power Conducted Emission	PASS
47 CFR Part 15, Subpart C 15.247(a)(2)	6dB Bandwidth	PASS
47 CFR Part 15, Subpart C 15.247(d)	Spurious RF Conducted Emission	PASS
47 CFR Part 15, Subpart C 15.247(b)	Maximum Conducted Output Power	PASS
47 CFR Part 15, Subpart C 15.247(e)	Power Spectral Density	PASS
47 CFR Part 15, Subpart C 15.109/15.205/15.209	Radiated Emissions	PASS
47 CFR Part 15, Subpart C 15.247(d)	Band Edge	PASS
47 CFR Part 15, Subpart C 15.203/15.247 (b)	Antenna Requirement	PASS

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co.,Ltd.
Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.10 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.
Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power Radiated	±2.20 dB	(1)
Radiated Emission 9kHz~30MHz	±3.66dB	(1)
Radiated Emission 30~1000MHz	±4.08dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
DTS Bandwidth	±1.9%	(1)
Maximum Conducted Output Power	± 1.18 dB	(1)
Maximum Power Spectral Density Level	±0.98 dB	(1)

Band-edge	±1.21dB	(1)
Unwanted Emissions In Non-restricted Freq Bands	9kHz-7GHz:±1.09dB 7GHz-26.5GHz: ±3.27dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

1.5. Auxiliary equipment information

Manufacturer	Description	Model	Parameters
SHENZHEN XIN HENG TYCO ELECTRONCS CO., LTD	AC/DC Charge	BS05A-0501000US	Input: 100-240V~50/60Hz 1.5A Max Output: 42.0V⎓1.0A

Note: This adapter is provided by the applicant and is shipped together with the Smart Luggage.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	Smart Luggage
Model/Type reference:	ES07X
EUT Rated Voltage:	DC 36.5V from battery or DC 42V/1A from adapter
Test Voltage:	DC 36.5V from battery or DC 42V/1A from adapter
Bluetooth Low Energy	
Supported type:	Bluetooth Low Energy
Modulation:	GFSK
Operation frequency:	2402MHz to 2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	PCB Antenna
Antenna gain:	-0.58dBi

Note1: For more details, please refer to the user's manual of the EUT.
Note2: Antenna gain provided by the applicant.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

There are 40 channels provided to the EUT and Channel 00/19/39 were selected for Bluetooth Low Energy test.

Operation Frequency List：

Channel	Frequency (MHz)
00	**2402**
02	2404
03	2406
⋮	⋮
19	**2440**
⋮	⋮
37	2476
38	2478
39	**2480**

Note: The line display in grey were the channel selected for testing

Software Version: FCC_assist_1.0.2.2.exe	
Test Mode	Power level
BLE 1M	10
BLE 2M	10

2.4. Equipments Used during the Test

Conducted Emission						
Test Equipment	Manufacturer	Model No.	Serial No.	Previous calibration	Last Cal.	Cal.Due
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2024/04/30	2025/04/29	2026/04/28
LISN	ROHDE & SCHWARZ	ESH2-Z5	860014/010	2024/04/30	2025/04/29	2026/04/28
Limitator	ROHDE & SCHWARZ	ESH3-Z2	100408	2024/04/30	2025/04/29	2026/04/28
Software:						
Name of Software:			Version:			
ES-K1			V1.71			

Radiated Emission						
Test Equipment	Manufacturer	Model No.	Serial No.	Previous calibration	Last Cal.	Cal.Due
Active Loop Antenna	Da Ze	ZN30900A	/	2021/05/13	2024/04/30	2027/04/29
Double cone logarithmic antenna	Schwarzbeck	VULB 9168	824	2020/04/07	2023/02/13	2026/02/12
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2021/12/23	2024/11/25	2027/11/24
Horn Antenna	Ocean Microwave	OBH100400	26999002	2022/02/22	2025/02/21	2028/02/20
Amplifier	MRT-AP01M06	MRT	S-001	2024/04/30	2025/04/29	2026/04/28
Amplifier	Brief&Smart	LNA-4018	2104197	2024/05/03	2025/05/02	2026/04/29
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2024/04/30	2025/04/29	2026/04/28
Spectrum Analyzer	RS	FSP	1164.4391.38	2024/05/03	2025/05/02	2026/04/28
Software:						
Name of Software:			Version:			
EZ_EMC(Below 1GHz)			V1.1.4.2			
EZ_EMC(Above 1GHz)			V1.1.4.2			

RF Conducted						
Test Equipment	Manufacturer	Model No.	Serial No.	Previous calibration	Last Cal.	Cal.Due
Spectrum Analyzer	Keysight	N9020A	MY53420874	2024/05/01	2025/04/30	2026/04/28
Temperature/Humidity Meter	Ji Yu	MC501	/	2024/05/04	2025/05/03	2026/05/05
Software:						
Name of Software:			Version:			
TST-PASS			V2.0			

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.1 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Remark: The following data is the battery charging mode data.

Line:	L1

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL250607001_fin"

6/7/2025 3:56PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.199500	55.00	10.0	64	8.6	QP	L1	GND
0.253500	49.30	10.0	62	12.3	QP	L1	GND
0.316500	44.40	10.0	60	15.4	QP	L1	GND
0.469500	40.10	10.0	57	16.4	QP	L1	GND
0.559500	39.90	10.0	56	16.1	QP	L1	GND
25.665000	40.80	10.5	60	19.2	QP	L1	GND

MEASUREMENT RESULT: "CTL250607001_fin2"

6/7/2025 3:56PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.199500	42.40	10.0	54	11.2	AV	L1	GND
0.267000	35.80	10.0	51	15.4	AV	L1	GND
0.330000	33.40	10.0	50	16.1	AV	L1	GND
0.469500	29.90	10.0	47	16.6	AV	L1	GND
2.292000	27.10	10.1	46	18.9	AV	L1	GND
4.663500	28.70	10.1	46	17.3	AV	L1	GND

Line:	N

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL250607006_fin"

6/7/2025 4:07PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.195000	49.30	10.0	64	14.5	QP	N	GND
0.208500	45.50	10.0	63	17.8	QP	N	GND
0.559500	38.80	10.0	56	17.2	QP	N	GND
4.393500	39.20	10.1	56	16.8	QP	N	GND
25.669500	44.10	10.5	60	15.9	QP	N	GND
25.957500	40.40	10.5	60	19.6	QP	N	GND

MEASUREMENT RESULT: "CTL250607006_fin2"

6/7/2025 4:07PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.199500	41.60	10.0	54	12.0	AV	N	GND
0.262500	33.00	10.0	51	18.4	AV	N	GND
0.465000	28.00	10.0	47	18.6	AV	N	GND
4.407000	32.40	10.1	46	13.6	AV	N	GND
7.264500	30.10	10.3	50	19.9	AV	N	GND
14.923500	30.70	11.1	50	19.3	AV	N	GND

3.2. Radiated Emissions and Band Edge

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(kHz))+40log(300/3)	2400/F(kHz)
0.49-1.705	3	20log(24000/F(kHz))+ 40log(30/3)	24000/F(kHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



Below 30MHz

(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



Below 1GHz

(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Above 1GHz

Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.1m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 0.1m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

TEST RESULTS

Remark:
1. For below 1GHz testing recorded worst at Bluetooth Low Energy 2M low channel.
2. For above 1GHz testing recorded worst at Bluetooth Low Energy 2M low channel.
3. Radiated emission test from 9 kHz to 10th harmonic of fundamental was verified, Found the emission level are attenuated 20dB below the limits from 9 kHz to 30MHz, so it does not recorded in report.

For 30MHz-1GHz

Horizontal

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#935 Date: 2025/06/17 Time: 16:21:02



Site LAB Chamber 2
Limit: FCC Part15 RE-Class C_30-1000MHz
EUT:
M/N:
Mode: BLE2M 2402MHz
Note: CTL2505142051-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	651.3704	7.07	22.57	29.64	46.00	16.36	peak	100	38	P	
2	689.8667	7.20	22.74	29.94	46.00	16.06	peak	100	10	P	
3	763.7103	7.59	24.84	32.43	46.00	13.57	peak	100	236	P	
4	840.6544	7.11	26.21	33.32	46.00	12.68	peak	100	236	P	
5	894.6405	7.01	26.40	33.41	46.00	12.59	peak	100	10	P	
6	961.3191	7.24	27.23	34.47	54.00	19.53	peak	100	278	P	

Vertical

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#936 Date: 2025/06/17 Time: 16:21:52



Site LAB Chamber 2
Limit: FCC Part15 RE-Class C_30-1000MHz
EUT:
M/N:
Mode: BLE2M 2402MHz
Note: CTL2505142051-WF

Polarization: ***Vertical***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	673.1395	8.17	22.61	30.78	46.00	15.22	peak	100	279	P	
2	744.2134	7.22	24.12	31.34	46.00	14.66	peak	100	279	P	
3	812.3991	7.47	25.91	33.38	46.00	12.62	peak	100	25	P	
4	849.5445	7.75	26.23	33.98	46.00	12.02	peak	100	335	P	
5	912.8620	6.69	26.70	33.39	46.00	12.61	peak	100	293	P	
6	943.7838	6.53	27.10	33.63	46.00	12.37	peak	100	38	P	

For 1GHz to 25GHz

Horizontal

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#465 Date: 2025/06/07 Time: 20:11:14



Site LAB Chamber 2 Polarization: ***Horizontal*** Temperature: 25(C)
Limit: FCC Part15 RE-Class C_Above 1GHz_PK Power: Humidity: 50 %
EUT: Distance: 3m
M/N:
Mode: BLE2M 2402MHz TX
Note: CTL2505142051-WF

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4485.000	48.86	-8.56	40.30	74.00	33.70	peak	150	257	P	
2	5747.250	48.48	-6.61	41.87	74.00	32.13	peak	150	360	P	
3	9602.000	48.33	0.45	48.78	74.00	25.22	peak	150	286	P	
4	12033.000	48.34	2.19	50.53	74.00	23.47	peak	150	286	P	
5	13743.625	49.44	3.83	53.27	74.00	20.73	peak	150	86	P	
6	16803.625	46.29	6.58	52.87	74.00	21.13	peak	150	29	P	

Vertical

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#466 Date: 2025/06/07 Time: 20:12:05



Site LAB Chamber 2
Limit: FCC Part15 RE-Class C_Above 1GHz_PK
EUT:
M/N:
Mode: BLE2M 2402MHz TX
Note: CTL2505142051-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4323.500	49.61	-9.10	40.51	74.00	33.49	peak	150	332	P	
2	7360.125	47.18	-2.85	44.33	74.00	29.67	peak	150	18	P	
3	9389.500	46.98	0.20	47.18	74.00	26.82	peak	150	346	P	
4	12020.250	47.39	2.20	49.59	74.00	24.41	peak	150	74	P	
5	13750.000	48.74	3.82	52.56	74.00	21.44	peak	150	18	P	
6	16786.625	45.57	6.55	52.12	74.00	21.88	peak	150	175	P	

EMARKS:

1. 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.
2. PK detector measurement value is lower than the average limit. Therefore, there is no need to test AV detector measurements.

Results of Band Edges Test (Radiated)

Remark: Both Bluetooth Low Energy 1M and Bluetooth Low Energy 2M were tested, but only the worst data of Bluetooth Low Energy 2M was reflected.

CH00	Horizontal

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#479 Date: 2025/06/07 Time: 20:41:37



Site LAB Chamber 2
Limit: FCC Part 15 C
EUT:
M/N:
Mode: BLE2M 2402MHz TX
Note: CTL2505142051-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	24.23	34.57	58.80	74.00	15.20	peak	150	360	P	
2	2310.000	13.88	34.57	48.45	54.00	5.55	AVG	150	360	P	
3	2390.000	25.41	34.75	60.16	74.00	13.84	peak	150	360	P	
4	2390.000	14.79	34.75	49.54	54.00	4.46	AVG	150	360	P	

CH00	Vertical

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#478 Date: 2025/06/07 Time: 20:40:36



Site LAB Chamber 2
Limit: FCC Part 15 C
EUT:
M/N:
Mode: BLE2M 2402MHz TX
Note: CTL2505142051-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	25.18	34.57	59.75	74.00	14.25	peak	150	0	P	
2	2310.000	14.02	34.57	48.59	54.00	5.41	AVG	150	0	P	
3	2390.000	25.18	34.75	59.93	74.00	14.07	peak	150	0	P	
4	2390.000	14.31	34.75	49.06	54.00	4.94	AVG	150	0	P	

CH39	Horizontal

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#480 Date: 2025/06/07 Time: 20:44:01



Site LAB Chamber 2
Limit: FCC Part 15 C
EUT:
M/N:
Mode: BLE2M 2480MHz TX
Note: CTL2505142051-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	25.31	35.03	60.34	74.00	13.66	peak	150	0	P	
2	2483.500	15.60	35.03	50.63	54.00	3.37	AVG	150	0	P	
3	2500.000	25.07	35.12	60.19	74.00	13.81	peak	150	0	P	
4	2500.000	13.66	35.12	48.78	54.00	5.22	AVG	150	0	P	

CH39	Vertical

Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194

Radiated Emission Measurement

File :RF_6 Data :#481 Date: 2025/06/07 Time: 20:45:12



Site LAB Chamber 2
Limit: FCC Part 15 C
EUT:
M/N:
Mode: BLE2M 2480MHz TX
Note: CTL2505142051-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	24.96	35.03	59.99	74.00	14.01	peak	150	360	P	
2	2483.500	15.06	35.03	50.09	54.00	3.91	AVG	150	360	P	
3	2500.000	24.76	35.12	59.88	74.00	14.12	peak	150	360	P	
4	2500.000	13.60	35.12	48.72	54.00	5.28	AVG	150	360	P	

3.3. Maximum Conducted Output Power

Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.

a) Set the RBW⩾DTS bandwidth.

b) Set VBW⩾[3×RBW].

c) Set span⩾[3×RBW].

d) Sweep time = auto couple.

e) Detector=peak.

f) Trace mode=max hold.

g) Allow trace to fully stabilize.

h) Use peak marker function to determine the peak amplitude level.

Test Configuration



Test Results

Raw data reference to Section 3 of document No. CTL2505142051-WF_Bluetooth Low Energy_Appendix.

3.4. Power Spectral Density

Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW ≥ 3× RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

Test Configuration

Test Results

Raw data reference to Section 4 of document No. CTL2505142051-WF_Bluetooth Low Energy_Appendix.

3.5. 6dB Bandwidth

Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

Test Configuration

Test Results

Raw data reference to Section 2 of document No. CTL2505142051-WF_Bluetooth Low Energy_Appendix.

3.6. Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF con-ducted or a radiated measurement, pro-vided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter com-plies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration

Test Results

Raw data reference to Section 5 of document No. CTL2505142051-WF_Bluetooth Low Energy_Appendix.

3.7. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(b) (4):

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Result:

The maximum gain of antenna was -0.58dBi.



4. Test Setup Photos of the EUT








TST PASS
Max23dBm
PORT1
PORT2
PORT4
Companion Device
POWER

5. Photos of the EUT

External Photos of EUT

BEKE
BEKE

BEKE
BEKE



POWER BANK
BEKE
RoHS MSDS UN38.3

AC/DC Charger
MODEL:XHK-922-42010
INPUT: 100V-240V~,
50/60Hz,1.5A(Max.)
OUTPUT: 42.0V ⎓ 1.0A
RED LIGHT MEANS CHARGING
GREEN LIGHT MEANS CHARGE.
FULL OR DISCONNECT
before charging,read the Instructions;
FABRICANT:
SHENZHEN XIN HENG TYCO ELECTRONICS CO., LTD
502, 4 Building, Pengfa 2nd Industrial Park, Fuming Community,
Fuhheng Street, Longhua District, Shenzhen, Guangdong, China
MADE IN CHINA

Internal Photos of EUT






X5-FY1-PCB-V1
00.18.0.00593
LENZOD
10 millimetres (mm) = 1 centimetre (cm)


10 millimetres (mm) = 1 centim