



**CFR 47 FCC PART 15 SUBPART C
RSS-247 Issue 4**

TEST REPORT

For

Laser Cutter And Engraver

**MODEL NUMBER: Creality Falcon A1C, Creality Falcon A1C 10W,
Creality Falcon A1C 5W, Creality Falcon A1C 5W+1.2W**

REPORT NUMBER: E04A26041085F00402

ISSUE DATE: July 24, 2026

FCC ID: 2BP7M-FALCONA1C

IC: 34222-FALCONA1C

Prepared for

**Shenzhen Creality Ecosystem Technology Co., Ltd
Room 1205, JinXiuHongDu Building, Meilong Blvd., Longhua Dist., Shenzhen,
China 518131**

Prepared by

Guangdong Global Testing Technology Co., Ltd.

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park,
Dongguan city, Guangdong, People's Republic of China, 523808**

**This report is based on a single evaluation of the submitted sample(s) of the above mentioned product, it does not imply an assessment of the production of the products.
This report shall not be reproduced, except in full, without the written approval of
Guangdong Global Testing Technology Co., Ltd.**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	July 24, 2026	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2020, Clause 11.9.2.3.2	FCC Part 15.247 (b)(3) RSS-247 Clause 6.3.2	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2020, Clause 11.8.1 or 11.8.2	FCC Part 15.247 (a)(2) RSS-247 Clause 6.3.1(a) ISED RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2020, Clause 11.10.5	FCC Part 15.247 (e) RSS-247 Clause 6.3.1(b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2020, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 6.6	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2020, Clause 11.12	FCC Part 15.247(d) FCC Part 15.205/15.209 RSS-247 Clause 6.6 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2020, Clause 11.6	None; for reporting purposes only.	Pass

Note:

1. This report is also performed according to ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 standards.
2. N/A: In this whole report not applicable.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C, RSS-247 Issue 4> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>MAXIMUM CONDUCTED OUTPUT POWER.....</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>9</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>9</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>10</i>
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>10</i>
5.8. <i>SETUP DIAGRAM</i>	<i>11</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	12
7. ANTENNA PORT TEST RESULTS	14
7.1. <i>Conducted Output Power.....</i>	<i>14</i>
7.2. <i>6dB Bandwidth and 99% Occupied Bandwidth</i>	<i>15</i>
7.3. <i>Power Spectral Density.....</i>	<i>17</i>
7.4. <i>Conducted Band edge and spurious emission</i>	<i>18</i>
7.5. <i>Duty Cycle</i>	<i>20</i>
8. RADIATED TEST RESULTS	21
8.1. <i>Radiated Band edge and Spurious Emission</i>	<i>28</i>
9. ANTENNA REQUIREMENT	50
10. AC POWER LINE CONDUCTED EMISSION	52

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Shenzhen Creality Ecosystem Technology Co., Ltd
Address: Room 1205, JinXiuHongDu Building, Meilong Blvd., Longhua Dist., Shenzhen, China 518131

Manufacturer Information

Company Name: Shenzhen Creality Ecosystem Technology Co., Ltd
Address: Room 1205, JinXiuHongDu Building, Meilong Blvd., Longhua Dist., Shenzhen, China 518131

EUT Information

Product Description: Laser Cutter And Engraver
Model: Creality Falcon A1C
Series Model: Creality Falcon A1C 10W, Creality Falcon A1C 5W, Creality Falcon A1C 5W+1.2W
Brand: 
Sample Received Date: May 28, 2026
Sample Status: Normal
Sample ID: A26041085 001
Date of Tested: May 28, 2026 to July 22, 2026

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C RSS-247 Issue 4	Pass

Prepared By:


Jek Chang

Project Engineer

Approved By:


Alan He

Alan He

Laboratory Manager

Checked By:


Alan He

Alan He

Laboratory Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 4, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, CFR 47 FCC Part 2, ANSI C63.10-2020, ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 and ISED RSS-GEN Issue 5

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 6947.01) Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1343) Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules ISED (Company No.: 30714) Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.		

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.			

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name		Laser Cutter And Engraver										
Model		Creality Falcon A1C										
Series Model		Creality Falcon A1C 10W, Creality Falcon A1C 5W, Creality Falcon A1C 5W+1.2W										
Model Difference		The difference of the models are laser module, others are the same. When selling the product, there are various combinations of laser modules available. Refer to the following table in detail.										
		<table><tr><td>Model</td><td>laser module</td></tr><tr><td>Creality Falcon A1C</td><td>1.2W laser module</td></tr><tr><td>Creality Falcon A1C 10W</td><td>10W laser module</td></tr><tr><td>Creality Falcon A1C 5W</td><td>5W laser module</td></tr><tr><td>Creality Falcon A1C 5W+1.2W</td><td>5W laser module and 1.2W laser module</td></tr></table>	Model	laser module	Creality Falcon A1C	1.2W laser module	Creality Falcon A1C 10W	10W laser module	Creality Falcon A1C 5W	5W laser module	Creality Falcon A1C 5W+1.2W	5W laser module and 1.2W laser module
		Model	laser module									
		Creality Falcon A1C	1.2W laser module									
		Creality Falcon A1C 10W	10W laser module									
		Creality Falcon A1C 5W	5W laser module									
Creality Falcon A1C 5W+1.2W	5W laser module and 1.2W laser module											
When the product is operating normally, only one laser module is required. Creality Falcon A1C 5W uses adapter2, while other models use adapter1.												
Hardware Version		V1.0										
Software Version		V1.0										
Adapter1 Ratings		MODEL: AK120WG-2400500W1 INPUT: 100-240V~ 50/60Hz 2.0A OUTPUT: 24.0V===5.0A 120.0W										
Adapter2 Ratings		MODEL: AK65WG-2400300W1 INPUT: 100-240V~ 50/60Hz 1.5A OUTPUT: 24.0V===3.0A 72.0W										
Power Supply	AC	120V/60Hz										
	DC	24V										

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7 IEEE 802.11n-HT40: Up to MCS7
Number of Channels:	IEEE 802.11b/g/n-HT20: 11 IEEE 802.11n-HT40: 7
Normal Test Voltage:	AC 120V/60Hz
Note:	1. The Antenna Gain was provided by customer, and this information may affect the validity of the results, customer should be responsible for this.

5.2. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.3. MAXIMUM CONDUCTED OUTPUT POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted Output Power (dBm)	Maximum EIRP (dBm)
b	2412 ~ 2462	1-11[11]	16.33	18.21
g	2412 ~ 2462	1-11[11]	15.38	17.26
n HT20	2412 ~ 2462	1-11[11]	14.44	16.32
n HT40	2422 ~ 2452	3-9[7]	14.48	16.36

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		EspRFTTestTool_v4.7_Manual					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	12	12	12	/		
802.11g	1	14	14	14			
802.11n HT20	1	14	14	14			

802.11n HT40	1	/	14	14	14
--------------	---	---	----	----	----

WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	FPC	1.88


Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ TX, RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ TX, RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ TX, RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	☒ TX, RX	ANT 1 can be used as transmitting/receiving antenna.

5.7. SUPPORT UNITS FOR SYSTEM TEST


No.	Equipment	Manufacturer	Model No.	Serial No.
1	PC	Lenovo	T14	/
2	Adapter	Shenzhen Guijin Technology Co.,Ltd.	AK120WG-2400500W1	/
3	Adapter	Shenzhen Guijin Technology Co.,Ltd.	AK65WG-2400300W1	/

5.8. SETUP DIAGRAM


AC conducted emission:



Radiated Emission:



RF conducted:



6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2025/08/25	2026/08/24
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2025/08/25	2026/08/24
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2025/08/25	2026/08/24
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2025/08/25	2026/08/24
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2025/08/25	2026/08/24
temperature humidity chamber	Espec	SH-241	SH-241-2014	2025/08/25	2026/08/24
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESCI3	101144	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2025/08/23	2026/08/22
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2025/09/20	2028/09/19
Biconilog Antenna	ETS	3142E	00243651	2025/02/22	2028/02/21
Loop Antenna	ETS	6502	00243668	2025/02/22	2028/02/21
RF Cable	TIMES Microwave	LMR240UF-NMMN-14M	N/A	2025/08/23	2026/08/22
RF Cable	TIMES Microwave	HF205-NMMN-11.00M	N/A	2025/08/23	2026/08/22
RF Cable	JCT	JCT-06S-NJ-NJ-2.5M	N/A	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2025/08/23	2026/08/22
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-1G1850	HYPA21003	2025/08/23	2026/08/22

Horn antenna	ETS	3117	00246069	2025/02/22	2028/02/21
Pre-Amplifier	HzEMC	HPA-184057	HYP A21004	2025/08/23	2026/08/22
Horn antenna	ETS	3116C	00246265	2025/02/22	2028/02/21
RF Filter Bank	HzEMC	HSW-F18	HSWF2218E01	2025/08/23	2026/08/22
RF Filter Bank	HzEMC	HPF18	HPF2218E02	2025/08/23	2026/08/22
RF Cable	TIMES Microwave	HF205-NMNM- 7.00M	N/A	2025/08/23	2026/08/22
RF Cable	TIMES Microwave	HF205-NMNM- 2.50M	N/A	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2025/08/23	2026/08/22
LISN/AMN	Rohde & Schwarz	ENV216	102843	2025/08/23	2026/08/22
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC Part 15.247 (b)(3) RSS-247 Clause 6.3.2	Conduct Output Power	1 watt or 30 dBm	2400-2483.5


TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.9.2.3.2

Connect the EUT to a low loss RF cable from the antenna port to the power sensor and meter or Spectrum analyzer (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	46%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to Appendix B

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC Part 15.247 (a)(2) RSS-247 Clause 6.3.1(a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 11.8.1 or 11.8.2 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission or The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100$ kHz, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement.

TEST SETUP**TEST ENVIRONMENT**

Temperature	25°C	Relative Humidity	46%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to Appendix B

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC Part 15.247 (e) RSS-247 Clause 6.3.1(b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Avg
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	46%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to Appendix B

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4		
Section	Test Item	Limit
FCC Part 15.247(d) RSS-247 Clause 6.6	Conducted Band edge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.11.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

Temperature	25°C	Relative Humidity	46%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to Appendix B

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	46%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to Appendix B

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands ^{Note 1}		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1G

The setting of the spectrum analyzer




RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST SETUP

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	58%
Atmosphere Pressure	101kPa		

TEST RESULTS


8.1. RADIATED BAND EDGE AND SPURIOUS EMISSION

Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)

All modes have been tested and the worst result as bellow:

1.2W laser module(adapter1)

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	49.40	40.66	22.13	-18.53	40.00	17.87	PK	Vertical	PASS
2	140.58	36.93	18.65	-18.28	43.50	24.85	PK	Vertical	PASS
3	256.98	39.95	19.81	-20.14	46.00	26.19	PK	Vertical	PASS
4	297.72	38.74	19.97	-18.77	46.00	26.03	PK	Vertical	PASS
5	374.35	34.90	18.32	-16.58	46.00	27.68	PK	Vertical	PASS
6	944.71	29.82	25.52	-4.30	46.00	20.48	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	154.16	36.74	18.65	-18.09	43.50	24.85	PK	Horizontal	PASS
2	248.25	46.32	26.03	-20.29	46.00	19.97	PK	Horizontal	PASS
3	300.63	45.26	26.62	-18.64	46.00	19.38	PK	Horizontal	PASS
4	395.69	35.56	19.80	-15.76	46.00	26.20	PK	Horizontal	PASS
5	853.53	29.75	23.51	-6.24	46.00	22.49	PK	Horizontal	PASS
6	983.51	29.84	25.87	-3.97	54.00	28.13	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

10W laser module(adapter1)

TX Radiated Test Result




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	63.95	47.23	26.53	-20.70	40.00	13.47	PK	Vertical	PASS
2	140.58	45.99	27.71	-18.28	43.50	15.79	PK	Vertical	PASS
3	173.56	45.23	25.30	-19.93	43.50	18.20	PK	Vertical	PASS
4	281.23	41.67	22.19	-19.48	46.00	23.81	PK	Vertical	PASS
5	479.11	40.21	26.66	-13.55	46.00	19.34	PK	Vertical	PASS
6	926.28	30.71	25.91	-4.80	46.00	20.09	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	61.04	39.73	19.40	-20.33	40.00	20.60	PK	Horizontal	PASS
2	169.68	37.74	18.56	-19.18	43.50	24.94	PK	Horizontal	PASS
3	245.34	46.05	25.70	-20.35	46.00	20.30	PK	Horizontal	PASS
4	275.41	44.81	25.19	-19.62	46.00	20.81	PK	Horizontal	PASS
5	881.66	29.74	24.23	-5.51	46.00	21.77	PK	Horizontal	PASS
6	983.51	29.20	25.23	-3.97	54.00	28.77	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

5W laser module(adapter1)

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	63.95	47.21	26.51	-20.70	40.00	13.49	PK	Vertical	PASS
2	141.55	46.07	27.82	-18.25	43.50	15.68	PK	Vertical	PASS
3	173.56	45.69	25.76	-19.93	43.50	17.74	PK	Vertical	PASS
4	280.26	42.24	22.77	-19.47	46.00	23.23	PK	Vertical	PASS
5	480.08	40.80	27.30	-13.50	46.00	18.70	PK	Vertical	PASS
6	935.01	29.29	24.64	-4.65	46.00	21.36	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	63.95	39.86	19.16	-20.70	40.00	20.84	PK	Horizontal	PASS
2	245.34	45.99	25.64	-20.35	46.00	20.36	PK	Horizontal	PASS
3	273.47	45.69	26.01	-19.68	46.00	19.99	PK	Horizontal	PASS
4	408.30	34.96	19.47	-15.49	46.00	26.53	PK	Horizontal	PASS
5	842.86	30.65	24.14	-6.51	46.00	21.86	PK	Horizontal	PASS
6	999.03	29.14	25.69	-3.45	54.00	28.31	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level

5W laser module(adapter2)

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	63.95	46.91	26.21	-20.70	40.00	13.79	PK	Vertical	PASS
2	141.55	46.55	28.30	-18.25	43.50	15.20	PK	Vertical	PASS
3	173.56	46.78	26.85	-19.93	43.50	16.65	PK	Vertical	PASS
4	280.26	41.85	22.38	-19.47	46.00	23.62	PK	Vertical	PASS
5	479.11	40.41	26.86	-13.55	46.00	19.14	PK	Vertical	PASS
6	967.02	29.88	25.52	-4.36	54.00	28.48	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	63.95	39.89	19.19	-20.70	40.00	20.81	PK	Horizontal	PASS
2	245.34	46.27	25.92	-20.35	46.00	20.08	PK	Horizontal	PASS
3	272.50	44.86	25.14	-19.72	46.00	20.86	PK	Horizontal	PASS
4	386.96	35.65	19.71	-15.94	46.00	26.29	PK	Horizontal	PASS
5	840.92	30.60	24.12	-6.48	46.00	21.88	PK	Horizontal	PASS
6	983.51	29.03	25.06	-3.97	54.00	28.94	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All modes have been tested and the worst result as bellow:

TX Radiated Test Result




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	1851.62	55.25	44.77	-10.48	74.00	29.23	PK	Vertical	PASS
2	2915.97	52.42	44.78	-7.64	74.00	29.22	PK	Vertical	PASS
3	4820.61	54.08	42.63	-11.45	74.00	31.37	PK	Vertical	PASS
4	7006.34	49.73	41.87	-7.86	74.00	32.13	PK	Vertical	PASS
5	15784.26	48.42	46.05	-2.37	74.00	27.95	PK	Vertical	PASS
6	17699.90	46.68	46.85	0.17	74.00	27.15	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level


TX Radiated Test Result



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2375.79	58.54	50.04	-8.50	74.00	23.96	PK	Horizontal	PASS
2	2596.53	57.53	49.40	-8.13	74.00	24.60	PK	Horizontal	PASS
3	4820.61	53.37	41.92	-11.45	74.00	32.08	PK	Horizontal	PASS
4	7016.34	50.05	42.21	-7.84	74.00	31.79	PK	Horizontal	PASS
5	11327.78	48.94	44.15	-4.79	74.00	29.85	PK	Horizontal	PASS
6	17684.89	46.60	46.86	0.26	74.00	27.14	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level


TX Radiated Test Result



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	1851.62	53.76	43.28	-10.48	74.00	30.72	PK	Vertical	PASS
2	2615.21	53.81	45.46	-8.35	74.00	28.54	PK	Vertical	PASS
3	3185.06	56.92	42.10	-14.82	74.00	31.90	PK	Vertical	PASS
4	4870.62	52.68	41.51	-11.17	74.00	32.49	PK	Vertical	PASS
5	16239.41	46.30	45.57	-0.73	74.00	28.43	PK	Vertical	PASS
6	17689.90	46.95	47.18	0.23	74.00	26.82	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2363.12	56.77	48.37	-8.40	74.00	25.63	PK	Horizontal	PASS
2	2600.53	56.82	48.66	-8.16	74.00	25.34	PK	Horizontal	PASS
3	3245.08	56.02	41.30	-14.72	74.00	32.70	PK	Horizontal	PASS
4	4870.62	54.74	43.57	-11.17	74.00	30.43	PK	Horizontal	PASS
5	9747.25	50.34	43.78	-6.56	74.00	30.22	PK	Horizontal	PASS
6	17674.89	46.55	46.87	0.32	74.00	27.13	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level


TX Radiated Test Result



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2131.04	54.12	45.08	-9.04	74.00	28.92	PK	Vertical	PASS
2	2537.85	54.33	45.86	-8.47	74.00	28.14	PK	Vertical	PASS
3	7006.34	50.03	42.17	-7.86	74.00	31.83	PK	Vertical	PASS
4	11572.86	48.40	43.99	-4.41	74.00	30.01	PK	Vertical	PASS
5	16689.56	46.04	45.55	-0.49	74.00	28.45	PK	Vertical	PASS
6	17694.90	46.52	46.73	0.21	74.00	27.27	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2315.11	56.47	47.67	-8.80	74.00	26.33	PK	Horizontal	PASS
2	2601.20	57.32	49.16	-8.16	74.00	24.84	PK	Horizontal	PASS
3	4920.64	52.78	41.64	-11.14	74.00	32.36	PK	Horizontal	PASS
4	7311.44	49.48	41.87	-7.61	74.00	32.13	PK	Horizontal	PASS
5	10752.58	48.96	43.67	-5.29	74.00	30.33	PK	Horizontal	PASS
6	17694.90	46.39	46.60	0.21	74.00	27.40	PK	Horizontal	PASS


Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

For 9KHz to 30MHz and above 18 GHz, a pre-scan was performed, and the result was 20 dB lower than the limit line, the test data was not shown in the report.

Band Edge

All modes have been tested and the worst result as bellow:

TX Radiated Test Result




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.12	28.72	51.36	22.64	74.00	22.64	PK	Vertical	PASS
2	2390.00	26.23	48.95	22.72	74.00	25.05	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.12	30.35	52.99	22.64	74.00	21.01	PK	Horizontal	PASS
2	2390.00	28.58	51.30	22.72	74.00	22.70	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	24.34	47.49	23.15	74.00	26.51	PK	Vertical	PASS
2	2489.51	27.19	50.33	23.14	74.00	23.67	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	25.79	48.94	23.15	74.00	25.06	PK	Horizontal	PASS
2	2498.85	28.20	51.31	23.11	74.00	22.69	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2387.94	30.57	53.25	22.68	74.00	20.75	PK	Vertical	PASS
2	2390.00	30.47	53.19	22.72	74.00	20.81	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result



Suspected Data List


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.42	38.70	61.39	22.69	74.00	12.61	PK	Horizontal	PASS
2	2390.00	36.32	59.04	22.72	74.00	14.96	PK	Horizontal	PASS

Final Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Pol	Verdict
1	2388.42	22.69	28.81	51.50	54.00	2.50	Horizontal	PASS
2	2390.00	22.72	28.95	51.67	54.00	2.33	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




Suspected Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	27.07	50.22	23.15	74.00	23.78	PK	Vertical	PASS
2	2492.55	30.63	53.76	23.13	74.00	20.24	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result



Suspected Data List

NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	32.16	55.31	23.15	74.00	18.69	PK	Horizontal	PASS
2	2486.95	34.49	57.63	23.14	74.00	16.37	PK	Horizontal	PASS

Final Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Pol	Verdict
1	2483.50	23.15	28.65	51.80	54.00	2.20	Horizontal	PASS
2	2486.95	23.14	27.26	50.40	54.00	3.60	Horizontal	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Standard	Requirement
RSS-Gen issue 5 6.8.	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list. For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested. For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location: This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

	Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.
--	---

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP




TEST ENVIRONMENT

Temperature	23.2°C	Relative Humidity	52%
Atmosphere Pressure	101kPa		

TEST RESULTS


1.2W laser module(adapter1)



Phase: N

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1635	26.84	9.62	36.46	65.28	-28.82	QP
2	0.1635	10.86	9.62	20.48	55.28	-34.80	AVG
3	0.4693	25.12	9.62	34.74	56.53	-21.79	QP
4	0.4693	20.81	9.62	30.43	46.53	-16.10	AVG
5	1.6125	18.70	9.68	28.38	56.00	-27.62	QP
6	1.6125	12.86	9.68	22.54	46.00	-23.46	AVG
7	4.4430	19.02	9.76	28.78	56.00	-27.22	QP
8	4.4430	13.29	9.76	23.05	46.00	-22.95	AVG
9	7.4085	20.62	9.92	30.54	60.00	-29.46	QP
10	7.4085	13.64	9.92	23.56	50.00	-26.44	AVG
11	10.3695	23.47	10.11	33.58	60.00	-26.42	QP
12	10.3695	15.01	10.11	25.12	50.00	-24.88	AVG




Phase: L1

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	27.50	9.71	37.21	65.52	-28.31	QP
2	0.1590	7.90	9.71	17.61	55.52	-37.91	AVG
3	0.2040	22.74	9.62	32.36	63.45	-31.09	QP
4	0.2040	-1.49	9.62	8.13	53.45	-45.32	AVG
5	0.4693	25.76	9.58	35.34	56.53	-21.19	QP
6	0.4693	24.63	9.58	34.21	46.53	-12.32	AVG
7	1.3785	19.59	9.69	29.28	56.00	-26.72	QP
8	1.3785	14.81	9.69	24.50	46.00	-21.50	AVG
9	4.4430	18.85	9.81	28.66	56.00	-27.34	QP
10	4.4430	13.26	9.81	23.07	46.00	-22.93	AVG
11	10.3695	23.23	10.17	33.40	60.00	-26.60	QP
12	10.3695	15.18	10.17	25.35	50.00	-24.65	AVG


10W laser module(adapter1)



Phase: N

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1680	23.95	9.61	33.56	65.06	-31.50	QP
2	0.1680	6.89	9.61	16.50	55.06	-38.56	AVG
3	0.4695	25.55	9.62	35.17	56.52	-21.35	QP
4	0.4695	24.49	9.62	34.11	46.52	-12.41	AVG
5	1.1895	19.66	9.68	29.34	56.00	-26.66	QP
6	1.1895	13.42	9.68	23.10	46.00	-22.90	AVG
7	2.7510	17.63	9.70	27.33	56.00	-28.67	QP
8	2.7510	12.81	9.70	22.51	46.00	-23.49	AVG
9	4.4430	19.03	9.76	28.79	56.00	-27.21	QP
10	4.4430	12.70	9.76	22.46	46.00	-23.54	AVG
11	9.6315	23.14	10.06	33.20	60.00	-26.80	QP
12	9.6315	15.26	10.06	25.32	50.00	-24.68	AVG




Phase: L1

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1723	25.01	9.70	34.71	64.85	-30.14	QP
2	0.1723	-0.12	9.70	9.58	54.85	-45.27	AVG
3	0.4693	25.72	9.58	35.30	56.53	-21.23	QP
4	0.4693	24.55	9.58	34.13	46.53	-12.40	AVG
5	1.8960	18.86	9.73	28.59	56.00	-27.41	QP
6	1.8960	12.54	9.73	22.27	46.00	-23.73	AVG
7	4.4430	19.36	9.81	29.17	56.00	-26.83	QP
8	4.4430	13.56	9.81	23.37	46.00	-22.63	AVG
9	7.4085	21.91	10.00	31.91	60.00	-28.09	QP
10	7.4085	13.91	10.00	23.91	50.00	-26.09	AVG
11	10.3695	23.82	10.17	33.99	60.00	-26.01	QP
12	10.3695	14.38	10.17	24.55	50.00	-25.45	AVG


5W laser module(adapter1)



Phase: N

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	26.70	9.63	36.33	65.52	-29.19	QP
2	0.1590	6.11	9.63	15.74	55.52	-39.78	AVG
3	0.4694	25.32	9.62	34.94	56.52	-21.58	QP
4	0.4694	23.96	9.62	33.58	46.52	-12.94	AVG
5	4.4430	18.99	9.76	28.75	56.00	-27.25	QP
6	4.4430	13.06	9.76	22.82	46.00	-23.18	AVG
7	7.4085	21.24	9.92	31.16	60.00	-28.84	QP
8	7.4085	14.37	9.92	24.29	50.00	-25.71	AVG
9	10.3650	22.84	10.11	32.95	60.00	-27.05	QP
10	10.3650	14.03	10.11	24.14	50.00	-25.86	AVG
11	13.3305	21.99	10.20	32.19	60.00	-27.81	QP
12	13.3305	13.24	10.20	23.44	50.00	-26.56	AVG




Phase: L1

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	27.32	9.71	37.03	65.52	-28.49	QP
2	0.1590	7.16	9.71	16.87	55.52	-38.65	AVG
3	0.4694	25.90	9.58	35.48	56.52	-21.04	QP
4	0.4694	24.75	9.58	34.33	46.52	-12.19	AVG
5	4.4430	19.04	9.81	28.85	56.00	-27.15	QP
6	4.4430	13.17	9.81	22.98	46.00	-23.02	AVG
7	6.6660	20.54	9.95	30.49	60.00	-29.51	QP
8	6.6660	13.89	9.95	23.84	50.00	-26.16	AVG
9	9.6315	23.67	10.13	33.80	60.00	-26.20	QP
10	9.6315	15.17	10.13	25.30	50.00	-24.70	AVG
11	12.5924	22.09	10.21	32.30	60.00	-27.70	QP
12	12.5924	13.61	10.21	23.82	50.00	-26.18	AVG


5W laser module(adapter2)



Phase: N

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	26.76	9.63	36.39	65.52	-29.13	QP
2	0.1590	6.07	9.63	15.70	55.52	-39.82	AVG
3	0.4694	25.69	9.62	35.31	56.52	-21.21	QP
4	0.4694	24.36	9.62	33.98	46.52	-12.54	AVG
5	1.8960	18.89	9.66	28.55	56.00	-27.45	QP
6	1.8960	12.67	9.66	22.33	46.00	-23.67	AVG
7	4.4430	18.49	9.76	28.25	56.00	-27.75	QP
8	4.4430	12.67	9.76	22.43	46.00	-23.57	AVG
9	7.4085	22.11	9.92	32.03	60.00	-27.97	QP
10	7.4085	14.35	9.92	24.27	50.00	-25.73	AVG
11	10.3695	22.79	10.11	32.90	60.00	-27.10	QP
12	10.3695	16.57	10.11	26.68	50.00	-23.32	AVG



Phase: L1

Mode: 802.11b 2437MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	27.31	9.71	37.02	65.52	-28.50	QP
2	0.1590	6.13	9.71	15.84	55.52	-39.68	AVG
3	0.4693	25.89	9.58	35.47	56.53	-21.06	QP
4	0.4693	25.01	9.58	34.59	46.53	-11.94	AVG
5	1.3785	19.09	9.69	28.78	56.00	-27.22	QP
6	1.3785	13.70	9.69	23.39	46.00	-22.61	AVG
7	4.4430	18.78	9.81	28.59	56.00	-27.41	QP
8	4.4430	12.79	9.81	22.60	46.00	-23.40	AVG
9	10.3695	23.86	10.17	34.03	60.00	-25.97	QP
10	10.3695	15.60	10.17	25.77	50.00	-24.23	AVG
11	12.5923	22.92	10.21	33.13	60.00	-26.87	QP
12	12.5923	15.16	10.21	25.37	50.00	-24.63	AVG

END OF REPORT