

4.6 Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

Test Configuration




Test Results



Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data. And record the worst data in the report.

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	-50.80	-20	Pass
b	2437	-50.24	-20	Pass
b	2462	-49.83	-20	Pass
g	2412	-44.12	-20	Pass
g	2437	-45.78	-20	Pass
g	2462	-42.46	-20	Pass
n20	2412	-46.65	-20	Pass
n20	2437	-48.05	-20	Pass
n20	2462	-44.92	-20	Pass
n40	2422	-35.81	-20	Pass
n40	2437	-34.05	-20	Pass
n40	2452	-27.36	-20	Pass



Test plot as follows:





802.11g



CH01





CH06





CH11



802.11n20



CH01





CH06





CH11



802.11n40



CH03



CH06



CH09