SAR TEST REPORT

Product Name: VOBBLE INTERACTIVE AUDIO PLAYER

Model Name: VP2025A

FCC ID: 2BPBE-VP2025A

Issued For : Avie-Vinson Entertainment Inc.

16192 Coastal Highway, Lewes, Delaware 19958, County of Sussex

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT25E015HA01

Sample Received Date: May 16, 2025

Date of Test: May 16, 2025, ~ May 23, 2025

Date of Issue: June 12, 2025

Max. SAR: Body:1.047 W/kg(1g)

Limbs:1.245 W/kg(10g)

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.

Table of Contents

1. General Information **5**

1.1 EUT Description 5

1.2 Test Environment 7

1.3 Test Factory 7

2. Test Standards and Limits **8**

3. SAR Measurement System **9**

3.1 Definition of Specific Absorption Rate (SAR) 9

3.2 SAR System 9

4. Tissue Simulating Liquids **12**

4.1 Simulating Liquids Parameter Check 12

5. SAR System Validation **14**

5.1 Validation System 14

5.2 Validation Result 15

6. SAR Evaluation Procedures **16**

7. EUT Antenna Location Sketch **17**

7.1 SAR test exclusion consider table 18

8. EUT Test Position **23**

8.1 Define Two Imaginary Lines on the Handset 23

8.2 Hotspot mode exposure position condition 24

9. Uncertainty **25**

9.1 Measurement Uncertainty 25

9.2 System validation Uncertainty 26

10. Conducted Power Measurement **27**

10.1 Test Result 27

10.2 Tune up power 44

11. EUT and Test Setup Photo **47**

11.1 EUT Photos 47

11.2 Setup Photos 50

12. SAR Result Summary **57**

12.1 Body-worn Hotspot SAR 57

12.2 Limbs SAR 61

12.3 Repeated SAR 65

12.4 Repeated SAR measurement 65

12.5 Simultaneous Multi-band Transmission Evaluation 66

13. Equipment List **68**

Appendix A. System Validation Plots 69

Appendix B. SAR Test Plots 87

Appendix C. Probe Calibration and Dipole Calibration Report 117

Revision History

Rev.	Issue Date	Contents
00	June 12, 2025	Initial Issue

TEST REPORT CERTIFICATION

Applicant	Avie-Vinson Entertainment Inc.
Address	16192 Coastal Highway, Lewes, Delaware 19958, County of Sussex
Manufacture	Shenzhen Ruizu Digital Technology Co.,Ltd.
Address	Room 203, Building 6, Fuqiao Fifth Industrial Zone, Qiaotou Community, Shenzhen, Guangdong, China
Product Name	VOBBLE INTERACTIVE AUDIO PLAYER
Trademark	N/A
Model Name	VP2025A
Sample number	LGT2505010-2

APPLICABLE STANDARDS	
STANDARD	**TEST RESULTS**
ANSI/IEEE Std. C95.1-2019 FCC 47 CFR Part 2 (2.1093) IEEE 1528: 2013	PASS

Prepared by:

Deng Deng

Deng Deng
Engineer

Approved by:

Vita Li
Manager

SHENZHEN LGT TEST SERVICE CO., LTD.
LGT
领冠检测

1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	VOBBLE INTERACTIVE AUDIO PLAYER		
Trademark	N/A		
Model Name	VP2025A		
Series Model	N/A		
Model Difference	N/A		
Device Category	Portable		
Product stage	Production unit		
RF Exposure Environment	General Population / Uncontrolled		
Hardware Version	MTK 6737		
Software Version	Android 8.1		
Frequency Range	GSM 850: 824 ~ 849 MHz PCS 1900: 1850 ~ 1910 MHz WCDMA Band II: 1850 ~ 1910 MHz WCDMA Band IV:1710 ~ 1755 MHz WCDMA Band V: 824 ~ 849 MHz LTE Band 2:1850 ~1910MHz LTE Band 4:1710 ~1755MHz LTE Band 5:824 ~ 849MHz LTE Band 12:699~716MHz LTE Band 13:777~787MHz WLAN 802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz WLAN 802.11a/n20/n40/ac20/ac40: 5150 ~ 5250 MHz WLAN 802.11a/n20/n40/ac20/ac40: 5250 ~ 5350 MHz WLAN 802.11a/n20/n40/ac20/ac40: 5470 ~ 5725 MHz WLAN 802.11a/n20/n40/ac20/ac40: 5725 ~ 5850 MHz Bluetooth: 2402 ~ 2480 MHz		
Max. Reported SAR: Test distance: Body:5mm Limbs:0mm	Mode	Body Worn Hotspot (W/kg)(1g)	Limbs (W/kg)(10g)
	GSM 850	1.007	1.155
	PCS 1900	1.047	1.018
	WCDMA Band II	0.979	1.245
	WCDMA Band IV	0.646	1.191
	WCDMA Band V	0.970	0.555
	LTE Band 2	1.002	1.254
	LTE Band 4	0.591	1.174
	LTE Band 5	0.521	0.495
	LTE Band 12	0.795	0.487
	LTE Band 13	0.777	0.461
	2.4G WLAN	0.444	0.272
	5.2G WLAN	0.319	0.371
	5.3G WLAN	0.323	0.238
	5.6G WLAN	0.476	0.470
	5.8G WLAN	0.371	0.260

	Bluetooth[Note]	0.328	0.131
1-g Sum SAR		1.523	1.724
Limit		1.6	4
Battery	Rated Voltage:3.8V Capacity: 1800mAh		
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN: 802.11b(DSSS): CCK, DQPSK, DBPSK 802.11g(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK, QPSK,16-QAM,64-QAM 5G WLAN: 802.11a(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11ac (OFDM): BPSK, QPSK,16-QAM,64-QAM,256-QAM Bluetooth: GFSK +π/4DQPSK+8DPSK BLE: GFSK		
Antenna Specification	GSM/WCDMA/LTE: FPC Antenna Bluetooth: FPC Antenna WLAN: FPC Antenna		
Operating Mode	Maximum continuous output		
SIM Card	Only support single SIM Card.		
Hotspot Mode	Support		
DTM Mode	Not Support		
Note 1: The BT value was Estimated.			

1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (℃)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	FCC Registration No.: 746540
	A2LA Certificate No.: 6727.01
	IC Registration No.: CN0136

2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE GENERAL POPULATION/UNCONTROLLED EXPOSURE PARTIAL BODY LIMIT 1.6 W/kg

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\mathbf{SAR} = \frac{d}{dt}\left(\frac{dW}{dm}\right) = \frac{d}{dt}\left(\frac{dW}{\rho dv}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$\mathbf{SAR} = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue;
ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:
- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.

The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 1g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 04/22 EPGO364 with following specifications is used
- Probe Length: 330 mm
- Length of Individual Dipoles: 2mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: ＜0.10 dB
- Spherical Isotropy: ＜0.10 dB
- Calibration range: 600 MHz to 6 GHz for head & body simulating liquid.
-Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Figure 1-MVG COMOSAR Dosimetric E field Probe

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

Figure-SN 06/22 SAM 148

Figure-SN 06/22 ELLI 51

3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS
The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	εr	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27

LIQUID MEASUREMENT RESULTS

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2025-05-16	20.6	41	750	20.3	Permittivity	41.90	41.98	0.19	±5
					Conductivity	0.89	0.91	2.25	±5
2025-05-19	21.5	46	835	21.2	Permittivity	41.50	41.93	1.04	±5
					Conductivity	0.90	0.93	3.33	±5
2025-05-20	21.8	49	1800	21.5	Permittivity	40.00	40.17	0.43	±5
					Conductivity	1.40	1.39	-0.71	±5
2025-05-18	21.7	57	1900	21.4	Permittivity	40.00	40.94	2.35	±5
					Conductivity	1.40	1.44	2.86	±5
2025-05-20	21.8	49	2450	21.5	Permittivity	39.20	40.48	3.27	±5
					Conductivity	1.80	1.75	-2.78	±5
2025-05-22	22.1	60	5200	21.8	Permittivity	36.00	36.86	2.39	±5
					Conductivity	4.66	4.64	-0.43	±5
2025-05-22	22.2	60	5400	21.9	Permittivity	35.80	35.93	0.36	±5
					Conductivity	4.86	4.92	1.23	±5
2025-05-23	23.8	54	5600	23.5	Permittivity	35.55	36.58	2.90	±5
					Conductivity	5.07	5.05	-0.30	±5
2025-05-23	23.9	54	5800	23.6	Permittivity	35.30	36.32	2.89	±5
					Conductivity	5.27	5.24	-0.57	±5

5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.



5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of ±10 %.

Date	Freq.	Power	Power drift	Tested Value	Normalized SAR	Target SAR	Tolerance
	(MHz)	(mW)	(%)	(W/Kg)	(W/kg)	1g(W/kg)	(%)
2025-05-16	750	100	0.830	8.30	8.37	-0.84	10
2025-05-19	835	100	0.980	9.80	9.73	0.72	10
2025-05-20	1800	100	3.859	38.59	39.03	-1.13	10
2025-05-18	1900	100	4.053	40.53	40.89	-0.88	10
2025-05-20	2450	100	5.444	54.44	54.21	0.42	10
2025-05-22	5200	100	8.130	81.30	80.96	0.42	10
2025-05-22	5400	100	8.506	85.06	84.63	0.51	10
2025-05-23	5600	100	8.118	81.18	80.97	0.26	10
2025-05-23	5800	100	8.264	82.64	81.68	1.18	10

Note:

1. The tolerance limit of System validation ±10%.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.

6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface

- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.

- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.

- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➢ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Vigilant Eye, support LTE/WLAN/BT mode.

Top side



Bottom side
(Back view)

Antenna Separation Distance(mm)						
ANT	Back Side	Front Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤5	≤5	≤5	35	104	17
WWAN	≤5	≤5	20	≤5	≤5	65

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.

7.1 SAR test exclusion consider table

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA IV	WCDMA V
Exposure Position	Calculated Frequency (MHz)	836.6	1850.2	1852.4	1712.6	846.6
	Maximum Turn-up power (dBm)	30	25.5	22.5	22	25
	Maximum rated power(mW)	1000.00	354.81	177.83	158.49	316.23
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.40	11.03	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.40	11.03	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	20	20	20	20	20
	exclusion threshold(mW)	65.60	44.11	44.08	45.85	65.21
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.40	11.03	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.40	11.03	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	65	65	65	65	65
	exclusion threshold(mW)	247.66	260.28	260.21	264.62	247.68
	Testing required?	YES	YES	NO	NO	YES

Exposure Position	Wireless Interface	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 12	LTE Band 13
	Calculated Frequency (MHz)	1860	1720	844	704	782
	Maximum Turn-up power (dBm)	22.3	22	25.3	25	25
	Maximum rated power(mW)	169.82	158.49	338.84	316.23	316.23
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.00	11.44	16.33	17.88	16.96
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.00	11.44	16.33	17.88	16.96
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	20	20	20	20	20
	exclusion threshold(mW)	43.99	45.75	65.31	71.51	67.85
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.00	11.44	16.33	17.88	16.96
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.00	11.44	16.33	17.88	16.96
	Testing required?	YES	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	65	65	65	65	65
	exclusion threshold(mW)	259.99	264.37	247.68	249.17	247.82
	Testing required?	NO	NO	YES	YES	YES

Exposure Position	Wireless Interface	BT	2.4G WLAN	5.2G WLAN
	Calculated Frequency (MHz)	2402	2412	5230
	Maximum Turn-up power (dBm)	9	16.5	15.8
	Maximum rated power(mW)	7.94	44.67	38.02
Back Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	9.68	9.66	6.56
	Testing required?	NO	YES	YES
Front Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	9.68	9.66	6.56
	Testing required?	NO	YES	YES
Left Edge	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	9.68	9.66	6.56
	Testing required?	NO	YES	YES
Right Edge	Separation distance (mm)	35	35	35
	exclusion threshold(mW)	67.75	67.61	45.91
	Testing required?	NO	NO	NO
Top Edge	Separation distance (mm)	104	104	104
	exclusion threshold(mW)	201.31	200.89	136.43
	Testing required?	NO	NO	NO
Bottom Edge	Separation distance (mm)	17	17	17
	exclusion threshold(mW)	32.91	32.84	22.30
	Testing required?	NO	YES	YES

Exposure Position	Wireless Interface	5.3G WLAN	5.6G WLAN	5.8G WLAN
	Calculated Frequency (MHz)	5260	5500	5745
	Maximum Turn-up power (dBm)	15.8	15	15
	Maximum rated power(mW)	38.02	31.62	31.62
Back Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	6.54	6.40	6.26
	Testing required?	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	6.54	6.40	6.26
	Testing required?	YES	YES	YES
Left Edge	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	6.54	6.40	6.26
	Testing required?	YES	YES	YES
Right Edge	Separation distance (mm)	35	35	35
	exclusion threshold(mW)	45.78	44.77	43.81
	Testing required?	NO	NO	NO
Top Edge	Separation distance (mm)	104	104	104
	exclusion threshold(mW)	136.04	133.04	130.17
	Testing required?	NO	NO	NO
Bottom Edge	Separation distance (mm)	17	17	17
	exclusion threshold(mW)	22.24	21.75	21.28
	Testing required?	YES	YES	YES

Note：

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <25mm,25mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance ≤50mm are determined by:

   [(max.power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)]*[√f(GHz）)≤3.0 for 1-g SAR and≤7.5 for10-g extremity SAR ,f(GHz) is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison

For <50mm distance, we just calculate mW of the exclusion threshold value(3.0)to do compare

5. per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following

   a)[threshold at 50mm in step 1]+(test separation distance -50mm)*(f (MHz)/150)]mW, at 100 MHz to 1500 MHz

   b) [threshold at 50mm in step1]+(test separation distance -50mm) *10]mW at＞1500MHz and≤ 6GHz

6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8.for each frequency band ,testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode ,thus the SAR can be excluded.

8. EUT Test Position

This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.

8.1 Define Two Imaginary Lines on the Handset

(1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width wt of the handset at the level of the acoustic output, and the midpoint of the width wb of the handset.
(2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
(3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position
1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost



Title Position
(1) To position the device in the “cheek” position described above.
(2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.



Body-worn Position Conditions:
Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.

8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm form that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	√0.5	√0.5	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	√0.5	√0.5	2.41	2.41	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	1.81	1.81	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algoritms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device holder uncertainty	3	N	1	1	1	3.00	3.00	7
Output Power Variation - SAR Drift Measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		K				20.95	20.69	

9.2 System validation Uncertainty

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	0.71	0.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algoritms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of Experimental Source from Numerical Source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR Drift Measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Distance	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		K				20.32	20.06	

10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	32.90	33.43	32.98	29.19	27.58	27.69
GPRS (GMSK, 1-Slot)	32.21	32.66	32.25	28.40	26.75	26.84
GPRS (GMSK, 2-Slot)	30.47	30.94	30.49	26.66	24.93	25.01
GPRS (GMSK, 3-Slot)	29.15	29.70	29.18	25.44	23.63	23.61
GPRS (GMSK, 4-Slot)	27.30	27.49	27.09	24.49	23.88	24.49
EGPRS (8PSK, 1-Slot)	26.16	26.53	26.05	23.41	22.92	22.79
EGPRS (8PSK, 2-Slot)	23.77	23.94	23.55	21.16	20.34	20.39
EGPRS (8PSK, 3-Slot)	22.00	22.16	21.54	19.48	18.78	18.75
EGPRS (8PSK, 4-Slot)	32.90	33.43	32.98	29.19	27.58	27.69
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	23.87	24.40	23.95	20.16	18.55	18.66
GPRS (GMSK, 1-Slot)	26.19	26.64	26.23	22.38	20.73	20.82
GPRS (GMSK, 2-Slot)	26.21	26.68	26.23	22.40	20.67	20.75
GPRS (GMSK, 3-Slot)	26.14	26.69	26.17	22.43	20.62	20.60
GPRS (GMSK, 4-Slot)	18.27	18.46	18.06	15.46	14.85	15.46
EGPRS (8PSK, 1-Slot)	20.14	20.51	20.03	17.39	16.90	16.77
EGPRS (8PSK, 2-Slot)	19.51	19.68	19.29	16.90	16.08	16.13
EGPRS (8PSK, 3-Slot)	18.99	19.15	18.53	16.47	15.77	15.74
EGPRS (8PSK, 4-Slot)	23.87	24.40	23.95	20.16	18.55	18.66
Remark: 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						

WCDMA

Band	WCDMA Band 2			WCDMA Band 4			WCDMA Band 5		
Channel	9262	9400	9538	1312	1450	1513	4132	4182	4233
Frequency (MHz)	1852.4	1880	1907.6	1712.6	1740	1752.4	826.4	836.4	846.6
RMC 12.2Kbps	22.09	21.51	21.01	21.83	21.35	21.6	24.48	24.86	24.87
HSDPA Subtest-1	22.06	21.52	20.93	21.85	21.3	21.55	24.36	24.76	24.82
HSDPA Subtest-2	21.77	20.91	20.5	21.37	20.96	20.72	23.89	24.26	24.5
HSDPA Subtest-3	20.24	19.73	19.37	20.39	19.78	20.35	22.55	23.34	23.44
HSDPA Subtest-4	20.6	20.14	19.6	20.36	19.93	19.81	22.87	23.39	22.93
HSUPA Subtest-1	21.06	21.27	20.74	20.56	21.12	21.37	23.07	24.57	24.62
HSUPA Subtest-2	21.36	21.41	20.84	21.36	21.23	21.38	23.48	24.75	24.81
HSUPA Subtest-3	20.46	19.77	19.59	20.37	20.02	20.07	22.9	23.39	23.55
HSUPA Subtest-4	21.69	21.45	20.9	21.5	21.34	21.53	23.72	24.8	24.83
HSUPA Subtest-5	20.67	20.8	20.14	20.56	20.71	20.67	23.23	24.09	24.11

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM (db)	MPR (db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	0≤ CM≤3.5	MAX(CM-1,0)
Note: CM=1 for $\beta c/\beta d$=12/15, $\beta hs/\beta c$=24/15.For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

2.4G WLAN

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11b	1	2412	16.65	46.24
	6	2437	16.39	43.55
	11	2462	15.86	38.55
802.11g	1	2412	15.71	37.24
	6	2437	15.26	33.57
	11	2462	14.75	29.85
802.11 n-HT20	1	2412	16.2	41.69
	6	2437	15.7	37.15
	11	2462	15.23	33.34
802.11 n-HT40	3	2422	14.74	29.79
	6	2437	14.15	26.00
	9	2452	13.64	23.12

Bluetooth

BT				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	6.02	4.00
	39	2441	6.1	4.07
	78	2480	6.18	4.15
π/4-QPSK(2Mbps)	0	2402	8.32	6.79
	39	2441	8.24	6.67
	78	2480	8.35	6.84
8DPSK(3Mbps)	0	2402	8.5	7.08
	39	2441	8.52	7.11
	78	2480	8.62	7.28

BLE

BLE				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	8.84	7.66
	19	2440	8.71	7.43
	39	2480	7.09	5.12

WLAN (5.2Gband)

5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	36	5180	14.69	29.44
	40	5200	14.94	31.19
	48	5240	15.32	34.04
802.11 n-HT20	36	5180	13.99	25.06
	40	5200	14.26	26.67
	48	5240	14.67	29.31
802.11 n-HT40	38	5190	15.09	32.28
	46	5230	15.56	35.97
802.11ac-VHT20	36	5180	13.91	24.60
	40	5200	13.96	24.89
	48	5240	14.51	28.25
802.11ac-VHT40	38	5190	14.51	28.25
	46	5230	15	31.62

WLAN (5.3G band)

5.3G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	52	5260	15.51	35.56
	60	5300	14.54	28.44
	64	5320	14.28	26.79
802.11 n-HT20	52	5260	14.81	30.27
	60	5300	13.79	23.93
	64	5320	13.52	22.49
802.11 n-HT40	54	5270	14.88	30.76
	62	5310	13.82	24.10
802.11ac-VHT20	52	5260	14.59	28.77
	60	5300	13.46	22.18
	64	5320	13.23	21.04
802.11ac-VHT40	54	5270	14.89	30.83
	62	5310	13.97	24.95

WLAN (5.6G band)

5.6G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	100	5500	13.17	20.75
	116	5580	14.55	28.51
	140	5700	14.03	25.29
802.11 n-HT20	100	5500	14.74	29.79
	116	5580	13.42	21.98
	140	5700	13.14	20.61
802.11 n-HT40	102	5510	14.4	27.54
	110	5550	13.67	23.28
	134	5670	14.62	28.97
802.11ac-VHT20	100	5500	12.62	18.28
	116	5580	13.37	21.73
	140	5700	12.88	19.41
802.11ac-VHT40	102	5510	12.54	17.95
	110	5550	13.25	21.13
	134	5670	13.84	24.21

WLAN (5.8G band)

5.8G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	149	5745	14.04	25.35
	157	5785	14.46	27.93
	165	5825	13.74	23.66
802.11n-HT20	149	5745	14.88	30.76
	157	5785	13.65	23.17
	165	5825	12.99	19.91
802.11n-HT40	151	5755	13.89	24.49
	159	5795	14.24	26.55
802.11ac-VHT20	149	5745	13.16	20.70
	157	5785	13.62	23.01
	165	5825	12.99	19.91
802.11ac-VHT40	151	5755	13.24	21.09
	159	5795	13.56	22.70

LTE Conducted Power

General Note:

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ⩽ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is > not ½ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ⩽ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is > not ½ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ⩽ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.93	21.23	21.17
1.4	1	2		21.68	21.27	21.04
1.4	1	5		21.22	21.32	20.79
1.4	3	0		20.84	20.16	20.12
1.4	3	1		20.71	20.19	20.01
1.4	3	2		20.49	20.22	19.92
1.4	6	0		20.64	20.18	20.02
1.4	1	0	16-QAM	21.02	20.28	19.55
1.4	1	2		21.09	20.35	19.65
1.4	1	5		21.03	20.27	19.57
1.4	3	0		21.15	20.43	19.89
1.4	3	1		21.06	20.35	19.83
1.4	3	2		21.12	20.40	19.93
1.4	6	0		20.07	19.24	18.82
3	1	0	QPSK	21.82	21.02	20.74
3	1	7		21.84	21.12	20.77
3	1	14		21.76	21.03	20.70
3	8	0		20.96	20.16	19.76
3	8	4		20.96	20.19	19.75
3	8	7		20.94	20.19	19.73
3	15	0		20.90	20.15	19.75
3	1	0	16-QAM	21.25	20.24	19.62
3	1	7		21.28	20.31	19.63
3	1	14		21.19	20.24	19.56
3	8	0		19.97	19.17	18.77
3	8	4		19.99	19.18	18.76
3	8	7		19.95	19.20	18.72
3	15	0		19.94	19.08	18.81

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.94	21.13	20.77
5	1	12		21.92	21.18	20.74
5	1	24		21.83	21.14	20.63
5	12	0		20.98	20.17	19.85
5	12	6		20.96	20.18	19.82
5	12	11		20.93	20.16	19.80
5	25	0		20.90	20.14	19.76
5	1	0	16-QAM	21.45	20.45	20.12
5	1	12		21.43	20.48	20.10
5	1	24		21.34	20.44	20.01
5	12	0		19.98	19.14	18.89
5	12	6		19.98	19.13	18.85
5	12	11		19.93	19.15	18.85
5	25	0		19.86	19.13	18.74
10	1	0	QPSK	21.92	21.10	21.21
10	1	24		21.86	21.16	20.93
10	1	49		21.61	21.14	20.78
10	25	0		20.92	20.29	19.88
10	25	12		20.85	20.26	19.83
10	25	24		20.77	20.18	19.77
10	50	0		20.80	20.30	19.87
10	1	0	16-QAM	21.34	20.14	19.88
10	1	24		21.24	20.49	19.74
10	1	49		21.09	20.31	19.62
10	25	0		19.94	19.23	18.73
10	25	12		19.85	19.28	18.85
10	25	24		19.79	19.18	18.78
10	50	0		19.83	19.19	18.78

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	21.72	21.10	21.13
15	1	37		21.74	21.17	20.99
15	1	74		21.39	21.18	20.77
15	36	0		20.93	20.19	20.03
15	36	18		20.82	20.24	19.93
15	36	39		20.66	20.25	19.88
15	75	0		20.80	20.23	19.98
15	1	0	16-QAM	21.31	20.33	20.22
15	1	38		21.14	20.35	20.07
15	1	75		20.88	20.37	19.87
15	36	0		19.93	19.22	19.00
15	36	18		19.82	19.26	18.91
15	36	39		19.68	19.25	18.85
15	75	0		19.76	19.17	18.98
20	1	0	QPSK	21.95	21.05	20.72
20	1	49		22.05	21.17	20.80
20	1	99		21.92	21.05	20.68
20	50	0		21.93	21.20	20.73
20	50	24		21.87	21.12	20.66
20	50	49		21.94	21.16	20.75
20	100	0		20.88	20.07	19.65
20	1	0	16-QAM	21.27	20.48	20.46
20	1	49		21.01	20.44	20.32
20	1	99		20.60	20.53	20.08
20	50	0		19.89	19.13	19.18
20	50	24		19.73	19.17	19.08
20	50	49		19.54	19.20	18.97
20	100	0		19.65	19.17	19.01

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.55	21.45	21.03
1.4	1	2		21.59	21.17	21.17
1.4	1	5		21.24	21.16	21.32
1.4	3	0		21.55	21.16	21.30
1.4	3	1		21.51	21.08	21.25
1.4	3	2		21.59	21.13	21.32
1.4	6	0		20.50	20.04	20.24
1.4	1	0	16-QAM	20.66	20.25	20.06
1.4	1	2		20.75	20.30	20.16
1.4	1	5		20.70	20.24	20.10
1.4	3	0		20.76	20.39	20.45
1.4	3	1		20.71	20.31	20.37
1.4	3	2		20.76	20.36	20.45
1.4	6	0		19.70	19.20	19.40
3	1	0	QPSK	21.41	21.01	21.25
3	1	7		21.51	21.04	21.30
3	1	14		21.44	20.96	21.27
3	8	0		20.56	20.14	20.28
3	8	4		20.57	20.11	20.28
3	8	7		20.60	20.11	20.30
3	15	0		20.55	20.06	20.27
3	1	0	16-QAM	20.89	20.24	20.04
3	1	7		20.96	20.27	20.09
3	1	14		20.93	20.17	20.05
3	8	0		19.59	19.13	19.26
3	8	4		19.61	19.12	19.26
3	8	7		19.63	19.10	19.29
3	15	0		19.59	19.01	19.33

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.56	21.16	21.17
5	1	12		21.59	21.12	21.24
5	1	24		21.54	21.04	21.20
5	12	0		20.60	20.15	20.27
5	12	6		20.62	20.14	20.30
5	12	11		20.61	20.12	20.31
5	25	0		20.54	20.07	20.21
5	1	0	16-QAM	21.07	20.50	20.44
5	1	12		21.18	20.43	20.54
5	1	24		21.12	20.33	20.53
5	12	0		19.62	19.14	19.31
5	12	6		19.65	19.10	19.34
5	12	11		19.64	19.07	19.35
5	25	0		19.54	19.12	19.19
10	1	0	QPSK	21.50	21.24	21.16
10	1	24		21.60	21.11	21.26
10	1	49		21.55	21.05	21.31
10	25	0		20.59	20.18	20.10
10	25	12		20.59	20.12	20.15
10	25	24		20.61	20.08	20.21
10	50	0		20.59	20.12	20.16
10	1	0	16-QAM	20.96	20.42	19.91
10	1	24		21.08	20.28	20.02
10	1	49		21.00	20.19	20.11
10	25	0		19.61	19.17	19.09
10	25	12		19.61	19.10	19.16
10	25	24		19.64	19.08	19.20
10	50	0		19.62	19.18	19.14

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	21.50	21.30	21.13
15	1	37		21.59	21.09	21.26
15	1	74		21.35	21.01	21.35
15	36	0		20.61	20.24	20.16
15	36	18		20.60	20.17	20.24
15	36	39		20.54	20.16	20.29
15	75	0		20.58	20.21	20.26
15	1	0	16-QAM	20.95	20.51	20.12
15	1	38		21.07	20.28	20.24
15	1	75		20.84	20.18	20.38
15	36	0		19.65	19.30	19.05
15	36	18		19.63	19.22	19.16
15	36	39		19.58	19.18	19.20
15	75	0		19.56	19.17	19.23
20	1	0	QPSK	21.56	21.03	21.27
20	1	49		21.68	21.14	21.37
20	1	99		21.57	21.00	21.29
20	50	0		20.61	20.23	20.06
20	50	24		20.57	20.14	20.11
20	50	49		20.44	20.09	20.21
20	100	0		20.51	20.16	20.12
20	1	0	16-QAM	20.90	20.66	20.25
20	1	49		20.94	20.34	20.34
20	1	99		20.57	20.26	20.54
20	50	0		19.66	19.25	19.10
20	50	24		19.61	19.15	19.15
20	50	49		19.48	19.08	19.24
20	100	0		19.53	19.17	19.12

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.45	24.72	25.00
1.4	1	2		24.54	24.83	25.06
1.4	1	5		24.48	24.75	24.96
1.4	3	0		24.45	24.89	24.87
1.4	3	1		24.40	24.83	24.81
1.4	3	2		24.49	24.89	24.85
1.4	6	0		23.36	23.79	23.85
1.4	1	0	16-QAM	23.49	23.92	23.55
1.4	1	2		23.55	23.98	23.62
1.4	1	5		23.49	23.97	23.55
1.4	3	0		23.60	24.09	23.92
1.4	3	1		23.56	24.02	23.85
1.4	3	2		23.61	24.11	23.93
1.4	6	0		22.55	22.92	22.90
3	1	0	QPSK	24.28	24.66	24.99
3	1	7		24.33	24.81	25.00
3	1	14		24.33	24.77	24.96
3	8	0		23.42	23.86	23.98
3	8	4		23.46	23.87	23.94
3	8	7		23.48	23.89	23.94
3	15	0		23.41	23.84	23.86
3	1	0	16-QAM	23.68	23.87	23.60
3	1	7		23.75	23.98	23.58
3	1	14		23.70	23.96	23.52
3	8	0		22.44	22.84	22.85
3	8	4		22.45	22.86	22.83
3	8	7		22.46	22.86	22.82
3	15	0		22.44	22.78	22.86

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.39	24.80	24.90
5	1	12		24.42	24.87	24.90
5	1	24		24.50	24.89	24.80
5	12	0		23.46	23.84	23.98
5	12	6		23.50	23.88	23.98
5	12	11		23.55	23.94	23.94
5	25	0		23.46	23.85	23.87
5	1	0	16-QAM	23.85	24.04	24.10
5	1	12		23.88	24.12	24.09
5	1	24		23.91	24.16	24.00
5	12	0		22.46	22.78	22.93
5	12	6		22.47	22.83	22.94
5	12	11		22.51	22.88	22.92
5	25	0		22.41	22.83	22.83
10	1	0	QPSK	24.38	24.68	25.01
10	1	24		24.52	24.82	25.05
10	1	49		24.72	24.93	25.06
10	25	0		23.47	23.76	23.90
10	25	12		23.56	23.87	23.91
10	25	24		23.65	23.93	23.92
10	50	0		23.57	23.86	23.94
10	1	0	16-QAM	23.75	23.77	23.78
10	1	24		23.85	23.98	23.69
10	1	49		24.05	24.06	23.65
10	25	0		22.47	22.73	22.88
10	25	12		22.54	22.83	22.85
10	25	24		22.65	22.90	22.89
10	50	0		22.56	22.87	22.89

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.74	24.74	24.88
1.4	1	2		24.78	24.73	24.74
1.4	1	5		24.72	24.65	24.77
1.4	3	0		23.82	23.76	23.72
1.4	3	1		23.80	23.73	23.68
1.4	3	2		23.79	23.73	23.64
1.4	6	0		23.75	23.70	23.48
1.4	1	0	16-QAM	23.93	23.78	23.29
1.4	1	2		24.03	23.81	23.34
1.4	1	5		23.98	23.78	23.23
1.4	3	0		24.05	23.91	23.67
1.4	3	1		23.99	23.85	23.59
1.4	3	2		24.06	23.92	23.62
1.4	6	0		22.98	22.83	22.63
3	1	0	QPSK	24.65	24.66	24.54
3	1	7		24.72	24.65	24.60
3	1	14		24.66	24.58	24.65
3	8	0		23.83	23.80	23.60
3	8	4		23.85	23.78	23.60
3	8	7		23.85	23.76	23.57
3	15	0		23.82	23.73	23.56
3	1	0	16-QAM	24.13	23.75	23.40
3	1	7		24.16	23.81	23.36
3	1	14		24.11	23.77	23.20
3	8	0		22.87	22.78	22.63
3	8	4		22.91	22.79	22.60
3	8	7		22.89	22.77	22.55
3	15	0		22.89	22.68	22.63

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.78	24.82	24.56
5	1	12		24.81	24.79	24.52
5	1	24		24.77	24.67	24.51
5	12	0		23.86	23.76	23.69
5	12	6		23.86	23.74	23.66
5	12	11		23.83	23.74	23.64
5	25	0		23.77	23.70	23.58
5	1	0	16-QAM	24.27	23.93	23.94
5	1	12		24.28	23.93	23.88
5	1	24		24.15	23.95	23.68
5	12	0		22.89	22.72	22.75
5	12	6		22.88	22.73	22.73
5	12	11		22.84	22.75	22.68
5	25	0		22.78	22.73	22.63
10	1	0	QPSK	24.81	24.67	24.59
10	1	24		24.92	24.75	24.67
10	1	49		24.85	24.64	24.62
10	25	0		24.81	24.77	24.57
10	25	12		24.75	24.71	24.51
10	25	24		24.86	24.75	24.55
10	50	0		23.80	23.76	23.69
10	1	0	16-QAM	24.19	23.89	23.52
10	1	24		24.10	23.80	23.56
10	1	49		24.05	23.86	23.36
10	25	0		22.86	22.76	22.72
10	25	12		22.83	22.75	22.73
10	25	24		22.80	22.75	22.69
10	50	0		22.84	22.80	22.72

LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.50	24.47	24.59
5	1	12		24.50	24.52	24.66
5	1	24		24.55	24.55	24.69
5	12	0		23.27	23.58	23.66
5	12	6		23.52	23.62	23.69
5	12	11		23.55	23.63	23.70
5	25	0		23.47	23.56	23.62
5	1	0	16-QAM	23.70	23.78	24.08
5	1	12		23.82	23.88	24.10
5	1	24		23.87	23.86	24.04
5	12	0		22.48	22.65	22.68
5	12	6		22.50	22.67	22.69
5	12	11		22.58	22.70	22.69
5	25	0		22.54	22.59	22.61
10	1	0	QPSK	/	24.46	/
10	1	24		/	24.55	/
10	1	49		/	24.71	/
10	25	0		/	23.47	/
10	25	12		/	23.57	/
10	25	24		/	23.65	/
10	50	0		/	23.57	/
10	1	0	16-QAM	/	23.78	/
10	1	24		/	23.98	/
10	1	49		/	23.98	/
10	25	0		/	22.53	/
10	25	12		/	22.61	/
10	25	24		/	22.68	/
10	50	0		/	22.61	/

10.2 Tune up power

Mode	GSM850			GSM1900		
CH	LOW	MID	HIGH	LOW	MID	HIGH
GPRS (1 Slot)	32±1dBm	32.5±1dBm	32±1dBm	28.5±1dBm	27±1dBm	27±1dBm
GPRS (2 Slot)	31.5±1dBm	32±1dBm	31.5±1dBm	27.5±1dBm	26±1dBm	26±1dBm
GPRS (3 Slot)	29.5±1dBm	30±1dBm	29.5±1dBm	26±1dBm	24±1dBm	24.3±1dBm
GPRS (4 Slot)	28.5±1dBm	29±1dBm	28.5±1dBm	24.5±1dBm	23±1dBm	23±1dBm
EDGE (1 Slot)	26.5±1dBm	26.5±1dBm	26.5±1dBm	23.5±1dBm	23±1dBm	23.5±1dBm
EDGE (2 Slot)	25.5±1dBm	26±1dBm	25.5±1dBm	22.5±1dBm	22±1dBm	22±1dBm
EDGE (3 Slot)	23±1dBm	23±1dBm	23±1dBm	20.5±1dBm	19.5±1dBm	19.5±1dBm
EDGE (4 Slot)	21.3±1dBm	21.5±1dBm	21±1dBm	18.5±1dBm	18±1dBm	18±1dBm

Mode	WCDMA Band II	WCDMA Band IV	WCDMA Band V
RMR	21.5±1dBm	21±1dBm	24±1dBm
HSDPA Subtest-1	21.5±1dBm	21±1dBm	24±1dBm
HSDPA Subtest-2	21±1dBm	20.5±1dBm	23.6±1dBm
HSDPA Subtest-3	19.5±1dBm	19.5±1dBm	22.5±1dBm
HSDPA Subtest-4	20±1dBm	19.5±1dBm	22.5±1dBm
HSUPA Subtest-1	20.5±1dBm	20.5±1dBm	24±1dBm
HSUPA Subtest-2	20.5±1dBm	20.5±1dBm	24±1dBm
HSUPA Subtest-3	19.5±1dBm	19.5±1dBm	23±1dBm
HSUPA Subtest-4	21±1dBm	20.8±1dBm	24±1dBm
HSUPA Subtest-5	20±1dBm	20±1dBm	23.5±1dBm

Mode	BT
GFSK	5.5±1dBm
π/4-DQPSK	7.5±1dBm
8DPSK	7.8±1dBm

Mode	BLE
GFSK(1Mbps)	8±1dBm

Mode	2.4G WLAN
802.11b	16±1dBm
802.11g	15±1dBm
802.11n(HT20)	15.5±1dBm
802.11n(HT40)	14±1dBm

Mode	5.2G WLAN
802.11a	14.5±1dBm
802.11 n-HT20	14±1dBm
802.11 n-HT40	14.8±1dBm
802.11 ac-VHT20	13.8±1dBm
802.11 ac-VHT40	14.3±1dBm

Mode	5.3G WLAN
802.11a	14.8±1dBm
802.11 n-HT20	14±1dBm
802.11 n-HT40	14±1dBm
802.11 ac-VHT20	13.8±1dBm
802.11 ac-VHT40	14±1dBm

Mode	5.6G WLAN
802.11a	13.8±1dBm
802.11 n-HT20	14±1dBm
802.11 n-HT40	13.8±1dBm
802.11 ac-VHT20	12.5±1dBm
802.11 ac-VHT40	13±1dBm

Mode	5.8G WLAN
802.11a	13.5±1dBm
802.11 n-HT20	14±1dBm
802.11 n-HT40	13.5±1dBm
802.11 ac-VHT20	13±1dBm
802.11 ac-VHT40	12.8±1dBm

BW[MHz]	RB Size	Mode	Band 2	Band 4	Band 5	Band 12	Band 13
1.4	1	QPSK	21±1dBm	21±1dBm	24.3±1dBm	24±1dBm	N/A
1.4	3		20±1dBm	21±1dBm	24±1dBm	23±1dBm	N/A
1.4	6		20±1dBm	20±1dBm	23±1dBm	23±1dBm	N/A
1.4	1	16-QAM	20.5±1dBm	20±1dBm	23±1dBm	23.5±1dBm	N/A
1.4	3		20.5±1dBm	19±1dBm	23.5±1dBm	23.5±1dBm	N/A
1.4	6		19.5±1dBm	19±1dBm	22±1dBm	22±1dBm	N/A
3	1	QPSK	21±1dBm	21±1dBm	24.3±1dBm	24±1dBm	N/A
3	8		20±1dBm	20±1dBm	23±1dBm	23±1dBm	N/A
3	15		20±1dBm	20±1dBm	23±1dBm	23±1dBm	N/A
3	1	16-QAM	20.5±1dBm	20±1dBm	23±1dBm	23.5±1dBm	N/A
3	8		19±1dBm	19±1dBm	22±1dBm	22±1dBm	N/A
3	15		19±1dBm	19±1dBm	22±1dBm	22±1dBm	N/A
5	1	QPSK	21±1dBm	21±1dBm	24±1dBm	24±1dBm	24±1dBm
5	12		20±1dBm	20±1dBm	23±1dBm	23±1dBm	23±1dBm
5	25		20±1dBm	20±1dBm	23±1dBm	23±1dBm	23±1dBm
5	1	16-QAM	20.5±1dBm	20.5±1dBm	23.5±1dBm	23.5±1dBm	23.5±1dBm
5	12		19±1dBm	19±1dBm	22±1dBm	22±1dBm	22±1dBm
5	25		19±1dBm	19±1dBm	22±1dBm	22±1dBm	22±1dBm
10	1	QPSK	21±1dBm	21±1dBm	24.3±1dBm	24±1dBm	24±1dBm
10	25		20±1dBm	19.8±1dBm	23±1dBm	24±1dBm	23±1dBm
10	50		20±1dBm	19.8±1dBm	23±1dBm	23±1dBm	22.8±1dBm
10	1	16-QAM	20.5±1dBm	20.5±1dBm	23.5±1dBm	23.5±1dBm	23±1dBm
10	25		19±1dBm	19±1dBm	22±1dBm	22±1dBm	22±1dBm
10	50		19±1dBm	19±1dBm	22±1dBm	22±1dBm	22±1dBm
15	1	QPSK	21±1dBm	21±1dBm	N/A	N/A	N/A
15	36		20±1dBm	20±1dBm	N/A	N/A	N/A
15	75		20±1dBm	20±1dBm	N/A	N/A	N/A
15	1	16-QAM	20.5±1dBm	20.5±1dBm	N/A	N/A	N/A
15	36		19±1dBm	19±1dBm	N/A	N/A	N/A
15	75		19±1dBm	19±1dBm	N/A	N/A	N/A
20	1	QPSK	21.3±1dBm	21±1dBm	N/A	N/A	N/A
20	50		21±1dBm	19.8±1dBm	N/A	N/A	N/A
20	100		20±1dBm	19.8±1dBm	N/A	N/A	N/A
20	1	16-QAM	20.5±1dBm	20±1dBm	N/A	N/A	N/A
20	50		19±1dBm	19±1dBm	N/A	N/A	N/A
20	100		19±1dBm	19±1dBm	N/A	N/A	N/A

11. EUT and Test Setup Photo

11.1 EUT Photos

Front side

Back side

Right Edge



Left Edge



Top Edge

Bottom Edge



11.2 Setup Photos

Body Front side (separation distance is 5mm)



Body Back side (separation distance is 5mm)



Body Left side (separation distance is 5mm)

Body Right side (separation distance is 5mm)

Body Top side (separation distance is 5mm)

Body Bottom side (separation distance is 5mm)



Body Front side (separation distance is 0mm)



Body Back side (separation distance is 0mm)



Body Left side (separation distance is 0mm)

Body Right side (separation distance is 0mm)

Body Top side (separation distance is 0mm)

Body Bottom side (separation distance is 0mm)



Liquid depth (15 cm)



12. SAR Result Summary

12.1 Body-worn Hotspot SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	GPRS Data-4 Slot	Front Side	836.6	0.122	-2.30	30.00	29.70	1.072	0.131	/
		Back Side	824.2	0.811	-0.04	29.50	29.15	1.084	0.879	/
		Back Side	836.6	0.940	2.38	30.00	29.70	1.072	**1.007**	**1**
		Back Side	848.8	0.826	-3.56	29.50	29.18	1.076	0.889	/
		Left Side	836.6	0.161	-3.74	30.00	29.70	1.072	0.173	/
		Right Side	836.6	0.388	1.06	30.00	29.70	1.072	0.416	/
		Top Side	836.6	0.162	2.43	30.00	29.70	1.072	0.174	/
		Bottom Side	836.6	0.07	3.61	30.00	29.70	1.072	0.075	/
PCS 1900	GPRS Data-4 Slot	Front Side	1850.2	0.696	-1.99	25.50	25.44	1.014	0.706	/
		Back Side	1850.2	1.033	3.96	25.50	25.44	1.014	**1.047**	**2**
		Back Side	1880	0.948	-3.59	24.00	23.63	1.089	1.032	/
		Back Side	1909.8	0.907	-3.47	24.00	23.61	1.094	0.992	/
		Left Side	1850.2	0.435	-1.56	25.50	25.44	1.014	0.441	/
		Right Side	1850.2	0.49	-0.87	25.50	25.44	1.014	0.497	/
		Top Side	1850.2	0.178	-3.25	25.50	25.44	1.014	0.180	/
		Bottom Side	1850.2	0.077	1.28	25.50	25.44	1.014	0.078	/
WCDMA Band II	RMC	Front Side	1852.4	0.6	2.14	22.50	22.09	1.099	0.659	/
		Back Side	1852.4	0.891	0.74	22.50	22.09	1.099	**0.979**	**3**
		Back Side	1880	0.768	0.22	22.50	21.51	1.256	0.965	/
		Back Side	1907.6	0.679	2.99	22.50	21.01	1.409	0.957	/
		Left Side	1852.4	0.378	-0.89	22.50	22.09	1.099	0.415	/
		Right Side	1852.4	0.421	1.89	22.50	22.09	1.099	0.463	/
		Top Side	1852.4	0.151	-2.39	22.50	22.09	1.099	0.166	/
WCDMA Band IV	RMC	Front Side	1712.6	0.42	-1.72	22.00	21.83	1.040	0.437	/
		Back Side	1712.6	0.621	3.35	22.00	21.83	1.040	**0.646**	**4**
		Left Side	1712.6	0.265	1.69	22.00	21.83	1.040	0.276	/
		Right Side	1712.6	0.292	0.29	22.00	21.83	1.040	0.304	/
		Top Side	1712.6	0.106	-2.00	22.00	21.83	1.040	0.110	/
WCDMA Band V	RMC	Front Side	846.6	0.122	0.91	25.00	24.87	1.030	0.126	/
		Back Side	826.4	0.86	2.61	25.00	24.48	1.127	0.969	/
		Back Side	836.4	0.902	2.17	25.00	24.86	1.033	0.932	/
		Back Side	846.6	0.941	1.64	25.00	24.87	1.030	**0.970**	**5**
		Left Side	846.6	0.163	3.59	25.00	24.87	1.030	0.168	/
		Right Side	846.6	0.388	-1.01	25.00	24.87	1.030	0.400	/
		Top Side	846.6	0.16	1.06	25.00	24.87	1.030	0.165	/
		Bottom Side	846.6	0.07	-0.75	25.00	24.87	1.030	0.072	/
2.4GHz WLAN	802.11b	Front Side	2412	0.227	-2.54	16.50	16.65	0.966	0.219	/
		Back Side	2412	0.460	-2.74	16.50	16.65	0.966	**0.444**	**6**
		Left Side	2412	0.193	-0.89	16.50	16.65	0.966	0.186	/
		Bottom Side	2412	0.090	-2.78	16.50	16.65	0.966	0.087	/
5.2GHz WLAN	802.11n-HT40	Front Side	5230	0.115	3.01	15.80	15.56	1.057	0.122	/
		Back Side	5230	0.302	-2.53	15.80	15.56	1.057	**0.319**	**7**
		Left Side	5230	0.052	-0.47	15.80	15.56	1.057	0.055	/
		Bottom Side	5230	0.037	-0.37	15.80	15.56	1.057	0.039	/

5.3GHz WLAN	802.11a	Front Side	5260	0.116	-0.13	15.80	15.51	1.069	0.124	/
		Back Side	5260	0.302	1.95	15.80	15.51	1.069	**0.323**	**8**
		Left Side	5260	0.053	1.43	15.80	15.51	1.069	0.057	/
		Bottom Side	5260	0.036	0.78	15.80	15.51	1.069	0.038	/
5.6GHz WLAN	802.11n-HT20	Front Side	5500	0.17	-0.78	15.00	14.74	1.062	0.180	/
		Back Side	5500	0.448	-2.04	15.00	14.74	1.062	**0.476**	**9**
		Left Side	5500	0.08	-2.87	15.00	14.74	1.062	0.085	/
		Bottom Side	5500	0.057	0.24	15.00	14.74	1.062	0.061	/
5.8GHz WLAN	802.11n-HT20	Front Side	5745	0.134	-1.85	15.00	14.88	1.028	0.138	/
		Back Side	5745	0.361	-1.81	15.00	14.88	1.028	**0.371**	**10**
		Left Side	5745	0.063	-0.29	15.00	14.88	1.028	0.065	/
		Bottom Side	5745	0.045	2.36	15.00	14.88	1.028	0.046	/

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	49	Front side	1860	0.634	1.91	22.30	22.05	1.059	0.672	/
			50	49	Front side	1860	0.561	0.27	22.00	21.94	1.014	0.569	/
			1	49	Back Side	1860	0.946	-1.25	22.30	22.05	1.059	**1.002**	**11**
			50	49	Back Side	1860	0.834	-2.49	22.00	21.94	1.014	0.846	/
			1	49	Left Side	1860	0.399	-0.11	22.30	22.05	1.059	0.423	/
			50	49	Left Side	1860	0.351	-3.85	22.00	21.94	1.014	0.356	/
			1	49	Right Side	1860	0.445	3.79	22.30	22.05	1.059	0.471	/
			50	49	Right Side	1860	0.395	2.75	22.00	21.94	1.014	0.400	/
			1	49	Top Side	1860	0.162	-1.70	22.30	22.05	1.059	0.172	/
			50	49	Top Side	1860	0.142	-2.05	22.00	21.94	1.014	0.144	/
LTE Band 4	20M	QPSK	1	49	Front side	1720	0.372	-2.68	22.00	21.68	1.076	0.400	/
			50	0	Front side	1720	0.326	-0.29	20.80	20.61	1.045	0.341	/
			1	49	Back Side	1720	0.549	-2.94	22.00	21.68	1.076	**0.591**	**12**
			50	0	Back Side	1720	0.483	-0.27	20.80	20.61	1.045	0.505	/
			1	49	Left Side	1720	0.231	-0.80	22.00	21.68	1.076	0.249	/
			50	0	Left Side	1720	0.207	0.64	20.80	20.61	1.045	0.216	/
			1	49	Right Side	1720	0.262	-2.45	22.00	21.68	1.076	0.282	/
			50	0	Right Side	1720	0.232	-1.31	20.80	20.61	1.045	0.242	/
			1	49	Top Side	1720	0.094	0.02	22.00	21.68	1.076	0.101	/
			50	0	Top Side	1720	0.083	-3.59	20.80	20.61	1.045	0.087	/

LTE Band 5	10M	QPSK	1	49	Front side	844	0.065	-0.34	25.30	25.06	1.057	0.069	/
			25	24	Front side	836.5	0.06	2.11	24.00	23.93	1.016	0.061	/
			1	49	Back Side	844	0.493	1.90	25.30	25.06	1.057	**0.521**	**13**
			25	24	Back Side	836.5	0.436	-1.76	24.00	23.93	1.016	0.443	/
			1	49	Left Side	844	0.211	-2.41	25.30	25.06	1.057	0.223	/
			25	24	Left Side	836.5	0.189	-0.07	24.00	23.93	1.016	0.192	/
			1	49	Right Side	844	0.232	2.28	25.30	25.06	1.057	0.245	/
			25	24	Right Side	836.5	0.204	-3.58	24.00	23.93	1.016	0.207	/
			1	49	Top Side	844	0.085	-1.11	25.30	25.06	1.057	0.090	/
			25	24	Top Side	836.5	0.075	-2.68	24.00	23.93	1.016	0.076	/
			1	49	Bottom Side	844	0.038	-1.22	25.30	25.06	1.057	0.040	/
			25	24	Bottom Side	836.5	0.036	-2.26	24.00	23.93	1.016	0.037	/
LTE Band 12	10M	QPSK	1	24	Front side	704	0.102	0.45	25.00	24.92	1.019	0.104	/
			25	24	Front side	704	0.092	3.66	25.00	24.86	1.033	0.095	/
			1	24	Back Side	704	0.780	-0.82	25.00	24.92	1.019	**0.795**	**14**
			25	24	Back Side	704	0.688	0.33	25.00	24.86	1.033	0.711	/
			1	24	Left Side	704	0.331	1.50	25.00	24.92	1.019	0.337	/
			25	24	Left Side	704	0.293	-3.58	25.00	24.86	1.033	0.303	/
			1	24	Right Side	704	0.368	-0.67	25.00	24.92	1.019	0.375	/
			25	24	Right Side	704	0.327	2.67	25.00	24.86	1.033	0.338	/
			1	24	Top Side	704	0.133	1.17	25.00	24.92	1.019	0.135	/
			25	24	Top Side	704	0.116	-1.55	25.00	24.86	1.033	0.120	/
			1	24	Bottom Side	704	0.059	-0.90	25.00	24.92	1.019	0.060	/
			25	24	Bottom Side	704	0.05	1.87	25.00	24.86	1.033	0.052	/

LTE Band 13	10M	QPSK	1	49	Front side	782	0.096	1.85	25.00	24.71	1.069	0.103	/
			25	24	Front side	782	0.086	3.94	24.00	23.65	1.084	0.093	/
			1	49	Back Side	782	0.727	0.09	25.00	24.71	1.069	**0.777**	**15**
			25	24	Back Side	782	0.641	-2.93	24.00	23.65	1.084	0.695	/
			1	49	Left Side	782	0.305	-3.09	25.00	24.71	1.069	0.326	/
			25	24	Left Side	782	0.268	1.20	24.00	23.65	1.084	0.290	/
			1	49	Right Side	782	0.342	-1.37	25.00	24.71	1.069	0.366	/
			25	24	Right Side	782	0.304	-0.70	24.00	23.65	1.084	0.330	/
			1	49	Top Side	782	0.124	-0.23	25.00	24.71	1.069	0.133	/
			25	24	Top Side	782	0.109	-2.59	24.00	23.65	1.084	0.118	/
			1	49	Bottom Side	782	0.054	2.58	25.00	24.71	1.069	0.058	/
			25	24	Bottom Side	782	0.046	-1.21	24.00	23.65	1.084	0.050	/

Note:

1. The test separation of all above table is 5mm.
2. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
   a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
   b. Scaled SAR(W/kg) = Measured SAR(W/kg) *Tune-up Scaling Factor
3. When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The “Portable Hotspot” feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.

12.2 Limbs SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	GPRS Data-4 Slot	Front Side	836.6	0.140	-2.19	30.00	29.70	1.072	0.150	/
		Back Side	836.6	1.078	0.72	30.00	29.70	1.072	**1.155**	**16**
		Left Side	836.6	0.184	2.15	30.00	29.70	1.072	0.197	/
		Right Side	836.6	0.445	-0.27	30.00	29.70	1.072	0.477	/
		Top Side	836.6	0.185	-0.97	30.00	29.70	1.072	0.198	/
		Bottom Side	836.6	0.082	1.56	30.00	29.70	1.072	0.088	/
PCS 1900	GPRS Data-4 Slot	Front Side	1850.2	0.676	-0.72	25.50	25.44	1.014	0.685	/
		Back Side	1850.2	1.004	1.09	25.50	25.44	1.014	**1.018**	**17**
		Left Side	1850.2	0.426	-3.18	25.50	25.44	1.014	0.432	/
		Right Side	1850.2	0.473	0.81	25.50	25.44	1.014	0.480	/
		Top Side	1850.2	0.171	0.13	25.50	25.44	1.014	0.173	/
		Bottom Side	1850.2	0.075	-0.88	25.50	25.44	1.014	0.076	/
WCDMA Band II	RMC	Front Side	1852.4	0.763	-3.44	22.50	22.09	1.099	0.839	/
		Back Side	1852.4	1.133	-3.88	22.50	22.09	1.099	**1.245**	**18**
		Left Side	1852.4	0.476	2.75	22.50	22.09	1.099	0.523	/
		Right Side	1852.4	0.532	3.83	22.50	22.09	1.099	0.585	/
		Top Side	1852.4	0.192	2.03	22.50	22.09	1.099	0.211	/
WCDMA Band IV	RMC	Front Side	1712.6	0.770	3.94	22.00	21.83	1.040	0.801	/
		Back Side	1712.6	1.145	0.12	22.00	21.83	1.040	**1.191**	**19**
		Left Side	1712.6	0.481	-1.26	22.00	21.83	1.040	0.500	/
		Right Side	1712.6	0.538	-1.33	22.00	21.83	1.040	0.559	/
		Top Side	1712.6	0.198	2.03	22.00	21.83	1.040	0.206	/
WCDMA Band V	RMC	Front Side	846.6	0.073	3.12	25.00	24.87	1.030	0.075	/
		Back Side	846.6	0.539	-2.61	25.00	24.87	1.030	**0.555**	**20**
		Left Side	846.6	0.096	2.30	25.00	24.87	1.030	0.099	/
		Right Side	846.6	0.225	2.54	25.00	24.87	1.030	0.232	/
		Top Side	846.6	0.095	-3.18	25.00	24.87	1.030	0.098	/
		Bottom Side	846.6	0.041	1.59	25.00	24.87	1.030	0.042	/
2.4GHz WLAN	802.11b	Front Side	2412	0.105	-2.21	16.50	16.65	0.966	0.101	/
		Back Side	2412	0.282	1.93	16.50	16.65	0.966	**0.272**	**21**
		Left Side	2412	0.050	2.31	16.50	16.65	0.966	0.048	/
		Bottom Side	2412	0.035	1.59	16.50	16.65	0.966	0.034	/
5.2GHz WLAN	802.11n-HT40	Front Side	5230	0.134	1.42	15.80	15.56	1.057	0.142	/
		Back Side	5230	0.351	-0.38	15.80	15.56	1.057	**0.371**	**22**
		Left Side	5230	0.064	-3.30	15.80	15.56	1.057	0.068	/
		Bottom Side	5230	0.042	1.15	15.80	15.56	1.057	0.044	/
5.3GHz WLAN	802.11a	Front Side	5260	0.082	-1.48	15.80	15.51	1.069	0.088	/
		Back Side	5260	0.223	-3.59	15.80	15.51	1.069	**0.238**	**23**
		Left Side	5260	0.042	2.44	15.80	15.51	1.069	0.045	/
		Bottom Side	5260	0.028	-0.07	15.80	15.51	1.069	0.030	/
5.6GHz WLAN	802.11n-HT20	Front Side	5500	0.163	-2.78	15.00	14.74	1.062	0.173	/
		Back Side	5500	0.443	-3.32	15.00	14.74	1.062	**0.470**	**24**
		Left Side	5500	0.078	-1.32	15.00	14.74	1.062	0.083	/
		Bottom Side	5500	0.054	-0.88	15.00	14.74	1.062	0.057	/
5.8GHz WLAN	802.11n-HT20	Front Side	5745	0.094	-2.65	15.00	14.88	1.028	0.097	/
		Back Side	5745	0.253	-0.21	15.00	14.88	1.028	**0.260**	**25**
		Left Side	5745	0.045	-1.10	15.00	14.88	1.028	0.046	/
		Bottom Side	5745	0.031	-0.50	15.00	14.88	1.028	0.032	/

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 10g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	49	Front side	1860	0.795	-1.63	22.30	22.05	1.059	0.842	/
			50	49	Front side	1860	0.699	0.77	22.00	21.94	1.014	0.709	/
			1	49	Back Side	1860	1.184	2.89	22.30	22.05	1.059	**1.254**	**26**
			1	49	Back Side	1880	0.947	-3.80	22.30	21.17	1.297	1.228	/
			1	49	Back Side	1900	0.855	2.07	22.30	20.80	1.413	1.208	/
			50	49	Back Side	1860	1.045	1.84	22.00	21.94	1.014	1.060	/
			1	49	Left Side	1860	0.500	-0.07	22.30	22.05	1.059	0.530	/
			50	49	Left Side	1860	0.440	-0.84	22.00	21.94	1.014	0.446	/
			1	49	Right Side	1860	0.558	-2.30	22.30	22.05	1.059	0.591	/
			50	49	Right Side	1860	0.494	-0.44	22.00	21.94	1.014	0.501	/
			1	49	Top Side	1860	0.201	-3.08	22.30	22.05	1.059	0.213	/
			50	49	Top Side	1860	0.177	-0.94	22.00	21.94	1.014	0.179	/
LTE Band 4	20M	QPSK	1	49	Front side	1720	0.734	-0.36	22.00	21.68	1.076	0.790	/
			50	0	Front side	1720	0.648	-1.47	20.80	20.61	1.045	0.677	/
			1	49	Back Side	1720	1.091	2.08	22.00	21.68	1.076	**1.174**	**27**
			50	0	Back Side	1720	0.959	-0.86	20.80	20.61	1.045	1.002	/
			1	49	Left Side	1720	0.460	-3.67	22.00	21.68	1.076	0.495	/
			50	0	Left Side	1720	0.408	-0.60	20.80	20.61	1.045	0.426	/
			1	49	Right Side	1720	0.517	-1.14	22.00	21.68	1.076	0.557	/
			50	0	Right Side	1720	0.455	-2.22	20.80	20.61	1.045	0.475	/
			1	49	Top Side	1720	0.184	-0.20	22.00	21.68	1.076	0.198	/
			50	0	Top Side	1720	0.161	1.74	20.80	20.61	1.045	0.168	/

LTE Band 5	10M	QPSK	1	49	Front side	844	0.063	-3.51	25.30	25.06	1.057	0.067	/
			25	24	Front side	836.5	0.054	1.85	24.00	23.93	1.016	0.055	/
			1	49	Back Side	844	0.468	2.35	25.30	25.06	1.057	**0.495**	**28**
			25	24	Back Side	836.5	0.414	2.54	24.00	23.93	1.016	0.421	/
			1	49	Left Side	844	0.198	-1.40	25.30	25.06	1.057	0.209	/
			25	24	Left Side	836.5	0.174	-3.60	24.00	23.93	1.016	0.177	/
			1	49	Right Side	844	0.220	0.90	25.30	25.06	1.057	0.232	/
			25	24	Right Side	836.5	0.196	-3.66	24.00	23.93	1.016	0.199	/
			1	49	Top Side	844	0.081	0.75	25.30	25.06	1.057	0.086	/
			25	24	Top Side	836.5	0.073	-2.34	24.00	23.93	1.016	0.074	/
			1	49	Bottom Side	844	0.036	-2.53	25.30	25.06	1.057	0.038	/
			25	24	Bottom Side	836.5	0.035	-1.27	24.00	23.93	1.016	0.036	/
LTE Band 12	10M	QPSK	1	24	Front side	704	0.066	1.22	25.00	24.92	1.019	0.067	/
			25	24	Front side	704	0.061	0.90	25.00	24.86	1.033	0.063	/
			1	24	Back Side	704	0.478	-0.99	25.00	24.92	1.019	**0.487**	**29**
			25	24	Back Side	704	0.420	0.86	25.00	24.86	1.033	0.434	/
			1	24	Left Side	704	0.204	-2.15	25.00	24.92	1.019	0.208	/
			25	24	Left Side	704	0.180	1.63	25.00	24.86	1.033	0.186	/
			1	24	Right Side	704	0.229	0.75	25.00	24.92	1.019	0.233	/
			25	24	Right Side	704	0.200	-0.54	25.00	24.86	1.033	0.207	/
			1	24	Top Side	704	0.083	-1.33	25.00	24.92	1.019	0.085	/
			25	24	Top Side	704	0.076	2.08	25.00	24.86	1.033	0.078	/
			1	24	Bottom Side	704	0.035	-0.29	25.00	24.92	1.019	0.036	/
			25	24	Bottom Side	704	0.030	-3.55	25.00	24.86	1.033	0.031	/

LTE Band 13	10M	QPSK	1	49	Front side	782	0.076	-2.14	25.00	24.71	1.069	0.081	/
			25	24	Front side	782	0.069	-1.81	24.00	23.65	1.084	0.075	/
			1	49	Back Side	782	0.578	1.56	25.00	24.71	1.069	**0.618**	**30**
			25	24	Back Side	782	0.508	0.38	24.00	23.65	1.084	0.551	/
			1	49	Left Side	782	0.245	-0.99	25.00	24.71	1.069	0.262	/
			25	24	Left Side	782	0.217	-0.90	24.00	23.65	1.084	0.235	/
			1	49	Right Side	782	0.273	-2.07	25.00	24.71	1.069	0.292	/
			25	24	Right Side	782	0.242	-2.02	24.00	23.65	1.084	0.262	/
			1	49	Top Side	782	0.098	-1.40	25.00	24.71	1.069	0.105	/
			25	24	Top Side	782	0.087	1.53	24.00	23.65	1.084	0.094	/
			1	49	Bottom Side	782	0.046	-1.04	25.00	24.71	1.069	0.049	/
			25	24	Bottom Side	782	0.042	-0.91	24.00	23.65	1.084	0.046	/

Note:

1. The test separation of all above table is 0mm.
2. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
   a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
   b. Scaled SAR(W/kg) = Measured SAR(W/kg) *Tune-up Scaling Factor
3. When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The “Portable Hotspot” feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.

12.3 Repeated SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)
GSM 850	GPRS Data-4 Slot	Back Side	824.2	0.806	-3.65	29.50	29.15	1.084	0.874
		Back Side	836.6	0.905	-2.22	30.00	29.70	1.072	0.970
		Back Side	848.8	0.811	-3.50	29.50	29.18	1.076	0.873
PCS 1900	GPRS Data-4 Slot	Back Side	1850.2	0.995	-1.55	25.50	25.44	1.014	1.009
		Back Side	1880	0.909	-0.60	24.00	23.63	1.089	0.990
		Back Side	1909.8	0.867	0.85	24.00	23.61	1.094	0.948
WCDMA Band II	RMC	Back Side	1852.4	0.864	-3.69	22.50	22.09	1.099	0.950
		Back Side	1880	0.768	-1.93	22.50	21.51	1.256	0.965
		Back Side	1907.6	0.655	1.49	22.50	21.01	1.409	0.923
WCDMA Band V	RMC	Back Side	826.4	0.818	0.11	25.00	24.48	1.127	0.922
		Back Side	836.4	0.862	-0.90	25.00	24.86	1.033	0.890
		Back Side	846.6	0.905	-3.33	25.00	24.87	1.030	0.932

12.4 Repeated SAR measurement

Band	Mode	Test Position	Ch.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio
GSM 850	GPRS Data-4 Slot	Back Side	824.2	0.811	0.806	1.006
		Back Side	836.6	0.940	0.905	1.039
		Back Side	848.8	0.826	0.811	1.019
PCS 1900	GPRS Data-4 Slot	Back Side	1850	1.033	0.995	1.039
		Back Side	1880	0.948	0.909	1.043
		Back Side	1910	0.907	0.867	1.047
WCDMA Band II	RMC	Back Side	1852	0.891	0.864	1.031
		Back Side	1880	0.768	0.768	1.000
		Back Side	1908	0.679	0.655	1.037
WCDMA Band V	RMC	Back Side	826.4	0.86	0.818	1.052
		Back Side	836.4	0.902	0.862	1.047
		Back Side	846.6	0.941	0.905	1.039

Note:

1. Per KDB 865664 D01,for each frequency band ,repeated SAR measurement is required only when the measured SAR is≥0.8W/Kg.
2. Per KDB 865664 D01,if the ratio of largest to smallest SAR for the original and first repeated measurement is≤1.2 and the measured SAR＜1.45W/Kg, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is＞1.20 or when the original or repeated measurement is ≥1.45W/Kg.
4. The ratio is the difference in percentage between original and repeated measured SAR.

12.5 Simultaneous Multi-band Transmission Evaluation

Application Simultaneous Transmission information:

Position	Simultaneous State
Body	1. GSM + 2.4GHz WLAN/5G WLAN
	2. GSM + Bluetooth
	3. WCDMA + 2.4GHz WLAN/5G WLAN
	4. WCDMA + Bluetooth
	5. LTE + 2.4GHz WLAN/5G WLAN
	6. LTE + Bluetooth
Limbs	1. GSM + 2.4GHz WLAN/5G WLAN
	2. GSM + Bluetooth
	3. WCDMA + 2.4GHz WLAN/5G WLAN
	4. WCDMA + Bluetooth
	5. LTE + 2.4GHz WLAN/5G WLAN
	6. LTE + Bluetooth

NOTE:
1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
4. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
a) (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[√f (GHz) /x] W/kg for test separation distances≤ 50 mm;
Where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.
b) 0.4W/Kg for 1-g SAR and 1.0W/Kg for 10-g SAR, when the separation distance is >50mm.

Estimated SAR		Maximum Turn-up Power		Antenna to user(mm)	Frequency (GHz)	Stand Alone SAR (1g) [W/kg]
		dBm	mW			
BT	Body	9	7.943	5	2.402	0.328

Estimated SAR		Maximum Turn-up Power		Antenna to user(mm)	Frequency (GHz)	Stand Alone SAR (10g) [W/kg]
		dBm	mW			
BT	Body	9	7.943	5	2.402	0.131

Simultaneous Mode	Position	Mode	Max. 1-g SAR (W/kg)	1-g Sum SAR (W/kg)
GSM + 2.4G WLAN + NFC	Body	GSM	1.047	1.491
		2.4G WLAN	0.444	
GSM + Bluetooth+ NFC	Body	GSM	1.047	1.375
		BT	0.328	
GSM + 5G WLAN+ NFC	Body	GSM	1.047	1.523
		5G WLAN	0.476	
WCDMA + 2.4G WLAN + NFC	Body	WCDMA	0.979	1.423
		2.4G WLAN	0.444	
WCDMA + Bluetooth+ NFC	Body	WCDMA	0.979	1.307
		BT	0.328	
WCDMA + 5G WLAN+ NFC	Body	WCDMA	0.979	1.455
		5G WLAN	0.476	
LTE + 2.4G WLAN + NFC	Body	LTE	1.002	1.446
		2.4G WLAN	0.444	
LTE + Bluetooth+ NFC	Body	LTE	1.002	1.330
		BT	0.328	
LTE + 5G WLAN+ NFC	Body	LTE	1.002	1.478
		5G WLAN	0.476	

Simultaneous Mode	Position	Mode	Max. 10-g SAR (W/kg)	10-g Sum SAR (W/kg)
GSM + 2.4G WLAN + NFC	Body	GSM	1.155	1.427
		2.4G WLAN	0.272	
GSM + Bluetooth+ NFC	Body	GSM	1.155	1.286
		BT	0.131	
GSM + 5G WLAN+ NFC	Body	GSM	1.155	1.625
		5G WLAN	0.470	
WCDMA + 2.4G WLAN + NFC	Body	WCDMA	1.245	1.517
		2.4G WLAN	0.272	
WCDMA + Bluetooth+ NFC	Body	WCDMA	1.245	1.376
		BT	0.131	
WCDMA + 5G WLAN+ NFC	Body	WCDMA	1.245	1.715
		5G WLAN	0.470	
LTE + 2.4G WLAN + NFC	Body	LTE	1.254	1.526
		2.4G WLAN	0.272	
LTE + Bluetooth+ NFC	Body	LTE	1.254	1.385
		BT	0.131	
LTE + 5G WLAN+ NFC	Body	LTE	1.254	1.724
		5G WLAN	0.470	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	DIP0G750	SN 06/22 DIP0G750-638	2025.02.05	2028.02.04
835MHz Dipole	MVG	DIP0G835	SN 06/22 DIP0G835-639	2025.02.05	2028.02.04
1800MHz Dipole	MVG	DIP1G800	SN 06/22 DIP1G800-640	2025.02.05	2028.02.04
1900MHz Dipole	MVG	DIP1G900	SN 06/22 DIP1G900-641	2025.02.05	2028.02.04
2450MHz Dipole	MVG	DIP2G450	SN 06/22 DIP2G450-645	2025.02.05	2028.02.04
5000MHz Dipole	MVG	DIP5G000	SN 06/22 DIP5G000-653	2025.02.05	2028.02.04
E-Field Probe	MVG	EPGO364	SN 04/22 EPGO364	2025.02.05	2026.02.04
Liquid Calibration Kit	MVG	OCPG 87	SN 06/22 OCPG87	2025.02.05	2026.02.04
Antenna	MVG	ANTA 73	SN 06/22 ANTA 73	N/A	N/A
Ellipsoid Phantom	MVG	ELLI 51	SN 06/22 ELLI 51	N/A	N/A
Phantom	MVG	SAM 148	SN 06/22 SAM148	N/A	N/A
Phone holder	MVG	MSH 117	SN 06/22 MSH 117	N/A	N/A
Laptop positioner	MVG	LSH 36	SN 06/22 LSH 38	N/A	N/A
Directional coupler	SHW	SHWDCP	202203280013	N/A	N/A
Network Analyzer	ZVL	R&S	116184	2025.03.05	2026.03.04
Multi Meter	DMM6500	Keithley	4527252	2025.03.06	2026.03.05
Signal Generator	Keysight	N5182B	MY59100717	2025.03.05	2026.03.04
Wireless Communication Test Set	R&S	CMW500	137737	2025.03.05	2026.03.04
Power Sensor	R&S	Z11	116184	2025.03.05	2026.03.04
Electronic Temperature hygrometer	N/A	ST-W2318	N/A	2025.03.05	2026.03.04
Temperature hygrometer	N/A	TP101	N/A	2025.03.05	2026.03.04

Appendix A. System Validation Plots

System Performance Check Data (750MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm,dy=8mm
Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm
Date of measurement: 2025-05-16

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW
Frequency (MHz)	750.000
Relative permittivity	41.98
Conductivity (S/m)	0.91
Probe	SN 04/22 EPGO364
ConvF	1.67
Crest factor:	1:1

SURFACE SAR	VOLUME SAR
	

Maximum location: X=3.00, Y=2.00 ; SAR Peak: 1.26 W/kg

SAR 10g (W/Kg)	0.574
SAR 1g (W/Kg)	0.830

Z Axis Scan


1.1
0.8
0.6
0.4
0.2
SAR (W/kg)
0.0 2.5 5.0 7.5 12.5 17.5 22.5 27.5 32.5 40.0
Z (mm)
W/kg
0.857
0.754
0.651
0.548
0.445
0.342
0.240
0.137
0.034

System Performance Check Data (835MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm,dy=8mm
Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm
Date of measurement: 2025-05-19

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW
Frequency (MHz)	835.000
Relative permittivity	41.93
Conductivity (S/m)	0.93
Probe	SN 04/22 EPGO364
ConvF	1.72
Crest factor:	1:1

SURFACE SAR	VOLUME SAR
	

Maximum location: X=2.00, Y=2.00 ; SAR Peak: 1.62 W/kg

SAR 10g (W/Kg)	0.639
SAR 1g (W/Kg)	0.980

Z Axis Scan


1.4
1.2
1.0
0.8
0.6
0.4
0.1
SAR (W/kg)
0.0 2.5 5.0 7.5 12.5 17.5 22.5 27.5 32.5 40.0
Z (mm)
W/kg
0.978
0.857
0.739
0.621
0.502
0.384
0.265
0.147
0.028
W/kg
0.935
0.822
0.708
0.595
0.482
0.368
0.255
0.142
0.028

System Performance Check Data (1800MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm, dy=8mm
Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm
Date of measurement: 2025-05-20

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW
Frequency (MHz)	1800.000
Relative permittivity	40.17
Conductivity (S/m)	1.39
Probe	SN 04/22 EPGO364
ConvF	1.92
Crest factor:	1:1

SURFACE	VOLUME SAR
	

Maximum location: X=3.00, Y=0.00 ; SAR Peak: 6.28 W/kg

SAR 10g (W/Kg)	2.084
SAR 1g (W/Kg)	3.859

Z Axis Scan


6.69
6.00
5.00
4.00
3.00
2.00
1.00
0.28
SAR (W/kg)
0.0 2.5 5.0 7.5 12.5 17.5 22.5 27.5 32.5 40.0
Z (mm)
W/kg
4.304
3.768
3.232
2.696
2.159
1.623
1.087
0.551
0.014

System Performance Check Data (1900MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm, dy=8mm
Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm
Date of measurement: 2025-05-18

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW
Frequency (MHz)	1900.000
Relative permittivity	40.94
Conductivity (S/m)	1.44
Probe	SN 04/22 EPGO364
ConvF	2.20
Crest factor:	1:1

SURFACE	VOLUME SAR
	

Maximum location: X=3.00, Y=2.00 ; SAR Peak: 7.11 W/kg

SAR 10g (W/Kg)	2.065
SAR 1g (W/Kg)	4.053

Z Axis Scan


9.69
8.00
6.00
4.00
2.00
0.28
SAR (W/kg)
0.0 2.5 5.0 7.5 12.5 17.5 22.5 27.5 32.5 40.0
Z (mm)
W/kg
6.012
5.260
4.509
3.758
3.006
2.255
1.504
0.752
0.001

System Performance Check Data (2450MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm, dy=8mm
Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm
Date of measurement: 2025-05-20

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW
Frequency (MHz)	2450.000
Relative permittivity	40.48
Conductivity (S/m)	1.75
Probe	SN 04/22 EPGO364
ConvF	2.33
Crest factor:	1:1

SURFACE	VOLUME SAR
	

Maximum location: X=2.00, Y=0.00 ; SAR Peak: 9.32 W/kg

SAR 10g (W/Kg)	2.388
SAR 1g (W/Kg)	5.444

Z Axis Scan


8.56
7.00
6.00
5.00
4.00
3.00
2.00
1.00
0.19
SAR (W/kg)
0.0 2.5 5.0 7.5 12.5 17.5 22.5 27.5 32.5 40.0
Z (mm)
W/kg
5.394
4.721
4.048
3.375
2.701
2.028
1.355
0.682
0.009

System Performance Check Data (5200MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm, dy=8mm
Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm
Date of measurement: 2025-05-22

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW
Frequency (MHz)	5200.000
Relative permittivity	36.86
Conductivity (S/m)	4.64
Probe	SN 04/22 EPGO364
ConvF	1.99
Crest factor:	1:1

SURFACE	VOLUME SAR
	

Maximum location: X=3.00, Y=2.00 ; SAR Peak: 28.17 W/kg

SAR 10g (W/Kg)	2.288
SAR 1g (W/Kg)	8.130

Z Axis Scan


26.45
20.00
15.00
10.00
5.00
0.01
SAR (W/kg)
0 2 4 6 8 10 12 14 16 18 20 22 24 26
Z (mm)
W/kg
16.147
14.129
12.111
10.093
8.075
6.057
4.039
2.021
0.002

System Performance Check Data (5400MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm, dy=8mm
Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm
Date of measurement: 2025-05-22

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels	Middle
Signal	CW
Frequency (MHz)	5400.000
Relative permittivity	35.93
Conductivity (S/m)	4.92
Probe	SN 04/22 EPGO364
ConvF	1.87
Crest factor:	1:1

SURFACE	VOLUME SAR
	

Maximum location: X=1.00, Y=0.00 ; SAR Peak: 29.28 W/kg

SAR 10g (W/Kg)	2.430
SAR 1g (W/Kg)	8.506

Z Axis Scan


30.98
25.00
20.00
15.00
10.00
5.00
0.14
SAR (W/kg)
0 2 4 6 8 10 12 14 16 18 20 22 24 26
Z (mm)
W/kg
18.956
16.587
14.217
11.848
9.479
7.110
4.741
2.372
0.002
W/kg
17.324
15.159
12.994
10.829
8.663
6.498
4.333
2.168
0.002

System Performance Check Data (5600MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm, dy=8mm
Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm
Date of measurement: 2025-05-23

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels	Middle
Signal	CW
Frequency (MHz)	5600.000
Relative permittivity	36.58
Conductivity (S/m)	5.05
Probe	SN 04/22 EPGO364
ConvF	1.87
Crest factor:	1:1

SURFACE	VOLUME SAR
	

Maximum location: X=5.00, Y=3.00 ; SAR Peak: 26.33 W/kg

SAR 10g (W/Kg)	2.375
SAR 1g (W/Kg)	8.118

Z Axis Scan


23.92
20.00
15.00
10.00
5.00
0.18
SAR (W/kg)
0 2 4 6 8 10 12 14 16 18 20 22 24 26
Z (mm)
W/kg
14.759
12.915
11.070
9.226
7.381
5.537
3.692
1.848
0.003
W/kg
13.813
12.087
10.361
8.634
6.908
5.182
3.456
1.730
0.004

System Performance Check Data (5800MHz)

Type: Phone measurement (Complete)
Area scan resolution: dx=8mm, dy=8mm
Zoom scan resolution: dx=4mm dy=4mm dz=2mm
Date of measurement: 2025-05-23

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW
Frequency (MHz)	5800.000
Relative permittivity	36.32
Conductivity (S/m)	5.24
Probe	SN 04/22 EPGO364
ConvF	1.71
Crest factor:	1:1

SURFACE	VOLUME SAR
	

Maximum location: X=5.00, Y=6.00 ; SAR Peak: 24.21 W/kg

SAR 10g (W/Kg)	2.400
SAR 1g (W/Kg)	8.264

Z Axis Scan


21.64
15.00
10.00
5.00
0.15
SAR (W/kg)
0 2 4 6 8 10 12 14 16 18 20 22 24 26
Z (mm)
W/kg
13.186
11.538
9.891
8.243
6.595
4.947
3.299
1.651
0.004
W/kg
12.205
10.680
9.155
7.629
6.104
4.579
3.054
1.529
0.004

Appendix B. SAR Test Plots

Plot 1:

Test Date	2025-05-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS850
Signal	TDMA (GPRS)
Frequency	836.6
SAR 10g (W/Kg)	0.586
SAR 1g (W/Kg)	0.940
ConvF	1.72
Relative permittivity	41.93
Conductivity (S/m)	0.93

Maximum location: X=15.00, Y=-24.00 ; SAR Peak: 1.57 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 2:

Test Date	2025-05-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS1900
Signal	TDMA (GPRS)
Frequency	1850.2
SAR 10g (W/Kg)	0.574
SAR 1g (W/Kg)	1.033
ConvF	2.20
Relative permittivity	40.94
Conductivity (S/m)	1.44

Maximum location: X=0.00, Y=-40.00 ; SAR Peak: 1.67 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 3:

Test Date	2025-05-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 2 (1900)
Signal	WCDMA
Frequency	1852.4
SAR 10g (W/Kg)	0.544
SAR 1g (W/Kg)	0.891
ConvF	2.20
Relative permittivity	40.94
Conductivity (S/m)	1.44

Maximum location: X=0.00, Y=-41.00 ; SAR Peak: 1.40 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 4:

Test Date	2025-05-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 4 (1700)
Signal	WCDMA
Frequency	1712.6
SAR 10g (W/Kg)	0.356
SAR 1g (W/Kg)	0.621
ConvF	1.92
Relative permittivity	40.17
Conductivity (S/m)	1.39

Maximum location: X=14.00, Y=-43.00 ; SAR Peak: 1.00 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 5:

Test Date	2025-05-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 5 (850)
Signal	WCDMA
Frequency	846.6
SAR 10g (W/Kg)	0.576
SAR 1g (W/Kg)	0.941
ConvF	1.72
Relative permittivity	41.93
Conductivity (S/m)	0.93

Maximum location: X=-15.00, Y=23.00 ; SAR Peak: 1.90 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 6:

Test Date	2025-05-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	ISM
Signal	IEEE 802.11b
Frequency	2412
SAR 10g (W/Kg)	0.186
SAR 1g (W/Kg)	0.460
ConvF	2.33
Relative permittivity	40.48
Conductivity (S/m)	1.75

Maximum location: X=7.00, Y=3.00 ; SAR Peak: 1.21 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 7:

Test Date	2025-05-22
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-1
Signal	IEEE 802.11n
Frequency	5230
SAR 10g (W/Kg)	0.156
SAR 1g (W/Kg)	0.302
ConvF	1.99
Relative permittivity	36.86
Conductivity (S/m)	4.64

Maximum location: X=-31.00, Y=42.00 ; SAR Peak: 2.13 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 8:

Test Date	2025-05-22
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2a
Signal	IEEE 802.11a
Frequency	5260
SAR 10g (W/Kg)	0.170
SAR 1g (W/Kg)	0.302
ConvF	1.87
Relative permittivity	35.93
Conductivity (S/m)	4.92

Maximum location: X=9.00, Y=48.00 ; SAR Peak: 1.99 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 9:

Test Date	2025-05-23
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2c
Signal	IEEE 802.11n
Frequency	5500
SAR 10g (W/Kg)	0.209
SAR 1g (W/Kg)	0.448
ConvF	1.87
Relative permittivity	36.58
Conductivity (S/m)	5.05

Maximum location: X=-8.00, Y=40.00 ; SAR Peak: 3.25 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 10:

Test Date	2025-05-23
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-3
Signal	IEEE 802.11n
Frequency	5745
SAR 10g (W/Kg)	0.227
SAR 1g (W/Kg)	0.361
ConvF	1.70
Relative permittivity	36.32
Conductivity (S/m)	5.24

Maximum location: X=-24.00, Y=-18.00 ; SAR Peak: 2.62 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 11:

Test Date	2025-05-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 2
Signal	LTE FDD
Frequency	1860
SAR 10g (W/Kg)	0.579
SAR 1g (W/Kg)	0.946
ConvF	2.20
Relative permittivity	40.94
Conductivity (S/m)	1.44

Maximum location: X=-5.00, Y=-46.00 ; SAR Peak: 1.56 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 12:

Test Date	2025-05-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 4
Signal	LTE FDD
Frequency	1720
SAR 10g (W/Kg)	0.319
SAR 1g (W/Kg)	0.549
ConvF	1.92
Relative permittivity	40.17
Conductivity (S/m)	1.39

Maximum location: X=13.00, Y=-47.00 ; SAR Peak: 0.90 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 13:

Test Date	2025-05-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 5
Signal	LTE FDD
Frequency	844
SAR 10g (W/Kg)	0.302
SAR 1g (W/Kg)	0.493
ConvF	1.72
Relative permittivity	41.93
Conductivity (S/m)	0.93

Maximum location: X=-9.00, Y=41.00 ; SAR Peak: 0.83 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 14:

Test Date	2025-05-16
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 12
Signal	LTE FDD
Frequency	704
SAR 10g (W/Kg)	0.409
SAR 1g (W/Kg)	0.780
ConvF	1.67
Relative permittivity	41.98
Conductivity (S/m)	0.91

Maximum location: X=-8.00, Y=1.00 ; SAR Peak: 1.51 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 15:

Test Date	2025-05-16
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 12
Signal	LTE FDD
Frequency	782
SAR 10g (W/Kg)	0.406
SAR 1g (W/Kg)	0.727
ConvF	1.67
Relative permittivity	41.98
Conductivity (S/m)	0.91

Maximum location: X=-10.00, Y=21.00 ; SAR Peak: 1.39 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 16:

Test Date	2025-05-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS850
Signal	TDMA (GPRS)
Frequency	836.6
SAR 10g (W/Kg)	1.078
SAR 1g (W/Kg)	2.207
ConvF	1.72
Relative permittivity	41.93
Conductivity (S/m)	0.93

Maximum location: X=0.00, Y=11.00 ; SAR Peak: 3.48 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 17:

Test Date	2025-05-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS1900
Signal	TDMA (GPRS)
Frequency	1850.2
SAR 10g (W/Kg)	1.004
SAR 1g (W/Kg)	1.828
ConvF	2.20
Relative permittivity	40.94
Conductivity (S/m)	1.44

Maximum location: X=8.00, Y=40.00 ; SAR Peak: 2.85 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 18:

Test Date	2025-05-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 2 (1900)
Signal	WCDMA
Frequency	1852.4
SAR 10g (W/Kg)	1.133
SAR 1g (W/Kg)	2.030
ConvF	2.20
Relative permittivity	40.94
Conductivity (S/m)	1.44

Maximum location: X=-1.00, Y=47.00 ; SAR Peak: 3.19 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 19:

Test Date	2025-05-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 4 (1700)
Signal	WCDMA
Frequency	1712.6
SAR 10g (W/Kg)	1.145
SAR 1g (W/Kg)	2.152
ConvF	1.92
Relative permittivity	40.17
Conductivity (S/m)	1.39

Maximum location: X=0.00, Y=47.00 ; SAR Peak: 3.60 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 20:

Test Date	2025-05-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 5 (850)
Signal	WCDMA
Frequency	846.6
SAR 10g (W/Kg)	0.539
SAR 1g (W/Kg)	0.960
ConvF	1.72
Relative permittivity	41.93
Conductivity (S/m)	0.93

Maximum location: X=-16.00, Y=16.00 ; SAR Peak: 1.65 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 21:

Test Date	2025-05-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	ISM
Signal	IEEE 802.11b
Frequency	2412
SAR 10g (W/Kg)	0.282
SAR 1g (W/Kg)	0.633
ConvF	2.33
Relative permittivity	40.48
Conductivity (S/m)	1.75

Maximum location: X=16.00, Y=8.00 ; SAR Peak: 1.61 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 22:

Test Date	2025-05-22
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-1
Signal	IEEE 802.11n
Frequency	5230
SAR 10g (W/Kg)	0.351
SAR 1g (W/Kg)	0.922
ConvF	1.99
Relative permittivity	36.86
Conductivity (S/m)	4.64

Maximum location: X=23.00, Y=40.00 ; SAR Peak: 5.20 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 23:

Test Date	2025-05-22
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2a
Signal	IEEE 802.11a
Frequency	5260
SAR 10g (W/Kg)	0.170
SAR 1g (W/Kg)	0.302
ConvF	1.87
Relative permittivity	35.93
Conductivity (S/m)	4.92

Maximum location: X=9.00, Y=48.00 ; SAR Peak: 1.99 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 24:

Test Date	2025-05-23
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2c
Signal	IEEE 802.11n
Frequency	5500
SAR 10g (W/Kg)	0.443
SAR 1g (W/Kg)	1.092
ConvF	1.87
Relative permittivity	36.58
Conductivity (S/m)	5.05

Maximum location: X=15.00, Y=41.00 ; SAR Peak: 5.06 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 25:

Test Date	2025-05-23
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-3
Signal	IEEE 802.11n
Frequency	5745
SAR 10g (W/Kg)	0.253
SAR 1g (W/Kg)	0.394
ConvF	1.70
Relative permittivity	36.32
Conductivity (S/m)	5.24

Maximum location: X=24.00, Y=56.00 ; SAR Peak: 2.51 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 26:

Test Date	2025-05-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 2
Signal	LTE FDD
Frequency	1860
SAR 10g (W/Kg)	1.184
SAR 1g (W/Kg)	2.109
ConvF	2.20
Relative permittivity	40.94
Conductivity (S/m)	1.44

Maximum location: X=2.00, Y=38.00 ; SAR Peak: 3.17 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 27:

Test Date	2025-05-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 4
Signal	LTE FDD
Frequency	1720
SAR 10g (W/Kg)	1.091
SAR 1g (W/Kg)	1.983
ConvF	1.92
Relative permittivity	40.17
Conductivity (S/m)	1.39

Maximum location: X=1.00, Y=37.00 ; SAR Peak: 3.24 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 28:

Test Date	2025-05-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 5
Signal	LTE FDD
Frequency	844
SAR 10g (W/Kg)	0.468
SAR 1g (W/Kg)	0.960
ConvF	1.72
Relative permittivity	41.93
Conductivity (S/m)	0.93

Maximum location: X=-16.00, Y=24.00 ; SAR Peak: 1.87 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 29:

Test Date	2025-05-16
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 12
Signal	LTE FDD
Frequency	704
SAR 10g (W/Kg)	0.478
SAR 1g (W/Kg)	0.959
ConvF	1.67
Relative permittivity	41.98
Conductivity (S/m)	0.91

Maximum location: X=-8.00, Y=32.00 ; SAR Peak: 1.68 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Plot 30:

Test Date	2025-05-16
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 13
Signal	LTE FDD
Frequency	782
SAR 10g (W/Kg)	0.578
SAR 1g (W/Kg)	1.145
ConvF	1.67
Relative permittivity	41.98
Conductivity (S/m)	0.91

Maximum location: X=-7.00, Y=48.00 ; SAR Peak: 1.83 W/kg

SURFACE SAR	VOLUME SAR
	
3D screen shot	**Hot spot position**
	



Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※※END OF THE REPORT※※※※※