

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: SVEA(HK)LIMITED
Address of applicant: FLAT/RM520, 5/F, CORE BUILDING 1, PH 1,1 SCIENCE PARK EAST AVE, SHA TIN, NT, HK, CHINA

Manufacturer: Sveaverken Intelligent Technology (shenzhen) Co., Ltd.
Address of manufacturer: Room 401-501, Building 13, Nangang Second Industrial Park, No.1026, Songbai Road, Sunshine Community, Xili Street, Nanshan District, Shenzhen

General Description of EUT:

Product Name: Robotic Feed Pusher
Trade Name: Sveaverken
Model No.: Nimbo X Kraft+
Adding Model(s): /
Rated Voltage: AC 120V for Adapter power
DC: 58.8V
Battery Capacity: 40000mAh
Model: H82-48V10A
Power Adapter: Input: 110-245VAC 45/65Hz
Battery: Ternary lithium battery 14celles
Output voltage : 58.8VDC
FCC ID: 2BPE2-LF02
Equipment Type: Fixed device

Technical Characteristics of EUT:

Bluetooth AP6275S

Bluetooth Version: V5.1 (BLE mode)
Frequency Range: 2402-2480MHz
RF Output Power: 3.74dBm (Conducted)
Data Rate: 1Mbps
Modulation: GFSK
Quantity of Channels: 40
Channel Separation: 2MHz
Type of Antenna: Glue stick antenna
Antenna Gain: 2.75dBi

Wi-Fi (2.4G) USB6111

Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)
2422-2452MHz for 802.11n(HT40)

RF Output Power:	15.75dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	Glue stick antenna
Antenna Gain:	2.75dBi
Wi-Fi (2.4G) AP6275S	
Support Standards:	802.11b, 802.11g, 802.11n, 802.11ax
Frequency Range:	2412-2462MHz for 802.11b/g/n(ax)(HE20)
RF Output Power:	Antenna 0:16.12dBm (Conducted) Antenna 1:15.71dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM, 256QAM
Quantity of Channels:	11 for 802.11b/g/n(ax)(HE20)
Channel Separation:	5MHz
Type of Antenna:	Glue stick antenna
Antenna Gain:	2.75dBi
Wi-Fi (5G) USB6111	
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40
Frequency Range:	5180-5240MHz, 5745-5825MHz
Max. RF Output Power:	5180-5240MHz:15.51dBm (Conducted) 5745-5825MHz:14.52dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM,256QAM
Type of Antenna:	Glue stick antenna
Antenna Gain:	5180-5240MHz:2.64dBi 5745-5825MHz:3.20dBi
Wi-Fi (5G) AP6275S	
Support Standards:	802.11a, 802.11n(HT20) , 802.11n-HT40, 802.11ac-VHT20/40/80, 802.11ax-HE20/40/80
Frequency Range:	5180-5240MHz, 5745-5825MHz
Max. RF Output Power:	5180-5240MHz: Antenna 0: 16.23dBm (Conducted) Antenna 1:15.65dBm (Conducted) 5745-5825MHz: Antenna 0: 14.88dBm (Conducted) Antenna 1:15.07dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Type of Antenna:	Glue stick antenna
Antenna Gain:	5180-5240MHz:2.64dBi 5745-5825MHz:3.20dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).

(B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Prediction Frequency	Output Power	Antenna Gain	Duty Cycle	Tune-Up Time-Averaged Power	ERP
	(MHz)	(dBm)	(dBi)	(%)	(dBm)	(dBm)
Bluetooth (AP6275S-ANT 0)	2402	3.74	2.75	100	4.00	4.60
Wi-Fi (2.4G) (USB6111)	2412	15.75	2.75	100	16.00	16.60
Wi-Fi (2.4G) (AP6275S-ANT 0)	2412	16.12	2.75	100	17.00	17.60
Wi-Fi (2.4G) (AP6275S-ANT 1)	2412	15.71	2.75	100	16.00	16.60
Wi-Fi (5G) (USB6111)	5180	15.51	2.64	100	16.00	16.49
Wi-Fi (5G) (USB6111)	5745	14.52	3.20	100	15.00	16.05
Wi-Fi (5G) (AP6275S-ANT 0)	5180	16.23	2.64	100	17.00	17.49
Wi-Fi (5G) (AP6275S-ANT 0)	5745	14.88	3.20	100	15.00	16.05
Wi-Fi (5G) (AP6275S-ANT 1)	5180	15.65	2.64	100	16.00	16.49
Wi-Fi (5G) (AP6275S-ANT 1)	5745	15.07	3.20	100	16.00	17.05

Frequency (MHz)	Option	Min. Distance	Max. Power		Exposure Limit	Ratio	Result
		(cm)	(dBm)	(mW)	(mW)		Pass/Fail
2402	C	20.00	4.60	2.88	768.00	0.01	Pass
2412	C	20.00	16.60	45.71	768.00	0.06	Pass
2412	C	20.00	17.60	57.54	768.00	0.07	Pass
2412	C	20.00	16.60	45.71	768.00	0.06	Pass
5180	C	20.00	16.49	44.57	768.00	0.06	Pass

5745	C	20.00	16.05	40.27	768.00	0.05	Pass
5180	C	20.00	17.49	56.10	768.00	0.07	Pass
5745	C	20.00	16.05	40.27	768.00	0.05	Pass
5180	C	20.00	16.49	44.57	768.00	0.06	Pass
5745	C	20.00	17.05	50.70	768.00	0.07	Pass

Note: 1. Time-Averaged Power=Output Power * Duty Cycle; ERP= Time-Averaged Power+ Antenna gain-2.15dB

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P_{th} (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Ratio 3	Simultaneous Ratio	Limit	Result
						Pass/Fail
USB6111 + (AP6275S-ANT 0) + (AP6275S-ANT 1)	0.06	0.07	0.07	0.2	1	Pass

Result: Pass