


FCC CERTIFICATION TEST REPORT

Applicant	:	HANSHOW PTE. LTD.
Address	:	138 ROBINSON ROAD #02-33 OXLEY TOWER SINGAPORE(068906)
Manufacturer	:	HANSHOW PTE. LTD.
Address	:	138 ROBINSON ROAD #02-33 OXLEY TOWER SINGAPORE(068906)
Equipment under Test	:	electronic shelf label
Model No.	:	Nebular Ultra-260WQ-N D1
Trade Mark	:	N/A
FCC ID	:	2BPF3-NU2-260W
Report No.	:	LS-R26070313-1F03
Issue Date	:	Aug. 08, 2026



LabSure Testing Services (Suzhou) Co., Ltd.

TABLE OF CONTENTS

	Test report declares.....	3
1	Summary of test results	6
2	General test information	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	8
2.3.	Assistant equipment used for test	8
2.4.	Block diagram of EUT configuration for test.....	8
2.5.	Deviations of test standard.....	8
2.6.	Test environment conditions	8
2.7.	Test laboratory	8
2.8.	Measurement uncertainty	9
3	Equipment used during test	10
4	20dB Bandwidth.....	12
4.1.	Block diagram of test setup.....	12
4.2.	Limits	12
4.3.	Test Procedure.....	12
4.4.	Test Result.....	12
4.5.	Original test data.....	13
5	Radiated emission	14
5.1.	Block diagram of test setup.....	14
5.2.	Limit	15
5.3.	Test Procedure.....	15
5.4.	Test result	16
6	Field Strength Of Fundamental	20
6.1.	Block diagram of test setup.....	20
6.2.	Limits	20
6.3.	Test Procedure.....	20
6.4.	Test Result.....	20
7	Frequency Stability	22
7.1.	Limit	22
7.2.	Test Procedure.....	22
7.3.	Test Result.....	22
8	Power Line Conducted Emission	23
8.1.	Block diagram of test setup.....	23
8.2.	Power Line Conducted Emission Limits.....	23
8.3.	Test Procedure.....	23
8.4.	Test Result.....	24

9	Antenna Requirements	25
10	Test setup photograph	26
11	Photos of the EUT	26

TEST REPORT DECLARE

Applicant	:	HANSHOW PTE. LTD.
Address	:	138 ROBINSON ROAD #02-33 OXLEY TOWER SINGAPORE(068906)
Manufacturer	:	HANSHOW PTE. LTD.
Address	:	138 ROBINSON ROAD #02-33 OXLEY TOWER SINGAPORE(068906)
Equipment under Test	:	electronic shelf label
Model No.	:	Nebular Ultra-260WQ-N D1
Trade Mark	:	N/A

Test Standard Used:

47 CFR FCC Part 15 Subpart C (Section 15.225)

Test procedure used:




ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

We Declare:

The equipment described above is tested by LabSure Testing Services (Suzhou) Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and LabSure Testing Services (Suzhou) Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above standards.

Report No:	LS-R26041310-6F02		
Date of Receipt:	Jul. 10, 2026	Date of Test:	Jul. 10, 2026 ~ Aug. 08, 2026

Prepared By: 	Reviewed By: 	Authorized By: 
Bacon Dong/Engineer	Leon Wu/Director	Chris Zhong/EMC Manager

Note:

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of LabSure Testing Services (Suzhou) Co., Ltd. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification. The results reported herein have been performed in accordance with the laboratory's terms of accreditation.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Aug. 08, 2026	

1 Summary of test results

Description of Test Item	Standard	Results
20dB Bandwidth	FCC Part 15: 15.215	PASS
Radiated Emission	FCC Part 15: 15.209	PASS
Field Strength Of Fundamental	FCC Part 15: 15.225	PASS
Frequency Stability	FCC Part 15: 15.225	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207	N/A
Antenna requirement	FCC Part 15: 15.203	PASS

2 General test information

2.1. Description of EUT

EUT* Name	:	electronic shelf label
Test Model Number	:	Nebular Ultra-260WQ-N D1
EUT function description	:	Please reference user manual of this device
Power Supply	:	DC 3V by Polymer Li-ion built-in battery
Radio Specification	:	NFC
Modulation	:	ASK
Data Rate	:	106kbps
Wireless charging Operation frequency	:	13.56MHz
Number of Channel	:	1
Antenna Type	:	Loop antenna

Note1: EUT is the ab. of equipment under test.

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number or Type	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test

EUT

2.5. Deviations of test standard

No Deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	20-28°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Lab Information	Company Name: LabSure Testing Services (Suzhou) Co., Ltd. Address: Phase II, No.16 Runsheng Road, Suzhou Industrial Park, Suzhou, People's Republic of China. Tel: +86-0512-62531270, www.lab-sure.com, Email: labsure@lab-sure.com
Accreditation Certificate	A2LA (Certificate No.: 7346.01) LabSure Testing Services (Suzhou) Co., Ltd. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1397) LabSure Testing Services (Suzhou) Co., Ltd. has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 32952; CAB No.:CN0182) LabSure Testing Services (Suzhou) Co., Ltd. has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
Note 1: All tests measurement facilities use to collect the measurement data are located at	

Phase II, No.16 Runsheng Road, Suzhou Industrial Park, Suzhou, China.

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in LabSure Testing Services (Suzhou) Co., Ltd. had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

2.8. Measurement uncertainty

Test Item	Uncertainty
20dB Emission Bandwidth	±1.9%
Carrier Frequency Separation	±1.9%
Maximum Power Spectral Density Level	±1.5dB
Number of Hopping Channel	±1.9%
Time of Occupancy	±0.56 %
Max Peak Conducted Output Power	±1.5 dB
Band-edge Spurious Emission	±1.9 %
Conducted RF Spurious Emission	30MHz-30MHz: ±1.5 dB
	1GHz-12.75GHz: ±1.9dB
	12.75GHz-26.5GHz: ±2.1dB
Uncertainty for Radiation Emission Test (9kHz - 1 GHz)	9kHz-30MHz: 3.4 dB
	30MHz-1000MHz: 2.4dB
Uncertainty for Radiation Emission Test (1 GHz - 40 GHz)	1GHz – 18GHz: 3.1dB
	18GHz – 40GHz: 4.3 dB
Uncertainty for Power Line Conduction Emission Test	3.4 dB (150 kHz - 30 MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	


3 Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Conducted Test					
MXA Signal Analyzer (10Hz-50GHz)	Keysight	N9020B	MY63470246	2026/05/27	1 Year
MXA Signal Analyzer (10Hz-26.5GHz)	Keysight	N9020B	MY56080159	2026/03/06	1 Year
MXG Vector Signal Generator (100kHz-6GHz)	Agilent	N5182A	MY50144775	2026/01/25	1 Year
EXG Analog Signal Generator (9kHz-40GHz)	Keysight	N5173B	MY59101189	2026/05/27	1 Year
Vector Signal Generator (4kHz-7.125GHz)	Rohde&Schwarz	SMCV100B	1432.7000K02-106109-gD	2026/05/27	1 Year
Wireless Connectivity Test Set	Anritsu Corp.	MT8862A	6272445466	2026/05/27	1 Year
Wideband Radio Communication Tester	Rohde&Schwarz	CMW 500	1201.0002K50-158800-Qi	2026/02/11	1 Year
RF Control Unit	Tonscend	JS0806-2	806JS2X022505261006	2026/05/27	1 Year
Temperature, humidity and pressure recorder	Huahanwei	THP40W-E	c0222020002d	2026/03/02	1 Year
Programmable Temperature Humidity Chamber	Zhixiang	ZXGDJS-225L	ZX20171127A	2026/01/24	1 Year
RF Test Software	Tonscend	JS1120-3	3.6.21	N/A	N/A
Radiated Spurious Emission in 3m EMI Chamber					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
3m Anechoic Chamber	CRT	3m-SAC	N/A	2024/05/18	3 Year
Loop antenna (9kHz-30MHz)	SCHWARZBECK	FMZB1519-60D	00058	2024/11/05	3 Year
Hybrid antenna (30MHz-1GHz)	TESEQ	CBL6141B	27421	2024/01/10	3 Year
Horn antenna (1-18GHz)	ETS-Lindgren	3117	157735	2024/01/19	3 Year
Horn antenna (18-40GHz)	Tonscend	HA32-40	806HA006712251046	2026/05/11	3 Year
Low Noise Amplifier (30MHz-1GHz)	Tonscend	TAP10M1G40N	806JSAP039904251006	2026/01/25	1 Year
Pre-Amplifier_HF (1-18GHz)	COM-MW	DPA8-1000-18000-1012	05231257	2026/01/25	1 Year
Pre-Amplifier_HF (18-40GHz)	Tonscend	TAP18040050	806JSAP049504261033	2026/05/06	1Year
EMI Test Receiver	Rohde & Schwarz	ESC17	101138	2026/01/25	1 Year
Spectrum Analyzer(9kHz-40GHz)	Rohde & Schwarz	FSV40-N	101642	2026/01/25	1 Year

Temperature, humidity and pressure recorder	Huahanwei	TH10R	c00286000E E1	2026/1/29	1 Year
Test software	TONSCEND	JS36-RSE	5.0.0	N/A	N/A
Power Line Conducted Emissions Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Shielding Room 1	Tai He Mao Rui	N/A	N/A	2024/01/25	3 Year
EMI Test Receiver	Rohde & Schwarz	ESCI3	101705	2026/01/25	1 Year
Two-Line V-Network	Rohde & Schwarz	ENV216	101064	2026/01/25	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	102704	2026/01/25	1 Year
Temperature, humidity and pressure recorder	HuaHanWei	THP40W-E	c0222020002 E	2026/01/25	1 Year
Test software	TONSCEND	JS32-CE	5.0.0	N/A	N/A

4 20dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


4.3. Test Procedure

- (1) The EUT was rotated 360 degrees and scanning the peak frequency spectrum.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW: 1% to 5% of the OBW and VBW: at least three times RBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.4. Test Result

Freq. (MHz)	20dB bandwidth Result (kHz)	Conclusion
13.56	1.5165	PASS


4.5. Original test data




5 Radiated emission

5.1. Block diagram of test setup

Test Setup Diagram for 9 kHz~30MHz



Test Setup Diagram for 30MHz~1GHz



5.2. Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$	$67.6-20\log(F) (\text{kHz})$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$	$87.6-20\log(F) (\text{kHz})$
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{10\text{m}}(\text{dBuV/m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 40\log(300\text{m}/10\text{m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 59.08$$

$$\text{Limit}_{10\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\log(30\text{m}/10\text{m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 19.08$$

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 40\log(300\text{m}/3\text{m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 80$$

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\log(30\text{m}/3\text{m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40$$

5.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

(2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m

According ANSI C63.10:2020 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 1GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1.5m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions. Spectrum frequency from 9kHz to 1GHz (tenth harmonic of fundamental frequency) was investigated.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2020 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz, 110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.


Frequency band	RBW
9kHz-150kHz	300Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

5.4. Test result


PASS. (See below detailed test result)

Radiated Emission test (9kHz-30MHz)




NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Verdict
1	1.05	16.37	36.42	20.05	67.22	30.80	PK	PASS
2	1.55	16.16	36.22	20.06	63.80	27.58	PK	PASS
3	2.25	17.42	37.52	20.10	69.54	32.02	PK	PASS
4	3.90	16.47	36.77	20.30	69.54	32.77	PK	PASS
5	6.91	17.74	38.04	20.30	69.54	31.50	PK	PASS
6	19.55	16.48	36.57	20.09	69.54	32.97	PK	PASS

Radiated Emission test (30MHz-1GHz)



NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin[dB]	Pol	Verdict
1	38.37	-16.14	43.92	27.78	40.00	12.22	V	PASS
2	119.97	-23.13	53.68	30.55	43.50	12.95	V	PASS
3	240.01	-22.05	61.68	39.63	46.00	6.37	V	PASS
4	360.04	-18.80	49.36	30.56	46.00	15.44	V	PASS
5	840.07	-8.55	39.99	31.44	46.00	14.56	V	PASS
6	960.11	-6.20	42.75	36.55	54.00	17.45	V	PASS



NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Pol	Verdict
1	119.97	-23.13	52.55	29.42	43.50	14.08	H	PASS
2	240.01	-22.05	61.86	39.81	46.00	6.19	H	PASS
3	360.04	-18.80	55.65	36.85	46.00	9.15	H	PASS
4	720.16	-10.87	45.73	34.86	46.00	11.14	H	PASS
5	840.07	-8.55	48.36	39.81	46.00	6.19	H	PASS
6	960.11	-6.20	46.56	40.36	54.00	13.64	H	PASS

6 Field Strength Of Fundamental

6.1. Block diagram of test setup

Same with 5.1.

6.2. Limits

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

6.3. Test Procedure


Same with 5.3.

6.4. Test Result

PASS. (See below detailed test result)

Note: All axis was tested, the worst data was recorded in this report.

Radiated Emission Test Result



NO.	Frequency [MHz]	Factor [dB/m]	Reading [dBμV]	Value [dBμV/m]	Limit [dBμV/m]	Margin[dB]	Detector	Verdict
1	12.59	20.02	18.05	38.07	69.54	31.47	PK	PASS
2	13.30	20.07	15.75	35.82	80.51	44.69	PK	PASS
3	13.50	20.07	15.11	35.18	90.47	55.29	PK	PASS
4	13.56	20.08	21.21	41.29	123.90	82.61	PK	PASS
5	13.67	20.08	15.88	35.96	90.47	54.51	PK	PASS
6	13.84	20.09	16.77	36.86	80.51	43.65	PK	PASS
7	14.84	20.07	15.69	35.76	69.54	33.78	PK	PASS

7 Frequency Stability

7.1. Limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ ($\pm 1.356\text{kHz}$) of the operating frequency over a temperature variation of -20 degrees to $+ 50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

7.2. Test Procedure

ANSI C63.10-2020 Clause 6.8


7.3. Test Result

PASS. (See below detailed test result)

Voltage	Temperature	Frequency (MHz)	Measured Frequency(MHz)	Frequency Tolerance(kHz)	Limit ($\pm 1.356\text{kHz}$)	Conclusion
Normal	20°C	13.5600000	13.5604215	0.4215	± 1.356	PASS
High	20°C	13.5600000	13.5604214	0.4214	± 1.356	PASS
Low	20°C	13.5600000	13.5604230	0.4230	± 1.356	PASS
Normal	-20°C	13.5600000	13.5604237	0.4237	± 1.356	PASS
Normal	-10°C	13.5600000	13.5604248	0.4248	± 1.356	PASS
Normal	0°C	13.5600000	13.5604234	0.4234	± 1.356	PASS
Normal	10°C	13.5600000	13.5604223	0.4223	± 1.356	PASS
Normal	30°C	13.5600000	13.5604236	0.4236	± 1.356	PASS
Normal	40°C	13.5600000	13.5604245	0.4245	± 1.356	PASS
Normal	50°C	13.5600000	13.5604219	0.4219	± 1.356	PASS

8 Power Line Conducted Emission

8.1. Block diagram of test setup



8.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

8.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 3 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

8.4. Test Result

No Applicable.

9 Antenna Requirements

For intentional device, according to FCC 47 CFR Section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10 Test setup photograph

Please find the detailed in APPENDIXES-Test Setup.

11 Photos of the EUT

Please find the photos of EUT in APPENDIXES-Photos.

END OF REPORT