

FCC Test Report

**Test Report
On Behalf of
Suzhou Fanxi Technology Co., Ltd.
For**

**Intelligent Face Recognition Terminal
Model No.: FCV5002, FCV5002-xx(where “xx” represents a
number in the range of 01 to 36), FCV5002-E-01-GC,
FCV5002-E-02-GC**

FCC ID: 2BPI7-FCV5002

Prepared For: Suzhou Fanxi Technology Co., Ltd.
Room 101-3, Building 40, No.666, Jianlin Road, High-tech Zone, Suzhou,
Jiangsu, 215000 China

Prepared By: Shenzhen HUAKE Testing Technology Co., Ltd.
1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai
Street, Bao'an District, Shenzhen, Guangdong, China

Date of Test: Jan. 05, 2026 ~ Feb. 05, 2026

Date of Report: Feb. 05, 2026

Report Number: HK2601050011-2E

Test Result Certification

Applicant's Name.....: Suzhou Fanxi Technology Co., Ltd.

Address: Room 101-3, Building 40, No.666, Jianlin Road, High-tech Zone,
Suzhou, Jiangsu, 215000 China

Manufacturer's Name: Suzhou Fanxi Technology Co., Ltd.

Address: Room 101-3, Building 40, No.666, Jianlin Road, High-tech Zone,
Suzhou, Jiangsu, 215000 China

Product Description

Trade Mark: N/A

Product Name.....: Intelligent Face Recognition Terminal

Model and/or Type Reference : FCV5002, FCV5002-xx(where "xx" represents a number in the
range of 01 to 36), FCV5002-E-01-GC, FCV5002-E-02-GC

Standards: FCC Rules and Regulations Part 15 Subpart C Section 15.225
ANSI C63.10: 2020

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test.....:

Date (s) of Performance of Tests: Jan. 05, 2026 ~ Feb. 05, 2026

Date of Issue.....: Feb. 05, 2026

Test Result.....: Pass

Testing Engineer

Len Liao

Len Liao

Technical Manager

Sliver Wan

Sliver Wan

Authorized Signatory

Jason Zhou

Jason Zhou



Table of Contents

1. Summary	5
1.1 Test Procedures and Results.....	5
1.2 Information of the Test Laboratory	5
1.3 Measurement Uncertainty	5
2. EUT Description	6
3. General Information.....	7
3.1 Description of Test Setup.....	7
3.2 Description of Support Units	8
3.3 Equipments List for All Test Items	9
4. Test Results and Measurement Data	10
4.1 Antenna Requirement.....	10
4.2 AC Conducted Emission	11
4.3 Radiated Emission Measurement.....	13
4.4 Occupied Bandwidth.....	22
4.5 Frequency Stability	24
5. Test Setup Photos of the EUT	26
6. Photos of the EUT.....	28

**** Issued History ****

Revision	Description	Issued Date	Remark
Revision 1.0	Initial Test Report Release	Feb. 05, 2026	Jason Zhou



1. Summary

1.1 Test Procedures and Results

Requirement	CFR 47 Section	Result
AC Conduction Emission, 0.15MHz to 30MHz	§15.207	N/A
Radiation Emission	§15.225, §15.205, §15.209, §15.35	PASS
Occupied Bandwidth	§ 15.215	PASS
Antenna Requirement	§ 15.203	PASS
Frequency Stability	§ 15.225	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

1.2 Information of the Test Laboratory

Shenzhen HUAKE Testing Technology Co., Ltd.

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

1.3 Measurement Uncertainty

Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.71dB, k=2

Radiated emission expanded uncertainty(9kHz-30MHz) = 3.90dB, k=2

Radiated emission expanded uncertainty(30MHz-1000MHz) = 3.90dB, k=2

Radiated emission expanded uncertainty(Above 1GHz) = 4.28dB, k=2



2. EUT Description

Equipment:	Intelligent Face Recognition Terminal
Model Name:	FCV5002
Series Model(s):	FCV5002-xx(where "xx" represents a number in the range of 01 to 36), FCV5002-E-01-GC, FCV5002-E-02-GC
Model Difference:	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: FCV5002.
FCC ID:	2BPI7-FCV5002
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Operation frequency:	13.56MHz
Modulation Type:	ASK
Power Source:	DC9V-24V
Power Rating:	DC9V-24V
Note: 1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. Antenna gain Refer to the antenna specifications. 3. The cable loss data is obtained from the supplier. 4. The test results in the report only apply to the tested sample.	


3. General Information

3.1 Description of Test Setup

Operation of EUT during Radiation testing:



Operation of EUT during RF Conducted testing:



The sample was placed (0.8m below 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The report only reflects the worst emission test results. The worst case is Y position.

3.2 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Trade Mark	Model/Type No.	Specification	Remark
1	Intelligent Face Recognition Terminal	N/A	FCV5002	N/A	EUT
2	Laptop	Lenovo	TP00096A	Input: DC20V, 2.25~3.25A Output: DC5V, 0.5A	

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.




3.3 Equipments List for All Test Items

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 19, 2025	1 Year
2.	L.I.S.N.	R&S	ENV216	HKE-002	Feb. 19, 2025	1 Year
3.	L.I.S.N.	R&S	ENV216	HKE-059	Feb. 19, 2025	1 Year
4.	EMI Test Receiver	R&S	ESR	HKE-005	Feb. 19, 2025	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-117	Feb. 19, 2025	1 Year
6.	Spectrum analyzer	R&S	FSV3044	HKE-126	Feb. 19, 2025	1 Year
7.	Preamplifier	EMCI	EMC051845S	HKE-006	Feb. 19, 2025	1 Year
8.	Preamplifier	Schwarzbeck	BBV 9743	HKE-016	Feb. 19, 2025	1 Year
9.	Preamplifier	A.H. Systems	SAS-574	HKE-182	Feb. 19, 2025	1 Year
10.	6dB Attenuator	Pasternack	6db	HKE-184	Feb. 19, 2025	1 Year
11.	EMI Test Receiver	Rohde & Schwarz	ESR-7	HKE-010	Feb. 19, 2025	1 Year
12.	Broadband Antenna	Schwarzbeck	VULB9168	HKE-167	Feb. 21, 2024	2 Year
13.	Loop Antenna	COM-POWER	AL-130R	HKE-014	Feb. 21, 2024	2 Year
14.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Feb. 21, 2024	2 Year
15.	EMI Test Software	Tonscend	JS32-CE 2.5.0.6	HKE-081	/	/
16.	EMI Test Software	Tonscend	JS32-RE 5.0.0	HKE-082	/	/
17.	10dB Attenuator	Schwarzbeck	VTSD9561F	HKE-153	Feb. 19, 2025	1 Year
18.	RF Automatic control unit	Tonscend	JS0806-2	HKE-060	Feb. 19, 2025	1 Year

4. Test Results and Measurement Data

4.1 Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	PCB antenna
The antenna used in this product is a PCB Antenna, which have non-standard antenna jack. It conforms to the standard requirements. The directional gains of antenna used for transmitting is 0dBi.	
	

4.2 AC Conducted Emission

4.2.1 Conducted Power Line Emission Limit


For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following.

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

4.2.2 Test Setup



Remark
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

4.2.3 Test Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.



HUAKE TESTING

4.2.4 Test Result

Not applicable.



Note: EUT Power Supply by DC Powered, so this test item not applicable.



4.3 Radiated Emission Measurement

4.3.1 Test Specification

Test Requirement:	FCC Part15 C Section 15.225(a) and 15.209				
Test Method:	ANSI C63.10: 2020				
Frequency Range:	9 kHz to 1 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber in below 1GHz. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					

Test Setup:	For radiated emissions  30MHz to 1GHz 
	Test Mode: Transmitting Mode
	Test Results: PASS

4.3.2 Limit

- The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

4.3.3 Frequencies in restricted band are complied to limit on Paragraph 15.209

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)	Field strength (microvolts/meter)
0.009-0.490	300	20log 2400/F (kHz)	2400/F (kHz)
0.490-1.705	30	20log 24000/F (kHz)	24000/F (kHz)
1.705-30	30	20log 30	30
30-88	3	40.0	100**
88-216	3	43.5	150**
216-960	3	46.0	200**
Above 960	3	54.0	500

NOTE:


**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., S 15.231 and 15.241.

4.3.4 Test Data

PASS

Field Strength of Fundamental

Antenna polarity: Horizontal




Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11.1966	-11.65	12.21	0.56	69.54	68.98	100	341	Horizontal
2	11.9050	-11.69	11.31	-0.38	69.54	69.92	100	225	Horizontal
3	12.8214	-11.76	11.21	-0.55	69.54	70.09	100	264	Horizontal
4	13.5618	-11.83	41.86	30.03	124.00	93.97	100	207	Horizontal
5	14.8424	-11.92	10.37	-1.55	69.54	71.09	100	106	Horizontal
6	16.1111	-11.99	10.60	-1.39	69.54	70.93	100	1	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical




Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11.6488	-11.68	11.89	0.21	69.54	69.33	100	354	Vertical
2	12.1451	-11.70	11.31	-0.39	69.54	69.93	100	137	Vertical
3	13.0455	-11.79	11.46	-0.33	69.54	69.87	100	41	Vertical
4	13.5618	-11.83	41.87	30.04	124.00	93.96	100	201	Vertical
5	14.6503	-11.92	10.24	-1.68	69.54	71.22	100	270	Vertical
6	16.3712	-12.01	10.85	-1.16	69.54	70.70	100	303	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

For 9KHz to 30MHz


Antenna polarity: Horizontal



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	0.0977	-10.35	34.83	24.48	107.80	83.32	100	358	Horizontal
2	0.2844	-11.25	37.52	26.27	98.52	72.25	100	1	Horizontal
3	0.6876	-10.95	38.02	27.07	70.87	43.80	100	122	Horizontal
4	1.3745	-10.51	25.57	15.06	64.87	49.81	100	24	Horizontal
5	3.7935	-11.25	17.07	5.82	69.50	63.68	100	1	Horizontal
6	13.5594	-11.83	42.54	30.71	69.50	38.79	100	235	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical




Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	0.0454	-10.38	42.53	32.15	114.45	82.30	100	359	Vertical
2	0.2396	-10.89	39.64	28.75	100.01	71.26	100	315	Vertical
3	0.7025	-10.95	38.81	27.86	70.68	42.82	100	250	Vertical
4	1.4491	-10.51	24.95	14.44	64.41	49.97	100	358	Vertical
5	3.3903	-11.26	17.68	6.42	69.50	63.08	100	315	Vertical
6	13.5594	-11.83	42.30	30.47	69.50	39.03	100	224	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

About 30MHz-1GHz

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Antenna polarity: Horizontal




Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	189.2392	-15.52	53.02	37.50	43.50	6.00	100	125	Horizontal
2	243.6136	-13.32	53.60	40.28	46.00	5.72	100	190	Horizontal
3	284.3944	-12.50	52.73	40.23	46.00	5.77	100	183	Horizontal
4	338.7688	-10.40	51.98	41.58	46.00	4.42	100	147	Horizontal
5	692.2022	-4.11	43.27	39.16	46.00	6.84	100	140	Horizontal
6	891.2513	-1.49	38.70	37.21	46.00	8.79	100	36	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	107.6777	-14.18	49.38	35.20	43.50	8.30	100	194	Vertical
2	216.4264	-14.69	53.12	38.43	46.00	7.57	100	122	Vertical
3	243.6136	-13.32	49.93	36.61	46.00	9.39	100	100	Vertical
4	270.8008	-12.52	51.49	38.97	46.00	7.03	100	96	Vertical
5	311.5816	-11.70	51.10	39.40	46.00	6.60	100	100	Vertical
6	338.7688	-10.40	49.87	39.47	46.00	6.53	100	82	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

4.4 Occupied Bandwidth

4.4.1 Test Specification

Test Requirement:	FCC Part15 C Section 15.215(c)
Test Method:	ANSI C63.10: 2020
Limit:	N/A
	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold. 4. Measure and record the results in the test report.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting Mode
Test Results:	PASS

4.4.2 Test Data

Test Channel (MHz)	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Conclusion
13.56	2.700	N/A	PASS

Test plots as follows:



4.5 Frequency Stability

4.5.1 Test Specification

Test Requirement:	FCC Part15 C Section 15.225
Test Method:	ANSI C63.10: 2020
Limit:	+/-0.01%
	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a spectrum analyzer. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to - 20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
Test Setup:	 The diagram illustrates the test setup. On the left is a green rectangular box labeled 'Spectrum Analyzer'. A horizontal line connects it to a yellow rectangular box on the right labeled 'EUT'.
Test Mode:	Transmitting Mode
Test Results:	PASS



4.5.2 Test Data



PASS

Note: this EUT was tested for all models and the worst case model data was reported.


Voltage (Vdc)	Temperature (°C)	Frequency (MHz)	Deviation (%)	Limit (%)
12.0	-20	13.560082	0.00060%	+/-0.01%
12.0	-10	13.560397	0.00293%	
12.0	0	13.560399	0.00294%	
12.0	10	13.560002	0.00001%	
12.0	20	13.560028	0.00021%	
12.0	30	13.55985	-0.00111%	
12.0	40	13.559971	-0.00021%	
12.0	50	13.559811	-0.00139%	
10.2	-20	13.560174	0.00128%	
10.2	-10	13.560056	0.00041%	
10.2	0	13.559903	-0.00072%	
10.2	10	13.56077	0.00568%	
10.2	20	13.559105	-0.00660%	
10.2	30	13.559811	-0.00139%	
10.2	40	13.55923	-0.00568%	
10.2	50	13.560261	0.00192%	
13.8	-20	13.560004	0.00003%	
13.8	-10	13.559869	-0.00097%	
13.8	0	13.560032	0.00024%	
13.8	10	13.559888	-0.00083%	
13.8	20	13.559915	-0.00063%	
13.8	30	13.559842	-0.00117%	
13.8	40	13.559709	-0.00215%	
13.8	50	13.559911	-0.00066%	

5. Test Setup Photos of the EUT

Radiated Emission



RF Conducted Emission





HUAKE TESTING

Page 28 of 28

Report No.: HK2601050011-2E

6. Photos of the EUT

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos.

-----End of test report-----



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China