

TEST REPORT

Report No.: 8427EU120803W1

Applicant: Shenzhen Ruheng Technology Co., Ltd.

Address: Room 1201, Yousuowei Building, 2000 Jiaxian Road,
Gangtou Community, Bantian Street, Longgang District,
Shenzhen, Guangdong, China

Product Name: Dash Cam

Model No.: D016

Trademark: TERUNSOUL

FCC ID: 2BPRI-D016-6

Test Standard(s): 47 CFR Part 15.247

Test Result: Pass

Date of Receipt: Jan. 08, 2026

Test Date: Jan. 08, 2026 - Jan. 28, 2026

Date of Issue: Feb. 04, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:



Landon Qiu/ Engineer

Reviewed and Approved by:



Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Feb. 04, 2026	Original	Valid



Table of Contents

1	COVER PAGE	1
2	GENERAL INFORMATION	5
2.1	APPLICANT INFORMATION	5
2.2	MANUFACTURER INFORMATION	5
2.3	FACTORY INFORMATION	5
2.4	GENERAL DESCRIPTION OF E.U.T.	5
2.5	TECHNICAL INFORMATION OF E.U.T.	6
3	TEST SUMMARY	7
3.1	TEST STANDARD	7
3.2	TEST VERDICT	7
3.3	TEST LABORATORY	8
4	TEST CONFIGURATION	9
4.1	TEST ENVIRONMENT	9
4.2	TEST EQUIPMENT	9
4.3	DESCRIPTION OF SUPPORT UNIT	11
4.4	TEST MODE	11
4.5	DESCRIPTION OF CALCULATION	11
4.5.1	Field Strength Calculation	11
4.5.2	Disturbance Calculation	11
4.6	MEASUREMENT UNCERTAINTY	12
4.7	DEVIATION FROM STANDARDS	12
4.8	ABNORMALITIES FROM STANDARD CONDITION	12
5	EVALUATION RESULTS (EVALUATION)	13
5.1	ANTENNA REQUIREMENT	13
5.1.1	Test Specification	13
5.1.2	Test Data	13
6	RADIO SPECTRUM MATTER TEST RESULTS (RF)	14
6.1	6dB BANDWIDTH	14
6.1.1	Test Specification	14
6.1.2	E.U.T. Operation	14
6.1.3	Test Setup Diagram	15
6.1.4	Test Data	15
6.2	MAXIMUM CONDUCTED OUTPUT POWER	16
6.2.1	Test Specification	16
6.2.2	E.U.T. Operation	16
6.2.3	Test Setup Diagram	16
6.2.4	Test Data	16
6.3	POWER SPECTRAL DENSITY	17
6.3.1	Test Specification	17
6.3.2	E.U.T. Operation	17
6.3.3	Test Setup Diagram	17
6.3.4	Test Data	17
6.4	EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	18
6.4.1	Test Specification	18
6.4.2	E.U.T. Operation	18
6.4.3	Test Setup Diagram	18

6.4.4	Test Data	18
6.5	BAND EDGE EMISSIONS (RADIATED)	19
6.5.1	Test Specification	19
6.5.2	E.U.T. Operation.....	19
6.5.3	Test Setup Diagram.....	19
6.5.4	Test Data	20
6.6	EMISSIONS IN FREQUENCY BANDS (BELOW 1GHz)	27
6.6.1	Test Specification	27
6.6.2	E.U.T. Operation.....	27
6.6.3	Test Setup Diagram.....	27
6.6.4	Test Data	28
6.7	EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHz).....	31
6.7.1	Test Specification	31
6.7.2	E.U.T. Operation.....	31
6.7.3	Test Setup Diagram.....	31
6.7.4	Test Data	32
ANNEX A	TEST SETUP PHOTOS	36
ANNEX B	EXTERNAL PHOTOS	36
ANNEX C	INTERNAL PHOTOS	36
ANNEX D	TEST DATA	37

2 General Information

2.1 Applicant Information

Applicant	Shenzhen Ruheng Technology Co., Ltd.
Address	Room 1201, Yousuowei Building, 2000 Jiaxian Road, Gangtou Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Ruheng Technology Co., Ltd.
Address	Room 1201, Yousuowei Building, 2000 Jiaxian Road, Gangtou Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China

2.3 Factory Information

Factory	Shenzhen Mili Automotive Electronics Co., Ltd.
Address	Building 2, Unit 1101, No. 2 Chongqing Road, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen.

2.4 General Description of E.U.T.

Product Name	Dash Cam
Model No. Under Test	D016
List Model No.	N/A
Description of Model differentiation	N/A
Rating(s)	Input: 5VDC, 3A (Car Charger Input: 12-30VDC; Output: 5VDC, 3A)
Car Charger	Model No.: CSXE1219 Input: 12-30VDC Output: 5VDC, 3A Manufacturer: Shenzhen Desimy Technology Co., LTD
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Test Sample No.	8427EU120803W-1/2(Normal), 8427EU120803W-2/2(Engineering)
Hardware Version	V1.X
Software Version	D016_V2.20260201.1_TERUNSOUL6
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	WiFi 2.4G: 802.11b, 802.11g, 802.11n(HT20/40) and 802.11ax(HEW20/40) WiFi 5G: 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40), 802.11ax(HEW20/40) U-NII-1/3
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Technology	WiFi 2.4G
Operation Mode	b, g, n(HT20), n(HT40), ax(HEW20), ax(HEW40)
Operating Frequency	802.11b/g/n(HT20)/ax(HEW20): 2412MHz to 2462MHz 802.11n(HT40)/ax(HEW40): 2422MHz to 2452MHz
Modulation Type	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20 and HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ax(HEW20 and HEW40): OFDMA(BPSK, QPSK, 16QAM, 64QAM, 256QAM,1024QAM)
Number of Channels	802.11b/g/n(HT20)/ax(HEW20): 11 Channels 802.11n(HT40)/ax(HEW40): 7 Channels
Antenna Type	FPC Antenna
Antenna Gain(Peak)	-2.79 dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

802.11ax RU configuration table						
Mode	Full RU (SU)	RU_26	RU_52	RU_106	RU_242	RU_484
802.11ax(HE20)	√	--	--	--	--	--
802.11ax(HE40)	√	--	--	--	--	--

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

Test Items	Standard	Method	Requirement	Results
Antenna requirement	47 CFR Part 15.247	---	47 CFR 15.203	Pass
6dB Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020+Cor 1-2023, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2020+Cor 1-2023 section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2020+Cor 1-2023, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2020+Cor 1-2023 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2020+Cor 1-2023 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020+Cor 1-2023 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020+Cor 1-2023 section 6.6.4 KDB 558074 D01	47 CFR 15.247(d), 15.209, 15.205	Pass

		15.247 Meas Guidance v05r02		
Note: (1) "N/A" denotes test is not applicable in this Test Report.				

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15℃ to +35℃
Working Voltage of the EUT	NV (Normal Voltage)	12VDC

4.2 Test Equipment

Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands 6dB Bandwidth					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-01-07	2027-01-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-01-07	2027-01-06
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2026-01-07	2027-01-06
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-402	2025-02-14	2026-02-13
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2025-02-14	2026-02-13
Power Meter	Anritsu	ML2495A	EE-416	2025-02-14	2026-02-13
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2025-07-29	2026-07-28
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	/	/

Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-01-07	2027-01-06
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2026-01-11	2029-01-10
Pre-amplifier	Agilent	8449B	EE-010	2026-01-07	2027-01-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-01-07	2027-01-06

DRG Horn Antenna	SCHWARZBECK	BBHA 9170	EE-410	2025-02-14	2026-02-13
Pre-amplifier	SKET	LNPA-1840-50	EE-411	2025-02-14	2026-02-13
Test Software	Farad	EZ-EMC	EE-015	/	/

Emissions in frequency bands (below 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-01-07	2027-01-06
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026-01-13	2029-01-12
Pre-amplifier	Agilent	8447D	EE-009	2026-01-07	2027-01-06
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-01-07	2027-01-06
Test Software	Farad	EZ-EMC	EE-015	/	/

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Car Charger	refer to clause 2.4	refer to clause 2.4	--
2	12V Battery	CHILWEE	6-DZF-12.2	EMC-PJ-031

4.4 Test Mode

No.	Test Modes	Description
TM1	802.11b Mode	Keep the EUT in 802.11b transmitting mode at lowest, middle and highest channel.
TM2	802.11g Mode	Keep the EUT in 802.11g transmitting mode at lowest, middle and highest channel.
TM3	802.11n(HT20) Mode	Keep the EUT in 802.11n(HT20) transmitting mode at lowest, middle and highest channel.
TM4	802.11n(HT40) Mode	Keep the EUT in 802.11n(HT40) transmitting mode at lowest, middle and highest channel.
TM5	802.11ax(HE20) Mode	Keep the EUT in 802.11ax(HE20) transmitting mode at lowest, middle and highest channel.
TM6	802.11ax(HE40) Mode	Keep the EUT in 802.11ax(HE40) transmitting mode at lowest, middle and highest channel.

4.5 Description of Calculation

4.5.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS \text{ (dBuV/m)} = RA \text{ (dBuV)} + AF \text{ (dB/m)} + CL \text{ (dB)} - AG \text{ (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

4.5.2 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test Item	Measurement Uncertainty
Occupied Channel Bandwidth	70 kHz
RF output power, conducted	1.04 dB
Power Spectral Density, conducted	0.91 dB
Unwanted Emissions, conducted	2.72 dB
Radiated Emission (1GHz- 18GHz)	Ur = 3.50 dB (Horizontal) Ur = 3.50 dB (Vertical)
Radiated Emission (9kHz- 30MHz)	Ur = 2.50 dB
Radiated Emission (30MHz- 1GHz)	Ur = 2.70 dB (Horizontal) Ur = 2.70 dB (Vertical)
Radiated Emission (18GHz- 40GHz)	Ur = 5.15 dB (Horizontal) Ur = 5.24 dB (Vertical)

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Condition

None

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

5.1.1 Test Specification

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

5.1.2 Test Data

PASS.

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

6 Radio Spectrum Matter Test Results (RF)

6.1 6dB Bandwidth


6.1.1 Test Specification

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

6.1.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.1.3 Test Setup Diagram



6.1.4 Test Data

PASS.

Please refer to Annex D for details.

6.2 Maximum Conducted Output Power


6.2.1 Test Specification

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.9.1 Maximum peak conducted output power

6.2.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.2.3 Test Setup Diagram



6.2.4 Test Data

PASS.

Please refer to Annex D for details.

6.3 Power Spectral Density


6.3.1 Test Specification

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.10, Maximum power spectral density level in the fundamental emission

6.3.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.3.3 Test Setup Diagram



6.3.4 Test Data

PASS.

Please refer to Annex D for details.

6.4 Emissions in non-restricted frequency bands


6.4.1 Test Specification

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.4.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.4.3 Test Setup Diagram



6.4.4 Test Data

PASS.

Please refer to Annex D for details.

6.5 Band edge emissions (Radiated)


6.5.1 Test Specification

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.10.5.2		

6.5.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.5.3 Test Setup Diagram



6.5.4 Test Data

PASS.

Please refer to the following pages.



Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11b					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	45.11	-2.81	42.30	74.00	-31.70	PK	PASS
H	2390.00	46.73	-2.69	44.04	74.00	-29.96	PK	PASS
H	**2400.00	61.93	-2.68	59.25	74.00	-14.75	PK	PASS
V	2310.00	43.27	-2.81	40.46	74.00	-33.54	PK	PASS
V	2390.00	47.19	-2.69	44.50	74.00	-29.50	PK	PASS
V	**2400.00	60.77	-2.68	58.09	74.00	-15.91	PK	PASS
H	2310.00	33.45	-2.81	30.64	54.00	-23.36	AV	PASS
H	2390.00	35.50	-2.69	32.81	54.00	-21.19	AV	PASS
H	**2400.00	47.76	-2.68	45.08	54.00	-8.92	AV	PASS
V	2310.00	33.07	-2.81	30.26	54.00	-23.74	AV	PASS
V	2390.00	34.97	-2.69	32.28	54.00	-21.72	AV	PASS
V	**2400.00	45.63	-2.68	42.95	54.00	-11.05	AV	PASS

Test Mode: 802.11b					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	42.89	-2.81	40.08	74.00	-33.92	PK	PASS
H	2390.00	47.20	-2.69	44.51	74.00	-29.49	PK	PASS
V	**2400.00	62.12	-2.68	59.44	74.00	-14.56	PK	PASS
V	2310.00	42.72	-2.81	39.91	74.00	-34.09	PK	PASS
H	2390.00	45.03	-2.69	42.34	74.00	-31.66	AV	PASS
H	**2400.00	62.69	-2.68	60.01	74.00	-13.99	AV	PASS
V	2310.00	31.22	-2.81	28.41	54.00	-25.59	AV	PASS
V	2390.00	36.16	-2.69	33.47	54.00	-20.53	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11g					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	42.89	-2.81	40.08	74.00	-33.92	PK	PASS
H	2390.00	47.20	-2.69	44.51	74.00	-29.49	PK	PASS
H	**2400.00	62.12	-2.68	59.44	74.00	-14.56	PK	PASS
V	2310.00	42.72	-2.81	39.91	74.00	-34.09	PK	PASS
V	2390.00	45.03	-2.69	42.34	74.00	-31.66	PK	PASS
V	**2400.00	62.69	-2.68	60.01	74.00	-13.99	PK	PASS
H	2310.00	31.22	-2.81	28.41	54.00	-25.59	AV	PASS
H	2390.00	36.16	-2.69	33.47	54.00	-20.53	AV	PASS
H	**2400.00	46.77	-2.68	44.09	54.00	-9.91	AV	PASS
V	2310.00	34.77	-2.81	31.96	54.00	-22.04	AV	PASS
V	2390.00	34.36	-2.69	31.67	54.00	-22.33	AV	PASS
V	**2400.00	46.83	-2.68	44.15	54.00	-9.85	AV	PASS

Test Mode: 802.11g					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	48.36	-2.56	45.80	74.00	-28.20	PK	PASS
H	2500.00	48.75	-2.54	46.21	74.00	-27.79	PK	PASS
V	**2483.50	48.80	-2.56	46.24	74.00	-27.76	PK	PASS
V	2500.00	49.79	-2.54	47.25	74.00	-26.75	PK	PASS
H	**2483.50	35.48	-2.56	32.92	54.00	-21.08	AV	PASS
H	2500.00	39.91	-2.54	37.37	54.00	-16.63	AV	PASS
V	**2483.50	38.86	-2.56	36.30	54.00	-17.70	AV	PASS
V	2500.00	38.11	-2.54	35.57	54.00	-18.43	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11n(HT20)					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	45.86	-2.81	43.05	74.00	-30.95	PK	PASS
H	2390.00	45.30	-2.69	42.61	74.00	-31.39	PK	PASS
H	**2400.00	61.99	-2.68	59.31	74.00	-14.69	PK	PASS
V	2310.00	42.20	-2.81	39.39	74.00	-34.61	PK	PASS
V	2390.00	48.82	-2.69	46.13	74.00	-27.87	PK	PASS
V	**2400.00	62.07	-2.68	59.39	74.00	-14.61	PK	PASS
H	2310.00	31.00	-2.81	28.19	54.00	-25.81	AV	PASS
H	2390.00	35.06	-2.69	32.37	54.00	-21.63	AV	PASS
H	**2400.00	48.34	-2.68	45.66	54.00	-8.34	AV	PASS
V	2310.00	31.33	-2.81	28.52	54.00	-25.48	AV	PASS
V	2390.00	34.46	-2.69	31.77	54.00	-22.23	AV	PASS
V	**2400.00	48.03	-2.68	45.35	54.00	-8.65	AV	PASS

Test Mode: 802.11n(HT20)					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	47.22	-2.56	44.66	74.00	-29.34	PK	PASS
H	2500.00	51.62	-2.54	49.08	74.00	-24.92	PK	PASS
V	**2483.50	48.37	-2.56	45.81	74.00	-28.19	PK	PASS
V	2500.00	50.54	-2.54	48.00	74.00	-26.00	PK	PASS
H	**2483.50	39.04	-2.56	36.48	54.00	-17.52	AV	PASS
H	2500.00	38.73	-2.54	36.19	54.00	-17.81	AV	PASS
V	**2483.50	36.62	-2.56	34.06	54.00	-19.94	AV	PASS
V	2500.00	37.92	-2.54	35.38	54.00	-18.62	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11n(HT40)					CH Low: 2422 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	45.29	-2.81	42.48	74.00	-31.52	PK	PASS
H	2390.00	47.71	-2.69	45.02	74.00	-28.98	PK	PASS
H	**2400.00	63.08	-2.68	60.40	74.00	-13.60	PK	PASS
V	2310.00	44.12	-2.81	41.31	74.00	-32.69	PK	PASS
V	2390.00	47.20	-2.69	44.51	74.00	-29.49	PK	PASS
V	**2400.00	61.32	-2.68	58.64	74.00	-15.36	PK	PASS
H	2310.00	31.86	-2.81	29.05	54.00	-24.95	AV	PASS
H	2390.00	36.20	-2.69	33.51	54.00	-20.49	AV	PASS
H	**2400.00	47.47	-2.68	44.79	54.00	-9.21	AV	PASS
V	2310.00	31.14	-2.81	28.33	54.00	-25.67	AV	PASS
V	2390.00	34.91	-2.69	32.22	54.00	-21.78	AV	PASS
V	**2400.00	48.08	-2.68	45.40	54.00	-8.60	AV	PASS

Test Mode: 802.11n(HT40)					CH High: 2452 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	47.14	-2.56	44.58	74.00	-29.42	PK	PASS
H	2500.00	49.18	-2.54	46.64	74.00	-27.36	PK	PASS
V	**2483.50	47.54	-2.56	44.98	74.00	-29.02	PK	PASS
V	2500.00	51.82	-2.54	49.28	74.00	-24.72	PK	PASS
H	**2483.50	37.96	-2.56	35.40	54.00	-18.60	AV	PASS
H	2500.00	38.02	-2.54	35.48	54.00	-18.52	AV	PASS
V	**2483.50	37.65	-2.56	35.09	54.00	-18.91	AV	PASS
V	2500.00	40.13	-2.54	37.59	54.00	-16.41	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11ax(HEW20)					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	45.82	-2.81	43.01	74.00	-30.99	PK	PASS
H	2390.00	47.25	-2.69	44.56	74.00	-29.44	PK	PASS
H	**2400.00	60.87	-2.68	58.19	74.00	-15.81	PK	PASS
V	2310.00	45.28	-2.81	42.47	74.00	-31.53	PK	PASS
V	2390.00	45.74	-2.69	43.05	74.00	-30.95	PK	PASS
V	**2400.00	61.55	-2.68	58.87	74.00	-15.13	PK	PASS
H	2310.00	31.87	-2.81	29.06	54.00	-24.94	AV	PASS
H	2390.00	37.58	-2.69	34.89	54.00	-19.11	AV	PASS
H	**2400.00	45.87	-2.68	43.19	54.00	-10.81	AV	PASS
V	2310.00	33.75	-2.81	30.94	54.00	-23.06	AV	PASS
V	2390.00	36.14	-2.69	33.45	54.00	-20.55	AV	PASS
V	**2400.00	46.43	-2.68	43.75	54.00	-10.25	AV	PASS

Test Mode: 802.11ax(HEW20)					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	48.34	-2.56	45.78	74.00	-28.22	PK	PASS
H	2500.00	51.68	-2.54	49.14	74.00	-24.86	PK	PASS
V	**2483.50	46.90	-2.56	44.34	74.00	-29.66	PK	PASS
V	2500.00	50.25	-2.54	47.71	74.00	-26.29	PK	PASS
H	**2483.50	38.65	-2.56	36.09	54.00	-17.91	AV	PASS
H	2500.00	40.39	-2.54	37.85	54.00	-16.15	AV	PASS
V	**2483.50	38.35	-2.56	35.79	54.00	-18.21	AV	PASS
V	2500.00	41.27	-2.54	38.73	54.00	-15.27	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11ax(HEW40)					CH Low: 2422 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	42.69	-2.81	39.88	74.00	-34.12	PK	PASS
H	2390.00	48.36	-2.69	45.67	74.00	-28.33	PK	PASS
H	**2400.00	63.15	-2.68	60.47	74.00	-13.53	PK	PASS
V	2310.00	44.72	-2.81	41.91	74.00	-32.09	PK	PASS
V	2390.00	47.10	-2.69	44.41	74.00	-29.59	PK	PASS
V	**2400.00	62.85	-2.68	60.17	74.00	-13.83	PK	PASS
H	2310.00	32.46	-2.81	29.65	54.00	-24.35	AV	PASS
H	2390.00	35.19	-2.69	32.50	54.00	-21.50	AV	PASS
H	**2400.00	45.53	-2.68	42.85	54.00	-11.15	AV	PASS
V	2310.00	34.16	-2.81	31.35	54.00	-22.65	AV	PASS
V	2390.00	35.29	-2.69	32.60	54.00	-21.40	AV	PASS
V	**2400.00	47.38	-2.68	44.70	54.00	-9.30	AV	PASS

Test Mode: 802.11ax(HEW40)					CH High: 2452 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	47.12	-2.56	44.56	74.00	-29.44	PK	PASS
H	2500.00	48.68	-2.54	46.14	74.00	-27.86	PK	PASS
V	**2483.50	48.90	-2.56	46.34	74.00	-27.66	PK	PASS
V	2500.00	50.30	-2.54	47.76	74.00	-26.24	PK	PASS
H	**2483.50	36.26	-2.56	33.70	54.00	-20.30	AV	PASS
H	2500.00	39.33	-2.54	36.79	54.00	-17.21	AV	PASS
V	**2483.50	38.84	-2.56	36.28	54.00	-17.72	AV	PASS
V	2500.00	39.35	-2.54	36.81	54.00	-17.19	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

6.6 Emissions in frequency bands (below 1GHz)


6.6.1 Test Specification

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.6.4		

6.6.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.6.3 Test Setup Diagram



6.6.4 Test Data

PASS.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, for 30MHz to 1000MHz, pre-scan all modulations, and found the 802.1b modulation Low channel which is the worst case, only the worst case is recorded in the report.



Emissions in frequency bands (below 1GHz) Test Data


TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	50.0566	49.88	-17.34	32.54	40.00	-7.46	QP	P	
2	175.0367	51.34	-20.03	31.31	43.50	-12.19	QP	P	
3	250.3011	49.43	-16.74	32.69	46.00	-13.31	QP	P	
4	375.9385	49.48	-13.47	36.01	46.00	-9.99	QP	P	
5 !	750.1082	48.05	-6.45	41.60	46.00	-4.40	QP	P	
6 *	900.1474	48.49	-4.69	43.80	46.00	-2.20	QP	P	

Emissions in frequency bands (below 1GHz) Test Data

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	66.2662	45.35	-19.78	25.57	40.00	-14.43	QP	P	
2	110.5687	48.61	-19.26	29.35	43.50	-14.15	QP	P	
3	175.0368	53.46	-20.03	33.43	43.50	-10.07	QP	P	
4	225.3080	53.69	-17.61	36.08	46.00	-9.92	QP	P	
5	250.3012	53.73	-16.92	36.81	46.00	-9.19	QP	P	
6 *	900.1474	47.46	-4.94	42.52	46.00	-3.48	QP	P	

6.7 Emissions in frequency bands (above 1GHz)


6.7.1 Test Specification

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.6.4		

6.7.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.7.3 Test Setup Diagram



6.7.4 Test Data**PASS.**

During the test, for 1GHz- 25GHz, pre-scan all modulations, and found the 802.11n(HT20) modulation which is the worst case, only the worst case is recorded in the report.



Radiated Spurious Emission (1GHz-25GHz)

Test Mode: 802.11n(HT20)					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4824.02	42.95	4.74	47.69	74.00	-26.31	PK	PASS
V	7236.48	33.11	9.84	42.95	74.00	-31.06	PK	PASS
V	9648.64	28.41	13.18	41.59	74.00	-32.41	PK	PASS
V	12060.16	*	*	*	74.00	*	PK	PASS
V	14472.54	*	*	*	74.00	*	PK	PASS
V	16884.26	*	*	*	74.00	*	PK	PASS
H	4824.26	40.19	4.74	44.93	74.00	-29.07	PK	PASS
H	7236.72	34.14	9.84	43.98	74.00	-30.02	PK	PASS
H	9648.29	30.06	13.18	43.24	74.00	-30.77	PK	PASS
H	12060.14	*	*	*	74.00	*	PK	PASS
H	14472.01	*	*	*	74.00	*	PK	PASS
H	16884.86	*	*	*	74.00	*	PK	PASS
V	4824.83	32.41	4.74	37.15	54.00	-16.86	AV	PASS
V	7236.82	24.78	9.84	34.62	54.00	-19.39	AV	PASS
V	9648.47	18.17	13.18	31.35	54.00	-22.66	AV	PASS
V	12060.20	*	*	*	54.00	*	AV	PASS
V	14472.47	*	*	*	54.00	*	AV	PASS
V	16884.83	*	*	*	54.00	*	AV	PASS
H	4824.06	32.40	4.74	37.14	54.00	-16.86	AV	PASS
H	7236.72	22.29	9.84	32.13	54.00	-21.87	AV	PASS
H	9648.29	19.01	13.18	32.19	54.00	-21.81	AV	PASS
H	12060.14	*	*	*	54.00	*	AV	PASS
H	14472.01	*	*	*	54.00	*	AV	PASS
H	16884.86	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: 802.11n(HT20)					CH Middle: 2437 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4874.97	40.61	4.90	45.51	74.00	-28.50	PK	PASS
V	7311.90	35.13	9.83	44.96	74.00	-29.05	PK	PASS
V	9748.31	30.79	13.21	44.00	74.00	-30.00	PK	PASS
V	12185.13	*	*	*	74.00	*	PK	PASS
V	14622.58	*	*	*	74.00	*	PK	PASS
V	17059.00	*	*	*	74.00	*	PK	PASS
H	4874.76	42.73	4.90	47.63	74.00	-26.37	PK	PASS
H	7311.13	33.18	9.83	43.01	74.00	-30.99	PK	PASS
H	9748.02	29.40	13.21	42.61	74.00	-31.40	PK	PASS
H	12185.51	*	*	*	74.00	*	PK	PASS
H	14622.70	*	*	*	74.00	*	PK	PASS
H	17059.98	*	*	*	74.00	*	PK	PASS
V	4874.75	30.11	4.90	35.01	54.00	-19.00	AV	PASS
V	7311.66	24.02	9.83	33.85	54.00	-20.16	AV	PASS
V	9748.32	17.89	13.21	31.10	54.00	-22.90	AV	PASS
V	12185.57	*	*	*	54.00	*	AV	PASS
V	14622.50	*	*	*	54.00	*	AV	PASS
V	17059.54	*	*	*	54.00	*	AV	PASS
H	4874.76	32.80	4.90	37.70	54.00	-16.30	AV	PASS
H	7311.13	24.79	9.83	34.62	54.00	-19.39	AV	PASS
H	9748.02	17.12	13.21	30.33	54.00	-23.68	AV	PASS
H	12185.51	*	*	*	54.00	*	AV	PASS
H	14622.70	*	*	*	54.00	*	AV	PASS
H	17059.98	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: 802.11n(HT20)					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4924.35	41.74	5.05	46.79	74.00	-27.22	PK	PASS
V	7386.01	33.08	9.83	42.91	74.00	-31.10	PK	PASS
V	9848.10	29.90	13.24	43.14	74.00	-30.87	PK	PASS
V	12310.17	*	*	*	74.00	*	PK	PASS
V	14772.46	*	*	*	74.00	*	PK	PASS
V	17234.12	*	*	*	74.00	*	PK	PASS
H	4924.92	41.15	5.05	46.20	74.00	-27.80	PK	PASS
H	7386.79	35.47	9.83	45.30	74.00	-28.71	PK	PASS
H	9848.79	28.00	13.24	41.24	74.00	-32.76	PK	PASS
H	12310.09	*	*	*	74.00	*	PK	PASS
H	14772.19	*	*	*	74.00	*	PK	PASS
H	17234.97	*	*	*	74.00	*	PK	PASS
V	4924.62	31.68	5.05	36.73	54.00	-17.27	AV	PASS
V	7386.08	24.35	9.83	34.18	54.00	-19.83	AV	PASS
V	9848.03	18.74	13.24	31.98	54.00	-22.02	AV	PASS
V	12310.91	*	*	*	54.00	*	AV	PASS
V	14772.24	*	*	*	54.00	*	AV	PASS
V	17234.58	*	*	*	54.00	*	AV	PASS
H	4924.92	31.80	5.05	36.85	54.00	-17.16	AV	PASS
H	7386.79	22.40	9.83	32.23	54.00	-21.78	AV	PASS
H	9848.79	18.59	13.24	31.83	54.00	-22.17	AV	PASS
H	12310.09	*	*	*	54.00	*	AV	PASS
H	14772.19	*	*	*	54.00	*	AV	PASS
H	17234.97	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

ANNEX A TEST SETUP PHOTOS

Please refer to the document "8427EU120803W1-ANNEX A.PDF"

ANNEX B EXTERNAL PHOTOS

Please refer to the document "8427EU120803W1-ANNEX B.PDF"

ANNEX C INTERNAL PHOTOS

Please refer to the document "8427EU120803W1-ANNEX C.PDF"



ANNEX D TEST DATA

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1


Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	/	/	8.354	8.400	99.45	0.02	0.26
		2437	/	/	8.350	8.397	99.44	0.02	0.04
		2462	/	/	8.353	8.400	99.44	0.02	0.04
802.11g	SISO	2412	/	/	0.149	0.197	75.63	1.21	0.45
		2437	/	/	0.148	0.196	75.51	1.22	0.61
		2462	/	/	0.149	0.196	76.02	1.19	0.46
802.11n (HT20)	SISO	2412	/	/	0.177	0.225	78.67	1.04	0.73
		2437	/	/	0.177	0.223	79.37	1.00	0.23
		2462	/	/	0.176	0.225	78.22	1.07	0.70
802.11n (HT40)	SISO	2422	/	/	0.181	0.229	79.04	1.02	0.66
		2437	/	/	0.181	0.228	79.39	1.00	0.47
		2452	/	/	0.181	0.228	79.39	1.00	0.36
802.11ax (HEW20)	SISO	2412	SU	/	0.175	0.224	78.13	1.07	0.64
		2437	SU	/	0.175	0.222	78.83	1.03	0.21
		2462	SU	/	0.175	0.223	78.48	1.05	0.41
802.11ax (HEW40)	SISO	2422	SU	/	0.171	0.220	77.73	1.09	0.61
		2437	SU	/	0.171	0.220	77.73	1.09	0.76
		2452	SU	/	0.173	0.219	79.00	1.02	0.41

1.2 Test Graph


1.2.1 Ant1




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11g LCH 2412MHz Ant1 (SISO) NTNV




802.11g_MCH_2437MHz_Ant1 (SISO) NTN




802.11g_HCH_2462MHz_Ant1 (SISO) NTN




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNv



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	13.151	/	Pass
		2437	/	/	1	13.154	/	Pass
		2462	/	/	1	13.107	/	Pass
802.11g	SISO	2412	/	/	1	18.298	/	Pass
		2437	/	/	1	18.294	/	Pass
		2462	/	/	1	18.377	/	Pass
802.11n (HT20)	SISO	2412	/	/	1	19.135	/	Pass
		2437	/	/	1	19.116	/	Pass
		2462	/	/	1	19.125	/	Pass
802.11n (HT40)	SISO	2422	/	/	1	38.240	/	Pass
		2437	/	/	1	38.242	/	Pass
		2452	/	/	1	38.345	/	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	19.068	/	Pass
		2437	SU	/	1	19.059	/	Pass
		2462	SU	/	1	19.059	/	Pass
802.11ax (HEW40)	SISO	2422	SU	/	1	37.841	/	Pass
		2437	SU	/	1	37.674	/	Pass
		2452	SU	/	1	37.577	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	9.781	≥ 0.5	Pass
		2437	/	/	1	9.742	≥ 0.5	Pass
		2462	/	/	1	9.738	≥ 0.5	Pass
802.11g	SISO	2412	/	/	1	16.949	≥ 0.5	Pass
		2437	/	/	1	17.112	≥ 0.5	Pass
		2462	/	/	1	17.072	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	/	/	1	18.098	≥ 0.5	Pass
		2437	/	/	1	18.072	≥ 0.5	Pass
		2462	/	/	1	18.129	≥ 0.5	Pass
802.11n (HT40)	SISO	2422	/	/	1	36.965	≥ 0.5	Pass
		2437	/	/	1	36.810	≥ 0.5	Pass
		2452	/	/	1	36.721	≥ 0.5	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	18.361	≥ 0.5	Pass
		2437	SU	/	1	18.085	≥ 0.5	Pass
		2462	SU	/	1	18.247	≥ 0.5	Pass
802.11ax (HEW40)	SISO	2422	SU	/	1	36.957	≥ 0.5	Pass
		2437	SU	/	1	36.231	≥ 0.5	Pass
		2452	SU	/	1	35.832	≥ 0.5	Pass

2.2 Test Graph


2.2.1 OBW




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11g LCH 2412MHz Ant1 (SISO) NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNv




2.2.2 6dB BW




802.11b HCH 2462MHz Ant1 (SISO) NTV




802.11g LCH 2412MHz Ant1 (SISO) NTV




802.11g MCH 2437MHz Ant1 (SISO) NTNV




802.11g HCH 2462MHz Ant1 (SISO) NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTN



802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTN



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Peak Conducted Output Power (dBm)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	13.24	<=30	Pass
		2437	/	/	10.10	<=30	Pass
		2462	/	/	10.53	<=30	Pass
802.11g	SISO	2412	/	/	12.21	<=30	Pass
		2437	/	/	11.74	<=30	Pass
		2462	/	/	11.53	<=30	Pass
802.11n (HT20)	SISO	2412	/	/	12.39	<=30	Pass
		2437	/	/	11.74	<=30	Pass
		2462	/	/	11.51	<=30	Pass
802.11n (HT40)	SISO	2422	/	/	11.79	<=30	Pass
		2437	/	/	11.52	<=30	Pass
		2452	/	/	11.47	<=30	Pass
802.11ax (HEW20)	SISO	2412	SU	/	13.68	<=30	Pass
		2437	SU	/	14.10	<=30	Pass
		2462	SU	/	14.58	<=30	Pass
802.11ax (HEW40)	SISO	2422	SU	/	14.01	<=30	Pass
		2437	SU	/	14.16	<=30	Pass
		2452	SU	/	14.61	<=30	Pass

4. Maximum Power Spectral Density


4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	1.04	<=8	Pass
		2437	/	/	-2.03	<=8	Pass
		2462	/	/	-1.64	<=8	Pass
802.11g	SISO	2412	/	/	-6.24	<=8	Pass
		2437	/	/	-6.77	<=8	Pass
		2462	/	/	-6.90	<=8	Pass
802.11n (HT20)	SISO	2412	/	/	-5.97	<=8	Pass
		2437	/	/	-6.79	<=8	Pass
		2462	/	/	-6.96	<=8	Pass
802.11n (HT40)	SISO	2422	/	/	-10.13	<=8	Pass
		2437	/	/	-10.59	<=8	Pass
		2452	/	/	-10.28	<=8	Pass
802.11ax (HEW20)	SISO	2412	SU	/	-4.54	<=8	Pass
		2437	SU	/	-4.00	<=8	Pass
		2462	SU	/	-3.63	<=8	Pass
802.11ax (HEW40)	SISO	2422	SU	/	-7.83	<=8	Pass
		2437	SU	/	-7.40	<=8	Pass
		2452	SU	/	-7.25	<=8	Pass

4.2 Test Graph


4.2.1 PSD




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11g LCH 2412MHz Ant1 (SISO) NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTNV




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTNV




802.11n(HT40) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNv



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)
802.11b	SISO	2412	/	/	1	1.00
		2437	/	/	1	-2.13
		2462	/	/	1	-1.53
802.11g	SISO	2412	/	/	1	-6.20
		2437	/	/	1	-6.78
		2462	/	/	1	-6.89
802.11n (HT20)	SISO	2412	/	/	1	-6.21
		2437	/	/	1	-6.76
		2462	/	/	1	-7.00
802.11n (HT40)	SISO	2422	/	/	1	-10.11
		2437	/	/	1	-10.61
		2452	/	/	1	-10.29
802.11ax (HEW20)	SISO	2412	SU	/	1	-4.57
		2437	SU	/	1	-4.10
		2462	SU	/	1	-3.62
802.11ax (HEW40)	SISO	2422	SU	/	1	-7.84
		2437	SU	/	1	-7.49
		2452	SU	/	1	-7.26
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020+Cor 1-2023, the channel contains the maximum PSD level was used to establish the reference level.						

5.1.2 CSE


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	/	/	1	1.00	-19.00	Pass
		2437	/	/	1	-2.13	-22.13	Pass
		2462	/	/	1	-1.53	-21.53	Pass
802.11g	SISO	2412	/	/	1	-6.20	-26.20	Pass
		2437	/	/	1	-6.78	-26.78	Pass
		2462	/	/	1	-6.89	-26.89	Pass
802.11n (HT20)	SISO	2412	/	/	1	-6.21	-26.21	Pass
		2437	/	/	1	-6.76	-26.76	Pass
		2462	/	/	1	-7.00	-27.00	Pass
802.11n (HT40)	SISO	2422	/	/	1	-10.11	-30.11	Pass
		2437	/	/	1	-10.61	-30.61	Pass
		2452	/	/	1	-10.29	-30.29	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	-4.57	-24.57	Pass
		2437	SU	/	1	-4.10	-24.10	Pass
		2462	SU	/	1	-3.62	-23.62	Pass
802.11ax (HEW40)	SISO	2422	SU	/	1	-7.84	-27.84	Pass
		2437	SU	/	1	-7.49	-27.49	Pass
		2452	SU	/	1	-7.26	-27.26	Pass
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020+Cor 1-2023, the channel contains the maximum PSD level was used to establish the reference level.								

5.2 Test Graph


5.2.1 Ref




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11g LCH 2412MHz Ant1 (SISO) NTNV




802.11g_MCH_2437MHz_Ant1 (SISO) NTN




802.11g_HCH_2462MHz_Ant1 (SISO) NTN




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTN




5.2.2 CSE




802.11b LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b LCH_2412MHz_Ant1 (SISO) NTNV




802.11b MCH_2437MHz_Ant1 (SISO) NTNV




802.11b MCH_2437MHz_Ant1 (SISO) NTNV




802.11b MCH_2437MHz_Ant1 (SISO) NTNV




802.11b MCH 2437MHz Ant1 (SISO) NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11b HCH_2462MHz_Ant1 (SISO) NTNV




802.11b HCH_2462MHz_Ant1 (SISO) NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11g LCH_2412MHz_Ant1 (SISO) _NTNV




802.11g LCH_2412MHz_Ant1 (SISO) _NTNV




802.11g LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g LCH_2412MHz_Ant1 (SISO) NTNV




802.11g MCH_2437MHz_Ant1 (SISO) NTNV




802.11g_MCH_2437MHz_Ant1 (SISO) NTNV




802.11g_MCH_2437MHz_Ant1 (SISO) NTNV




802.11g_MCH_2437MHz_Ant1 (SISO) NTN




802.11g_HCH_2462MHz_Ant1 (SISO) NTN




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO) NTN




802.11g_HCH_2462MHz_Ant1 (SISO) NTN




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTN




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTN




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTNv




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTNv




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNV




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNV




802.11ax(HEW20)_HCH_2462MHz_SU / Ant1 (SISO) NTNv




802.11ax(HEW20)_HCH_2462MHz_SU / Ant1 (SISO) NTNv




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) LCH 2422MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTN




802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNV



802.11ax(HEW40) HCH 2452MHz SU / Ant1 (SISO) NTNV



STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---