

TEST REPORT

Report No.: 8427EU120809W2

Applicant: Shenzhen Ruheng Technology Co., Ltd.

Address: Room 1201, Yousuowei Building, 2000 Jiaxian Road,
Gangtou Community, Bantian Street, Longgang District,
Shenzhen, Guangdong, China

Product Name: Dash Cam

Model No.: D018

Trademark: TERUNSOUL

FCC ID: 2BPRI-D018

Test Standard(s): 47 CFR Part 15E

Test Result: Pass

Date of Receipt: Jan. 08, 2026

Test Date: Jan. 08, 2026 - Jan. 28, 2026

Date of Issue: Feb. 04, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:



Landon Qiu/ Engineer

Reviewed and Approved by:



Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Feb. 04, 2026	Original	Valid



Table of Contents

1	COVER PAGE	1
2	GENERAL INFORMATION	5
2.1	APPLICANT INFORMATION	5
2.2	MANUFACTURER INFORMATION	5
2.3	FACTORY INFORMATION	5
2.4	GENERAL DESCRIPTION OF E.U.T.	5
2.5	TECHNICAL INFORMATION OF E.U.T.	6
3	TEST SUMMARY	8
3.1	TEST STANDARD	8
3.2	TEST VERDICT	8
3.3	TEST LABORATORY	9
4	TEST CONFIGURATION	10
4.1	TEST ENVIRONMENT	10
4.2	TEST EQUIPMENT	10
4.3	DESCRIPTION OF SUPPORT UNIT	12
4.4	TEST MODE	12
4.5	DESCRIPTION OF CALCULATION	12
4.5.1	Field Strength Calculation	12
4.5.2	Disturbance Calculation	12
4.6	MEASUREMENT UNCERTAINTY	13
4.7	DEVIATION FROM STANDARDS	13
4.8	ABNORMALITIES FROM STANDARD CONDITION	13
5	EVALUATION RESULTS (EVALUATION)	14
5.1	ANTENNA REQUIREMENT	14
5.1.1	Test Specification	14
5.1.2	Test Data	14
6	RADIO SPECTRUM MATTER TEST RESULTS (RF)	15
6.1	DUTY CYCLE	15
6.1.1	Test Specification	15
6.1.2	E.U.T. Operation	15
6.1.3	Test Setup Diagram	15
6.1.4	Test Data	15
6.2	EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	16
6.2.1	Test Specification	16
6.2.2	E.U.T. Operation	17
6.2.3	Test Setup Diagram	17
6.2.4	Test Data	17
6.3	MAXIMUM CONDUCTED OUTPUT POWER	18
6.3.1	Test Specification	18
6.3.2	E.U.T. Operation	19
6.3.3	Test Setup Diagram	19
6.3.4	Test Data	19
6.4	POWER SPECTRAL DENSITY	20
6.4.1	Test Specification	20
6.4.2	E.U.T. Operation	21
6.4.3	Test Setup Diagram	21

6.4.4	Test Data	21
6.5	FREQUENCY STABILITY	22
6.5.1	Test Specification	22
6.5.2	E.U.T. Operation.....	22
6.5.3	Test Setup Diagram.....	22
6.5.4	Test Data	22
6.6	BAND EDGE EMISSIONS (RADIATED)	23
6.6.1	Test Specification	23
6.6.2	E.U.T. Operation.....	25
6.6.3	Test Setup Diagram.....	25
6.6.4	Test Data	25
6.7	UNDESIRABLE EMISSION LIMITS (BELOW 1GHz).....	47
6.7.1	Test Specification	47
6.7.2	E.U.T. Operation.....	48
6.7.3	Test Setup Diagram.....	49
6.7.4	Test Data	49
6.8	UNDESIRABLE EMISSION LIMITS (ABOVE 1GHz)	52
6.8.1	Test Specification	52
6.8.2	E.U.T. Operation.....	54
6.8.3	Test Setup Diagram.....	54
6.8.4	Test Data	54
ANNEX A	TEST SETUP PHOTOS	61
ANNEX B	EXTERNAL PHOTOS	61
ANNEX C	INTERNAL PHOTOS	61
ANNEX D	TEST DATA	62

2 General Information

2.1 Applicant Information

Applicant	Shenzhen Ruheng Technology Co., Ltd.
Address	Room 1201, Yousuowei Building, 2000 Jiaxian Road, Gangtou Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Ruheng Technology Co., Ltd.
Address	Room 1201, Yousuowei Building, 2000 Jiaxian Road, Gangtou Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China

2.3 Factory Information

Factory	Shenzhen Mili Automotive Electronics Co., Ltd.
Address	Building 2, Unit 1101, No. 2 Chongqing Road, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen.

2.4 General Description of E.U.T.

Product Name	Dash Cam
Model No. Under Test	D018
List Model No.	N/A
Description of Model differentiation	N/A
Rating(s)	Input: 5VDC, 3A (Car Charger Input: 12-30VDC; Output: 5VDC, 3A)
Car Charger	Model No.: CSXE1219 Input: 12-30VDC Output: 5VDC, 3A Manufacturer: Shenzhen Desimy Technology Co., LTD
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Test Sample No.	8427EU120809W-1/2(Normal), 8427EU120809W-2/2(Engineering)
Hardware Version	V1.1
Software Version	D018_V2.20260202.1TERUNSOUL
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	WiFi 2.4G: 802.11b, 802.11g, 802.11n(HT20/40) and 802.11ax(HEW20/40) WiFi 5G: 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40), 802.11ax(HEW20/40) U-NII-1/3
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Technology	WiFi 5G
Operation Mode	a, n(HT20), n(HT40), ac(VHT20), ac(VHT40), ax(HEW20), ax(HEW40)
Operating Frequency	U-NII-1: 5150 MHz to 5250 MHz U-NII-3: 5725 MHz to 5850 MHz
Modulation Type	802.11a: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM); 802.11ax: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM).
Number of Channels	802.11a/n(HT20)/ac(HT20)/ax(HE20): U-NII Band 1: 4; U-NII Band 3: 5; 802.11n(HT40)/ac(HT40)/ax(HE40): U-NII Band 1: 2; U-NII Band 3: 2;
Antenna Type	FPC Antenna
Antenna Gain(Peak)	U-NII-1: 5150 MHz to 5250 MHz: 3.48dBi U-NII-3: 5725 MHz to 5850 MHz: 3.48dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

U-NII-1			
Bandwidth:	20MHz	Bandwidth:	40MHz
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190
40	5200	46	5230
44	5220	/	/
48	5240	/	/
U-NII-3			
Bandwidth:	20MHz	Bandwidth:	40MHz
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755
153	5765	159	5795
157	5785	/	/
161	5805	/	/
165	5825	/	/

802.11ax RU configuration table						
Mode	Full RU (SU)	RU_26	RU_52	RU_106	RU_242	RU_484
802.11ax(HE20)	√	--	--	--	--	--
802.11ax(HE40)	√	--	--	--	--	--

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

47 CFR Part 15E: Unlicensed National Information Infrastructure Devices

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

Test Items	Standard	Method	Requirement	Results
Antenna requirement	47 CFR Part 15E	---	Part 15.203	Pass
Duty Cycle	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023 section 12.2 (b)	---	Pass
Emission bandwidth and occupied bandwidth	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023, section 6.9 & 12.5 KDB 789033 D02, Clause C.2	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. 47 CFR Part 15.407(e)	Pass
Maximum conducted output power	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023, section 12.4	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)	Pass
Power spectral density	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023, section 12.6	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)	Pass
Frequency stability	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023, section 6.8	47 CFR Part 15.407(g)	Pass
Band edge emissions (Radiated)	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass
Undesirable emission limits (below 1GHz)	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023, section 12.7.4,	47 CFR Part 15.407(b)(9)	Pass

		12.7.5		
Undesirable emission limits (above 1GHz)	47 CFR Part 15E	ANSI C63.10-2020+Cor 1-2023, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass
Note: (1) "N/A" denotes test is not applicable in this Test Report.				

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15℃ to +35℃
Working Voltage of the EUT	NV (Normal Voltage)	12VDC

4.2 Test Equipment

Duty Cycle Emission bandwidth and occupied bandwidth Maximum conducted output power Power spectral density Frequency stability					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-01-07	2027-01-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-01-07	2027-01-06
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2026-01-07	2027-01-06
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-402	2025-02-14	2026-02-13
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2025-02-14	2026-02-13
Power Meter	Anritsu	ML2495A	EE-416	2025-02-14	2026-02-13
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2025-07-29	2026-07-28
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	/	/

Band edge emissions (Radiated) Undesirable emission limits (above 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-01-07	2027-01-06
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2026-01-11	2029-01-10
Pre-amplifier	Agilent	8449B	EE-010	2026-01-07	2027-01-06
MXG RF Vector	Agilent	N5182A	EE-012	2026-01-07	2027-01-06

Signal Generator					
DRG Horn Antenna	SCHWARZBECK	BBHA 9170	EE-410	2025-02-14	2026-02-13
Pre-amplifier	SKET	LNPA-1840-50	EE-411	2025-02-14	2026-02-13
Test Software	Farad	EZ-EMC	EE-015	/	/

Undesirable emission limits (below 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-01-07	2027-01-06
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026-01-13	2029-01-12
Pre-amplifier	Agilent	8447D	EE-009	2026-01-07	2027-01-06
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-01-07	2027-01-06
Test Software	Farad	EZ-EMC	EE-015	/	/

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Car Charger	refer to clause 2.4	refer to clause 2.4	--
2	12V Battery	CHILWEE	6-DZF-12.2	EMC-PJ-031

4.4 Test Mode

No.	Test Modes	Description
TM1	802.11a Mode	Keep the EUT in continuously transmitting mode with 802.11a modulation type at lowest, middle and highest channel. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report.
TM2	802.11n(HT20) Mode	Keep the EUT in 802.11n(HT20) transmitting mode at lowest, middle and highest channel.
TM3	802.11n(HT40) Mode	Keep the EUT in 802.11n(HT40) transmitting mode at lowest, middle and highest channel.
TM4	802.11ac(HT20) Mode	Keep the EUT in 802.11ac(HT20) transmitting mode at lowest, middle and highest channel.
TM5	802.11ac(HT40) Mode	Keep the EUT in 802.11ac(HT40) transmitting mode at lowest, middle and highest channel.
TM6	802.11ax(HE20) Mode	Keep the EUT in 802.11ax(HE20) transmitting mode at lowest, middle and highest channel.
TM7	802.11ax(HE40) Mode	Keep the EUT in 802.11ax(HE40) transmitting mode at lowest, middle and highest channel.

4.5 Description of Calculation

4.5.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS \text{ (dBuV/m)} = RA \text{ (dBuV)} + AF \text{ (dB/m)} + CL \text{ (dB)} - AG \text{ (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

4.5.2 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test Item	Measurement Uncertainty
Time of Occupancy (Dwell Time)	1.8 %
Occupied Channel Bandwidth	70 kHz
RF output power, conducted	1.04 dB
Power Spectral Density, conducted	0.91 dB
Radiated Emission (1GHz- 18GHz)	Ur = 3.50 dB (Horizontal) Ur = 3.50 dB (Vertical)
Radiated Emission (9kHz- 30MHz)	Ur = 2.50 dB
Radiated Emission (30MHz- 1GHz)	Ur = 2.70 dB (Horizontal) Ur = 2.70 dB (Vertical)
Radiated Emission (18GHz- 40GHz)	Ur = 5.15 dB (Horizontal) Ur = 5.24 dB (Vertical)

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Condition

None

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

5.1.1 Test Specification

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.2 Test Data

PASS.

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

6 Radio Spectrum Matter Test Results (RF)

6.1 Duty Cycle


6.1.1 Test Specification

Test Requirement:	All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x , and maximum-power transmission duration, T , are required for each tested mode of operation.
Test Limit:	No limits, only for report use.
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 12.2 (b)
Procedure:	i) Set the center frequency of the instrument to the center frequency of the transmission. ii) Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. iii) Set VBW $\geq$ RBW. iv) Set detector = peak. v) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100.

6.1.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.1.3 Test Setup Diagram



6.1.4 Test Data

PASS.

Please refer to Annex D for details.

6.2 Emission bandwidth and occupied bandwidth

6.2.1 Test Specification


Test Requirement:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: 47 CFR Part 15.407(e)
Test Limit:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 6.9 & 12.5 KDB 789033 D02, Clause C.2
Procedure:	Emission bandwidth: a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth. b) Set the VBW > RBW. c) Detector = peak. d) Trace mode = max hold. e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. Occupied bandwidth: a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Step a) through step c) might require iteration to adjust within the specified range. e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used. f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until

	99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies. h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s). 6 dB emission bandwidth: a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
--	--

6.2.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.2.3 Test Setup Diagram



6.2.4 Test Data

PASS.

Please refer to Annex D for details.

6.3 Maximum conducted output power

6.3.1 Test Specification


Test Requirement:	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm). For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations. For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally

	installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 12.4
Procedure:	Refer to ANSI C63.10-2020+Cor 1-2023 section 12.4

6.3.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.3.3 Test Setup Diagram



6.3.4 Test Data

PASS.

Please refer to Annex D for details.

6.4 Power spectral density

6.4.1 Test Specification


Test Requirement:	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations. For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 12.6

Procedure:	Refer to ANSI C63.10-2020+Cor 1-2023, section 12.6
------------	--

6.4.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.4.3 Test Setup Diagram



6.4.4 Test Data

PASS.

Please refer to Annex D for details.

6.5 Frequency stability


6.5.1 Test Specification

Test Requirement:	47 CFR Part 15.407(g)
Test Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 6.8
Procedure:	Refer to ANSI C63.10-2020+Cor 1-2023 section 6.8

6.5.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.5.3 Test Setup Diagram



6.5.4 Test Data

PASS.

Please refer to Annex D for details.

6.6 Band edge emissions (Radiated)

6.6.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																										
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table border="1"> <thead> <tr> <th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr> </thead> <tbody> <tr> <td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr> <tr> <td>¹ 0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr> <tr> <td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr> <tr> <td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr> <tr> <td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr> <tr> <td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr> <tr> <td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr> <tr> <td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr> <tr> <td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr> <tr> <td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr> <tr> <td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr> <tr> <td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr> <tr> <td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr> <tr> <td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr> <tr> <td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr> <tr> <td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr> <tr> <td>13.36-13.41</td><td></td><td></td><td></td></tr> </tbody> </table> ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated			MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41			
MHz	MHz	MHz	GHz																																																																								
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																								
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																								
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																								
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																								
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																								
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																								
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																								
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																								
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																								
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																								
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																								
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																								
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																								
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																								
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																								
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																								
13.36-13.41																																																																											


	based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 12.7.4, 12.7.6, 12.7.7																								
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor																								

	2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	--

6.6.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.6.3 Test Setup Diagram



6.6.4 Test Data

PASS.

Please refer to the following pages.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11a					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.36	5.79	53.15	68.23	-15.09	PK	PASS
H	5350.00	44.42	6.45	50.87	68.23	-17.36	PK	PASS
V	5150.00	49.46	5.79	55.25	68.23	-12.99	PK	PASS
V	5350.00	44.64	6.45	51.09	68.23	-17.15	PK	PASS
H	5150.00	36.93	5.79	42.72	54.00	-11.29	AV	PASS
H	5350.00	31.45	6.45	37.90	54.00	-16.11	AV	PASS
V	5150.00	34.22	5.79	40.01	54.00	-13.99	AV	PASS
V	5350.00	32.31	6.45	38.76	54.00	-15.25	AV	PASS

Test Mode: 802.11a					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.19	5.79	54.98	68.23	-13.26	PK	PASS
H	5350.00	44.26	6.45	50.71	68.23	-17.53	PK	PASS
V	5150.00	49.43	5.79	55.22	68.23	-13.02	PK	PASS
V	5350.00	44.32	6.45	50.77	68.23	-17.46	PK	PASS
H	5150.00	35.24	5.79	41.03	54.00	-12.97	AV	PASS
H	5350.00	31.24	6.45	37.69	54.00	-16.31	AV	PASS
V	5150.00	36.07	5.79	41.86	54.00	-12.15	AV	PASS
V	5350.00	32.69	6.45	39.14	54.00	-14.86	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.23	5.79	55.02	68.23	-13.21	PK	PASS
H	5350.00	44.22	6.45	50.67	68.23	-17.56	PK	PASS
V	5150.00	49.22	5.79	55.01	68.23	-13.22	PK	PASS
V	5350.00	46.14	6.45	52.59	68.23	-15.65	PK	PASS
H	5150.00	35.41	5.79	41.20	54.00	-12.81	AV	PASS
H	5350.00	31.85	6.45	38.30	54.00	-15.71	AV	PASS
V	5150.00	36.46	5.79	42.25	54.00	-11.76	AV	PASS
V	5350.00	32.91	6.45	39.36	54.00	-14.65	AV	PASS

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.34	5.79	54.13	68.23	-14.10	PK	PASS
H	5350.00	46.74	6.45	53.19	68.23	-15.05	PK	PASS
V	5150.00	49.09	5.79	54.88	68.23	-13.36	PK	PASS
V	5350.00	46.58	6.45	53.03	68.23	-15.21	PK	PASS
H	5150.00	34.20	5.79	39.99	54.00	-14.01	AV	PASS
H	5350.00	32.58	6.45	39.03	54.00	-14.97	AV	PASS
V	5150.00	34.90	5.79	40.69	54.00	-13.32	AV	PASS
V	5350.00	32.61	6.45	39.06	54.00	-14.94	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.84	5.79	55.63	68.23	-12.61	PK	PASS
H	5350.00	44.16	6.45	50.61	68.23	-17.62	PK	PASS
V	5150.00	48.03	5.79	53.82	68.23	-14.42	PK	PASS
V	5350.00	44.56	6.45	51.01	68.23	-17.22	PK	PASS
H	5150.00	34.51	5.79	40.30	54.00	-13.70	AV	PASS
H	5350.00	31.30	6.45	37.75	54.00	-16.26	AV	PASS
V	5150.00	34.34	5.79	40.13	54.00	-13.88	AV	PASS
V	5350.00	32.69	6.45	39.14	54.00	-14.86	AV	PASS

Test Mode: 802.11n(HT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.33	5.79	55.12	68.23	-13.11	PK	PASS
H	5350.00	44.92	6.45	51.37	68.23	-16.87	PK	PASS
V	5150.00	49.98	5.79	55.77	68.23	-12.46	PK	PASS
V	5350.00	46.74	6.45	53.19	68.23	-15.05	PK	PASS
H	5150.00	35.68	5.79	41.47	54.00	-12.54	AV	PASS
H	5350.00	31.94	6.45	38.39	54.00	-15.62	AV	PASS
V	5150.00	35.57	5.79	41.36	54.00	-12.65	AV	PASS
V	5350.00	31.15	6.45	37.60	54.00	-16.41	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ac(VHT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.53	5.79	53.32	68.23	-14.92	PK	PASS
H	5350.00	45.31	6.45	51.76	68.23	-16.47	PK	PASS
V	5150.00	47.37	5.79	53.16	68.23	-15.07	PK	PASS
V	5350.00	44.39	6.45	50.84	68.23	-17.40	PK	PASS
H	5150.00	34.12	5.79	39.91	54.00	-14.09	AV	PASS
H	5350.00	33.14	6.45	39.59	54.00	-14.42	AV	PASS
V	5150.00	34.28	5.79	40.07	54.00	-13.93	AV	PASS
V	5350.00	32.65	6.45	39.10	54.00	-14.91	AV	PASS

Test Mode: 802.11ac(VHT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.11	5.79	53.90	68.23	-14.34	PK	PASS
H	5350.00	44.81	6.45	51.26	68.23	-16.97	PK	PASS
V	5150.00	47.54	5.79	53.33	68.23	-14.91	PK	PASS
V	5350.00	44.85	6.45	51.30	68.23	-16.94	PK	PASS
H	5150.00	34.17	5.79	39.96	54.00	-14.04	AV	PASS
H	5350.00	32.95	6.45	39.40	54.00	-14.60	AV	PASS
V	5150.00	36.40	5.79	42.19	54.00	-11.82	AV	PASS
V	5350.00	32.69	6.45	39.14	54.00	-14.87	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11 ac(VHT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.26	5.79	55.05	68.23	-13.18	PK	PASS
H	5350.00	44.02	6.45	50.47	68.23	-17.77	PK	PASS
V	5150.00	49.32	5.79	55.11	68.23	-13.13	PK	PASS
V	5350.00	44.59	6.45	51.04	68.23	-17.19	PK	PASS
H	5150.00	36.04	5.79	41.83	54.00	-12.18	AV	PASS
H	5350.00	33.16	6.45	39.61	54.00	-14.39	AV	PASS
V	5150.00	35.68	5.79	41.47	54.00	-12.54	AV	PASS
V	5350.00	32.61	6.45	39.06	54.00	-14.95	AV	PASS

Test Mode: 802.11 ac(VHT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.36	5.79	53.15	68.23	-15.08	PK	PASS
H	5350.00	46.61	6.45	53.06	68.23	-15.18	PK	PASS
V	5150.00	49.49	5.79	55.28	68.23	-12.96	PK	PASS
V	5350.00	45.69	6.45	52.14	68.23	-16.10	PK	PASS
H	5150.00	34.52	5.79	40.31	54.00	-13.69	AV	PASS
H	5350.00	32.94	6.45	39.39	54.00	-14.61	AV	PASS
V	5150.00	36.16	5.79	41.95	54.00	-12.05	AV	PASS
V	5350.00	33.10	6.45	39.55	54.00	-14.46	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.83	5.79	53.62	68.23	-14.62	PK	PASS
H	5350.00	44.76	6.45	51.21	68.23	-17.02	PK	PASS
V	5150.00	48.27	5.79	54.06	68.23	-14.18	PK	PASS
V	5350.00	46.08	6.45	52.53	68.23	-15.70	PK	PASS
H	5150.00	36.38	5.79	42.17	54.00	-11.84	AV	PASS
H	5350.00	33.58	6.45	40.03	54.00	-13.97	AV	PASS
V	5150.00	36.55	5.79	42.34	54.00	-11.67	AV	PASS
V	5350.00	31.53	6.45	37.98	54.00	-16.02	AV	PASS

Test Mode: 802.11ax(HEW20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.30	5.79	53.09	68.23	-15.14	PK	PASS
H	5350.00	46.57	6.45	53.02	68.23	-15.21	PK	PASS
V	5150.00	49.89	5.79	55.68	68.23	-12.55	PK	PASS
V	5350.00	44.79	6.45	51.24	68.23	-17.00	PK	PASS
H	5150.00	36.92	5.79	42.71	54.00	-11.29	AV	PASS
H	5350.00	31.70	6.45	38.15	54.00	-15.85	AV	PASS
V	5150.00	35.65	5.79	41.44	54.00	-12.57	AV	PASS
V	5350.00	32.52	6.45	38.97	54.00	-15.04	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.32	5.79	55.11	68.23	-13.13	PK	PASS
H	5350.00	46.11	6.45	52.56	68.23	-15.68	PK	PASS
V	5150.00	48.98	5.79	54.77	68.23	-13.47	PK	PASS
V	5350.00	46.45	6.45	52.90	68.23	-15.33	PK	PASS
H	5150.00	34.49	5.79	40.28	54.00	-13.72	AV	PASS
H	5350.00	31.70	6.45	38.15	54.00	-15.86	AV	PASS
V	5150.00	34.89	5.79	40.68	54.00	-13.33	AV	PASS
V	5350.00	33.40	6.45	39.85	54.00	-14.15	AV	PASS

Test Mode: 802.11ax(HEW40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.26	5.79	55.05	68.23	-13.18	PK	PASS
H	5350.00	45.40	6.45	51.85	68.23	-16.38	PK	PASS
V	5150.00	49.22	5.79	55.01	68.23	-13.23	PK	PASS
V	5350.00	44.46	6.45	50.91	68.23	-17.32	PK	PASS
H	5150.00	34.08	5.79	39.87	54.00	-14.13	AV	PASS
H	5350.00	32.55	6.45	39.00	54.00	-15.01	AV	PASS
V	5150.00	35.17	5.79	40.96	54.00	-13.04	AV	PASS
V	5350.00	32.27	6.45	38.72	54.00	-15.29	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11a					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	43.25	7.55	50.80	68.23	-17.44	PK	PASS
H	5700.00	48.14	7.56	55.70	105.23	-49.53	PK	PASS
H	5720.00	50.39	7.59	57.98	110.83	-52.85	PK	PASS
H	5725.00	50.57	7.68	58.25	122.23	-63.98	PK	PASS
V	5650.00	44.20	7.55	51.75	68.23	-16.48	PK	PASS
V	5700.00	45.07	7.56	52.63	105.23	-52.60	PK	PASS
V	5720.00	49.44	7.59	57.03	110.83	-53.80	PK	PASS
V	5725.00	50.33	7.68	58.01	122.23	-64.23	PK	PASS
H	5650.00	29.76	7.55	37.31	54.00	-16.69	AV	PASS
H	5700.00	33.47	7.56	41.03	54.00	-12.98	AV	PASS
H	5720.00	32.25	7.59	39.84	54.00	-14.17	AV	PASS
H	5725.00	34.29	7.68	41.97	54.00	-12.04	AV	PASS
V	5650.00	31.22	7.55	38.77	54.00	-15.24	AV	PASS
V	5700.00	30.85	7.56	38.41	54.00	-15.59	AV	PASS
V	5720.00	34.94	7.59	42.53	54.00	-11.47	AV	PASS
V	5725.00	37.81	7.68	45.49	54.00	-8.51	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11a					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.66	7.55	53.21	68.23	-15.02	PK	PASS
H	5700.00	45.59	7.56	53.15	105.23	-52.09	PK	PASS
H	5720.00	49.49	7.59	57.08	110.83	-53.75	PK	PASS
H	5725.00	51.56	7.68	59.24	122.23	-62.99	PK	PASS
V	5650.00	44.15	7.55	51.70	68.23	-16.53	PK	PASS
V	5700.00	47.68	7.56	55.24	105.23	-49.99	PK	PASS
V	5720.00	50.54	7.59	58.13	110.83	-52.71	PK	PASS
V	5725.00	51.48	7.68	59.16	122.23	-63.08	PK	PASS
H	5650.00	31.78	7.55	39.33	54.00	-14.67	AV	PASS
H	5700.00	31.06	7.56	38.62	54.00	-15.38	AV	PASS
H	5720.00	33.80	7.59	41.39	54.00	-12.62	AV	PASS
H	5725.00	36.97	7.68	44.65	54.00	-9.36	AV	PASS
V	5650.00	31.09	7.55	38.64	54.00	-15.36	AV	PASS
V	5700.00	32.67	7.56	40.23	54.00	-13.77	AV	PASS
V	5720.00	35.65	7.59	43.24	54.00	-10.77	AV	PASS
V	5725.00	34.41	7.68	42.09	54.00	-11.92	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.66	7.55	53.21	68.23	-15.02	PK	PASS
H	5700.00	45.59	7.56	53.15	105.23	-52.09	PK	PASS
H	5720.00	49.49	7.59	57.08	110.83	-53.75	PK	PASS
H	5725.00	51.56	7.68	59.24	122.23	-62.99	PK	PASS
V	5650.00	44.15	7.55	51.70	68.23	-16.53	PK	PASS
V	5700.00	47.68	7.56	55.24	105.23	-49.99	PK	PASS
V	5720.00	50.54	7.59	58.13	110.83	-52.71	PK	PASS
V	5725.00	51.48	7.68	59.16	122.23	-63.08	PK	PASS
H	5650.00	31.78	7.55	39.33	54.00	-14.67	AV	PASS
H	5700.00	31.06	7.56	38.62	54.00	-15.38	AV	PASS
H	5720.00	33.80	7.59	41.39	54.00	-12.62	AV	PASS
H	5725.00	36.97	7.68	44.65	54.00	-9.36	AV	PASS
V	5650.00	31.09	7.55	38.64	54.00	-15.36	AV	PASS
V	5700.00	32.67	7.56	40.23	54.00	-13.77	AV	PASS
V	5720.00	35.65	7.59	43.24	54.00	-10.77	AV	PASS
V	5725.00	34.41	7.68	42.09	54.00	-11.92	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	52.42	7.55	59.97	122.23	-62.26	PK	PASS
H	5855.00	48.27	7.56	55.83	110.83	-55.01	PK	PASS
H	5875.00	47.81	7.59	55.40	105.23	-49.84	PK	PASS
H	5925.00	43.38	7.68	51.06	68.23	-17.18	PK	PASS
V	5850.00	49.51	7.55	57.06	122.23	-65.17	PK	PASS
V	5855.00	49.94	7.56	57.50	110.83	-53.34	PK	PASS
V	5875.00	48.83	7.59	56.42	105.23	-48.81	PK	PASS
V	5925.00	45.27	7.68	52.95	68.23	-15.29	PK	PASS
H	5850.00	37.86	7.55	45.41	54.00	-8.60	AV	PASS
H	5855.00	32.86	7.56	40.42	54.00	-13.58	AV	PASS
H	5875.00	33.57	7.59	41.16	54.00	-12.84	AV	PASS
H	5925.00	30.41	7.68	38.09	54.00	-15.92	AV	PASS
V	5850.00	37.50	7.55	45.05	54.00	-8.95	AV	PASS
V	5855.00	35.14	7.56	42.70	54.00	-11.31	AV	PASS
V	5875.00	33.60	7.59	41.19	54.00	-12.82	AV	PASS
V	5925.00	29.66	7.68	37.34	54.00	-16.67	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.66	7.55	53.21	68.23	-15.02	PK	PASS
H	5700.00	46.20	7.56	53.76	105.23	-51.47	PK	PASS
H	5720.00	48.82	7.59	56.41	110.83	-54.42	PK	PASS
H	5725.00	50.30	7.68	57.98	122.23	-64.26	PK	PASS
V	5650.00	46.72	7.55	54.27	68.23	-13.96	PK	PASS
V	5700.00	45.28	7.56	52.84	105.23	-52.40	PK	PASS
V	5720.00	47.80	7.59	55.39	110.83	-55.45	PK	PASS
V	5725.00	50.08	7.68	57.76	122.23	-64.47	PK	PASS
H	5650.00	28.33	7.55	35.88	54.00	-18.12	AV	PASS
H	5700.00	32.82	7.56	40.38	54.00	-13.63	AV	PASS
H	5720.00	33.59	7.59	41.18	54.00	-12.83	AV	PASS
H	5725.00	35.82	7.68	43.50	54.00	-10.50	AV	PASS
V	5650.00	30.01	7.55	37.56	54.00	-16.44	AV	PASS
V	5700.00	30.57	7.56	38.13	54.00	-15.88	AV	PASS
V	5720.00	33.81	7.59	41.40	54.00	-12.60	AV	PASS
V	5725.00	36.41	7.68	44.09	54.00	-9.92	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	49.37	7.55	56.92	122.23	-65.32	PK	PASS
H	5855.00	49.57	7.56	57.13	110.83	-53.70	PK	PASS
H	5875.00	45.71	7.59	53.30	105.23	-51.93	PK	PASS
H	5925.00	45.13	7.68	52.81	68.23	-15.43	PK	PASS
V	5850.00	52.07	7.55	59.62	122.23	-62.62	PK	PASS
V	5855.00	49.84	7.56	57.40	110.83	-53.44	PK	PASS
V	5875.00	46.54	7.59	54.13	105.23	-51.11	PK	PASS
V	5925.00	45.40	7.68	53.08	68.23	-15.15	PK	PASS
H	5850.00	36.44	7.55	43.99	54.00	-10.02	AV	PASS
H	5855.00	35.76	7.56	43.32	54.00	-10.68	AV	PASS
H	5875.00	31.86	7.59	39.45	54.00	-14.55	AV	PASS
H	5925.00	28.92	7.68	36.60	54.00	-17.41	AV	PASS
V	5850.00	34.75	7.55	42.30	54.00	-11.70	AV	PASS
V	5855.00	33.61	7.56	41.17	54.00	-12.83	AV	PASS
V	5875.00	32.14	7.59	39.73	54.00	-14.28	AV	PASS
V	5925.00	29.43	7.68	37.11	54.00	-16.89	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.32	7.55	52.87	68.23	-15.36	PK	PASS
H	5700.00	45.47	7.56	53.03	105.23	-52.20	PK	PASS
H	5720.00	48.63	7.59	56.22	110.83	-54.62	PK	PASS
H	5725.00	49.09	7.68	56.77	122.23	-65.47	PK	PASS
V	5650.00	45.47	7.55	53.02	68.23	-15.21	PK	PASS
V	5700.00	46.38	7.56	53.94	105.23	-51.30	PK	PASS
V	5720.00	47.00	7.59	54.59	110.83	-56.24	PK	PASS
V	5725.00	51.86	7.68	59.54	122.23	-62.70	PK	PASS
H	5650.00	28.23	7.55	35.78	54.00	-18.23	AV	PASS
H	5700.00	31.16	7.56	38.72	54.00	-15.28	AV	PASS
H	5720.00	32.10	7.59	39.69	54.00	-14.32	AV	PASS
H	5725.00	34.11	7.68	41.79	54.00	-12.22	AV	PASS
V	5650.00	30.86	7.55	38.41	54.00	-15.60	AV	PASS
V	5700.00	30.83	7.56	38.39	54.00	-15.61	AV	PASS
V	5720.00	32.20	7.59	39.79	54.00	-14.22	AV	PASS
V	5725.00	35.02	7.68	42.70	54.00	-11.31	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	52.48	7.55	60.03	122.23	-62.21	PK	PASS
H	5855.00	49.00	7.56	56.56	110.83	-54.27	PK	PASS
H	5875.00	47.87	7.59	55.46	105.23	-49.77	PK	PASS
H	5925.00	46.34	7.68	54.02	68.23	-14.21	PK	PASS
V	5850.00	49.05	7.55	56.60	122.23	-65.64	PK	PASS
V	5855.00	49.81	7.56	57.37	110.83	-53.47	PK	PASS
V	5875.00	45.88	7.59	53.47	105.23	-51.76	PK	PASS
V	5925.00	45.53	7.68	53.21	68.23	-15.03	PK	PASS
H	5850.00	36.61	7.55	44.16	54.00	-9.84	AV	PASS
H	5855.00	34.63	7.56	42.19	54.00	-11.82	AV	PASS
H	5875.00	30.13	7.59	37.72	54.00	-16.29	AV	PASS
H	5925.00	29.26	7.68	36.94	54.00	-17.06	AV	PASS
V	5850.00	37.09	7.55	44.64	54.00	-9.37	AV	PASS
V	5855.00	32.44	7.56	40.00	54.00	-14.00	AV	PASS
V	5875.00	32.67	7.59	40.26	54.00	-13.74	AV	PASS
V	5925.00	28.06	7.68	35.74	54.00	-18.26	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.84	7.55	53.39	68.23	-14.84	PK	PASS
H	5700.00	45.42	7.56	52.98	105.23	-52.25	PK	PASS
H	5720.00	49.47	7.59	57.06	110.83	-53.78	PK	PASS
H	5725.00	51.31	7.68	58.99	122.23	-63.24	PK	PASS
V	5650.00	45.80	7.55	53.35	68.23	-14.89	PK	PASS
V	5700.00	47.50	7.56	55.06	105.23	-50.17	PK	PASS
V	5720.00	51.00	7.59	58.59	110.83	-52.24	PK	PASS
V	5725.00	52.63	7.68	60.31	122.23	-61.93	PK	PASS
H	5650.00	30.30	7.55	37.85	54.00	-16.16	AV	PASS
H	5700.00	32.76	7.56	40.32	54.00	-13.69	AV	PASS
H	5720.00	35.12	7.59	42.71	54.00	-11.30	AV	PASS
H	5725.00	37.72	7.68	45.40	54.00	-8.61	AV	PASS
V	5650.00	28.59	7.55	36.14	54.00	-17.86	AV	PASS
V	5700.00	30.88	7.56	38.44	54.00	-15.57	AV	PASS
V	5720.00	35.01	7.59	42.60	54.00	-11.40	AV	PASS
V	5725.00	37.53	7.68	45.21	54.00	-8.80	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	50.59	7.55	58.14	122.23	-64.10	PK	PASS
H	5855.00	50.85	7.56	58.41	110.83	-52.42	PK	PASS
H	5875.00	48.26	7.59	55.85	105.23	-49.39	PK	PASS
H	5925.00	44.03	7.68	51.71	68.23	-16.53	PK	PASS
V	5850.00	51.65	7.55	59.20	122.23	-63.04	PK	PASS
V	5855.00	47.38	7.56	54.94	110.83	-55.89	PK	PASS
V	5875.00	45.35	7.59	52.94	105.23	-52.30	PK	PASS
V	5925.00	44.14	7.68	51.82	68.23	-16.42	PK	PASS
H	5850.00	37.86	7.55	45.41	54.00	-8.59	AV	PASS
H	5855.00	32.16	7.56	39.72	54.00	-14.28	AV	PASS
H	5875.00	31.06	7.59	38.65	54.00	-15.36	AV	PASS
H	5925.00	31.37	7.68	39.05	54.00	-14.95	AV	PASS
V	5850.00	36.24	7.55	43.79	54.00	-10.22	AV	PASS
V	5855.00	34.85	7.56	42.41	54.00	-11.59	AV	PASS
V	5875.00	32.07	7.59	39.66	54.00	-14.34	AV	PASS
V	5925.00	28.58	7.68	36.26	54.00	-17.74	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	44.97	7.55	52.52	68.23	-15.72	PK	PASS
H	5700.00	45.13	7.56	52.69	105.23	-52.54	PK	PASS
H	5720.00	47.25	7.59	54.84	110.83	-55.99	PK	PASS
H	5725.00	51.73	7.68	59.41	122.23	-62.82	PK	PASS
V	5650.00	43.56	7.55	51.11	68.23	-17.13	PK	PASS
V	5700.00	46.35	7.56	53.91	105.23	-51.32	PK	PASS
V	5720.00	50.31	7.59	57.90	110.83	-52.94	PK	PASS
V	5725.00	52.29	7.68	59.97	122.23	-62.27	PK	PASS
H	5650.00	30.84	7.55	38.39	54.00	-15.62	AV	PASS
H	5700.00	32.61	7.56	40.17	54.00	-13.84	AV	PASS
H	5720.00	32.35	7.59	39.94	54.00	-14.07	AV	PASS
H	5725.00	37.98	7.68	45.66	54.00	-8.34	AV	PASS
V	5650.00	29.98	7.55	37.53	54.00	-16.47	AV	PASS
V	5700.00	30.04	7.56	37.60	54.00	-16.40	AV	PASS
V	5720.00	33.17	7.59	40.76	54.00	-13.25	AV	PASS
V	5725.00	36.60	7.68	44.28	54.00	-9.73	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	49.02	7.55	56.57	122.23	-65.67	PK	PASS
H	5855.00	50.90	7.56	58.46	110.83	-52.37	PK	PASS
H	5875.00	47.41	7.59	55.00	105.23	-50.23	PK	PASS
H	5925.00	46.49	7.68	54.17	68.23	-14.07	PK	PASS
V	5850.00	49.99	7.55	57.54	122.23	-64.70	PK	PASS
V	5855.00	50.36	7.56	57.92	110.83	-52.91	PK	PASS
V	5875.00	46.75	7.59	54.34	105.23	-50.89	PK	PASS
V	5925.00	45.68	7.68	53.36	68.23	-14.87	PK	PASS
H	5850.00	35.46	7.55	43.01	54.00	-11.00	AV	PASS
H	5855.00	35.62	7.56	43.18	54.00	-10.83	AV	PASS
H	5875.00	30.51	7.59	38.10	54.00	-15.90	AV	PASS
H	5925.00	31.70	7.68	39.38	54.00	-14.63	AV	PASS
V	5850.00	37.66	7.55	45.21	54.00	-8.80	AV	PASS
V	5855.00	33.44	7.56	41.00	54.00	-13.00	AV	PASS
V	5875.00	30.37	7.59	37.96	54.00	-16.05	AV	PASS
V	5925.00	30.50	7.68	38.18	54.00	-15.82	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.13	7.55	52.68	68.23	-15.56	PK	PASS
H	5700.00	48.66	7.56	56.22	105.23	-49.02	PK	PASS
H	5720.00	49.05	7.59	56.64	110.83	-54.19	PK	PASS
H	5725.00	50.57	7.68	58.25	122.23	-63.99	PK	PASS
V	5650.00	46.18	7.55	53.73	68.23	-14.50	PK	PASS
V	5700.00	45.94	7.56	53.50	105.23	-51.74	PK	PASS
V	5720.00	47.16	7.59	54.75	110.83	-56.08	PK	PASS
V	5725.00	51.33	7.68	59.01	122.23	-63.23	PK	PASS
H	5650.00	28.85	7.55	36.40	54.00	-17.61	AV	PASS
H	5700.00	30.34	7.56	37.90	54.00	-16.10	AV	PASS
H	5720.00	35.78	7.59	43.37	54.00	-10.64	AV	PASS
H	5725.00	35.53	7.68	43.21	54.00	-10.80	AV	PASS
V	5650.00	28.49	7.55	36.04	54.00	-17.97	AV	PASS
V	5700.00	31.10	7.56	38.66	54.00	-15.34	AV	PASS
V	5720.00	33.09	7.59	40.68	54.00	-13.32	AV	PASS
V	5725.00	36.14	7.68	43.82	54.00	-10.18	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	53.00	7.55	60.55	122.23	-61.68	PK	PASS
H	5855.00	49.52	7.56	57.08	110.83	-53.75	PK	PASS
H	5875.00	46.37	7.59	53.96	105.23	-51.27	PK	PASS
H	5925.00	46.38	7.68	54.06	68.23	-14.17	PK	PASS
V	5850.00	49.67	7.55	57.22	122.23	-65.01	PK	PASS
V	5855.00	50.83	7.56	58.39	110.83	-52.45	PK	PASS
V	5875.00	48.01	7.59	55.60	105.23	-49.63	PK	PASS
V	5925.00	44.12	7.68	51.80	68.23	-16.44	PK	PASS
H	5850.00	36.32	7.55	43.87	54.00	-10.14	AV	PASS
H	5855.00	32.55	7.56	40.11	54.00	-13.89	AV	PASS
H	5875.00	30.66	7.59	38.25	54.00	-15.75	AV	PASS
H	5925.00	28.63	7.68	36.31	54.00	-17.69	AV	PASS
V	5850.00	36.73	7.55	44.28	54.00	-9.73	AV	PASS
V	5855.00	34.51	7.56	42.07	54.00	-11.93	AV	PASS
V	5875.00	33.09	7.59	40.68	54.00	-13.33	AV	PASS
V	5925.00	30.63	7.68	38.31	54.00	-15.70	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

6.7 Undesirable emission limits (below 1GHz)

6.7.1 Test Specification


Test Requirement:	47 CFR Part 15.407(b)(9)																								
Test Limit:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209.																								
	Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:																								
	<table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																						
	0.009-0.490	2400/F(kHz)	300																						
	0.490-1.705	24000/F(kHz)	30																						
	1.705-30.0	30	30																						
	30-88	100 **	3																						
	88-216	150 **	3																						
	216-960	200 **	3																						
Above 960	500	3																							
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.																									
In the emission table above, the tighter limit applies at the band edges.																									
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.																									
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 12.7.4, 12.7.5																								
Procedure:	Below 1GHz: a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for																								

	Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

6.7.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.7.3 Test Setup Diagram



6.7.4 Test Data

PASS.


Please to see the following pages.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

For test of 30MHz-1GHz, during the test, pre-scan all modes, and found the U-NII-1 / 802.11a is worse case, the report only record this mode.

Undesirable emission limits (below 1GHz) Test Data


TM1 / Polarization: Horizontal / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	150.0108	47.77	-21.74	26.03	43.50	-17.47	QP	P	
2	250.3012	51.18	-16.74	34.44	46.00	-11.56	QP	P	
3	275.1570	52.97	-16.19	36.78	46.00	-9.22	QP	P	
4	375.9385	46.89	-13.47	33.42	46.00	-12.58	QP	P	
5 *	750.1083	51.15	-6.45	44.70	46.00	-1.30	QP	P	
6	842.1296	44.76	-5.29	39.47	46.00	-6.53	QP	P	

Undesirable emission limits (below 1GHz) Test Data

TM1 / Polarization: Vertical / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	42.8997	47.40	-17.85	29.55	40.00	-10.45	QP	P	
2	58.6126	52.81	-18.34	34.47	40.00	-5.53	QP	P	
3	175.0365	53.36	-20.03	33.33	43.50	-10.17	QP	P	
4	225.3080	52.27	-17.61	34.66	46.00	-11.34	QP	P	
5	250.3010	56.90	-16.92	39.98	46.00	-6.02	QP	P	
6	552.8832	50.01	-9.24	40.77	46.00	-5.23	QP	P	

6.8 Undesirable emission limits (above 1GHz)

6.8.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)			
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.			
	For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.			
	MHz	MHz	MHz	GHz
	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
	6.31175-6.31225	123-138	2200-2300	14.47-14.5
	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
	12.57675-12.57725	322-335.4	3600-4400	(²)
	13.36-13.41			
¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.				
² Above 38.6				
The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated				


	based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 12.7.4, 12.7.6, 12.7.7																								
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor																								

	2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	--

6.8.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.8.3 Test Setup Diagram



6.8.4 Test Data

PASS.

Please to see the following pages.

For test of 1GHz-40GHz, during the test, pre-scan all modes, and found the U-NII-1 / 802.11n(HT20) & U-NII-3 / 802.11n(HT20) is worse case, the report only record this mode.

The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3206.78	47.99	0.02	48.02	68.23	-20.21	PK	PASS
V	7510.37	42.55	9.84	52.39	68.23	-15.84	PK	PASS
V	9502.73	36.35	13.15	49.50	68.23	-18.73	PK	PASS
V	10360.00	43.61	13.79	57.40	68.23	-10.83	PK	PASS
V	14007.34	36.50	17.34	53.83	68.23	-14.40	PK	PASS
V	15540.75	*	*	*	68.23	*	PK	PASS
H	3200.75	45.17	-0.87	44.30	68.23	-23.93	PK	PASS
H	7500.50	41.54	9.83	51.37	68.23	-16.86	PK	PASS
H	9501.50	35.54	13.15	48.68	68.23	-19.55	PK	PASS
H	10362.50	43.26	13.79	57.05	68.23	-11.18	PK	PASS
H	14008.46	37.59	17.34	54.93	68.23	-13.30	PK	PASS
H	15540.25	*	*	*	68.23	*	PK	PASS
V	3206.78	34.78	0.02	34.80	54.00	-19.20	AV	PASS
V	7510.37	28.76	9.84	38.60	54.00	-15.40	AV	PASS
V	9502.73	22.37	13.15	35.52	54.00	-18.48	AV	PASS
V	10360.00	32.48	13.79	46.27	54.00	-7.73	AV	PASS
V	14007.34	22.53	17.34	39.86	54.00	-14.14	AV	PASS
V	15540.75	*	*	*	54.00	*	AV	PASS
H	3200.75	33.95	-0.87	33.08	54.00	-20.92	AV	PASS
H	7500.50	28.40	9.83	38.23	54.00	-15.77	AV	PASS
H	9501.50	23.92	13.15	37.06	54.00	-16.94	AV	PASS
H	10362.50	30.16	13.79	43.95	54.00	-10.05	AV	PASS
H	14008.46	22.06	17.34	39.40	54.00	-14.60	AV	PASS
H	15540.25	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Middle: 5200 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3407.64	45.24	-0.11	45.13	68.23	-23.10	PK	PASS
V	8020.08	42.77	10.37	53.14	68.23	-15.09	PK	PASS
V	9708.73	35.09	13.20	48.29	68.23	-19.94	PK	PASS
V	10401.75	42.17	13.91	56.08	68.23	-12.15	PK	PASS
V	14318.83	35.00	17.46	52.46	68.23	-15.77	PK	PASS
V	15600.75	*	*	*	68.23	*	PK	PASS
H	3410.50	46.41	-0.10	46.32	68.23	-21.91	PK	PASS
H	8003.85	42.35	10.33	52.68	68.23	-15.55	PK	PASS
H	9709.60	37.24	13.20	50.44	68.23	-17.79	PK	PASS
H	10402.00	43.85	13.91	57.76	68.23	-10.47	PK	PASS
H	14305.86	37.39	17.44	54.83	68.23	-13.40	PK	PASS
H	15600.00	*	*	*	68.23	*	PK	PASS
V	3407.64	33.18	-0.11	33.08	54.00	-20.92	AV	PASS
V	8020.08	29.20	10.37	39.57	54.00	-14.43	AV	PASS
V	9708.73	24.73	13.20	37.93	54.00	-16.07	AV	PASS
V	10401.75	32.48	13.91	46.39	54.00	-7.61	AV	PASS
V	14318.83	22.22	17.46	39.68	54.00	-14.32	AV	PASS
V	15600.75	*	*	*	54.00	*	AV	PASS
H	3410.50	32.30	-0.10	32.20	54.00	-21.80	AV	PASS
H	8003.85	30.53	10.33	40.86	54.00	-13.14	AV	PASS
H	9709.60	24.22	13.20	37.42	54.00	-16.58	AV	PASS
H	10402.00	30.71	13.91	44.62	54.00	-9.38	AV	PASS
H	14305.86	23.44	17.44	40.88	54.00	-13.12	AV	PASS
H	15600.00	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3705.62	45.78	1.10	46.87	68.23	-21.36	PK	PASS
V	8202.84	41.28	10.86	52.14	68.23	-16.09	PK	PASS
V	9812.17	36.51	13.23	49.75	68.23	-18.48	PK	PASS
V	10482.50	44.05	13.96	58.01	68.23	-10.22	PK	PASS
V	14710.98	37.23	17.58	54.82	68.23	-13.41	PK	PASS
V	15721.50	*	*	*	68.23	*	PK	PASS
H	3717.39	47.62	1.11	48.73	68.23	-19.50	PK	PASS
H	8219.34	41.95	10.90	52.85	68.23	-15.38	PK	PASS
H	9804.94	37.86	13.23	51.09	68.23	-17.14	PK	PASS
H	10482.50	43.96	13.96	57.92	68.23	-10.31	PK	PASS
H	14709.10	37.62	17.58	55.20	68.23	-13.03	PK	PASS
H	15721.25	*	*	*	68.23	*	PK	PASS
V	3705.62	32.56	1.10	33.65	54.00	-20.35	AV	PASS
V	8202.84	30.63	10.86	41.49	54.00	-12.51	AV	PASS
V	9812.17	24.21	13.23	37.45	54.00	-16.55	AV	PASS
V	10482.50	30.94	13.96	44.90	54.00	-9.10	AV	PASS
V	14710.98	22.34	17.58	39.92	54.00	-14.08	AV	PASS
V	15721.50	*	*	*	54.00	*	AV	PASS
H	3717.39	32.15	1.11	33.25	54.00	-20.75	AV	PASS
H	8219.34	28.90	10.90	39.80	54.00	-14.20	AV	PASS
H	9804.94	22.22	13.23	35.45	54.00	-18.55	AV	PASS
H	10482.50	30.44	13.96	44.40	54.00	-9.60	AV	PASS
H	14709.10	24.13	17.58	41.71	54.00	-12.29	AV	PASS
H	15721.25	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3213.85	46.91	-0.82	46.09	68.23	-22.14	PK	PASS
V	7505.03	41.41	9.83	51.24	68.23	-16.99	PK	PASS
V	9503.92	36.92	13.15	50.08	68.23	-18.15	PK	PASS
V	11491.50	42.33	15.22	57.55	68.23	-10.68	PK	PASS
V	14006.25	36.48	17.34	53.82	68.23	-14.41	PK	PASS
V	17236.50	*	*	*	68.23	*	PK	PASS
H	3200.75	45.02	-0.87	44.15	68.23	-24.08	PK	PASS
H	7501.00	41.33	9.83	51.16	68.23	-17.07	PK	PASS
H	9500.00	35.98	13.14	49.12	68.23	-19.12	PK	PASS
H	11490.25	43.26	15.22	58.48	68.23	-9.75	PK	PASS
H	14018.26	37.38	17.36	54.74	68.23	-13.49	PK	PASS
H	17236.50	*	*	*	68.23	*	PK	PASS
V	3213.85	34.97	-0.82	34.16	54.00	-19.84	AV	PASS
V	7505.03	28.61	9.83	38.44	54.00	-15.56	AV	PASS
V	9503.92	23.08	13.15	36.23	54.00	-17.77	AV	PASS
V	11491.50	31.77	15.22	46.99	54.00	-7.01	AV	PASS
V	14006.25	24.46	17.34	41.80	54.00	-12.20	AV	PASS
V	17236.50	*	*	*	54.00	*	AV	PASS
H	3200.75	32.48	-0.87	31.61	54.00	-22.39	AV	PASS
H	7501.00	28.02	9.83	37.85	54.00	-16.15	AV	PASS
H	9500.00	24.06	13.14	37.20	54.00	-16.80	AV	PASS
H	11490.25	30.32	15.22	45.54	54.00	-8.47	AV	PASS
H	14018.26	24.40	17.36	41.75	54.00	-12.25	AV	PASS
H	17236.50	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Middle: 5785 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3411.73	47.76	-0.09	47.67	68.23	-20.56	PK	PASS
V	8017.68	41.41	10.37	51.77	68.23	-16.46	PK	PASS
V	9705.37	36.91	13.20	50.12	68.23	-18.11	PK	PASS
V	11571.25	43.74	15.31	59.05	68.23	-9.18	PK	PASS
V	14310.17	37.81	17.45	55.25	68.23	-12.98	PK	PASS
V	17355.25	*	*	*	68.23	*	PK	PASS
H	3405.88	46.48	-0.12	46.36	68.23	-21.87	PK	PASS
H	8001.51	42.40	10.32	52.72	68.23	-15.51	PK	PASS
H	9715.77	35.66	13.20	48.86	68.23	-19.37	PK	PASS
H	11570.00	42.27	15.31	57.58	68.23	-10.65	PK	PASS
H	14318.68	36.09	17.46	53.55	68.23	-14.68	PK	PASS
H	17355.75	*	*	*	68.23	*	PK	PASS
V	3411.73	32.39	-0.09	32.30	54.00	-21.70	AV	PASS
V	8017.68	30.49	10.37	40.86	54.00	-13.14	AV	PASS
V	9705.37	24.74	13.20	37.94	54.00	-16.06	AV	PASS
V	11571.25	31.82	15.31	47.13	54.00	-6.87	AV	PASS
V	14310.17	23.62	17.45	41.07	54.00	-12.93	AV	PASS
V	17355.25	*	*	*	54.00	*	AV	PASS
H	3405.88	32.12	-0.12	32.01	54.00	-21.99	AV	PASS
H	8001.51	29.12	10.32	39.45	54.00	-14.55	AV	PASS
H	9715.77	22.77	13.20	35.97	54.00	-18.03	AV	PASS
H	11570.00	32.14	15.31	47.45	54.00	-6.55	AV	PASS
H	14318.68	23.25	17.46	40.71	54.00	-13.29	AV	PASS
H	17355.75	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH High: 5825MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3715.17	45.48	1.10	46.58	68.23	-21.65	PK	PASS
V	8220.20	41.22	10.90	52.12	68.23	-16.11	PK	PASS
V	9812.09	37.48	13.23	50.71	68.23	-17.52	PK	PASS
V	11651.25	44.57	15.39	59.96	68.23	-8.27	PK	PASS
V	14708.44	36.51	17.57	54.09	68.23	-14.14	PK	PASS
V	17476.50	*	*	*	68.23	*	PK	PASS
H	3706.31	47.40	1.10	48.49	68.23	-19.74	PK	PASS
H	8202.44	42.14	10.86	53.00	68.23	-15.23	PK	PASS
H	9816.55	35.67	13.23	48.90	68.23	-19.33	PK	PASS
H	11652.50	44.82	15.39	60.21	68.23	-8.02	PK	PASS
H	14718.62	35.94	17.59	53.53	68.23	-14.70	PK	PASS
H	17476.50	*	*	*	68.23	*	PK	PASS
V	3715.17	34.59	1.10	35.69	54.00	-18.31	AV	PASS
V	8220.20	29.56	10.90	40.46	54.00	-13.54	AV	PASS
V	9812.09	22.05	13.23	35.29	54.00	-18.71	AV	PASS
V	11651.25	30.34	15.39	45.73	54.00	-8.27	AV	PASS
V	14708.44	22.05	17.57	39.62	54.00	-14.38	AV	PASS
V	17476.50	*	*	*	54.00	*	AV	PASS
H	3706.31	34.49	1.10	35.59	54.00	-18.41	AV	PASS
H	8202.44	28.05	10.86	38.91	54.00	-15.09	AV	PASS
H	9816.55	24.49	13.23	37.73	54.00	-16.27	AV	PASS
H	11652.50	30.26	15.39	45.65	54.00	-8.35	AV	PASS
H	14718.62	22.78	17.59	40.37	54.00	-13.63	AV	PASS
H	17476.50	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

ANNEX A TEST SETUP PHOTOS

Please refer to the document "8427EU120809W1-ANNEX A.PDF"

ANNEX B EXTERNAL PHOTOS

Please refer to the document "8427EU120809W1-ANNEX B.PDF"

ANNEX C INTERNAL PHOTOS

Please refer to the document "8427EU120809W1-ANNEX C.PDF"



ANNEX D TEST DATA

1. Duty Cycle

1.1 Test Result

1.1.1 Ant1


Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	/	/	0.149	0.196	76.02	1.19	0.59
		5200	/	/	0.148	0.196	75.51	1.22	0.59
		5240	/	/	0.149	0.195	76.41	1.17	0.04
		5745	/	/	0.148	0.195	75.90	1.20	0.35
		5785	/	/	0.148	0.195	75.90	1.20	0.53
		5825	/	/	0.149	0.196	76.02	1.19	0.45
802.11n (HT20)	SISO	5180	/	/	0.176	0.224	78.57	1.05	0.50
		5200	/	/	0.177	0.224	79.02	1.02	0.45
		5240	/	/	0.176	0.223	78.92	1.03	0.17
		5745	/	/	0.179	0.224	79.91	0.97	0.43
		5785	/	/	0.176	0.224	78.57	1.05	0.49
		5825	/	/	0.177	0.224	79.02	1.02	0.52
802.11n (HT40)	SISO	5190	/	/	0.181	0.228	79.39	1.00	0.07
		5230	/	/	0.181	0.228	79.39	1.00	0.41
		5755	/	/	0.181	0.228	79.39	1.00	0.44
		5795	/	/	0.181	0.228	79.39	1.00	0.35
802.11ac (VHT20)	SISO	5180	/	/	0.164	0.212	77.36	1.11	0.61
		5200	/	/	0.165	0.212	77.83	1.09	0.62
		5240	/	/	0.165	0.213	77.46	1.11	0.52
		5745	/	/	0.165	0.211	78.20	1.07	0.24
		5785	/	/	0.165	0.211	78.20	1.07	0.06
		5825	/	/	0.165	0.212	77.83	1.09	0.56
802.11ac (VHT40)	SISO	5190	/	/	0.157	0.205	76.59	1.16	0.75
		5230	/	/	0.157	0.204	76.96	1.14	0.40
		5755	/	/	0.156	0.205	76.10	1.19	0.89
		5795	/	/	0.157	0.204	76.96	1.14	0.22
802.11ax (HEW20)	SISO	5180	SU	/	0.175	0.222	78.83	1.03	0.35
		5200	SU	/	0.175	0.222	78.83	1.03	0.19
		5240	SU	/	0.177	0.223	79.37	1.00	0.55
		5745	SU	/	0.175	0.223	78.48	1.05	0.21
		5785	SU	/	0.175	0.223	78.48	1.05	0.57
		5825	SU	/	0.175	0.224	78.13	1.07	0.52

802.11ax (HEW40)	SISO	5190	SU	/	0.171	0.219	78.08	1.07	0.45
		5230	SU	/	0.171	0.219	78.08	1.07	0.31
		5755	SU	/	0.171	0.220	77.73	1.09	0.76
		5795	SU	/	0.171	0.218	78.44	1.05	0.41




1.2 Test Graph


1.2.1 Ant1




802.11a HCH 5240MHz Ant1 NTN




802.11a LCH 5745MHz Ant1 NTN




802.11a MCH 5785MHz Ant1 NTN




802.11a HCH 5825MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1 NTN




802.11n(HT20) MCH 5200MHz Ant1 NTN




802.11n(HT20) HCH_5240MHz_Ant1_NTNV




802.11n(HT20) LCH_5745MHz_Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1 NTN




802.11n(HT40) HCH 5230MHz Ant1 NTN




802.11n(HT40) LCH 5755MHz Ant1 NTN




802.11n(HT40) HCH 5795MHz Ant1 NTN




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT20) LCH 5745MHz Ant1 NTN




802.11ac(VHT20) MCH 5785MHz Ant1 NTN




802.11ac(VHT20) HCH 5825MHz Ant1 NTN




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTNV




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTNV




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN




802.11ax(HEW20) LCH 5745MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5785MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5825MHz SU / Ant1 NTN




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTN




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTN



802.11ax(HEW40) LCH 5755MHz SU / Ant1 NTNV



802.11ax(HEW40) HCH 5795MHz SU / Ant1 NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	1	17.059	/	Pass
		5200	/	/	1	17.155	/	Pass
		5240	/	/	1	17.096	/	Pass
		5745	/	/	1	17.434	/	Pass
		5785	/	/	1	17.518	/	Pass
		5825	/	/	1	17.450	/	Pass
802.11n (HT20)	SISO	5180	/	/	1	18.109	/	Pass
		5200	/	/	1	18.148	/	Pass
		5240	/	/	1	18.083	/	Pass
		5745	/	/	1	18.535	/	Pass
		5785	/	/	1	18.288	/	Pass
		5825	/	/	1	18.561	/	Pass
802.11n (HT40)	SISO	5190	/	/	1	36.437	/	Pass
		5230	/	/	1	36.223	/	Pass
		5755	/	/	1	37.045	/	Pass
		5795	/	/	1	36.752	/	Pass
802.11ac (VHT20)	SISO	5180	/	/	1	18.119	/	Pass
		5200	/	/	1	18.093	/	Pass
		5240	/	/	1	18.026	/	Pass
		5745	/	/	1	18.458	/	Pass
		5785	/	/	1	18.448	/	Pass
		5825	/	/	1	18.470	/	Pass
802.11ac (VHT40)	SISO	5190	/	/	1	36.335	/	Pass
		5230	/	/	1	36.148	/	Pass
		5755	/	/	1	37.016	/	Pass
		5795	/	/	1	36.774	/	Pass
802.11ax (HEW20)	SISO	5180	SU	/	1	19.024	/	Pass
		5200	SU	/	1	18.963	/	Pass
		5240	SU	/	1	19.015	/	Pass
		5745	SU	/	1	19.226	/	Pass
		5785	SU	/	1	19.338	/	Pass
		5825	SU	/	1	19.363	/	Pass
802.11ax (HEW40)	SISO	5190	SU	/	1	37.833	/	Pass
		5230	SU	/	1	37.625	/	Pass
		5755	SU	/	1	38.262	/	Pass
		5795	SU	/	1	38.025	/	Pass

2.1.2 26dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	1	22.884	/	Pass
		5200	/	/	1	23.726	/	Pass
		5240	/	/	1	23.140	/	Pass
802.11n (HT20)	SISO	5180	/	/	1	23.077	/	Pass
		5200	/	/	1	22.983	/	Pass
		5240	/	/	1	23.568	/	Pass
802.11n (HT40)	SISO	5190	/	/	1	43.075	/	Pass
		5230	/	/	1	43.058	/	Pass
802.11ac (VHT20)	SISO	5180	/	/	1	22.480	/	Pass
		5200	/	/	1	22.605	/	Pass
		5240	/	/	1	22.969	/	Pass
802.11ac (VHT40)	SISO	5190	/	/	1	42.828	/	Pass
		5230	/	/	1	42.296	/	Pass
802.11ax (HEW20)	SISO	5180	SU	/	1	22.327	/	Pass
		5200	SU	/	1	22.222	/	Pass
		5240	SU	/	1	22.889	/	Pass
802.11ax (HEW40)	SISO	5190	SU	/	1	43.146	/	Pass
		5230	SU	/	1	42.771	/	Pass

2.1.3 6dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5745	/	/	1	16.059	≥ 0.5	Pass
		5785	/	/	1	16.360	≥ 0.5	Pass
		5825	/	/	1	16.363	≥ 0.5	Pass
802.11n (HT20)	SISO	5745	/	/	1	17.307	≥ 0.5	Pass
		5785	/	/	1	17.279	≥ 0.5	Pass
		5825	/	/	1	17.596	≥ 0.5	Pass
802.11n (HT40)	SISO	5755	/	/	1	36.343	≥ 0.5	Pass
		5795	/	/	1	35.941	≥ 0.5	Pass
802.11ac (VHT20)	SISO	5745	/	/	1	17.582	≥ 0.5	Pass
		5785	/	/	1	17.556	≥ 0.5	Pass
		5825	/	/	1	17.581	≥ 0.5	Pass
802.11ac (VHT40)	SISO	5755	/	/	1	36.356	≥ 0.5	Pass
		5795	/	/	1	35.569	≥ 0.5	Pass
802.11ax (HEW20)	SISO	5745	SU	/	1	18.115	≥ 0.5	Pass
		5785	SU	/	1	18.409	≥ 0.5	Pass
		5825	SU	/	1	18.589	≥ 0.5	Pass
802.11ax (HEW40)	SISO	5755	SU	/	1	37.776	≥ 0.5	Pass
		5795	SU	/	1	37.727	≥ 0.5	Pass

2.2 Test Graph


2.2.1 OBW




802.11a HCH 5240MHz Ant1 NTN




802.11a LCH 5745MHz Ant1 NTN




802.11a MCH 5785MHz Ant1 NTN




802.11a HCH 5825MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1_NTNV




802.11n(HT20) MCH 5200MHz Ant1_NTNV




802.11n(HT20) HCH 5240MHz Ant1_NTNV




802.11n(HT20) LCH 5745MHz Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1_NTNV




802.11n(HT40) HCH 5230MHz Ant1_NTNV




802.11n(HT40) LCH 5755MHz Ant1 NTNV




802.11n(HT40) HCH 5795MHz Ant1 NTNV




802.11ac(VHT20) LCH 5180MHz Ant1 NTN




802.11ac(VHT20) MCH 5200MHz Ant1 NTN




802.11ac(VHT20) HCH 5240MHz Ant1_NTNV




802.11ac(VHT20) LCH 5745MHz Ant1_NTNV




802.11ac(VHT20) MCH 5785MHz Ant1 NTN




802.11ac(VHT20) HCH 5825MHz Ant1 NTN




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT40) LCH 5755MHz Ant1 NTN




802.11ac(VHT40) HCH 5795MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTVN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTVN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTVN




802.11ax(HEW20) LCH 5745MHz SU / Ant1 NTVN




802.11ax(HEW20) MCH 5785MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5825MHz SU / Ant1 NTN




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTVN




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTVN




802.11ax(HEW40) LCH 5755MHz SU / Ant1 NTN




802.11ax(HEW40) HCH 5795MHz SU / Ant1 NTN




2.2.2 26dB BW




802.11a HCH 5240MHz Ant1 NTNV




802.11n(HT20) LCH 5180MHz Ant1 NTNV




802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1_NTNV




802.11n(HT40) HCH 5230MHz Ant1_NTNV




802.11ac(VHT20) LCH 5180MHz Ant1 NTN




802.11ac(VHT20) MCH 5200MHz Ant1 NTN




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTVN




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTVN



2.2.3 6dB BW



802.11a HCH 5825MHz Ant1_NTNV



802.11n(HT20) LCH 5745MHz Ant1_NTNV

