FCC TEST REPORT

FCC ID: 2BPRV-Q8

On Behalf of

Shenzhen Gaodi Technology Co., Ltd.

Wireless Microphone

Model No.:Q8

Prepared for	:	Shenzhen Gaodi Technology Co., Ltd.
Address	:	Room 308-37, 3rd Floor, Building C, Shenfang Building, Huahang Community, Huaqiangbei Subdistrict, Futian District, Shenzhen City

Prepared By	:	Shenzhen PSI Testing Co., Ltd.
Address	:	1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number	:	psi2505183-C01-R03
Date of Receipt	:	May 22, 2025
Date of Test	:	May 22, 2025-June 3, 2025
Date of Report	:	June 3, 2025
Version Number	:	V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results	**6**
1.1. Description of Standards and Results	6
2. General Information	**7**
2.1. Description of Device (EUT)	7
2.2. Model list	8
2.3. Accessories of Device (EUT)	8
2.4. Tested Supporting System Details	8
2.5. Block Diagram of connection between EUT and simulators	8
2.6. Test Mode Description	9
2.7. Software test version and power setting information	9
2.8. Test Conditions	10
2.9. Test Facility	10
2.10. Measurement Uncertainty	10
2.11. Test Equipment List	11
3. Maximum Peak Output Power	**12**
3.1. Limit	12
3.2. Test Procedure	12
3.3. Test Setup	12
3.4. Test Result	12
4. Bandwidth	**13**
4.1. Limit	13
4.2. Test Procedure	13
4.3. Test Result	13
5. Carrier Frequency Separation	**25**
5.1. Limit	25
5.2. Test Procedure	25
5.3. Test Result	25
6. Number Of Hopping Channel	**31**
6.1. Limit	31
6.2. Test Procedure	31
6.3. Test Result	31
7. Dwell Time	**37**
7.1. Test limit	37
7.2. Test Procedure	37
7.3. Test Result	37
8. Out-of-band Emissions	**47**
8.1. Test Limits	47
8.2. Test Procedure	47
8.3. Test Setup	47
8.4. Test Results	47
Band Edge(Hopping)	**55**
9. Radiated Emissions	**72**

9.1. Limit 72
9.2. Block Diagram of Test setup 75
9.3. Test Procedure 76
9.4. Test Results 76
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported. 76
10. Band Edge Test 84
10.1. Block Diagram of Test Setup 84
10.2. Test Limit 84
10.3. Test Procedure 84
10.4. Test Results 85
11. Power Line Conducted Emissions 88
11.1. Block Diagram of Test Setup 88
11.2. Limit 88
11.3. Test Procedure 88
11.4. Test Results 89
12. Frequency stability 92
12.1. Test limit 92
12.2. Test Procedure 92
12.3. Test Setup 92
12.4. Test Results 92
13. Antenna Requirements 93
13.1. Limit 93
13.2. Result 93
14. Photos of test setup 94
15. Photos of EUT 94

TEST REPORT DECLARATION

Applicant	:	Shenzhen Gaodi Technology Co., Ltd.
Address	:	Room 308-37, 3rd Floor, Building C, Shenfang Building, Huahang Community, Huaqiangbei Subdistrict, Futian District, Shenzhen City
Manufacturer	:	Shenzhen Gaodi Technology Co., Ltd.
Address	:	Room 308-37, 3rd Floor, Building C, Shenfang Building, Huahang Community, Huaqiangbei Subdistrict, Futian District, Shenzhen City
EUT Description	:	Wireless Microphone
		(A) Model No. : Q8
		(B) Trademark : /

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2013

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....…..:	Felix Pang Test Engineer	Felix Pang
Approved by (name + signature)…....:	Simple Guan Project Manager	Simple Guan
Date of issue……..:	June 3, 2025	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	June 3, 2025	Initial released Issue	Felix Pang

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1), RSS-247(5.4 b), ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215, RSS-247(5.1 a), ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1), RSS-247(5.1 b), ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1), RSS-247(5.1 d),ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1), RSS-247(5.1 d),ANSI C63.10 :2013	P
Radiated Spurious Emission	FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-Gen(8.9), RSS-247(5.5), ANSI C63.10 :2013	P
Out-of-band Emissions	FCC Part 15: 15.247(d), RSS-Gen(8.9), RSS-247(5.5), ANSI C63.10 :2013	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d), RSS-Gen(6.13), RSS-247(5.5), ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207, RSS-GEN(8.8),ANSI C63.10 :2013	P
Frequency stability	RSS-GEN(6.11)	N/A
Antenna requirement	FCC Part 15: 15.203, RSS-GEN(6.8)	P

Note:
1. P is an abbreviation for Pass.
2. F is an abbreviation for Fail.
3. N/A is an abbreviation for Not Applicable.
4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty.
5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.

2. General Information

2.1. Description of Device (EUT)

Product Name	:	Wireless Microphone
Model No.	:	Q8
Diff	:	/
Power supply	:	Input: 5 V⎓ 50 mA or DC 3.7 V powered by battery
Radio Technology	:	Bluetooth BR&EDR
Operation frequency	:	2402-2480MHz
Channel No.	:	79 channels
Channel Separation	:	1MHz
Modulation	:	GFSK, π/4-DQPSK, 8DPSK
Antenna Type	:	Chip antenna, maximum gain is 2.71dBi
PMN	:	N/A
HVIN	:	N/A
Software version	:	1T2_wireless_mic_sdk-v1.4.3_76D_TX
Hardware version/FVIN	:	XY-Q8-TX-V3.1
Note	:	Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information.

2.2. Model list

/

2.3. Accessories of Device (EUT)

Accessories 1 : N/A

Manufacturer : N/A

Model : N/A

Rating : N/A

2.4. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	AC Adapter	Xiaomi	MDY-08-EH	/
2	N/A	N/A	N/A	N/A

2.5. Block Diagram of connection between EUT and simulators

Conducted Emissions: **Adapter** → EUT

Radiation Emission: EUT

2.6. Test Mode Description

The test software used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK / Pi/4-DQPSK / 8DPSK Carrier Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK / Pi/4-DQPSK / 8DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
GFSK / Pi/4-DQPSK / 8DPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480

2.7. Software test version and power setting information

Software testing version	FCC Assist 1.0.4		
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:		
Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
GFSK, Pi/4-DQPSK, 8DPSK	CH0	2402	TX level is set as defaults value.
	CH39	2441	TX level is set as defaults value.
	CH78	2480	TX level is set as defaults value.

2.8. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.9. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission
Registration Number: 916281

2.10. Measurement Uncertainty

(95% confidence levels, k=2)

Item	**Uncertainty**
Uncertainty for Power point Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Occupied-Bandwidth	968Hz

2.11.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2024.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2024.12.18	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2024.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2024.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LAPA_01G18G-45dB	SK2022032901	/	2024.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_0118G-45	SK2020010801	/	2024.12.18	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-1111533-Fz	/	2024.12.18	1 Year
13.	RF Sensor Unit	Tachoy	TR1029-2	20220428P008	/	2024.12.18	1 Year
14.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2024.12.18	1 Year
15.	Temp. & Humid Chamber	Auchno	9606	/	/	2024.12.18	1 Year
16.	Regulated DC Power Supply	Xinouhua	ADC120V10A	202211251638	/	2024.12.18	1 Year
17.	Cable	SKET	Cable-RE-1	#02/#03	/	2024.12.18	1 Year
18.	Cable	SKET	Cable-RE-2	#01	/	2024.12.18	1 Year
19.	Cable	SKET	Cable-RE-3	#04	/	2024.12.18	1 Year
20.	Cable	SKET	Cable-CE-1	A-E-24	/	2024.12.18	1 Year
21.	6dB Attenuator	Schwarzbeck	DGA 9552N 6dB	CK4186	/	2024.12.18	1 Year
22.	Power meter	Agilent	E4419B	GB40202121	/	2024.12.18	1 Year

For Test Software Information

Item	Software Name	Manufacturer	Version
RE	EZ_EMC	Farad	PSI-3A1
CE	EZ_EMC	Farad	PSI-3A1
RF	RTS	TACHOY	V1.0.0

3. Maximum Peak Output Power

3.1. Limit

Please refer FCC part 15.247 & RSS-247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Mode	Test channel	Peak Output Power (dBm)	Peak Output Power Limit (dBm)	Result
GFSK	Lowest	-7.62	21.00	Pass
	Middle	-6.48		
	Highest	-5.40		
π/4DQPSK	Lowest	-6.68	21.00	Pass
	Middle	-5.56		
	Highest	-4.48		
8DPSK	Lowest	-6.63	21.00	Pass
	Middle	-5.46		
	Highest	-4.29		

4. Bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in RSS-GEN, FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Verdict
1-DH5	2402	Ant1	0.952	Pass
1-DH5	2441	Ant1	0.943	Pass
1-DH5	2480	Ant1	0.941	Pass
2-DH5	2402	Ant1	1.309	Pass
2-DH5	2441	Ant1	1.28	Pass
2-DH5	2480	Ant1	1.309	Pass
3-DH5	2402	Ant1	1.261	Pass
3-DH5	2441	Ant1	1.266	Pass
3-DH5	2480	Ant1	1.262	Pass

Test Graphs

-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2480MHz Ant1



Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
1-DH5	2402	Ant1	0.871
1-DH5	2441	Ant1	0.859
1-DH5	2480	Ant1	0.864
2-DH5	2402	Ant1	1.191
2-DH5	2441	Ant1	1.178
2-DH5	2480	Ant1	1.186
3-DH5	2402	Ant1	1.171
3-DH5	2441	Ant1	1.192
3-DH5	2480	Ant1	1.148

Test Graphs

OBW NVNT 1-DH5 2402MHz Ant1



OBW NVNT 1-DH5 2441MHz Ant1



OBW NVNT 1-DH5 2480MHz Ant1



OBW NVNT 2-DH5 2402MHz Ant1



OBW NVNT 2-DH5 2441MHz Ant1



OBW NVNT 2-DH5 2480MHz Ant1



OBW NVNT 3-DH5 2402MHz Ant1



OBW NVNT 3-DH5 2441MHz Ant1



OBW NVNT 3-DH5 2480MHz Ant1



5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

Please refer FCC part 15.247 & RSS-247.

5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 300kHz RBW and 300kHz VBW.

5.3. Test Result

Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
1-DH5	Ant1	2401.824	2402.82	0.996	0.635	Pass
1-DH5	Ant1	2440.818	2441.834	1.016	0.629	Pass
1-DH5	Ant1	2478.832	2479.818	0.986	0.627	Pass
2-DH5	Ant1	2401.8448	2402.8328	0.988	0.873	Pass
2-DH5	Ant1	2440.8292	2441.8276	0.9984	0.853	Pass
2-DH5	Ant1	2478.8188	2479.8068	0.988	0.873	Pass
3-DH5	Ant1	2401.8318	2403.0122	1.1804	0.841	Pass
3-DH5	Ant1	2440.8578	2442.1734	1.3156	0.844	Pass
3-DH5	Ant1	2478.8188	2480.15	1.3312	0.841	Pass

Test Graphs

CFS NVNT 1-DH5 2402MHz Ant1



CFS NVNT 1-DH5 2441MHz Ant1

CFS NVNT 1-DH5 2480MHz Ant1



CFS NVNT 2-DH5 2402MHz Ant1

CFS NVNT 2-DH5 2441MHz Ant1

CFS NVNT 2-DH5 2480MHz Ant1

CFS NVNT 3-DH5 2402MHz Ant1

CFS NVNT 3-DH5 2441MHz Ant1

CFS NVNT 3-DH5 2480MHz Ant1

6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.
Please refer FCC part 15.247 & RSS-247.

6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result

Mode	Antenna	Hopping Number	Limit	Verdict
1-DH5	Ant1	79	15	Pass
2-DH5	Ant1	79	15	Pass
3-DH5	Ant1	79	15	Pass

Test Graphs

Hopping No. NVNT 1-DH5 2402MHz Ant1

Hopping No. NVNT 1-DH5 2441MHz Ant1

Hopping No. NVNT 1-DH5 2480MHz Ant1

Hopping No. NVNT 2-DH5 2402MHz Ant1



Hopping No. NVNT 2-DH5 2441MHz Ant1



Hopping No. NVNT 2-DH5 2480MHz Ant1

Hopping No. NVNT 3-DH5 2402MHz Ant1



Hopping No. NVNT 3-DH5 2441MHz Ant1



Hopping No. NVNT 3-DH5 2480MHz Ant1



7. Dwell Time

7.1. Test limit

Please refer FCC part 15.247 & RSS-247.

Frequency hopping systems operating in the 2400MHz-2483.5MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.2.6. The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

7.2.7. Dwell Time=Pulse Time* Hops Number

7.3. Test Result

Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
1-DH1	2441	Ant1	0.382	120.712	316	31600	400	Pass
1-DH3	2441	Ant1	1.638	263.718	161	31600	400	Pass
1-DH5	2441	Ant1	2.887	291.587	101	31600	400	Pass
2-DH1	2441	Ant1	0.39	124.41	319	31600	400	Pass
2-DH3	2441	Ant1	1.643	276.024	168	31600	400	Pass
2-DH5	2441	Ant1	2.891	332.465	115	31600	400	Pass
3-DH1	2441	Ant1	0.392	125.048	319	31600	400	Pass
3-DH3	2441	Ant1	1.643	279.31	170	31600	400	Pass
3-DH5	2441	Ant1	2.891	326.683	113	31600	400	Pass

Test Graphs

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst

Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH3 2441MHz Ant1 One Burst

Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH1 2441MHz Ant1 One Burst

Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH3 2441MHz Ant1 One Burst

Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH5 2441MHz Ant1 One Burst

Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH1 2441MHz Ant1 One Burst

Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH3 2441MHz Ant1 One Burst

Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2441MHz Ant1 One Burst

Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



8. Out-of-band Emissions

8.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part 15.209(a) is not required.
Please refer section 15.247.

8.2. Test Procedure

Connect the transmitter ouput to spectrum analvzer using a low loss RF cable, and set the spectrum analvzerto RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting aremade of the in-band reference level, bandedge and out-of-band emissions.

8.3. Test Setup



8.4. Test Results

PASS.

The test results are listed in next pages.

Band Edge: Pass

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-41.87	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-42.78	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-43.18	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-45.08	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-43.23	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-43.58	-20	Pass

Test Graphs

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge(Hopping)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	Hopping	-48.34	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-45.38	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-47.99	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-49.28	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-48.71	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-49.94	-20	Pass

Test Graphs

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission

Conducted spurious emission: Pass

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-37.92	-20	Pass
NVNT	1-DH5	2441	Ant1	-39.22	-20	Pass
NVNT	1-DH5	2480	Ant1	-40.79	-20	Pass
NVNT	2-DH5	2402	Ant1	-38.95	-20	Pass
NVNT	2-DH5	2441	Ant1	-40.87	-20	Pass
NVNT	2-DH5	2480	Ant1	-45.11	-20	Pass
NVNT	3-DH5	2402	Ant1	-41.79	-20	Pass
NVNT	3-DH5	2441	Ant1	-42.7	-20	Pass
NVNT	3-DH5	2480	Ant1	-44.88	-20	Pass

Test Graphs

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref

Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission

Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission

Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref

Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission



9. Radiated Emissions

9.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

RSS-GEN Restricted frequency band

Table 7 – Restricted frequency bands[Note 1]		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5

8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 – 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 – 8500	
108 – 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSS.

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: The peak limit is 20 dB higher than the average limit

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (μV/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz Note 1	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

9.2. Block Diagram of Test setup

9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



9.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

9.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

(2) Setup EUT and simulator

(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.

(a) Change work frequency or channel of device if practicable.

(b) Change modulation type of device if practicable.

(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions

(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated

(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.

(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

9.4. Test Results

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz:					
Test Date	:	2025.5.23	Temperature	:	24.3℃
Test Engineer	:	Felix Pang	Humidity	:	56.4%
Test Mode	:	8DPSK mode			
Test Results	:	**PASS**			

Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of 8DPSK mode, High Channel 2480MHz (DC 3.7 V) was listed in this report.

Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.7312	28.85	-15.88	12.97	40.00	-27.03	QP
2	39.8541	28.60	-14.66	13.94	40.00	-26.06	QP
3 *	42.0065	29.16	-14.75	14.41	40.00	-25.59	QP
4	50.5860	28.26	-15.21	13.05	40.00	-26.95	QP
5	56.7916	28.39	-15.87	12.52	40.00	-27.48	QP
6	61.7780	28.02	-16.32	11.70	40.00	-28.30	QP

Note: 1.Level = Reading + Factor Margin = Level - Limit

Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	201.3930	39.24	-18.30	20.94	43.50	-22.56	QP
2	303.5437	32.02	-14.55	17.47	46.00	-28.53	QP
3	408.9460	37.77	-11.85	25.92	46.00	-20.08	QP
4	447.9821	37.08	-10.99	26.09	46.00	-19.91	QP
5	593.0496	32.75	-7.45	25.30	46.00	-20.70	QP
6 *	952.0937	30.45	-2.10	28.35	46.00	-17.65	QP

Note: 1.Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:					
Test Date	:	2025.5.23	Temperature	:	24.3℃
Test Engineer	:	Felix Pang	Humidity	:	56.4%
Test Mode	:	GFSK, π/4 DQPSK, 8DPSK mode			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.				

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	59.4	-13.25	46.15	74	-27.85	Peak
2	4804	V	48.08	-13.25	34.83	54	-19.17	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	57.68	-13.25	44.43	74	-29.57	Peak
6	4804	H	48.95	-13.25	35.7	54	-18.3	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4882	V	57.27	-12.98	44.29	74	-29.71	Peak
2	4882	V	47.7	-12.98	34.72	54	-19.28	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	57.63	-12.98	44.65	74	-29.35	Peak
6	4882	H	48.35	-12.98	35.37	54	-18.63	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	58.89	-12.7	46.19	74	-27.81	Peak
2	4960	V	47.07	-12.7	34.37	54	-19.63	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	57.89	-12.7	45.19	74	-28.81	Peak
6	4960	H	47.93	-12.7	35.23	54	-18.77	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.							

Test Mode : π/4 DQPSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	57.34	-13.25	44.09	74	-29.91	Peak
2	4804	V	48.13	-13.25	34.88	54	-19.12	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	58.58	-13.25	45.33	74	-28.67	Peak
6	4804	H	47.73	-13.25	34.48	54	-19.52	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : π/4 DQPSK TX Mid								
1	4882	V	58.54	-12.98	45.56	74	-28.44	Peak
2	4882	V	48.46	-12.98	35.48	54	-18.52	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	58.77	-12.98	45.79	74	-28.21	Peak
6	4882	H	47.08	-12.98	34.1	54	-19.9	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : π/4 DQPSK TX High								
1	4960	V	59.37	-12.7	46.67	74	-27.33	Peak
2	4960	V	48.74	-12.7	36.04	54	-17.96	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	59.07	-12.7	46.37	74	-27.63	Peak
6	4960	H	48.65	-12.7	35.95	54	-18.05	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.							

Test Mode : 8DPSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	58.39	-13.25	45.14	74	-28.86	Peak
2	4804	V	47.02	-13.25	33.77	54	-20.23	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	57.63	-13.25	44.38	74	-29.62	Peak
6	4804	H	48.58	-13.25	35.33	54	-18.67	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : 8DPSK TX Mid								
1	4882	V	59.64	-12.98	46.66	74	-27.34	Peak
2	4882	V	47.66	-12.98	34.68	54	-19.32	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	59.49	-12.98	46.51	74	-27.49	Peak
6	4882	H	47.2	-12.98	34.22	54	-19.78	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : 8D PSK TX High								
1	4960	V	57.41	-12.7	44.71	74	-29.29	Peak
2	4960	V	48.61	-12.7	35.91	54	-18.09	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	57.26	-12.7	44.56	74	-29.44	Peak
6	4960	H	47.87	-12.7	35.17	54	-18.83	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.							

10. Band Edge Test

10.1.Block Diagram of Test Setup



10.2.Test Limit

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Please refer section RSS-GEN&15.247.

10.3.Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

10.4.Test Results

Test Date	:	2025.5.24	Temperature	:	24.3℃
Test Engineer	:	Felix Pang	Humidity	:	56.4%
Test Results	:	**PASS**			

Frequency Range : **2310MHz~2410MHz**								
Test Mode : GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	62.61	-20.45	42.16	74	-31.84	Peak
2	2390	H	--	-20.45	--	54	-11.84	Avg
3	2400	H	62.38	-20.41	41.97	74	-32.03	Peak
4	2400	H	--	-20.41	--	54	-12.03	Avg
1	2390	V	62.54	-20.45	42.09	74	-31.91	Peak
2	2390	V	--	-20.45	--	54	-11.91	Avg
3	2400	V	62.91	-20.41	42.5	74	-31.5	Peak
4	2400	V	--	-20.41	--	54	-11.5	Avg
Frequency Range : **2450MHz~2550MHz**								
Test Mode : GFSK TX 2480MHz								
1	2483.5	H	62.77	-20.15	42.62	74	-31.38	Peak
2	2483.5	H	--	-20.15	--	54	-11.38	Avg
1	2483.5	V	62.54	-20.15	42.39	74	-31.61	Peak
2	2483.5	V	--	-20.15	--	54	-11.61	Avg

Note:
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.
Result=Reading + Correct Factor. Margin= Result-Limit.
3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

Frequency Range : **2310MHz~2410MHz**								
Test Mode : π/4 DQPSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	62.52	-20.45	42.07	74	-31.93	Peak
2	2390	H	--	-20.45	--	54	-11.93	Avg
3	2400	H	62.88	-20.41	42.47	74	-31.53	Peak
4	2400	H	--	-20.41	--	54	-11.53	Avg
1	2390	V	62.03	-20.45	41.58	74	-32.42	Peak
2	2390	V	--	-20.45	--	54	-12.42	Avg
3	2400	V	62.83	-20.41	42.42	74	-31.58	Peak
4	2400	V	--	-20.41	--	54	-11.58	Avg
Frequency Range : **2450MHz~2550MHz**								
Test Mode : π/4 DQPSK TX 2480MHz								
1	2483.5	H	62.66	-20.15	42.51	74	-31.49	Peak
2	2483.5	H	--	-20.15	--	54	-11.49	Avg
1	2483.5	V	62.06	-20.15	41.91	74	-32.09	Peak
2	2483.5	V	--	-20.15	--	54	-12.09	Avg

Note:
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.
Result=Reading + Correct Factor. Margin= Result-Limit.
3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

Frequency Range : **2310MHz~2410MHz**								
Test Mode : 8DPSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	62.5	-20.45	42.05	74	-31.95	Peak
2	2390	H	--	-20.45	--	54	-11.95	Avg
3	2400	H	62.67	-20.41	42.26	74	-31.74	Peak
4	2400	H	--	-20.41	--	54	-11.74	Avg
1	2390	V	62.01	-20.45	41.56	74	-32.44	Peak
2	2390	V	--	-20.45	--	54	-12.44	Avg
3	2400	V	62.9	-20.41	42.49	74	-31.51	Peak
4	2400	V	--	-20.41	--	54	-11.51	Avg
Frequency Range : **2450MHz~2550MHz**								
Test Mode : 8DPSK TX 2480MHz								
1	2483.5	H	62.1	-20.15	41.95	74	-32.05	Peak
2	2483.5	H	--	-20.15	--	54	-12.05	Avg
1	2483.5	V	62.83	-20.15	42.68	74	-31.32	Peak
2	2483.5	V	--	-20.15	--	54	-11.32	Avg

Note:
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.
Result=Reading + Correct Factor. Margin= Result-Limit.
3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

11. Power Line Conducted Emissions

11.1.Block Diagram of Test Setup



11.2.Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

11.3.Test Procedure

(1) The EUT was placed on a non-metallic table, 80cm above the ground plane.

(2) Setup the EUT and simulator as shown in 10.1

(3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on conducted Emission test.

(4) The bandwidth of test receiver is set at 10KHz.

(5) The frequency range from 150 KHz to 30MHz is checked.

11.4.Test Results

Test Date	:	2025.5.24	Temperature	:	24.3℃
Test Engineer	:	Felix Pang	Humidity	:	56.4%
Test Mode	:	8DPSK mode			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out. 4. All modes have been tested, and only worst data of 8DPSK mode, High Channel 2480MHz (AC 120V/ 60Hz) was listed in this report.				

Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.7035	12.40	10.04	22.44	56.00	-33.56	QP	P	
2	0.7035	0.59	10.04	10.63	46.00	-35.37	AVG	P	
3	0.8250	11.50	10.05	21.55	56.00	-34.45	QP	P	
4	0.8250	0.06	10.05	10.11	46.00	-35.89	AVG	P	
5	0.9014	13.09	10.05	23.14	56.00	-32.86	QP	P	
6	0.9014	-0.25	10.05	9.80	46.00	-36.20	AVG	P	
7	0.9735	12.06	10.06	22.12	56.00	-33.88	QP	P	
8	0.9735	-0.07	10.06	9.99	46.00	-36.01	AVG	P	
9 *	1.0859	14.64	10.06	24.70	56.00	-31.30	QP	P	
10	1.0859	0.93	10.06	10.99	46.00	-35.01	AVG	P	
11	1.2930	10.24	10.06	20.30	56.00	-35.70	QP	P	
12	1.2930	0.56	10.06	10.62	46.00	-35.38	AVG	P	

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.4920	14.03	10.02	24.05	56.13	-32.08	QP	P	
2	0.4920	2.21	10.02	12.23	46.13	-33.90	AVG	P	
3	0.7035	11.73	10.04	21.77	56.00	-34.23	QP	P	
4	0.7035	1.23	10.04	11.27	46.00	-34.73	AVG	P	
5	0.7755	13.69	10.04	23.73	56.00	-32.27	QP	P	
6	0.7755	1.73	10.04	11.77	46.00	-34.23	AVG	P	
7 *	0.8925	14.21	10.05	24.26	56.00	-31.74	QP	P	
8	0.8925	1.65	10.05	11.70	46.00	-34.30	AVG	P	
9	1.0320	13.96	10.06	24.02	56.00	-31.98	QP	P	
10	1.0320	1.76	10.06	11.82	46.00	-34.18	AVG	P	
11	1.1895	13.32	10.06	23.38	56.00	-32.62	QP	P	
12	1.1895	1.71	10.06	11.77	46.00	-34.23	AVG	P	

Note: Level = Reading + Factor Margin = Level - Limit

12. Frequency stability

12.1. Test limit

Please refer section RSS-Gen.

Regulation RSS-Gen If the frequency stability of the licence-exempt radio apparatus is not specified in the applicable RSS, the fundamental emissions of the radio apparatus should be kept within at least the central 80% of its permitted operating frequency band in order to minimize the possibility of out-of-band operation. In addition, its occupied bandwidth shall be entirely outside the restricted bands and the prohibited TV bands of 54-72 MHz, 76-88 MHz, 174-216 MHz, and 470-602 MHz, unless otherwise indicated.

12.2. Test Procedure

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.3. Test Setup



Temperature controller

12.4. Test Results

Not Applicable.

13. Antenna Requirements

13.1.Limit

For intentional device, according to FCC 47 CFR Section 15.203 and RSS-GEN, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2.Result

The EUT antenna is Chip antenna. It complies with the standard requirement.

14. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

15. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

------ END OF REPORT------