

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
BLE	2402MHz	5.09	3.23	3.32	0.00138	1.0	PASS
WIFI 2.4G	2437MHz	14.41	27.61	3.32	0.01181	1.0	
LTE BAND 5	824-849 MHz	20.68	116.9499	6.01	0.0928	0.55	
LTE BAND 7	2500-2570 MHz	22.54	179.4734	2.75	0.0673	1.0	
LTE BAND 12	699.7-715.3 MHz	24.29	268.5344	2.03	0.0853	0.46	
GSM850	824-849MHz	28.33	1156.1122	6.01	0.5404	0.55	
GSM1900	1850-1910MHz	27.21	893.3055	4.52	0.2963	1.0	

The Simultaneous Transmission:

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$$

BLE + 2.4G WIFI +4G/2G=(0.00138/1)+(0.01181/1)+(0.5401/0.55) =0.00135+0.01181+0.9825 =0.99566<1

The max power density is less than MPE exempt limit, so it is compliance.