

TEST REPORT

Applicant: Silk Road Hong Kong Ecommerce Limited

Address of Applicant: RM 1552,15F, AMIATA INDUSTRIAL BUILDING, 58 LEI MUK ROAD, KWAI CHUNG, HONG KONG, China

Manufacturer/Factory: Shen Zhen Wisezec Intelligent Technology Co., Ltd

Address of Manufacturer/Factory: 401-1, A6 Building, Fangxing Technology Park A, No. 13th Baonan Road, Longgang Community, Longgang Street, Shenzhen, China

Equipment Under Test (EUT)

Product Name: Smart bird feeder

Model No.: TTBF002CP, TTBF001CP01, TTBF001CP02

Trade Mark: TITTO

FCC ID: 2BPV4-TTBF002CP

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: May 27, 2025

Date of Test: May 28, 2025-June 19, 2025

Date of report issued: June 19, 2025

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	June 19, 2025	Original

Prepared By:




Date:

June 19, 2025

Project Engineer

Check By:



Date:

June 19, 2025

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	5
5 GENERAL INFORMATION	6
5.1 GENERAL DESCRIPTION OF EUT	6
5.2 TEST MODE	8
5.3 DESCRIPTION OF SUPPORT UNITS	8
5.4 DEVIATION FROM STANDARDS.....	8
5.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	8
5.6 TEST FACILITY	8
5.7 TEST LOCATION	8
5.8 ADDITIONAL INSTRUCTIONS.....	8
6 TEST INSTRUMENTS LIST	9
7 TEST RESULTS AND MEASUREMENT DATA	11
7.1 ANTENNA REQUIREMENT.....	11
7.2 CONDUCTED EMISSIONS	12
7.3 CONDUCTED OUTPUT POWER	17
7.4 CHANNEL BANDWIDTH.....	18
7.5 POWER SPECTRAL DENSITY	19
7.6 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS.....	20
7.6.1 Conducted Emission Method	20
7.6.2 Radiated Emission Method	21
8 TEST SETUP PHOTO	32
9 EUT CONSTRUCTIONAL DETAILS.....	32
10 APPENDIX FOR BLE	33
10.1 DTS BANDWIDTH	33
10.1.1 Test Result.....	33
10.1.2 Test Graphs.....	33
10.2 OCCUPIED CHANNEL BANDWIDTH	34
10.2.1 Test Result.....	34
10.2.2 Test Graphs.....	34
10.3 MAXIMUM CONDUCTED OUTPUT POWER.....	35
10.3.1 Test Result.....	35
10.3.2 Test Graphs.....	35
10.4 MAXIMUM POWER SPECTRAL DENSITY	36
10.4.1 Test Result.....	36
10.4.2 Test Graphs.....	36
10.5 BAND EDGE MEASUREMENTS	37
10.5.1 Test Result.....	37
10.5.2 Test Graphs.....	37
10.6 CONDUCTED SPURIOUS EMISSION	38
10.6.1 Test Result.....	38

10.6.2	Test Graphs.....	38
10.7	DUTY CYCLE.....	40
10.7.1	Test Result.....	40
10.7.2	Test Graphs.....	40

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. N/A: not applicable
3. Test according to ANSI C63.10:2013

Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	Smart bird feeder
Model No.:	TTBF002CP, TTBF001CP01, TTBF001CP02
Test Model No.:	TTBF002CP, TTBF001CP02
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance design, appearance color and model name for commercial purpose.	
Test sample(s) ID:	GTS2025050411-1
Sample(s) Status:	Engineer sample
S/N:	N/A
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Data Rate:	LE 1M PHY: 1Mbps
Antenna Type:	PCB Antenna
Antenna Gain:	0.5dBi(Declared by applicant)
Power Supply:	DC 3.7V (Powered by Rechargeable Li-ion Battery) DC 5.0V (Powered by solar energy) The battery is charged via USB DC5V

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
HUAWEI	Mobile Phone	MATE 30	N/A
APPLE	USB Charger	A1399	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. ● ISED—Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).
--

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test software provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 11, 2025	Apr. 10, 2026
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 12, 2025	Apr. 11, 2026
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 12, 2025	Apr. 11, 2026
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul. 02, 2024	Jul. 01, 2025
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.16, 2024	Nov.15, 2025
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2025	Apr. 10, 2026
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2025	Apr. 10, 2026
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2025	Apr. 10, 2026
11	FSV-Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 11, 2025	Mar. 10, 2026
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2025	Apr. 10, 2026
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 13, 2024	Nov. 12, 2025
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2025	Apr. 10, 2026
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 15, 2025	Apr. 14, 2026
16	RE cable 1	GTS	N/A	GTS675	Jul. 02, 2024	Jul. 01, 2025
17	RE cable 2	GTS	N/A	GTS676	Jul. 02, 2024	Jul. 01, 2025
18	RE cable 3	GTS	N/A	GTS677	Jul. 02, 2024	Jul. 01, 2025
19	RE cable 4	GTS	N/A	GTS678	Jul. 02, 2024	Jul. 01, 2025
20	RE cable 5	GTS	N/A	GTS679	Jul. 02, 2024	Jul. 01, 2025
21	RE cable 6	GTS	N/A	GTS680	Jul. 02, 2024	Jul. 01, 2025
22	RE cable 7	GTS	N/A	GTS681	Jul. 05, 2024	Jul. 04, 2025
23	RE cable 8	GTS	N/A	GTS682	Jul. 05, 2024	Jul. 04, 2025
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	Jul. 12, 2022	Jul. 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	Apr. 11, 2025	Apr. 10, 2026
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	Thermo meter	JINCHUANG	GSP-8A	GTS642	Apr. 15, 2025	Apr. 14, 2026
6	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	Apr. 12, 2025	Apr. 11, 2026
7	ISN	SCHWARZBECK	NTFM 8158	GTS565	Apr. 11, 2025	Apr. 10, 2026
8	High voltage probe	SCHWARZBECK	TK9420	GTS537	Apr. 11, 2025	Apr. 10, 2026
9	Antenna end assembly	Weinschel	1870A	GTS560	Apr. 11, 2025	Apr. 10, 2026
10	EMI Test Software	AUDIX	E3-6.100622	GTS726	N/A	N/A
11	Current probe	CYBERTEK	EM5011	GTS698	Jan. 13, 2025	Jan. 12, 2026

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 11, 2025	Apr. 10, 2026
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 11, 2025	Apr. 10, 2026
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 11, 2025	Apr. 10, 2026
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Power Meter	Keysight	N1924A	GTS673	Apr. 11, 2025	Apr. 10, 2026
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 11, 2025	Apr. 10, 2026
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 11, 2025	Apr. 10, 2026
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 11, 2025	Apr. 10, 2026
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 15, 2025	Apr. 14, 2026
11	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 02, 2024	Nov. 01, 2025


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Aug. 17, 2024	Aug. 16, 2025

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna: The antenna is PCB antenna, reference to the appendix II for details	

7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data

Pre-scan all test modes, found worst case at 2480MHz, and so only show the test result of 2480MHz,


Model No.: TTBF002CP

Line:



Freq	Reading	LISN/ISN	Cable	Level	Limit	Over	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.16	19.76	9.94	0.01	39.71	65.34	-25.63	QP
0.16	7.69	9.94	0.01	27.64	55.34	-27.70	Average
0.33	13.25	9.63	0.01	32.89	59.53	-26.64	QP
0.33	-1.25	9.63	0.01	18.39	49.53	-31.14	Average
0.48	10.10	9.83	0.01	29.94	56.32	-26.38	QP
0.48	-3.41	9.83	0.01	16.43	46.32	-29.89	Average
0.73	8.69	9.76	0.02	28.47	56.00	-27.53	QP
0.73	1.53	9.76	0.02	21.31	46.00	-24.69	Average
2.92	9.29	9.51	0.05	28.85	56.00	-27.15	QP
2.92	1.37	9.51	0.05	20.93	46.00	-25.07	Average
6.42	10.35	9.73	0.08	30.16	60.00	-29.84	QP
6.42	2.35	9.73	0.08	22.16	50.00	-27.84	Average


Neutral:



Freq	Reading	LISN/ISN	Cable	Level	Limit	Over	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.16	19.44	9.90	0.01	39.35	65.56	-26.21	QP
0.16	5.84	9.90	0.01	25.75	55.56	-29.81	Average
0.47	9.69	9.73	0.01	29.43	56.49	-27.06	QP
0.47	-7.05	9.73	0.01	12.69	46.49	-33.80	Average
0.72	10.47	9.87	0.02	30.36	56.00	-25.64	QP
0.72	2.11	9.87	0.02	22.00	46.00	-24.00	Average
2.98	8.07	9.81	0.05	27.93	56.00	-28.07	QP
2.98	0.25	9.81	0.05	20.11	46.00	-25.89	Average
5.30	7.93	9.74	0.07	27.74	60.00	-32.26	QP
5.30	0.19	9.74	0.07	20.00	50.00	-30.00	Average
12.25	7.37	9.82	0.14	27.33	60.00	-32.67	QP
12.25	-0.31	9.82	0.14	19.65	50.00	-30.35	Average


Model No.: TTBF001CP02

Line:



Freq	Reading	LISN/ISN	Cable	Level	Limit	Over	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.16	20.18	9.94	0.01	40.13	65.34	-25.21	QP
0.16	8.24	9.94	0.01	28.19	55.34	-27.15	Average
0.33	13.24	9.63	0.01	32.88	59.57	-26.69	QP
0.33	0.27	9.63	0.01	19.91	49.57	-29.66	Average
0.75	8.29	9.76	0.02	28.07	56.00	-27.93	QP
0.75	-3.26	9.76	0.02	16.52	46.00	-29.48	Average
2.07	6.06	9.81	0.04	25.91	56.00	-30.09	QP
2.07	-2.35	9.81	0.04	17.50	46.00	-28.50	Average
6.15	9.50	9.74	0.08	29.32	60.00	-30.68	QP
6.15	1.32	9.74	0.08	21.14	50.00	-28.86	Average
12.38	7.63	9.70	0.14	27.47	60.00	-32.53	QP
12.38	0.37	9.70	0.14	20.21	50.00	-29.79	Average

Neutral:




Freq	Reading	LISN/ISN	Cable	Level	Limit	Over	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.16	19.58	9.90	0.01	39.49	65.56	-26.07	QP
0.16	5.64	9.90	0.01	25.55	55.56	-30.01	Average
0.55	11.27	9.81	0.02	31.10	56.00	-24.90	QP
0.55	-6.28	9.81	0.02	13.55	46.00	-32.45	Average
0.88	6.22	9.84	0.03	26.09	56.00	-29.91	QP
0.88	-3.22	9.84	0.03	16.65	46.00	-29.35	Average
2.85	7.69	9.75	0.05	27.49	56.00	-28.51	QP
2.85	-0.21	9.75	0.05	19.59	46.00	-26.41	Average
6.09	8.81	9.70	0.08	28.59	60.00	-31.41	QP
6.09	0.63	9.70	0.08	20.41	50.00	-29.59	Average
10.34	8.63	9.59	0.11	28.33	60.00	-31.67	QP
10.34	1.01	9.59	0.11	20.71	50.00	-29.29	Average

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a green trace on its screen, is connected to an E.U.T (Equipment Under Test) by a red cable. Both the Spectrum Analyzer and the E.U.T are positioned on a table labeled 'Non-Conducted Table'. This table is supported by a 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for BLE.

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	>500KHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green signal trace, is connected to an E.U.T (Equipment Under Test) by a red cable. Both the Spectrum Analyzer and the E.U.T are positioned on a 'Non-Conducted Table'. This table is supported by a 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BLE.


7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	8dBm/3kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green curve, is connected to an E.U.T (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T are positioned on a brown rectangular table labeled 'Non-Conducted Table'. This table is supported by two vertical legs and sits on a grey horizontal bar labeled 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BLE.


7.6 Spurious Emission in Non-restricted & restricted Bands

7.6.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BLE.


7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Note: For Duty cycle ≥ 98%, average detector set as above For Duty cycle < 98%, average detector set as below: VBW ≥ 1 / T					
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP/PK/AV	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:

Refer to section 6.0 for details

Test mode:

Refer to section 5.2 for details

Test environment:

Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
--------	-------	---------	-----	---------	----------

Test voltage:	AC 120V, 60Hz
Test results:	Pass

Measurement data:*Remark:*

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ 9kHz~30MHz


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz

Pre-scan all test modes, found worst case at 2480MHz, and so only show the test result of 2480MHz,


Model No.: TTBF002CP

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
64.433	32.02	11.36	1.56	32.36	12.58	40.00	-27.42	QP
103.806	40.51	10.14	1.98	32.50	20.13	43.50	-23.37	QP
206.398	35.61	10.19	2.89	32.39	16.30	43.50	-27.20	QP
377.259	31.73	14.25	3.79	32.26	17.51	46.00	-28.49	QP
399.030	35.33	14.78	3.88	32.25	21.74	46.00	-24.26	QP
755.387	24.85	21.31	5.30	31.26	20.20	46.00	-25.80	QP


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
57.796	43.60	12.26	1.46	32.33	24.99	40.00	-15.01	QP
87.112	42.85	8.99	1.74	32.45	21.13	40.00	-18.87	QP
104.536	46.55	10.36	1.99	32.50	26.40	43.50	-17.10	QP
216.024	36.07	9.76	2.96	32.38	16.41	46.00	-29.59	QP
401.839	33.82	14.84	3.89	32.25	20.30	46.00	-25.70	QP
938.833	24.15	23.48	5.85	31.10	22.38	46.00	-23.62	QP


Model No.: TTBF001CP02

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
119.856	49.13	12.59	2.17	32.48	31.41	43.50	-12.09	QP
216.024	53.00	9.76	2.96	32.38	33.34	46.00	-12.66	QP
360.448	53.36	13.81	3.71	32.27	38.61	46.00	-7.39	QP
425.028	52.07	15.40	3.96	32.24	39.19	46.00	-6.81	QP
480.528	45.86	16.50	4.13	32.21	34.28	46.00	-11.72	QP
827.493	39.63	22.35	5.54	31.10	36.42	46.00	-9.58	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
34.882	36.91	13.07	1.18	32.30	18.86	40.00	-21.14	QP
69.600	36.23	10.84	1.64	32.38	16.33	40.00	-23.67	QP
119.856	46.03	12.59	2.17	32.48	28.31	43.50	-15.19	QP
216.024	43.94	9.76	2.96	32.38	24.28	46.00	-21.72	QP
501.179	43.77	16.82	4.20	32.20	32.59	46.00	-13.41	QP
601.427	42.65	19.03	4.64	31.83	34.49	46.00	-11.51	QP

■ Above 1GHz

■ Unwanted Emissions in Non-restricted Frequency Bands

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	36.06	32.01	6.01	38.54	35.54	74.00	-38.46	Vertical
7206.00	30.67	36.21	7.92	39.14	35.66	74.00	-38.34	Vertical
9608.00	31.00	38.20	14.87	40.22	43.85	74.00	-30.15	Vertical
4804.00	40.30	32.01	6.01	38.54	39.78	74.00	-34.22	Horizontal
7206.00	32.62	36.21	7.92	39.14	37.61	74.00	-36.39	Horizontal
9608.00	29.67	38.20	14.87	40.22	42.52	74.00	-31.48	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.68	32.01	6.01	38.54	24.16	54.00	-29.84	Vertical
7206.00	19.59	36.21	7.92	39.14	24.58	54.00	-29.42	Vertical
9608.00	19.00	38.20	14.87	40.22	31.85	54.00	-22.15	Vertical
4804.00	29.01	32.01	6.01	38.54	28.49	54.00	-25.51	Horizontal
7206.00	21.74	36.21	7.92	39.14	26.73	54.00	-27.27	Horizontal
9608.00	18.91	38.20	14.87	40.22	31.76	54.00	-22.24	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	36.28	32.10	6.03	38.52	35.89	74.00	-38.11	Vertical
7320.00	30.81	36.30	8.04	39.22	35.93	74.00	-38.07	Vertical
9760.00	31.13	38.20	11.35	40.25	40.43	74.00	-33.57	Vertical
4880.00	40.56	32.10	6.03	38.52	40.17	74.00	-33.83	Horizontal
7320.00	32.79	36.30	8.04	39.22	37.91	74.00	-36.09	Horizontal
9760.00	29.82	38.20	11.35	40.25	39.12	74.00	-34.88	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	24.86	32.10	6.03	38.52	24.47	54.00	-29.53	Vertical
7320.00	19.72	36.30	8.04	39.22	24.84	54.00	-29.16	Vertical
9760.00	19.11	38.20	11.35	40.25	28.41	54.00	-25.59	Vertical
4880.00	29.22	32.10	6.03	38.52	28.83	54.00	-25.17	Horizontal
7320.00	21.87	36.30	8.04	39.22	26.99	54.00	-27.01	Horizontal
9760.00	19.03	38.20	11.35	40.25	28.33	54.00	-25.67	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	36.38	32.20	6.05	38.51	36.12	74.00	-37.88	Vertical
7440.00	30.88	36.30	8.16	39.31	36.03	74.00	-37.97	Vertical
9920.00	31.19	38.24	10.76	40.28	39.91	74.00	-34.09	Vertical
4960.00	40.67	32.20	6.05	38.51	40.41	74.00	-33.59	Horizontal
7440.00	32.86	36.30	8.16	39.31	38.01	74.00	-35.99	Horizontal
9920.00	29.89	38.24	10.76	40.28	38.61	74.00	-35.39	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	24.97	32.20	6.05	38.51	24.71	54.00	-29.29	Vertical
7440.00	19.79	36.30	8.16	39.31	24.94	54.00	-29.06	Vertical
9920.00	19.18	38.24	10.76	40.28	27.90	54.00	-26.10	Vertical
4960.00	29.34	32.20	6.05	38.51	29.08	54.00	-24.92	Horizontal
7440.00	21.95	36.30	8.16	39.31	27.10	54.00	-26.90	Horizontal
9920.00	19.11	38.24	10.76	40.28	27.83	54.00	-26.17	Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Restricted Frequency Bands

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	46.75	27.00	4.13	39.14	38.74	74.00	-35.26	Horizontal
2390.00	47.91	27.08	4.17	39.34	39.82	74.00	-34.18	Horizontal
2310.00	46.81	27.00	4.13	39.14	38.80	74.00	-35.20	Vertical
2390.00	47.28	27.08	4.17	39.34	39.19	74.00	-34.81	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	39.23	27.00	4.13	39.14	31.22	54.00	-22.78	Horizontal
2390.00	38.99	27.08	4.17	39.34	30.90	54.00	-23.10	Horizontal
2310.00	39.18	27.00	4.13	39.14	31.17	54.00	-22.83	Vertical
2390.00	39.98	27.08	4.17	39.34	31.89	54.00	-22.11	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.48	27.27	4.08	39.56	40.27	74.00	-33.73	Horizontal
2500.00	47.04	27.30	4.06	39.60	38.80	74.00	-35.20	Horizontal
2483.50	48.51	27.27	4.08	39.56	40.30	74.00	-33.70	Vertical
2500.00	48.27	27.30	4.06	39.60	40.03	74.00	-33.97	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	39.88	27.27	4.08	39.56	31.67	54.00	-22.33	Horizontal
2500.00	39.20	27.30	4.06	39.60	30.96	54.00	-23.04	Horizontal
2483.50	39.53	27.27	4.08	39.56	31.32	54.00	-22.68	Vertical
2500.00	39.64	27.30	4.06	39.60	31.40	54.00	-22.60	Vertical

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.


10 Appendix for BLE

10.1 DTS Bandwidth

10.1.1 Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.6426	0.5	PASS
BLE_1M	Ant1	2440	0.6231	0.5	PASS
BLE_1M	Ant1	2480	0.6151	0.5	PASS

10.1.2 Test Graphs




10.2 Occupied Channel Bandwidth

10.2.1 Test Result

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0009	2401.5268	2402.5277	---	---
BLE_1M	Ant1	2440	1.0064	2439.5197	2440.5261	---	---
BLE_1M	Ant1	2480	0.99673	2479.5237	2480.5204	---	---

10.2.2 Test Graphs




10.3 Maximum conducted output power

10.3.1 Test Result

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-3.2	≤30	PASS
BLE_1M	Ant1	2440	-2.91	≤30	PASS
BLE_1M	Ant1	2480	-2.95	≤30	PASS

10.3.2 Test Graphs




10.4 Maximum power spectral density

10.4.1 Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-12.55	≤8.00	PASS
BLE_1M	Ant1	2440	-12.91	≤8.00	PASS
BLE_1M	Ant1	2480	-12.8	≤8.00	PASS

10.4.2 Test Graphs




10.5 Band edge measurements

10.5.1 Test Result

Test Mode	Antenna	Channel	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-3.87	-41.78	≤-23.87	PASS
BLE_1M	Ant1	High	2480	-3.59	-45.58	≤-23.59	PASS

10.5.2 Test Graphs





10.6 Conducted Spurious Emission

10.6.1 Test Result

Test Mode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	0~Reference	-3.91	-3.91	---	PASS
BLE_1M	Ant1	2402	30~1000	-3.91	-61.4	≤-23.91	PASS
BLE_1M	Ant1	2402	1000~26500	-3.91	-27.9	≤-23.91	PASS
BLE_1M	Ant1	2440	0~Reference	-3.68	-3.68	---	PASS
BLE_1M	Ant1	2440	30~1000	-3.68	-62.71	≤-23.68	PASS
BLE_1M	Ant1	2440	1000~26500	-3.68	-27.57	≤-23.68	PASS
BLE_1M	Ant1	2480	0~Reference	-3.61	-3.61	---	PASS
BLE_1M	Ant1	2480	30~1000	-3.61	-61.47	≤-23.61	PASS
BLE_1M	Ant1	2480	1000~26500	-3.61	-28.51	≤-23.61	PASS

10.6.2 Test Graphs






10.7 Duty Cycle

10.7.1 Test Result

Test Mode	Antenna	Frequency[MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	0.26	0.62	41.94	3.77
BLE_1M	Ant1	2440	0.25	0.62	40.32	3.94
BLE_1M	Ant1	2480	0.25	0.62	40.32	3.94

10.7.2 Test Graphs



-----End-----