

TEST REPORT

Applicant: NEXhome Smart Technologies Co., Ltd.

Address: 7th Floor, A Bldg Star-Net Plaza, No.33 Xingang Avenue, High-tech Zone, Fuzhou, Fujian, China

Product Name: Access Control

FCC ID: 2BPYV-M10K35P

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: 2602R47906E-RF-00A

Report Date: 2026/4/11

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Reviewed By: Alice Tan

Title: RF Engineer

Pedro Yun

Approved By: Pedro Yun

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL ▲	5
1.4 EQUIPMENT MODIFICATIONS	5
2. SUMMARY OF TEST RESULTS	6
3. DESCRIPTION OF TEST CONFIGURATION	7
3.1 OPERATION FREQUENCY DETAIL	7
3.2 EUT OPERATION CONDITION	7
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	7
3.4 SUPPORT CABLE LIST AND DETAILS	8
3.5 BLOCK DIAGRAM OF TEST SETUP	8
3.6 TEST FACILITY	10
3.7 MEASUREMENT UNCERTAINTY	10
4. REQUIREMENTS AND TEST PROCEDURES	11
4.1 AC LINE CONDUCTED EMISSIONS	11
4.1.1 Applicable Standard	11
4.1.2 EUT Setup	12
4.1.3 EMI Test Receiver Setup	12
4.1.4 Test Procedure	13
4.1.5 Corrected Result & Margin Calculation	13
4.1.6 Test Result	13
4.2 RADIATION SPURIOUS EMISSIONS	14
4.2.1 Applicable Standard	14
4.2.2 EUT Setup	14
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
4.2.4 Test Procedure	17
4.2.5 Corrected Result & Margin Calculation	17
4.2.6 Test Result	17
4.3 MINIMUM 6 DB BANDWIDTH	18
4.3.1 Applicable Standard	18
4.3.2 EUT Setup	18
4.3.3 Test Procedure	18
4.3.4 Test Result	18
4.4 MAXIMUM CONDUCTED OUTPUT POWER	19
4.4.1 Applicable Standard	19
4.4.2 EUT Setup	19
4.4.3 Test Procedure	19
4.4.4 Test Result	19
4.5 MAXIMUM POWER SPECTRAL DENSITY	20
4.5.1 Applicable Standard	20

4.5.2 EUT Setup.....	20
4.5.3 Test Procedure.....	20
4.5.4 Test Result.....	20
4.6 CONDUCTED SPURIOUS EMISSION	21
4.6.1 Applicable Standard	21
4.6.2 EUT Setup.....	21
4.6.3 Test Procedure.....	21
4.6.4 Test Result.....	21
4.7 DUTY CYCLE.....	22
4.7.1 EUT Setup.....	22
4.7.2 Test Procedure.....	22
4.7.3 Judgment	22
4.8 ANTENNA REQUIREMENT	23
4.8.1 Applicable Standard	23
4.8.2 Judgment	23
5. TEST DATA AND RESULTS	24
5.1 AC LINE CONDUCTED EMISSIONS	24
5.2 RADIATION SPURIOUS EMISSIONS.....	27
5.3 6dB EMISSION BANDWIDTH	42
5.4 MAXIMUM CONDUCTED OUTPUT POWER	44
5.5 POWER SPECTRAL DENSITY	46
5.6 CONDUCTED SPURIOUS EMISSION	48
5.7 DUTY CYCLE.....	52
EXHIBIT A - EUT PHOTOGRAPHS	53
EXHIBIT B - TEST SETUP PHOTOGRAPHS	54

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2602R47906E-RF-00A	Original Report	2026/4/11

1. GENERAL INFORMATION

1.1 General Description Of Equipment under Test

EUT Name:	Access Control
EUT Model:	DH-K35 Pro
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	6.16dBm
Modulation Type:	GFSK
Rated Input Voltage:	DC 12V from Adapter or DC 48V from POE
Serial Number:	For AC Line Conducted Emissions and Radiated Spurious Emission tests:3IAZ-2 For RF Conducted test:3IAZ-1
EUT Received Date:	2026/3/12
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail▲

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
FPC	50	2.4-2.5GHz	-1.2dBi
The design of compliance with §15.203:			
☒	Unit uses a permanently attached antenna.		
☐	Unit uses a unique coupling to the intentional radiator.		
☐	Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.		

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC §15.205,§15.209,§15.247(d)	Radiated Spurious Emission	Compliant
FCC §15.247(a)(2)	6dB Emission Bandwidth	Compliant
FCC §15.247(b)(3)	Maximum Conducted Output Power	Compliant
FCC §15.247(d)	Conducted Spurious Emission	Compliant
FCC §15.247(e)	Power Spectral Density	Compliant
FCC §15.203	Antenna Requirement	Compliant
Note 1: Per 15B report, powered by DC12V adapter was the worst for AC Line Conducted Emissions and Radiated Spurious Emission, so only performed it this report.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
...	...	38	2478
19	2440	39	2480

Note 1: The above frequencies in bold were performed the test.

Note 2: For AC line conducted emissions, the maximum output power mode and channel was tested.

Note 3: For Radiated Spurious Emissions 9kHz~1GHz and 18~25GHz, the maximum output power mode and channel was tested.

3.2 EUT Operation Condition


The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:	EMI_Test_Tool.exe		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
BLE 1Mbps	8.1	8.1	8.1
BLE 2Mbps	8.1	8.1	8.1

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
CWT	Adapter	2ABB018F	/
NEXhome Smart Technologies Co . , Ltd.	Test board	unknown	unknown
DELL	Laptop	E6410	GMLGPM1
TOTO Link	Router	LR1200	190924004S1
unknown	card reader	unknown	unknown

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	no	no	1.5	Adapter	Test board
8Pin Cable	no	no	0.2	Test board	EUT
RJ45 Cable	no	no	1.5	Laptop	Router
RJ45 Cable	no	no	1.5	Router	EUT
Signal Cable	no	no	1.0	Test board	card reader




Spurious Emissions:

Below 1GHz:



Above 1GHz:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.55 dB
Power Spectral Density, conducted	±0.55 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.06dB, 30MHz~1GHz: 6.13 dB, 1GHz~6GHz: 4.79 dB, 6GHz~18GHz: 4.63 dB, 18GHz~26.5GHz: 4.79 dB, 26.5GHz~40GHz: 4.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.83 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground[protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Result& Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor=attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions


4.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2.2 EUT Setup


9kHz-30MHz:




30MHz~1GHz:



1-18GHz:



18-25GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz-150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz-30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30 MHz-1000 MHz	Peak	120 kHz	500 kHz	/	PK
	QP	/	/	120 kHz	QP

1GHz- 25GHz:

Pre-scan:

Measurement	Detector	RBW	Video B/W
PK	PK	1MHz	3 MHz
Ave.	PK	1MHz	5kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was required in Quasi-peak measurement for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average measurement, peak and Average measurement for frequencies above 1 GHz.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

For Radiated 18-25GHz test, which was performed at 1.0 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.0m
Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.0m]})$ dB = 9.54 dB

4.2.5 Corrected Result & Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in μ V/m

E_{Log} is the field strength of the emission, in dB μ V/m

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10} (d_{\text{standard}}/d_{\text{measure}})$$

The basic equation except 18-25GHz test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For Radiated 18-25GHz test:

Factor = Antenna Factor + Cable Loss- Distance extrapolation Factor- Amplifier Gain

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.


4.3 Minimum 6 dB Bandwidth

4.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

4.3.2 EUT Setup



4.3.3 Test Procedure

According to ANSI C63.10-2020 Section 11.8

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

4.3.4 Test Result

Please refer to section 5.3.


4.4 Maximum Conducted Output Power

4.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.4.3 Test Procedure

According to ANSI C63.10-2020 Section 11.9.1.1

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Set span $\geq [3 \times \text{RBW}]$.
- Sweep time = No faster than coupled (auto) time.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

4.4.4 Test Result

Please refer to section 5.4.


4.5 Maximum power spectral density

4.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.5.3 Test Procedure

According to ANSI C63.10-2020 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span >1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

4.5.4 Test Result

Please refer to section 5.5.


4.6 Conducted Spurious Emission

4.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.6.3 Test Procedure

According to ANSI C63.10-2020 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

4.6.4 Test Result

Please refer to section 5.6.

4.7 Duty Cycle

4.7.1 EUT Setup



4.7.2 Test Procedure

According to ANSI C63.10-2020 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.7.3 Judgment

Report only, please refer to section 5.7.

4.8 Antenna Requirement

4.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.8.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. TEST DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	3IAZ-2	Test Date:	2026/03/23
Test Site:	CE	Test Mode:	Transmitting
Tester:	Leesin Xiang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.2	Relative Humidity: (%)	62	ATM Pressure: (kPa)	100.9
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2025/6/25	2026/6/24
Unknown	Coaxial Cable	RG 142	C-0200-05	2025/5/6	2026/5/5
R&S	EMI Test Receiver	ESCI	100224	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below plots.

Note: BLE 2Mbps High channel was tested.

Project No.: 2602R47906E-RF
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 3IAZ-2
Tester: Leesin Xiang
Note:


Date: 2026-03-23



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.150	35.22	11.20	46.42	65.99	19.57	QP
2	0.150	20.02	11.20	31.22	55.99	24.77	Average
3	0.157	34.20	11.14	45.34	65.62	20.28	QP
4	0.157	17.76	11.14	28.90	55.62	26.72	Average
5	0.171	31.90	11.04	42.94	64.93	21.99	QP
6	0.171	16.24	11.04	27.28	54.93	27.65	Average
7	0.286	26.04	10.74	36.78	60.64	23.86	QP
8	0.286	14.47	10.74	25.21	50.64	25.43	Average
9	0.369	25.95	10.70	36.65	58.52	21.87	QP
10	0.369	16.82	10.70	27.52	48.52	21.00	Average
11	4.836	21.39	10.89	32.28	56.00	23.72	QP
12	4.836	13.41	10.89	24.30	46.00	21.70	Average

Project No.: 2602R47906E-RF
 Port: neutral
 Test Mode: Transmitting
 IF B/W 9kHz PK/AV

Serial No.: 3IAZ-2
 Tester: Leesin Xiang
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.150	35.10	10.70	45.80	65.99	20.19	QP
2	0.150	20.30	10.70	31.00	55.99	24.99	Average
3	0.157	34.56	10.73	45.29	65.64	20.35	QP
4	0.157	17.89	10.73	28.62	55.64	27.02	Average
5	0.163	32.42	10.75	43.17	65.28	22.11	QP
6	0.163	16.69	10.75	27.44	55.28	27.84	Average
7	0.287	26.02	10.78	36.80	60.61	23.81	QP
8	0.287	14.04	10.78	24.82	50.61	25.79	Average
9	0.377	23.30	10.67	33.97	58.35	24.38	QP
10	0.377	13.20	10.67	23.87	48.35	24.48	Average
11	4.952	21.88	10.85	32.73	56.00	23.27	QP
12	4.952	13.95	10.85	24.80	46.00	21.20	Average

5.2 Radiation Spurious Emissions

1)9kHz - 1GHz

Serial Number:	3IAZ-2	Test Date:	2026/3/25
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Alan Xie	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	25	Relative Humidity: (%)	44	ATM Pressure: (kPa)	100.7

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-2	2024/4/16	2027/4/15
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2025/7/1	2026/6/30
Sonoma	Amplifier	310N	372193	2025/7/30	2026/7/29
R&S	EMI Test Receiver	ESCI	100035	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below plots.

Note: BLE 2Mbps High channel was tested.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Project No.: 2602R47906E-RF


Serial No.: 3IAZ-2

Polarization: Parallel

Tester: Alan Xie

Test Mode: Transmitting

Note: Peak:RBW:200Hz VBW:1kHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.017	-6.28	49.74	43.46	123.12	79.66	Peak
2	0.024	-3.21	48.01	44.80	119.99	75.19	Peak
3	0.034	-2.81	45.93	43.12	116.94	73.82	Peak
4	0.045	-0.78	44.14	43.36	114.55	71.19	Peak
5	0.067	1.40	40.64	42.04	111.11	69.07	Peak
6	0.088	2.41	36.83	39.24	108.72	69.48	Peak

Project No.: 2602R47906E-RF


Serial No.: 3IAZ-2

Polarization: Parallel

Tester: Alan Xie

Test Mode: Transmitting

Note: Peak:RBW:9kHz VBW:30kHz



30MHz-1GHz

Project No.: 2602R47906E-RF

Serial No.: 3IAZ-2


Polarization: Horizontal

Tester: Alan Xie

Test Mode: Transmitting

Note: Peak:RBW:120kHz VBW:500kHz

Date: 2026-03-25



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	31.62	39.70	-4.90	34.80	40.00	5.20	QP
2	172.27	47.67	-11.58	36.09	43.50	7.41	Peak
3	190.05	47.82	-11.91	35.91	43.50	7.59	Peak
4	249.87	54.09	-11.26	42.83	46.00	3.17	QP
5	254.72	52.51	-10.71	41.80	46.00	4.20	QP
6	267.65	48.96	-9.23	39.73	46.00	6.27	Peak

Project No.: 2602R47906E-RF

Serial No.: 3IAZ-2


Polarization: Vertical

Tester: Alan Xie

Test Mode: Transmitting

Note: Peak:RBW:120kHz VBW:500kHz

Date: 2026-03-25



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	31.62	37.70	-4.90	32.80	40.00	7.20	QP
2	59.10	47.60	-17.43	30.17	40.00	9.83	Peak
3	97.90	45.96	-14.20	31.76	43.50	11.74	Peak
4	105.98	44.22	-11.93	32.29	43.50	11.21	Peak
5	206.22	43.44	-12.14	31.30	43.50	12.20	Peak
6	249.87	47.43	-11.26	36.17	46.00	9.83	Peak

2) 1-25GHz:

Serial Number:	3IAZ-2	Test Date:	2026/3/25~2026/4/2
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Leo Xiao	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.3-25.6	Relative Humidity: (%)	46-49	ATM Pressure: (kPa)	100.3~100.7

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AH	Horn Antenna	SAS-571	1177	2026/1/22	2029/1/21
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2026/2/21	2029/2/20
HUBER+SUHNER	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26EA	2025/7/1	2026/6/30
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2025/11/14	2026/11/13
AH	Preamplifier	PAM-0118P	530	2025/6/3	2026/6/2
AH	Preamplifier	PAM-0118P	469	2025/4/11	2026/4/10
AH	Preamplifier	PAM-1840VH	191	2025/9/4	2026/9/3
R&S	Spectrum Analyzer	FSV40	101944	2025/8/8	2026/8/7
Audix	Test Software	E3	191218 V9	N/A	N/A
E-Microwave	Band Rejection Filter	OBSF-2400-2483.5-S	OE01601525	2026/2/19	2027/2/18
Micro-tronics	High Pass Filter	HPM50111	G217	2025/11/29	2026/11/28

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below plots.

1-18GHz:


BLE 1M Low Channel Horizontal				BLE 1M Low Channel Vertical			
Project No.: 2602R47906E-RF Serial No.: 3IAZ-2 Polarization: Horizontal Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Peak:RBW:1MHz,VBW:3MHz Level (dBuV/m) 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 1000 2000 3000 4000 5000 6000 Frequency (MHz) Fundamental test with Filter Switch Unit PK AV Date: 2026-03-25				Project No.: 2602R47906E-RF Serial No.: 3IAZ-2 Polarization: Vertical Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Peak:RBW:1MHz,VBW:3MHz Level (dBuV/m) 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 1000 2000 3000 4000 5000 6000 Frequency (MHz) Fundamental test with Filter Switch Unit PK AV Date: 2026-03-25			
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4804.00	54.55	-5.25	49.30	74.00	24.70	Peak

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4804.00	54.79	-5.25	49.54	74.00	24.46	Peak




Project No.: 2602R47906E-RF Serial No.: 3IAZ-2 Polarization: Horizontal Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Level (dBuV/m) 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 6000 8400 10800 13200 15600 18000 Frequency (MHz) PK AV Date: 2026-03-25				Project No.: 2602R47906E-RF Serial No.: 3IAZ-2 Polarization: Vertical Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Level (dBuV/m) 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 6000 8400 10800 13200 15600 18000 Frequency (MHz) PK AV Date: 2026-03-25			
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	7206.00	48.95	-5.32	43.63	74.00	30.37	Peak
2	17995.20	49.79	6.89	56.68	74.00	17.32	Peak
3	17995.20	39.34	6.89	46.23	54.00	7.77	Average

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	7206.00	48.61	-5.32	43.29	74.00	30.71	Peak
2	17983.20	50.14	6.82	56.96	74.00	17.04	Peak
3	17983.20	39.31	6.82	46.13	54.00	7.87	Average

BLE 1M Middle Channel Horizontal



BLE 1M Middle Channel Vertical



BLE 1M High Channel Horizontal							
Project No.: 2602R47906E-RF Polarization: Horizontal Test Mode: Transmitting Note: BLE 1M high channel 2480MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3IAZ-2 Tester: Leo Xiao			
Date: 2026-03-25							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4960.00	57.49	-4.63	52.86	74.00	21.14	Peak

BLE 1M High Channel Vertical							
Project No.: 2602R47906E-RF Polarization: Vertical Test Mode: Transmitting Note: BLE 1M high channel 2480MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3IAZ-2 Tester: Leo Xiao			
Date: 2026-03-25							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4960.00	57.43	-4.63	52.80	74.00	21.20	Peak

Project No.: 2602R47906E-RF Polarization: Horizontal Test Mode: Transmitting Note: BLE 1M high channel 2480MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3IAZ-2 Tester: Leo Xiao			
Date: 2026-03-25							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	7440.00	48.57	-4.41	44.16	74.00	29.84	Peak
2	17990.40	50.53	6.86	57.39	74.00	16.61	Peak
3	17990.40	38.81	6.86	45.67	54.00	8.33	Average


Project No.: 2602R47906E-RF Polarization: Vertical Test Mode: Transmitting Note: BLE 1M high channel 2480MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3IAZ-2 Tester: Leo Xiao			
Date: 2026-03-25							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	7440.00	48.71	-4.41	44.30	74.00	29.70	Peak
2	17992.80	50.27	6.88	57.15	74.00	16.85	Peak
3	17992.80	38.51	6.88	45.39	54.00	8.61	Average

BLE 2M Low Channel Horizontal

Project No.: 2602R47906E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BLE 2M low channel 2402MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3IAZ-2
Tester: Leo Xiao

Date: 2026-04-02




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1586.80	49.98	-7.32	42.66	74.00	31.34	Peak

BLE 2M Low Channel Vertical

Project No.: 2602R47906E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BLE 2M low channel 2402MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3IAZ-2
Tester: Leo Xiao

Date: 2026-04-02




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1597.00	52.84	-7.28	45.56	74.00	28.44	Peak

Project No.: 2602R47906E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BLE 2M low channel 2402MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3IAZ-2
Tester: Leo Xiao

Date: 2026-04-02




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4804.00	54.49	-7.50	46.99	74.00	27.01	Peak
2	7206.00	49.54	-3.61	45.93	74.00	28.07	Peak
3	17977.60	48.21	10.08	58.29	74.00	15.71	Peak
4	17977.60	36.24	10.08	46.32	54.00	7.68	Average

Project No.: 2602R47906E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BLE 2M low channel 2402MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 3IAZ-2
Tester: Leo Xiao

Date: 2026-04-02






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4804.00	53.49	-7.50	45.99	74.00	28.01	Peak
2	7206.00	49.82	-3.61	46.21	74.00	27.79	Peak
3	17988.80	48.68	10.13	58.81	74.00	15.19	Peak
4	17988.80	36.78	10.13	46.91	54.00	7.09	Average

BLE 2M Middle Channel Horizontal



BLE 2M Middle Channel Vertical




Project No.: 2602R47906E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BLE 2M high channel 2480MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3IAZ-2
Tester: Leo Xiao

Date: 2026-04-02

Fundamental test with
Filter Switch Unit




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3521.80	50.96	-4.65	46.31	74.00	27.69	Peak

Project No.: 2602R47906E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BLE 2M high channel 2480MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3IAZ-2
Tester: Leo Xiao

Date: 2026-04-02

Fundamental test with
Filter Switch Unit




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1598.20	52.86	-7.28	45.58	74.00	28.42	Peak

Project No.: 2602R47906E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BLE 2M high channel 2480MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3IAZ-2
Tester: Leo Xiao

Date: 2026-04-02




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4960.00	58.16	-7.44	50.72	74.00	23.28	Peak
2	7440.00	51.03	-2.52	48.51	74.00	25.49	Peak
3	17972.00	48.50	10.04	58.54	74.00	15.46	Peak
4	17972.00	37.24	10.04	47.28	54.00	6.72	Average

Project No.: 2602R47906E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BLE 2M high channel 2480MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3IAZ-2
Tester: Leo Xiao


Date: 2026-04-02



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4960.00	55.09	-7.44	47.65	74.00	26.35	Peak
2	7440.00	50.17	-2.52	47.65	74.00	26.35	Peak
3	17986.00	50.18	10.12	60.30	74.00	13.70	Peak
4	17986.00	37.52	10.12	47.64	54.00	6.36	Average


18-25GHz:

No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power (BLE 2M High channel).




Bandedge:


BLE 1M Low Channel Bandedge Horizontal




BLE 1M Low Channel Bandedge Vertical




BLE 1M High Channel Bandedge Horizontal




BLE 1M High Channel Bandedge Vertical




BLE 2M Low Channel Bandedge Horizontal




BLE 2M Low Channel Bandedge Vertical



BLE 2M High Channel Bandedge Horizontal



BLE 2M High Channel Bandedge Vertical



5.3 6dB Emission Bandwidth

Test Information:

Serial No.:	3IAZ-1	Test Date:	2026/03/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.9	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.6
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2025/06/06	2026/06/05
R&S	Spectrum Analyzer	FSV40	101461	2025/08/03	2026/08/02
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Channel	Result (MHz)	Limit (MHz)	Verdict
BLE 1Mbps Low	0.680	≥0.5	Pass
BLE 1Mbps Middle	0.679	≥0.5	Pass
BLE 1Mbps High	0.679	≥0.5	Pass
BLE 2Mbps Low	1.148	≥0.5	Pass
BLE 2Mbps Middle	1.148	≥0.5	Pass
BLE 2Mbps High	1.162	≥0.5	Pass

BLE_1M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:11:20

BLE_1M_Middle_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:12:10

BLE_1M_High_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:13:10

BLE_2M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:14:06

BLE_2M_Middle_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:14:57

BLE_2M_High_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:15:44

5.4 Maximum Conducted Output Power

Test Information:

Serial No.:	3IAZ-1	Test Date:	2026/03/26~2026/4/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.9~25.4	Relative Humidity: (%)	49~52	ATM Pressure: (kPa)	100.5~100.6
----------------------	-----------	---------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2025/06/06	2026/06/05
R&S	Spectrum Analyzer	FSV40	101461	2025/08/03	2026/08/02
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Channel	Peak Output Power (dBm)	Limit (dBm)	Verdict
BLE 1Mbps Low	4.58	30.00	Pass
BLE 1Mbps Middle	5.30	30.00	Pass
BLE 1Mbps High	5.95	30.00	Pass
BLE 2Mbps Low	4.56	30.00	Pass
BLE 2Mbps Middle	5.33	30.00	Pass
BLE 2Mbps High	6.16	30.00	Pass

BLE_1M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 11.APR.2026 16:04:56

BLE_1M_Middle_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 11.APR.2026 16:06:54

BLE_1M_High_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 11.APR.2026 16:10:16

BLE_2M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:05:52

BLE_2M_Middle_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:06:29

BLE_2M_High_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:07:05

5.5 Power Spectral Density

Test Information:

Serial No.:	3IAZ-1	Test Date:	2026/03/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.9	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.6
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2025/06/06	2026/06/05
R&S	Spectrum Analyzer	FSV40	101461	2025/08/03	2026/08/02
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Channel	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
BLE 1Mbps Low	-8.16	8	Pass
BLE 1Mbps Middle	-7.43	8	Pass
BLE 1Mbps High	-6.60	8	Pass
BLE 2Mbps Low	-12.42	8	Pass
BLE 2Mbps Middle	-11.72	8	Pass
BLE 2Mbps High	-10.91	8	Pass

BLE_1M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:20:44

BLE_1M_Middle_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:21:55

BLE_1M_High_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:22:52

BLE_2M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:24:00

BLE_2M_Middle_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:25:03

BLE_2M_High_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:26:36

5.6 Conducted Spurious Emission

Test Information:

Serial No.:	3IAZ-1	Test Date:	2026/03/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:







Temperature: (°C)	24.9	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.6
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2025/06/06	2026/06/05
R&S	Spectrum Analyzer	FSV40	101461	2025/08/03	2026/08/02
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:
Note: The maximum path attenuation of 30MHz-25GHz was added into the offset.




BLE_1M_High_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:31:22

BLE_1M_High_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:31:49

BLE_2M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:32:37

BLE_2M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:33:06

BLE_2M_Low_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:33:32

BLE_2M_Middle_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:34:13

BLE_2M_Middle_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:34:41

BLE_2M_High_Channel




ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:35:21

BLE_2M_High_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:35:44

BLE_2M_High_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:36:09

5.7 Duty Cycle

Test Information:

Serial No.:	3IAZ-1	Test Date:	2026/03/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	24.9	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.6
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2025/06/06	2026/06/05
R&S	Spectrum Analyzer	FSV40	101461	2025/08/03	2026/08/02
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Channel	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	1/Ton (Hz)	VBW Setting (kHz)
BLE 1Mbps Middle	0.412	2.782	14.81	2427	3
BLE 2Mbps Middle	0.204	2.562	7.96	4902	5

BLE_1M_Middle_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:01:57

BLE_2M_Middle_Channel



ProjectNo.:2602R47906E-RF Tester:Jeff Wei
Date: 26.MAR.2026 20:03:00

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2602R47906E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2602R47906E-RF-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2602R47906E-RF-00A-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******