


3.2 x 1.6 x 0.5 (mm) WiFi/Bluetooth Ceramic Chip Antenna 3216

Engineering Specification

1. Product Number

H 2 U 3 4 W G T Q W 0 1 0 0



2. Features

- *Stable and reliable in performances
- *Low profile, compact size
- *RoHS compliance
- *SMT processes compatible

3. Applications

- *ISM 2.4 GHz applications
- *ZigBee/BLE applications
- *Bluetooth earphone systems
- *Hand-held devices when WiFi / Bluetooth functions are needed, e.g., Smart phones
- *IEEE802.11 b/g/n
- *Wireless PCMCIA cards or USB dongles

UNICTRON TECHNOLOGIES CORPORATION
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification

DOCUMENT
NO.

H2U34WGTQW0100

REV.
D

PAGE 1 OF 10

4. Description


Unictron's AA055 ceramic chip antenna is designed for ISM 2.4GHz applications, covering frequencies 2400~2500MHz. Fabricated with proprietary design and processes, AA055 shows excellent performance and is fully compatible with SMT processes which can decrease the assembly cost and improve device's quality and consistency.

5. Layout Guide & Electrical Specifications

5-1. Layout Guide (unit : mm)

Solder Land Pattern:

The solder land pattern (gray marking areas) is shown below. Recommendation on matching circuit will be provided according to customer's installation conditions.



5-2. Electrical Specifications (Evaluation Board Dimensions: 80 x 40 mm²)

5-2-1. Electrical Table

Characteristics		Specifications	Unit
Outline Dimensions		3.2 x 1.6 x 0.5	mm
Ground Plane Dimensions		80 x 40	mm
Working Frequency		2400~2500	MHz
Bandwidth		100 (typical)	MHz
VSWR		2 Max. (typical)	
Characteristic Impedance		50	Ω
Polarization		Linear Polarization	
Peak Gain	(@2442 MHz)	2.5 (typical)	dBi
Efficiency		84 (typical)	%

UNICTRON TECHNOLOGIES CORPORATION
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert

**TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification**


**DOCUMENT
NO.**

H2U34WGTQW0100


**REV.
D**

5-2-2. Return Loss & VSWR

Return Loss (S_{11})




VSWR(S_{11})



6. Outline Dimensions of Antenna & Evaluation Board (unit: mm)

6-1. Antenna Dimensions



NOTE:

1. All materials are RoHS compliant.
2. "A~C" Critical Dimensions.
3. "()" Reference Dimensions.

UNICTRON TECHNOLOGIES CORPORATION
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert


TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification

DOCUMENT
NO.

H2U34WGTQW0100

REV.
D

6-2. Evaluation Board with Antenna



UNICTRON TECHNOLOGIES CORPORATON
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert

**TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification**





DOCUMENT
NO.

H2U34WGTQW0100

REV.
D

7. Radiation Pattern (with 80 x 40 mm² Evaluation Board)

7-1. 3D Gain Pattern @ 2442 MHz (unit: dBi)



UNICTRON TECHNOLOGIES CORPORATON
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : **Xenia**

Designed by : **Ken**

Checked by : **Mike**

Approved by : **Herbert**

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification

**DOCUMENT
NO.**

H2U34WGTQW0100


REV.

D

7-2. 3D Efficiency Table

Frequency (MHz)	2400	2410	2420	2430	2442	2450	2460	2470	2480	2490	2500
Efficiency (dB)	-1.4	-1.0	-0.9	-0.7	-0.7	-0.8	-0.9	-1.1	-1.2	-1.3	-1.4
Efficiency (%)	72.8	78.7	82.3	84.4	84.5	84.0	82.0	78.6	76.1	74.6	72.5
Peak Gain (dBi)	1.5	1.8	2.1	2.4	2.5	2.5	2.4	2.1	1.9	1.9	1.8

7-3. 3D Efficiency vs. Frequency



UNICTRON TECHNOLOGIES CORPORATON
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : **Xenia**

Designed by : **Ken**

Checked by : **Mike**

Approved by : **Herbert**

**TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification**

**DOCUMENT
NO.**


H2U34WGTQW0100

REV.

D


8. Frequency tuning

8-1. Chip antenna tuning scenario :



8-2. Matching circuit :

With the following recommended values of matching and tuning components, the center frequencies will be about 2442 MHz at our standard 80x40 mm² evaluation board. However, these are typical reference values which may need to be changed when circuit boards or part vendors are different.



System Matching Circuit Component			
Location	Description	Vendor	Tolerance
1	1.2pF, (0402)	DARFON	±0.1 pF
2	3.3nH, (0402)	DARFON	±0.1 nH
3	N/A	-	-
4 Fine tuning element	1.5pF, (0402)	DARFON	±0.1 pF

UNICTRON TECHNOLOGIES CORPORATON
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert


TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification

**DOCUMENT
NO.**

H2U34WGTQW0100

**REV.
D**

8-3. Reference for frequency tuning element



UNICTRON TECHNOLOGIES CORPORATON
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification

**DOCUMENT
NO.**


H2U34WGTQW0100

**REV.
D**

PAGE 8 OF 10

9. Soldering Conditions

9-1. Typical Soldering Profile for Lead-free Process



10. Reminders for users of Unictron's AA055 ceramic chip antennas

- 10-1. This chip antenna is made of ceramic materials which are relatively more rigid and brittle compared to printed circuit board materials. Bending of circuit board at the locations where chip antenna is mounted may cause the cracking of solder joints or antenna itself.
- 10-2. Punching/cutting of the break-off tab of PCB panel may cause severe bending of the circuit board which may result in cracking of solder joints or chip antenna itself. Therefore break-off tab shall be located away from the installation site of chip antenna.
- 10-3. Be cautious when ultrasonic welding process needs to be used near the locations where chip antennas are installed. Strong ultrasonic vibration may cause the cracking of chip antenna solder joints.

UNICTRON TECHNOLOGIES CORPORATION
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification

**DOCUMENT
NO.**


H2U34WGTQW0100

**REV.
D**

11. Packing

- (1) Quantity/Reel: 5000 pcs/Reel
- (2) Plastic tape:

a. Tape Drawing



b. Tape Dimensions (unit: mm)

Feature	Specifications	Tolerances
W	12.00	±0.30
P	4.00	±0.10
E	1.75	±0.10
F	5.50	±0.10
P2	2.00	±0.10
D	1.50	+0.10 -0.00
Po	4.00	±0.10
10Po	40.00	±0.20

12. Operating & Storage Conditions

12-1. Operating

- (1) Maximum Input Power: 2 W
- (2) Operating Temperature: -40°C to 85°C

12-2. Storage

- (1) Storage Temperature: -5°C to 40°C
- (2) Relative Humidity: 20% to 70%
- (3) Shelf Life: 1 year

13. Notice

- (1) Installation Guide:

Please refer to Unictron's application note "General guidelines for the installation of Unictron's chip antennas" for further information.

- (2) All specifications are subject to change without notice.

UNICTRON TECHNOLOGIES CORPORATION
Room 609, Building 3, Pingshan Private Enterprise
Science and Technology Park, No. 65, Lishan Road,
Pingshan Community, Taoyuan Subdistrict, Nanshan
District, Shenzhen City

THIS DRAWINGS AND SPECIFICATIONS ARE THE
PROPERTY OF UNICTRON TECHNOLOGIES
CORPORATION AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR
SALE OF APPARATUS OR DEVICES WITHOUT
PERMISSION

Prepared by : Xenia

Designed by : Ken

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip
Antenna (AA055) Engineering Specification

DOCUMENT
NO.

H2U34WGTQW0100

REV.
D