

PART NUMBER "A"	COUNTRY OF ORIGIN "B"
XX = CN	Made in China
XX = MY	Assembled in China with PCBA from Malaysia
XX = MX	Assembled in Mexico



SEE Tabulation column
COUNTRY OF ORIGIN "B"

PART NUMBER "A"	COUNTRY OF ORIGIN "B"
XX = MY	Assembled in China with PCBA from Malaysia

Wi-Fi

ETL
LISTED
US

CONFORMS TO
UL STD 217
Multi-Criteria
Smoke Alarm

Intertek
4002588

YYYY, MMM, DD

Smoke sensitivity : 3.10 +/- 0.89 %/ft OBS

©2025 Kidde.

Model RGSDR-RW

Photoelectric Smoke Alarm w/
Voice, Wire-Free Interconnect,
& Wi-Fi, AA battery powered.
Constant exposures to high or low
temperatures or high humidity may
reduce battery life.

Clean annually.
See User Guide for
more info.

XXXXXX

XXXXXXXXXXXXXXXXXXXX

SMOKE ALARM: 3 long beeps, repeating. NOTE: Not a CO alarm, but can transmit a
CO ALARM signal: 4 quick beeps, repeating. STANDBY: Green LED blinks every 60s.
FAULT: Amber LED blinks 1-4 times with 3 chirps every 60s. LOW BATTERY: Amber
LED blinks every 6s with 1 chirp every 60s. END OF UNIT LIFE: Amber LED blinks twice
with 2 chirps every 60s. Temp Range: 40 °F (4.4 °C) to 100 °F (37.8 °C). Humidity Range: up
to 95% relative humidity (RH), non-condensing. REPLACE BATTERIES AT LEAST ONCE A YEAR.

⚠

WARNING: USE ONLY BATTERIES SPECIFIED IN MARKING

(Energizer E91, Gold
Peak 15A, Golden Power GLR6A). USE OF A DIFFERENT BATTERY MAY HAVE A DETRIMENTAL
EFFECT ON ALARM OPERATION. NOTE: Do not use lithium batteries in this unit. Unit will not
attach to mounting bracket without batteries installed.

Contains FCC ID SAK-ESP3253 FCC ID 2BQ4X-RGSDR-RW
Kidde, 1016 Corporate Park Drive, Mebane, NC 27302 1-877-542-5471.

Assembled in China
with PCBA from Malaysia

PIN: L-000684-MY-00 RevA

QR CODE

