

CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

N Series RC

MODEL NUMBER: NRC01

REPORT NUMBER: 4791883648-3-RF-3

ISSUE DATE: September 11, 2025

FCC ID: 2BQAI-NRC01

Prepared for

**Spatial Hover Inc
10415A Westpark Dr. Houston TX 77042 Houston Texas United States**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	September 11, 2025	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2020, Clause 11.9.2.3.1	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2020, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2020, Clause 11.10.5	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2020, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2020, Clause 11.12	FCC Part 15.247 (d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2020, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>8</i>
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	<i>9</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>MAXIMUM POWER</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>10</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>10</i>
5.6. <i>WORST-CASE CONFIGURATIONS.....</i>	<i>11</i>
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>12</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST</i>	<i>13</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	14
7. ANTENNA PORT TEST RESULTS	17
7.1. <i>CONDUCTED OUTPUT POWER</i>	<i>17</i>
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i>	<i>18</i>
7.3. <i>POWER SPECTRAL DENSITY</i>	<i>20</i>
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION.....</i>	<i>22</i>
7.5. <i>DUTY CYCLE</i>	<i>24</i>
8. RADIATED TEST RESULTS.....	25
8.1. <i>RESTRICTED BANDEDGE</i>	<i>33</i>
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i>	<i>56</i>
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i>	<i>62</i>
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i>	<i>98</i>
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i>	<i>101</i>
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ).....</i>	<i>103</i>
9. ANTENNA REQUIREMENT	105
10. AC POWER LINE CONDUCTED EMISSION	106

11.	TEST DATA.....	110
11.1.	APPENDIX A: DTS BANDWIDTH.....	110
11.1.1.	Test Result.....	110
11.1.2.	Test Graphs.....	111
11.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....	123
11.2.1.	Test Result.....	123
11.2.2.	Test Graphs.....	124
11.3.	APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....	136
11.3.1.	Test Result.....	136
11.4.	APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY.....	138
11.4.1.	Test Result.....	138
11.4.2.	Test Graphs.....	139
11.5.	APPENDIX E: BAND EDGE MEASUREMENTS.....	151
11.5.1.	Test Result.....	151
11.5.2.	Test Graphs.....	152
11.6.	APPENDIX F: CONDUCTED SPURIOUS EMISSION.....	160
11.6.1.	Test Result.....	160
11.6.2.	Test Graphs.....	162
11.7.	APPENDIX G: DUTY CYCLE.....	198
11.7.1.	Test Result.....	198
11.7.2.	Test Graphs.....	199

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Spatial Hover Inc
Address: 10415A Westpark Dr. Houston TX 77042 Houston Texas United States

Manufacturer Information


Company Name: Spatial Hover Inc
Address: 10415A Westpark Dr. Houston TX 77042 Houston Texas United States

EUT Information

EUT Name: N Series RC
Model: NRC01
Sample Received Date: July 29, 2025
Sample Status: Normal
Sample ID: 8705555
Date of Tested: July 29, 2025 to September 11, 2025


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	Pass

Prepared By:



Fanny Huang
Project Engineer

Checked By:



Kebo Zhang
Operations Leader

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C , KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, CFR 47 FCC Part 2, ANSI C63.10-2020, ANSI C63.10-2020 + Cor.1-2023.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	N Series RC
Model	NRC01

Frequency Range:	2412 MHz to 2462 MHz
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11ax: OFDM(1024-QAM, 64-QAM, 16-QAM, QPSK, BPSK)
Radio Technology:	IEEE 802.11b/g/n HT20/n HT40/ax HE20/ax HE40
Normal Test Voltage:	7.2 Vdc via battery
Power Supply	DC 5V

Note: All power supply modes have been pre-scanned, only the worst data was recorded in the report.

5.2. CHANNEL LIST

Channel List For Bandwidth=20 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List For Bandwidth=40 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.3. MAXIMUM POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)
b	2412 ~ 2462	1-11[11]	24.27
g	2412 ~ 2462	1-11[11]	22.7
n HT20	2412 ~ 2462	1-11[11]	22.16
n HT40	2422 ~ 2452	3-9[7]	22.18
ax HE20	2412 ~ 2462	1-11[11]	22.29
ax HE40	2422 ~ 2452	3-9[7]	22.41

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz
ax HE20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
ax HE40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		SetUp					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	20	20	20	/		
	2	20	20	20			
802.11g	1	18.5	18.5	18.5			
	2	18.5	18.5	18.5			
802.11n HT20	1	18.5	18.5	17.5			
	2	18.5	18.5	17.5			
802.11n HT40	1	/			17	18	16
	2	/			17	18	16
802.11ax HE20	1	18.5	18.5	17.5	/		
	2	18.5	18.5	17.5			
802.11ax HE40	1	/			17.5	18.5	16.5
	2	/			17.5	18.5	16.5

5.6. WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

802.11n HT40 mode: MCS0

802.11ax HE20 mode: MCS0

802.11ax HE40 mode: MCS0

All modes support SISO and MIMO mode.

SISO mode and MIMO mode have the same power setting, so only the worst case power mode(MIMO) will be record in the report.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port.

Conducted bandedge and spurious emissions tests were performed with SISO mode, as this port was found to have the worst case in terms of power settings amongst all supported possible SISO & MIMO port combinations.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	Dipole Antenna	2.5
2	2412-2462	Dipole Antenna	2.5

The EUT support Space Time Coding(STBC) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the STBC results the Directional Gain was calculated in accordance with the following method.

$$\text{Directional gain} = 10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/NANT] \text{ dBi}$$

$$\text{Directional gain(ANT0 \& ANT1)} = 2.5 \text{ dBi}$$

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11ax HE20	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11ax HE40	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
Note: 1.WLAN 2.4G & SRD 2.4G, WLAN 5.8G & SRD 5.8G, BT & SRD 2.4G & WLAN 2.4G, BT & SRD 5.8G & WLAN 5.8G, BT & SRD 2.4G & WLAN 5.1G, WLAN 5.1G & SRD 5.8G can transmit simultaneously. (declared by client)		

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E42-80	/
2	AC Adaptor	Lenovo	ADLX65YCC3D	Input: AC 100-240V, 1.8A, 50-60Hz Output: DC 20V, 3.25A, 65.0W Max

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



Note: AC Adaptor only use for AC POWER LINE CONDUCTED EMISSION test.

6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.27,2024	Dec.26,2025
Vector Signal Generator	R&S	SMBV100A	261637	Sep.28, 2024	Sep.27, 2025
Signal Generator	R&S	SMB100A	178553	Sep.28, 2024	Sep.27, 2025
Signal Analyzer	R&S	FSV40	101118	Sep.28, 2024	Sep.27, 2025
Software					
Description	Manufacturer		Name	Version	
For R&S TS 8997 Test System	Rohde & Schwarz		EMC 32	10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.13, 2024	Sep.12, 2025
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.28, 2024	Sep.27, 2025
DC power supply	Keysight	E3642A	MY55159130	Sep.28, 2024	Sep.27, 2025
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.28, 2024	Sep.27, 2025
Attenuator	Aglient	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.27,2024	Dec.26,2025
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.28, 2024	Sep.27, 2025
Two-Line V-Network	R&S	ENV216	101983	Sep.28, 2024	Sep.27, 2025
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.28, 2024	Sep.27, 2025
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.28, 2024	Sep.27, 2025
EMI Measurement Receiver	R&S	ESR26	101377	Sep.28, 2024	Sep.27, 2025
Horn Antenna	TDK	HRN-0118	130940	Dec.10, 2024	Dec.11, 2027
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.28, 2024	Sep.27, 2025
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.28, 2024	Sep.27, 2025
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.28, 2024	Sep.27, 2025
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.8, 2024	Oct.7, 2025
Barometer	Yiyi	Baro	N/A	Oct.10, 2024	Oct.9, 2025
Attenuator	Agilent	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.1°C	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2V

TEST DATE / ENGINEER

Test Date	August 12, 2025	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 1 % to 5 % of the OBW but not less than 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP**TEST ENVIRONMENT**

Temperature	24.1℃	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2V

TEST DATE / ENGINEER

Test Date	August 12, 2025	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$> 1.5 \times \text{OBW bandwidth}$
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.1℃	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2V

TEST DATE / ENGINEER

Test Date	August 12, 2025	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.11.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	$\geq 1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

Temperature	24.1℃	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2V

TEST DATE / ENGINEER

Test Date	August 12, 2025	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.1℃	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2V

TEST DATE / ENGINEER

Test Date	August 12, 2025	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	23.5°C	Relative Humidity	60.1%
Atmosphere Pressure	101kPa	Test Voltage	


TEST DATE / ENGINEER

Test Date	September 8, 2025	Test By	Stipe Zheng
-----------	-------------------	---------	-------------

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.320	17.65	31.68	49.33	74.00	-24.67	peak
2	2390.000	15.73	31.69	47.42	74.00	-26.58	peak

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	16.87	31.69	48.56	74.00	-25.44	peak

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	15.22	31.99	47.21	74.00	-26.79	peak
2	2487.405	16.68	32.00	48.68	74.00	-25.32	peak

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.920	25.73	31.69	57.42	74.00	-16.58	peak
2	2390.000	24.95	31.69	56.64	74.00	-17.36	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.920	8.94	31.69	40.63	54.00	-13.37	AVG
2	2390.000	9.15	31.69	40.84	54.00	-13.16	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.91	31.99	52.90	74.00	-21.10	peak
2	2484.105	21.16	31.99	53.15	74.00	-20.85	peak

Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	8.43	31.99	40.42	54.00	-13.58	AVG
2	2484.105	7.16	31.99	39.15	54.00	-14.85	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.200	26.77	31.68	58.45	74.00	-15.55	peak
2	2390.000	25.17	31.69	56.86	74.00	-17.14	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.200	12.01	31.68	43.69	54.00	-10.31	AVG
2	2390.000	12.92	31.69	44.61	54.00	-9.39	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.50	31.99	52.49	74.00	-21.51	peak
2	2485.590	20.97	32.00	52.97	74.00	-21.03	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.25	31.99	41.24	54.00	-12.76	AVG
2	2485.590	7.60	32.00	39.60	54.00	-14.40	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.600	32.90	31.67	64.57	74.00	-9.43	peak
2	2390.000	29.98	31.69	61.67	74.00	-12.33	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.600	14.62	31.67	46.29	54.00	-7.71	AVG
2	2390.000	16.92	31.69	48.61	54.00	-5.39	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.11	31.99	54.10	74.00	-19.90	peak
2	2485.510	23.55	32.00	55.55	74.00	-18.45	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.75	31.99	41.74	54.00	-12.26	AVG
2	2485.510	9.35	32.00	41.35	54.00	-12.65	AVG

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.960	27.90	31.68	59.58	74.00	-14.42	peak
2	2390.000	27.40	31.69	59.09	74.00	-14.91	peak

Test Mode:	802.11ax HE20 AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.960	12.63	31.68	44.31	54.00	-9.69	AVG
2	2390.000	13.79	31.69	45.48	54.00	-8.52	AVG

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	24.02	31.99	56.01	74.00	-17.99	peak

Test Mode:	802.11ax HE20 AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	10.65	31.99	42.64	54.00	-11.36	AVG

Test Mode:	802.11ax HE40 PK	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.625	36.12	31.68	67.80	74.00	-6.20	peak
2	2390.000	31.43	31.69	63.12	74.00	-10.88	peak

Test Mode:	802.11ax HE40 AV	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.625	18.45	31.68	50.13	54.00	-3.87	AVG
2	2390.000	18.53	31.69	50.22	54.00	-3.78	AVG

Test Mode:	802.11ax HE40 PK	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.81	31.99	54.80	74.00	-19.20	peak
2	2489.080	24.80	32.00	56.80	74.00	-17.20	peak


Test Mode:	802.11ax HE40 AV	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.79	31.99	41.78	54.00	-12.22	AVG
2	2489.080	9.26	32.00	41.26	54.00	-12.74	AVG


8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1438.000	48.05	-12.22	35.83	74.00	-38.17	peak
2	1842.000	46.10	-10.12	35.98	74.00	-38.02	peak
3	2128.000	45.02	-9.76	35.26	74.00	-38.74	peak
4	2314.000	49.88	-8.99	40.89	74.00	-33.11	peak
5	2412.000	57.41	-8.57	48.84	/	/	fundamental
6	2572.000	46.20	-7.92	38.28	74.00	-35.72	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1164.000	46.60	-13.58	33.02	74.00	-40.98	peak
2	1440.000	48.24	-12.22	36.02	74.00	-37.98	peak
3	1908.000	46.59	-10.20	36.39	74.00	-37.61	peak
4	2316.000	52.21	-8.98	43.23	74.00	-30.77	peak
5	2412.000	56.22	-8.57	47.65	/	/	fundamental
6	2776.000	44.56	-7.12	37.44	74.00	-36.56	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1438.000	47.70	-12.22	35.48	74.00	-38.52	peak
2	1728.000	46.65	-10.56	36.09	74.00	-37.91	peak
3	2008.000	46.33	-10.27	36.06	74.00	-37.94	peak
4	2344.000	51.35	-8.85	42.50	74.00	-31.50	peak
5	2437.000	66.68	-8.47	58.21	/	/	fundamental
6	2808.000	44.27	-7.01	37.26	74.00	-36.74	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1438.000	48.26	-12.22	36.04	74.00	-37.96	peak
2	1714.000	46.67	-10.65	36.02	74.00	-37.98	peak
3	1956.000	45.78	-10.25	35.53	74.00	-38.47	peak
4	2342.000	51.82	-8.87	42.95	74.00	-31.05	peak
5	2437.000	58.88	-8.47	50.41	/	/	fundamental
6	2842.000	44.48	-6.86	37.62	74.00	-36.38	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1168.000	46.54	-13.56	32.98	74.00	-41.02	peak
2	1440.000	48.34	-12.22	36.12	74.00	-37.88	peak
3	1718.000	46.78	-10.64	36.14	74.00	-37.86	peak
4	2322.000	50.10	-8.96	41.14	74.00	-32.86	peak
5	2462.000	52.01	-8.35	43.66	/	/	fundamental
6	2778.000	44.13	-7.12	37.01	74.00	-36.99	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1168.000	47.33	-13.56	33.77	74.00	-40.23	peak
2	1438.000	50.29	-12.22	38.07	74.00	-35.93	peak
3	1788.000	45.99	-10.16	35.83	74.00	-38.17	peak
4	2322.000	52.45	-8.96	43.49	74.00	-30.51	peak
5	2462.000	53.34	-8.36	44.98	/	/	fundamental
6	2838.000	43.93	-6.89	37.04	74.00	-36.96	peak


8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	41.79	0.64	42.43	74.00	-31.57	peak
2	6930.000	38.07	6.27	44.34	74.00	-29.66	peak
3	9735.000	35.18	12.99	48.17	74.00	-25.83	peak
4	10485.000	34.36	14.15	48.51	74.00	-25.49	peak
5	13740.000	26.96	23.19	50.15	74.00	-23.85	peak
6	18000.000	22.40	28.54	50.94	74.00	-23.06	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4500.000	42.33	-0.33	42.00	74.00	-32.00	peak
2	6915.000	38.02	6.24	44.26	74.00	-29.74	peak
3	9135.000	34.63	10.67	45.30	74.00	-28.70	peak
4	11280.000	32.88	17.33	50.21	74.00	-23.79	peak
5	13890.000	25.76	23.64	49.40	74.00	-24.60	peak
6	17940.000	22.45	28.02	50.47	74.00	-23.53	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.10	0.75	42.85	74.00	-31.15	peak
2	6885.000	38.53	6.15	44.68	74.00	-29.32	peak
3	9375.000	33.99	11.66	45.65	74.00	-28.35	peak
4	11460.000	32.69	17.59	50.28	74.00	-23.72	peak
5	13410.000	27.90	22.48	50.38	74.00	-23.62	peak
6	17865.000	22.94	27.35	50.29	74.00	-23.71	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4635.000	41.80	0.08	41.88	74.00	-32.12	peak
2	6855.000	37.90	6.08	43.98	74.00	-30.02	peak
3	9690.000	35.53	12.88	48.41	74.00	-25.59	peak
4	12360.000	30.47	19.52	49.99	74.00	-24.01	peak
5	13530.000	27.02	22.88	49.90	74.00	-24.10	peak
6	17805.000	23.39	26.82	50.21	74.00	-23.79	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	45.05	0.86	45.91	74.00	-28.09	peak
2	6855.000	38.56	6.08	44.64	74.00	-29.36	peak
3	11250.000	32.68	17.31	49.99	74.00	-24.01	peak
4	12690.000	30.11	19.85	49.96	74.00	-24.04	peak
5	13800.000	26.99	23.27	50.26	74.00	-23.74	peak
6	17985.000	22.32	28.41	50.73	74.00	-23.27	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	41.84	0.86	42.70	74.00	-31.30	peak
2	6870.000	37.83	6.12	43.95	74.00	-30.05	peak
3	10605.000	34.72	14.56	49.28	74.00	-24.72	peak
4	12675.000	30.97	19.83	50.80	74.00	-23.20	peak
5	14175.000	26.40	23.57	49.97	74.00	-24.03	peak
6	18000.000	22.43	28.54	50.97	74.00	-23.03	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4635.000	42.35	0.08	42.43	74.00	-31.57	peak
2	6975.000	38.82	6.39	45.21	74.00	-28.79	peak
3	9735.000	35.06	12.99	48.05	74.00	-25.95	peak
4	11520.000	32.42	17.73	50.15	74.00	-23.85	peak
5	13650.000	26.85	23.06	49.91	74.00	-24.09	peak
6	18000.000	22.02	28.54	50.56	74.00	-23.44	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4515.000	42.17	-0.29	41.88	74.00	-32.12	peak
2	6840.000	38.29	6.04	44.33	74.00	-29.67	peak
3	8835.000	34.68	9.60	44.28	74.00	-29.72	peak
4	11115.000	32.21	16.88	49.09	74.00	-24.91	peak
5	13995.000	26.16	24.08	50.24	74.00	-23.76	peak
6	17925.000	22.70	27.87	50.57	74.00	-23.43	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4770.000	41.33	0.48	41.81	74.00	-32.19	peak
2	6975.000	37.93	6.39	44.32	74.00	-29.68	peak
3	9735.000	35.02	12.99	48.01	74.00	-25.99	peak
4	11265.000	32.44	17.32	49.76	74.00	-24.24	peak
5	13065.000	28.34	20.88	49.22	74.00	-24.78	peak
6	17970.000	22.30	28.27	50.57	74.00	-23.43	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	41.38	0.64	42.02	74.00	-31.98	peak
2	6945.000	38.28	6.31	44.59	74.00	-29.41	peak
3	8835.000	34.85	9.60	44.45	74.00	-29.55	peak
4	11505.000	31.90	17.70	49.60	74.00	-24.40	peak
5	14040.000	25.48	23.97	49.45	74.00	-24.55	peak
6	17910.000	22.32	27.75	50.07	74.00	-23.93	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4590.000	42.03	-0.06	41.97	74.00	-32.03	peak
2	6930.000	38.46	6.27	44.73	74.00	-29.27	peak
3	8820.000	35.17	9.56	44.73	74.00	-29.27	peak
4	10995.000	32.80	16.32	49.12	74.00	-24.88	peak
5	13590.000	27.65	22.98	50.63	74.00	-23.37	peak
6	17910.000	22.29	27.75	50.04	74.00	-23.96	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4500.000	42.56	-0.33	42.23	74.00	-31.77	peak
2	6810.000	37.80	5.97	43.77	74.00	-30.23	peak
3	8835.000	35.34	9.60	44.94	74.00	-29.06	peak
4	11055.000	33.88	16.60	50.48	74.00	-23.52	peak
5	13995.000	26.39	24.08	50.47	74.00	-23.53	peak
6	17925.000	22.90	27.87	50.77	74.00	-23.23	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.41	0.60	44.01	74.00	-29.99	peak
2	6870.000	38.34	6.12	44.46	74.00	-29.54	peak
3	9735.000	34.39	12.99	47.38	74.00	-26.62	peak
4	11235.000	31.90	17.30	49.20	74.00	-24.80	peak
5	13620.000	27.78	23.03	50.81	74.00	-23.19	peak
6	17955.000	22.17	28.14	50.31	74.00	-23.69	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	41.29	0.60	41.89	74.00	-32.11	peak
2	6975.000	37.68	6.39	44.07	74.00	-29.93	peak
3	8220.000	34.89	8.63	43.52	74.00	-30.48	peak
4	11325.000	32.61	17.38	49.99	74.00	-24.01	peak
5	12360.000	30.21	19.52	49.73	74.00	-24.27	peak
6	17820.000	23.34	26.95	50.29	74.00	-23.71	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4500.000	42.34	-0.33	42.01	74.00	-31.99	peak
2	7320.000	39.00	6.89	45.89	74.00	-28.11	peak
3	11040.000	33.11	16.53	49.64	74.00	-24.36	peak
4	12735.000	30.11	19.94	50.05	74.00	-23.95	peak
5	13935.000	26.50	23.83	50.33	74.00	-23.67	peak
6	17925.000	22.71	27.87	50.58	74.00	-23.42	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4650.000	41.85	0.12	41.97	74.00	-32.03	peak
2	7320.000	38.39	6.89	45.28	74.00	-28.72	peak
3	8190.000	36.79	8.58	45.37	74.00	-28.63	peak
4	10590.000	35.34	14.51	49.85	74.00	-24.15	peak
5	14025.000	26.83	24.02	50.85	74.00	-23.15	peak
6	17985.000	22.48	28.41	50.89	74.00	-23.11	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4785.000	41.28	0.53	41.81	74.00	-32.19	peak
2	6870.000	38.28	6.12	44.40	74.00	-29.60	peak
3	8835.000	35.33	9.60	44.93	74.00	-29.07	peak
4	11475.000	31.58	17.62	49.20	74.00	-24.80	peak
5	13620.000	27.24	23.03	50.27	74.00	-23.73	peak
6	17985.000	21.91	28.41	50.32	74.00	-23.68	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4770.000	41.79	0.48	42.27	74.00	-31.73	peak
2	6975.000	37.89	6.39	44.28	74.00	-29.72	peak
3	9405.000	34.48	11.79	46.27	74.00	-27.73	peak
4	11130.000	33.72	16.94	50.66	74.00	-23.34	peak
5	13470.000	27.97	22.72	50.69	74.00	-23.31	peak
6	17925.000	22.53	27.87	50.40	74.00	-23.60	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4695.000	41.97	0.25	42.22	74.00	-31.78	peak
2	6870.000	38.21	6.12	44.33	74.00	-29.67	peak
3	8490.000	34.97	9.01	43.98	74.00	-30.02	peak
4	11115.000	32.72	16.88	49.60	74.00	-24.40	peak
5	13470.000	27.63	22.72	50.35	74.00	-23.65	peak
6	17970.000	22.11	28.27	50.38	74.00	-23.62	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5715.000	40.76	2.41	43.17	74.00	-30.83	peak
2	6870.000	38.51	6.12	44.63	74.00	-29.37	peak
3	8835.000	35.49	9.60	45.09	74.00	-28.91	peak
4	11100.000	32.73	16.80	49.53	74.00	-24.47	peak
5	13935.000	26.66	23.83	50.49	74.00	-23.51	peak
6	17910.000	22.92	27.75	50.67	74.00	-23.33	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	42.14	0.72	42.86	74.00	-31.14	peak
2	6945.000	38.24	6.31	44.55	74.00	-29.45	peak
3	8835.000	35.02	9.60	44.62	74.00	-29.38	peak
4	11250.000	33.09	17.31	50.40	74.00	-23.60	peak
5	13635.000	27.73	23.05	50.78	74.00	-23.22	peak
6	17940.000	22.81	28.02	50.83	74.00	-23.17	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4665.000	41.58	0.16	41.74	74.00	-32.26	peak
2	6870.000	38.46	6.12	44.58	74.00	-29.42	peak
3	8820.000	35.78	9.56	45.34	74.00	-28.66	peak
4	11055.000	33.83	16.60	50.43	74.00	-23.57	peak
5	14010.000	26.20	24.07	50.27	74.00	-23.73	peak
6	17775.000	23.84	26.63	50.47	74.00	-23.53	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.000	41.34	0.68	42.02	74.00	-31.98	peak
2	6960.000	37.75	6.35	44.10	74.00	-29.90	peak
3	9375.000	33.32	11.66	44.98	74.00	-29.02	peak
4	11235.000	32.57	17.30	49.87	74.00	-24.13	peak
5	13965.000	26.10	23.96	50.06	74.00	-23.94	peak
6	17775.000	23.40	26.63	50.03	74.00	-23.97	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4785.000	41.53	0.53	42.06	74.00	-31.94	peak
2	6915.000	37.75	6.24	43.99	74.00	-30.01	peak
3	8820.000	35.02	9.56	44.58	74.00	-29.42	peak
4	11325.000	32.85	17.38	50.23	74.00	-23.77	peak
5	13905.000	26.39	23.70	50.09	74.00	-23.91	peak
6	17925.000	22.72	27.87	50.59	74.00	-23.41	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.49	0.60	44.09	74.00	-29.91	peak
2	7245.000	37.45	6.86	44.31	74.00	-29.69	peak
3	8865.000	36.31	9.68	45.99	74.00	-28.01	peak
4	11070.000	32.95	16.67	49.62	74.00	-24.38	peak
5	14070.000	26.26	23.89	50.15	74.00	-23.85	peak
6	17925.000	22.62	27.87	50.49	74.00	-23.51	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	41.24	0.60	41.84	74.00	-32.16	peak
2	6975.000	38.05	6.39	44.44	74.00	-29.56	peak
3	9150.000	34.34	10.74	45.08	74.00	-28.92	peak
4	11400.000	33.53	17.44	50.97	74.00	-23.03	peak
5	14010.000	26.56	24.07	50.63	74.00	-23.37	peak
6	17970.000	22.59	28.27	50.86	74.00	-23.14	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4890.000	41.56	0.78	42.34	74.00	-31.66	peak
2	6900.000	38.36	6.19	44.55	74.00	-29.45	peak
3	8835.000	34.68	9.60	44.28	74.00	-29.72	peak
4	11145.000	32.12	17.02	49.14	74.00	-24.86	peak
5	13935.000	26.50	23.83	50.33	74.00	-23.67	peak
6	18000.000	22.04	28.54	50.58	74.00	-23.42	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3915.000	43.98	-2.63	41.35	74.00	-32.65	peak
2	6870.000	38.12	6.12	44.24	74.00	-29.76	peak
3	8850.000	34.38	9.65	44.03	74.00	-29.97	peak
4	11070.000	32.96	16.67	49.63	74.00	-24.37	peak
5	13635.000	27.46	23.05	50.51	74.00	-23.49	peak
6	17805.000	23.59	26.82	50.41	74.00	-23.59	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	45.23	0.82	46.05	74.00	-27.95	peak
2	6870.000	38.37	6.12	44.49	74.00	-29.51	peak
3	8835.000	34.99	9.60	44.59	74.00	-29.41	peak
4	10920.000	32.90	15.93	48.83	74.00	-25.17	peak
5	14025.000	26.61	24.02	50.63	74.00	-23.37	peak
6	17775.000	23.27	26.63	49.90	74.00	-24.10	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.05	0.86	42.91	74.00	-31.09	peak
2	6975.000	38.38	6.39	44.77	74.00	-29.23	peak
3	9525.000	33.79	12.32	46.11	74.00	-27.89	peak
4	11070.000	33.10	16.67	49.77	74.00	-24.23	peak
5	13890.000	26.70	23.64	50.34	74.00	-23.66	peak
6	17970.000	22.27	28.27	50.54	74.00	-23.46	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4515.000	42.35	-0.29	42.06	74.00	-31.94	peak
2	6975.000	38.28	6.39	44.67	74.00	-29.33	peak
3	8850.000	35.23	9.65	44.88	74.00	-29.12	peak
4	11235.000	32.07	17.30	49.37	74.00	-24.63	peak
5	13980.000	26.34	24.01	50.35	74.00	-23.65	peak
6	17835.000	23.19	27.09	50.28	74.00	-23.72	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4785.000	41.01	0.53	41.54	74.00	-32.46	peak
2	6855.000	38.74	6.08	44.82	74.00	-29.18	peak
3	9525.000	34.04	12.32	46.36	74.00	-27.64	peak
4	11130.000	33.54	16.94	50.48	74.00	-23.52	peak
5	12375.000	30.24	19.57	49.81	74.00	-24.19	peak
6	17985.000	21.87	28.41	50.28	74.00	-23.72	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	42.10	0.72	42.82	74.00	-31.18	peak
2	6855.000	38.36	6.08	44.44	74.00	-29.56	peak
3	8820.000	35.02	9.56	44.58	74.00	-29.42	peak
4	11115.000	32.76	16.88	49.64	74.00	-24.36	peak
5	13665.000	27.34	23.09	50.43	74.00	-23.57	peak
6	17760.000	24.29	26.54	50.83	74.00	-23.17	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4785.000	41.03	0.53	41.56	74.00	-32.44	peak
2	6960.000	38.26	6.35	44.61	74.00	-29.39	peak
3	11355.000	32.59	17.40	49.99	74.00	-24.01	peak
4	12375.000	30.45	19.57	50.02	74.00	-23.98	peak
5	13650.000	27.59	23.06	50.65	74.00	-23.35	peak
6	17835.000	23.49	27.09	50.58	74.00	-23.42	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4995.000	41.71	1.04	42.75	74.00	-31.25	peak
2	6855.000	38.25	6.08	44.33	74.00	-29.67	peak
3	9285.000	33.21	11.29	44.50	74.00	-29.50	peak
4	11415.000	32.65	17.48	50.13	74.00	-23.87	peak
5	13950.000	26.25	23.89	50.14	74.00	-23.86	peak
6	17910.000	22.74	27.75	50.49	74.00	-23.51	peak


Test Mode:	802.11ax HE40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4785.000	41.70	0.53	42.23	74.00	-31.77	peak
2	6975.000	37.87	6.39	44.26	74.00	-29.74	peak
3	8820.000	35.07	9.56	44.63	74.00	-29.37	peak
4	10560.000	35.15	14.41	49.56	74.00	-24.44	peak
5	13560.000	27.24	22.94	50.18	74.00	-23.82	peak
6	17940.000	22.70	28.02	50.72	74.00	-23.28	peak


8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0105	80.60	-101.40	-20.80	47.18	-67.98	peak
2	0.0151	75.87	-101.37	-25.50	44.02	-69.52	peak
3	0.0280	70.79	-101.38	-30.59	38.66	-69.25	peak
4	0.0405	69.92	-101.44	-31.52	35.45	-66.97	peak
5	0.0626	64.81	-101.53	-36.72	31.67	-68.39	peak
6	0.1014	63.56	-101.79	-38.23	27.48	-65.71	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	78.77	-101.65	-22.88	23.77	-46.65	peak
2	0.2126	72.89	-101.74	-28.85	21.05	-49.90	peak
3	0.2384	69.78	-101.78	-32.00	20.05	-52.05	peak
4	0.2767	66.82	-101.83	-35.01	18.76	-53.77	peak
5	0.3431	65.17	-101.90	-36.73	16.89	-53.62	peak
6	0.4142	63.23	-101.98	-38.75	15.26	-54.01	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5705	63.87	-62.07	1.80	32.48	-30.68	peak
2	1.5120	57.83	-62.04	-4.21	24.01	-28.22	peak
3	1.9354	57.34	-61.85	-4.51	29.54	-34.05	peak
4	4.9755	53.39	-61.48	-8.09	29.54	-37.63	peak
5	9.6676	52.68	-60.85	-8.17	29.54	-37.71	peak
6	17.9893	54.09	-60.91	-6.82	29.54	-36.36	peak


8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18456.000	50.00	-5.30	44.70	74.00	-29.30	peak
2	19592.000	50.08	-5.44	44.64	74.00	-29.36	peak
3	21064.000	48.99	-4.85	44.14	74.00	-29.86	peak
4	23016.000	46.80	-3.44	43.36	74.00	-30.64	peak
5	24912.000	45.42	-2.18	43.24	74.00	-30.76	peak
6	25712.000	43.85	-0.79	43.06	74.00	-30.94	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18176.000	48.90	-5.51	43.39	74.00	-30.61	peak
2	19816.000	48.16	-5.30	42.86	74.00	-31.14	peak
3	22160.000	47.16	-4.31	42.85	74.00	-31.15	peak
4	23688.000	45.37	-3.18	42.19	74.00	-31.81	peak
5	24488.000	45.40	-2.34	43.06	74.00	-30.94	peak
6	25640.000	44.30	-1.12	43.18	74.00	-30.82	peak


8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	62.0100	28.82	-14.99	13.83	40.00	-26.17	QP
2	151.2500	33.06	-13.38	19.68	43.50	-23.82	QP
3	398.6000	32.10	-9.61	22.49	46.00	-23.51	QP
4	480.0800	38.32	-7.86	30.46	46.00	-15.54	QP
5	743.9200	26.68	-3.62	23.06	46.00	-22.94	QP
6	1000.0000	27.99	-0.13	27.86	54.00	-26.14	QP

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 7.2V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	54.2500	33.57	-15.02	18.55	40.00	-21.45	QP
2	144.4600	37.55	-13.76	23.79	43.50	-19.71	QP
3	250.1900	29.97	-14.56	15.41	46.00	-30.59	QP
4	480.0800	27.47	-7.86	19.61	46.00	-26.39	QP
5	802.1200	26.80	-2.57	24.23	46.00	-21.77	QP
6	989.3300	27.65	-0.28	27.37	54.00	-26.63	QP

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a).

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	22.4℃	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2V

TEST DATE / ENGINEER

Test Date	September 4, 2025	Test By	Deacon Tan
-----------	-------------------	---------	------------

TEST RESULTS

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1520	38.90	9.74	48.64	65.89	-17.25	QP
2	0.1520	19.48	9.74	29.22	55.89	-26.67	AVG
3	0.1570	32.92	9.73	42.65	65.62	-22.97	QP
4	0.1570	18.60	9.73	28.33	55.62	-27.29	AVG
5	0.4127	30.77	9.64	40.41	57.59	-17.18	QP
6	0.4127	24.87	9.64	34.51	47.59	-13.08	AVG
7	1.2319	16.96	9.65	26.61	56.00	-29.39	QP
8	1.2319	11.90	9.65	21.55	46.00	-24.45	AVG
9	3.5924	11.26	9.73	20.99	56.00	-35.01	QP
10	3.5924	2.13	9.73	11.86	46.00	-34.14	AVG
11	15.8102	10.71	9.74	20.45	60.00	-39.55	QP
12	15.8102	3.37	9.74	13.11	50.00	-36.89	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1539	35.24	9.64	44.88	65.79	-20.91	QP
2	0.1539	16.03	9.64	25.67	55.79	-30.12	AVG
3	0.1637	40.15	9.64	49.79	65.27	-15.48	QP
4	0.1637	18.08	9.64	27.72	55.27	-27.55	AVG
5	0.4119	28.98	9.64	38.62	57.61	-18.99	QP
6	0.4119	23.90	9.64	33.54	47.61	-14.07	AVG
7	1.2268	14.46	9.63	24.09	56.00	-31.91	QP
8	1.2268	8.99	9.63	18.62	46.00	-27.38	AVG
9	3.9784	11.21	9.63	20.84	56.00	-35.16	QP
10	3.9784	3.12	9.63	12.75	46.00	-33.25	AVG
11	15.9906	8.76	9.74	18.50	60.00	-41.50	QP
12	15.9906	3.11	9.74	12.85	50.00	-37.15	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


11. TEST DATA


11.1. APPENDIX A: DTS BANDWIDTH

11.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B-MIMO	Ant1	2412	8.16	2407.92	2416.08	≥0.5	PASS
	Ant2	2412	8.16	2407.92	2416.08	≥0.5	PASS
	Ant1	2437	8.16	2432.92	2441.08	≥0.5	PASS
	Ant2	2437	8.16	2432.92	2441.08	≥0.5	PASS
	Ant1	2462	8.16	2457.92	2466.08	≥0.5	PASS
	Ant2	2462	8.16	2457.92	2466.08	≥0.5	PASS
11G-MIMO	Ant1	2412	16.28	2403.88	2420.16	≥0.5	PASS
	Ant2	2412	16.16	2404.00	2420.16	≥0.5	PASS
	Ant1	2437	16.36	2428.84	2445.20	≥0.5	PASS
	Ant2	2437	16.16	2428.96	2445.12	≥0.5	PASS
	Ant1	2462	16.28	2453.88	2470.16	≥0.5	PASS
	Ant2	2462	16.24	2453.92	2470.16	≥0.5	PASS
11N20MIMO	Ant1	2412	17.12	2403.40	2420.52	≥0.5	PASS
	Ant2	2412	17.36	2403.40	2420.76	≥0.5	PASS
	Ant1	2437	17.16	2428.40	2445.56	≥0.5	PASS
	Ant2	2437	17.36	2428.32	2445.68	≥0.5	PASS
	Ant1	2462	17.04	2453.44	2470.48	≥0.5	PASS
	Ant2	2462	17.44	2453.32	2470.76	≥0.5	PASS
11N40MIMO	Ant1	2422	36.16	2403.92	2440.08	≥0.5	PASS
	Ant2	2422	35.60	2404.24	2439.84	≥0.5	PASS
	Ant1	2437	36.32	2418.84	2455.16	≥0.5	PASS
	Ant2	2437	35.68	2419.08	2454.76	≥0.5	PASS
	Ant1	2452	35.92	2434.00	2469.92	≥0.5	PASS
	Ant2	2452	35.84	2434.00	2469.84	≥0.5	PASS
11AX20MIMO	Ant1	2412	18.56	2402.68	2421.24	≥0.5	PASS
	Ant2	2412	18.76	2402.68	2421.44	≥0.5	PASS
	Ant1	2437	18.60	2427.68	2446.28	≥0.5	PASS
	Ant2	2437	18.76	2427.68	2446.44	≥0.5	PASS
	Ant1	2462	18.56	2452.64	2471.20	≥0.5	PASS
	Ant2	2462	18.72	2452.68	2471.40	≥0.5	PASS
11AX40MIMO	Ant1	2422	37.52	2403.20	2440.72	≥0.5	PASS
	Ant2	2422	37.60	2403.12	2440.72	≥0.5	PASS
	Ant1	2437	37.84	2418.04	2455.88	≥0.5	PASS
	Ant2	2437	37.84	2418.12	2455.96	≥0.5	PASS
	Ant1	2452	37.76	2433.20	2470.96	≥0.5	PASS
	Ant2	2452	37.84	2433.12	2470.96	≥0.5	PASS

11.1.2. Test Graphs







11B-MIMO_Ant2_2437




11B-MIMO_Ant1_2462




11B-MIMO_Ant2_2462




11G-MIMO_Ant1_2412




11G-MIMO_Ant2_2412




11G-MIMO_Ant1_2437




11G-MIMO_Ant2_2437




11G-MIMO_Ant1_2462




11G-MIMO_Ant2_2462




11N20MIMO_Ant1_2412




11N20MIMO_Ant2_2412




11N20MIMO_Ant1_2437




11N20MIMO_Ant2_2437




11N20MIMO_Ant1_2462




11N20MIMO_Ant2_2462




11N40MIMO_Ant1_2422




11N40MIMO_Ant2_2422




11N40MIMO_Ant1_2437




11N40MIMO_Ant2_2437




11N40MIMO_Ant1_2452




11N40MIMO_Ant2_2452




11AX20MIMO_Ant1_2412




11AX20MIMO_Ant2_2412




11AX20MIMO_Ant1_2437




11AX20MIMO_Ant2_2437




11AX20MIMO_Ant1_2462




11AX20MIMO_Ant2_2462




11AX40MIMO_Ant1_2422




11AX40MIMO_Ant2_2422




11AX40MIMO_Ant1_2437



11AX40MIMO_Ant2_2437



11AX40MIMO_Ant1_2452




11AX40MIMO_Ant2_2452


11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

11.2.1. Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B-MIMO	Ant1	2412	13.067	2405.5265	2418.5934	PASS
	Ant2	2412	13.107	2405.4865	2418.5934	PASS
	Ant1	2437	13.107	2430.4865	2443.5934	PASS
	Ant2	2437	13.187	2430.4066	2443.5934	PASS
	Ant1	2462	13.147	2455.4466	2468.5934	PASS
	Ant2	2462	13.187	2455.4066	2468.5934	PASS
11G-MIMO	Ant1	2412	16.583	2403.7283	2420.3117	PASS
	Ant2	2412	16.543	2403.7682	2420.3117	PASS
	Ant1	2437	16.583	2428.7283	2445.3117	PASS
	Ant2	2437	16.583	2428.7283	2445.3117	PASS
	Ant1	2462	16.583	2453.7283	2470.3117	PASS
	Ant2	2462	16.583	2453.7283	2470.3117	PASS
11N20MIMO	Ant1	2412	17.702	2403.1688	2420.8711	PASS
	Ant2	2412	17.702	2403.1688	2420.8711	PASS
	Ant1	2437	17.662	2428.1688	2445.8312	PASS
	Ant2	2437	17.702	2428.1688	2445.8711	PASS
	Ant1	2462	17.662	2453.1688	2470.8312	PASS
	Ant2	2462	17.702	2453.1688	2470.8711	PASS
11N40MIMO	Ant1	2422	36.044	2404.0180	2440.0619	PASS
	Ant2	2422	36.204	2403.9381	2440.1419	PASS
	Ant1	2437	36.044	2418.9381	2454.9820	PASS
	Ant2	2437	36.044	2419.0180	2455.0619	PASS
	Ant1	2452	36.044	2433.9381	2469.9820	PASS
	Ant2	2452	36.124	2433.9381	2470.0619	PASS
11AX20MIMO	Ant1	2412	18.941	2402.5694	2421.5105	PASS
	Ant2	2412	18.941	2402.5694	2421.5105	PASS
	Ant1	2437	18.901	2427.5694	2446.4705	PASS
	Ant2	2437	18.941	2427.5694	2446.5105	PASS
	Ant1	2462	18.941	2452.5295	2471.4705	PASS
	Ant2	2462	18.941	2452.5295	2471.4705	PASS
11AX40MIMO	Ant1	2422	37.722	2403.1389	2440.8611	PASS
	Ant2	2422	37.802	2403.1389	2440.9411	PASS
	Ant1	2437	37.802	2418.1389	2455.9411	PASS
	Ant2	2437	37.722	2418.1389	2455.8611	PASS
	Ant1	2452	37.802	2433.1389	2470.9411	PASS
	Ant2	2452	37.722	2433.1389	2470.8611	PASS

11.2.2. Test Graphs







11B-MIMO_Ant2_2437




11B-MIMO_Ant1_2462




11B-MIMO_Ant2_2462




11G-MIMO_Ant1_2412




11G-MIMO_Ant2_2412




11G-MIMO_Ant1_2437




11G-MIMO_Ant2_2437




11G-MIMO_Ant1_2462




11G-MIMO_Ant2_2462



11N20MIMO_Ant1_2412



11N20MIMO_Ant2_2412



11N20MIMO_Ant1_2437