

CFR 47 FCC PART 15 SUBPART E

TEST REPORT

For

Spatial NT Series Aircraft, Spatial N Series Aircraft

MODEL NUMBER: S3T, S3

REPORT NUMBER: 4791883648-1-RF-2

ISSUE DATE: September 22, 2025

FCC ID:2BQAI-S3T

Prepared for

**Spatial Hover Inc
10415A Westpark Dr. Houston TX 77042 Houston Texas United States**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	September 5, 2025	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
ON TIME AND DUTY CYCLE	ANSI C63.10-2020, Clause 12.2	None; for reporting purposes only.	Pass
6dB AND 26dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	KDB 789033 D02 v02r01 Section C.1	FCC Part 15.407 (a)/(e),	Pass
CONDUCTED OUTPUT POWER	KDB 789033 D02 v02r01 Section E.3.a (Method PM)/KDB 789033 D02 v02r01 Section E.3.a (Method PM) Section E.2.d (Method SA-2)	FCC 15.407 (a)	Pass
POWER SPECTRAL DENSITY	KDB 789033 D02 v02r01 Section F	FCC 15.407 (a)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2.	FCC 15.207	N/A
Radiated Emissions and Band Edge Measurement	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	FCC 15.407 (b) FCC 15.209 FCC 15.205	Pass
FREQUENCY STABILITY	ANSI C63.10-2020, Clause 6.8	FCC 15.407 (g)	Pass
Antenna Requirement	N/A	FCC 47 CFR Part 15.203/ 15.407(a)(1) (2)	Pass

Note:

1. N/A: In this whole report not applicable.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART E> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>8</i>
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	<i>9</i>
5.2. <i>CHANNEL LIST</i>	<i>10</i>
5.3. <i>MAXIMUM POWER</i>	<i>15</i>
5.4. <i>TEST CHANNEL CONFIGURATION</i>	<i>15</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	<i>16</i>
5.6. <i>WORSE CASE CONFIGURATIONS.....</i>	<i>17</i>
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>18</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST</i>	<i>19</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	20
7. ANTENNA PORT TEST RESULTS	23
7.1. <i>ON TIME AND DUTY CYCLE</i>	<i>23</i>
7.2. <i>6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH ...</i>	<i>24</i>
7.3. <i>CONDUCTED OUTPUT POWER</i>	<i>26</i>
7.4. <i>POWER SPECTRAL DENSITY</i>	<i>28</i>
7.5. <i>FREQUENCY STABILITY.....</i>	<i>30</i>
8. RADIATED TEST RESULTS	32
8.1. <i>RESTRICTED BANDEDGE</i>	<i>40</i>
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~7 GHZ)</i>	<i>54</i>
8.3. <i>SPURIOUS EMISSIONS(7 GHZ~18 GHZ)</i>	<i>60</i>
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i>	<i>90</i>
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i>	<i>93</i>
8.6. <i>SPURIOUS EMISSIONS(26 GHZ~40 GHZ)</i>	<i>95</i>
8.7. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i>	<i>97</i>
9. ANTENNA REQUIREMENT	99

10.	TEST DATA.....	100
10.1.	APPENDIX A: EMISSION BANDWIDTH.....	100
10.1.1.	Test Result.....	100
10.1.2.	Test Graphs	101
10.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....	113
10.2.1.	Test Result.....	113
10.2.2.	Test Graphs	114
10.3.	APPENDIX C: MIN EMISSION BANDWIDTH	126
10.3.1.	Test Result.....	126
10.3.2.	Test Graphs	127
10.4.	APPENDIX D: MAXIMUM CONDUCTED OUTPUT POWER.....	139
10.4.1.	Test Result.....	139
10.5.	APPENDIX E: MAXIMUM POWER SPECTRAL DENSITY	143
10.5.1.	Test Result.....	143
10.5.2.	Test Graphs	144
10.6.	APPENDIX F: FREQUENCY STABILITY.....	158
10.6.1.	Test Result.....	158
10.7.	APPENDIX G: DUTY CYCLE.....	159
10.7.1.	Test Result.....	159
10.7.2.	Test Graphs	160

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Spatial Hover Inc
Address: 10415A Westpark Dr. Houston TX 77042 Houston Texas United States

Manufacturer Information

Company Name: Spatial Hover Inc
Address: 10415A Westpark Dr. Houston TX 77042 Houston Texas United States

EUT Information

EUT Name: Spatial NT Series Aircraft, Spatial N Series Aircraft
Model: S3T
Series Model: S3
Sample Received Date: July 23, 2025
Sample Status: Normal
Sample ID: 8705555
Date of Tested: July 23, 2025 to September 22, 2025


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART E	Pass

Prepared By:



Fanny Huang
Project Engineer

Checked By:



Kebo Zhang
Operations Leader

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART E , ANSI C63.10-2020, ANSI C63.10-2020 + Cor.1-2023, CFR 47 FCC Part 2, KDB 789033 D02 v02r01, RSS-GEN Issue 5, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 40 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
	5.37 dB (26 GHz ~ 40 GHz)
Duty Cycle	±0.028%
Emission Bandwidth and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.766 dB
Maximum Power Spectral Density Level	±1.22 dB
Frequency Stability	±2.76%
Dynamic Frequency Selection	±1.01 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Spatial NT Series Aircraft, Spatial N Series Aircraft
Model	S3T
Series Model	S3
Model Difference	S3 is identical with the test model S3T except the PTZ camera. S3T has thermal camera function but S3 hasn't.

Radio Technology	SRD 5.8G
Operation Frequency	5.8G 1.4 MHz Bandwidth (5728.5 MHz ~ 5848.12 MHz) 5.8G 3 MHz Bandwidth (5727.5 MHz ~ 5847.2 MHz) 5.8 GHz 10 MHz Bandwidth (5730.5 MHz ~ 5844.5 MHz) 5.8 GHz 20 MHz Bandwidth (5735.5 MHz ~ 5839.5 MHz) 5.8 GHz 40 MHz Bandwidth (5745.5 MHz ~ 5829.5 MHz)
Modulation	OFDM (QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
Battery	DC 15.4V
Power Supply	DC 15.4V

5.2. CHANNEL LIST

5.8 GHz 1.4 MHz Bandwidth							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5728.5	31	5758.5	61	5788.5	91	5818.5
2	5730.12	32	5760.12	62	5790.12	92	5820.12
3	5730.5	33	5760.5	63	5790.5	93	5820.5
4	5732.12	34	5762.12	64	5792.12	94	5822.12
5	5732.5	35	5762.5	65	5792.5	95	5822.5
6	5734.12	36	5764.12	66	5794.12	96	5824.12
7	5734.5	37	5764.5	67	5794.5	97	5824.5
8	5736.12	38	5766.12	68	5796.12	98	5826.12
9	5736.5	39	5766.5	69	5796.5	99	5826.5
10	5738.12	40	5768.12	70	5798.12	100	5828.12
11	5738.5	41	5768.5	71	5798.5	101	5828.5
12	5740.12	42	5770.12	72	5800.12	102	5830.12
13	5740.5	43	5770.5	73	5800.5	103	5830.5
14	5742.12	44	5772.12	74	5802.12	104	5832.12
15	5742.5	45	5772.5	75	5802.5	105	5832.5
16	5744.12	46	5774.12	76	5804.12	106	5834.12
17	5744.5	47	5774.5	77	5804.5	107	5834.5
18	5746.12	48	5776.12	78	5806.12	108	5836.12
19	5746.5	49	5776.5	79	5806.5	109	5836.5
20	5748.12	50	5778.12	80	5808.12	110	5838.12
21	5748.5	51	5778.5	81	5808.5	111	5838.5
22	5750.12	52	5780.12	82	5810.12	112	5840.12
23	5750.5	53	5780.5	83	5810.5	113	5840.5
24	5752.12	54	5782.12	84	5812.12	114	5842.12
25	5752.5	55	5782.5	85	5812.5	115	5842.5
26	5754.12	56	5784.12	86	5814.12	116	5844.12
27	5754.5	57	5784.5	87	5814.5	117	5844.5
28	5756.12	58	5786.12	88	5816.12	118	5846.12
29	5756.5	59	5786.5	89	5816.5	119	5846.5
30	5758.12	60	5788.12	90	5818.12	120	5848.12

5.8 GHz 3 MHz Bandwidth							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5727.5	21	5757.5	41	5787.5	61	5817.5
2	5730.2	22	5760.2	42	5790.2	62	5820.2
3	5730.5	23	5760.5	43	5790.5	63	5820.5
4	5733.2	24	5763.2	44	5793.2	64	5823.2
5	5733.5	25	5763.5	45	5793.5	65	5823.5
6	5736.2	26	5766.2	46	5796.2	66	5826.2
7	5736.5	27	5766.5	47	5796.5	67	5826.5
8	5739.2	28	5769.2	48	5799.2	68	5829.2
9	5739.5	29	5769.5	49	5799.5	69	5829.5
10	5742.2	30	5772.2	50	5802.2	70	5832.2
11	5742.5	31	5772.5	51	5802.5	71	5832.5
12	5745.2	32	5775.2	52	5805.2	72	5835.2
13	5745.5	33	5775.5	53	5805.5	73	5835.5
14	5748.2	34	5778.2	54	5808.2	74	5838.2
15	5748.5	35	5778.5	55	5808.5	75	5838.5
16	5751.2	36	5781.2	56	5811.2	76	5841.2
17	5751.5	37	5781.5	57	5811.5	77	5841.5
18	5754.2	38	5784.2	58	5814.2	78	5844.2
19	5754.5	39	5784.5	59	5814.5	79	5844.5
20	5757.2	40	5787.2	60	5817.2	80	5847.2

5.8 GHz 10 MHz Bandwidth							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5730.5	30	5759.5	59	5788.5	88	5817.5
2	5731.5	31	5760.5	60	5789.5	89	5818.5
3	5732.5	32	5761.5	61	5790.5	90	5819.5
4	5733.5	33	5762.5	62	5791.5	91	5820.5
5	5734.5	34	5763.5	63	5792.5	92	5821.5
6	5735.5	35	5764.5	64	5793.5	93	5822.5
7	5736.5	36	5765.5	65	5794.5	94	5823.5
8	5737.5	37	5766.5	66	5795.5	95	5824.5
9	5738.5	38	5767.5	67	5796.5	96	5825.5
10	5739.5	39	5768.5	68	5797.5	97	5826.5
11	5740.5	40	5769.5	69	5798.5	98	5827.5
12	5741.5	41	5770.5	70	5799.5	99	5828.5
13	5742.5	42	5771.5	71	5800.5	100	5829.5
14	5743.5	43	5772.5	72	5801.5	101	5830.5
15	5744.5	44	5773.5	73	5802.5	102	5831.5
16	5745.5	45	5774.5	74	5803.5	103	5832.5
17	5746.5	46	5775.5	75	5804.5	104	5833.5
18	5747.5	47	5776.5	76	5805.5	105	5834.5
19	5748.5	48	5777.5	77	5806.5	106	5835.5
20	5749.5	49	5778.5	78	5807.5	107	5836.5
21	5750.5	50	5779.5	79	5808.5	108	5837.5
22	5751.5	51	5780.5	80	5809.5	109	5838.5
23	5752.5	52	5781.5	81	5810.5	110	5839.5
24	5753.5	53	5782.5	82	5811.5	111	5840.5
25	5754.5	54	5783.5	83	5812.5	112	5841.5
26	5755.5	55	5784.5	84	5813.5	113	5842.5
27	5756.5	56	5785.5	85	5814.5	114	5843.5
28	5757.5	57	5786.5	86	5815.5	115	5844.5
29	5758.5	58	5787.5	87	5816.5	/	/

5.8 GHz 20 MHz Bandwidth							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5735.5	28	5762.5	55	5789.5	82	5816.5
2	5736.5	29	5763.5	56	5790.5	83	5817.5
3	5737.5	30	5764.5	57	5791.5	84	5818.5
4	5738.5	31	5765.5	58	5792.5	85	5819.5
5	5739.5	32	5766.5	59	5793.5	86	5820.5
6	5740.5	33	5767.5	60	5794.5	87	5821.5
7	5741.5	34	5768.5	61	5795.5	88	5822.5
8	5742.5	35	5769.5	62	5796.5	89	5823.5
9	5743.5	36	5770.5	63	5797.5	90	5824.5
10	5744.5	37	5771.5	64	5798.5	91	5825.5
11	5745.5	38	5772.5	65	5799.5	92	5826.5
12	5746.5	39	5773.5	66	5800.5	93	5827.5
13	5747.5	40	5774.5	67	5801.5	94	5828.5
14	5748.5	41	5775.5	68	5802.5	95	5829.5
15	5749.5	42	5776.5	69	5803.5	96	5830.5
16	5750.5	43	5777.5	70	5804.5	97	5831.5
17	5751.5	44	5778.5	71	5805.5	98	5832.5
18	5752.5	45	5779.5	72	5806.5	99	5833.5
19	5753.5	46	5780.5	73	5807.5	100	5834.5
20	5754.5	47	5781.5	74	5808.5	101	5835.5
21	5755.5	48	5782.5	75	5809.5	102	5836.5
22	5756.5	49	5783.5	76	5810.5	103	5837.5
23	5757.5	50	5784.5	77	5811.5	104	5838.5
24	5758.5	51	5785.5	78	5812.5	105	5839.5
25	5759.5	52	5786.5	79	5813.5	/	/
26	5760.5	53	5787.5	80	5814.5	/	/
27	5761.5	54	5788.5	81	5815.5	/	/

5.8 GHz 40 MHz Bandwidth							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5745.5	23	5767.5	45	5789.5	67	5811.5
2	5746.5	24	5768.5	46	5790.5	68	5812.5
3	5747.5	25	5769.5	47	5791.5	69	5813.5
4	5748.5	26	5770.5	48	5792.5	70	5814.5
5	5749.5	27	5771.5	49	5793.5	71	5815.5
6	5750.5	28	5772.5	50	5794.5	72	5816.5
7	5751.5	29	5773.5	51	5795.5	73	5817.5
8	5752.5	30	5774.5	52	5796.5	74	5818.5
9	5753.5	31	5775.5	53	5797.5	75	5819.5
10	5754.5	32	5776.5	54	5798.5	76	5820.5
11	5755.5	33	5777.5	55	5799.5	77	5821.5
12	5756.5	34	5778.5	56	5800.5	78	5822.5
13	5757.5	35	5779.5	57	5801.5	79	5823.5
14	5758.5	36	5780.5	58	5802.5	80	5824.5
15	5759.5	37	5781.5	59	5803.5	81	5825.5
16	5760.5	38	5782.5	60	5804.5	82	5826.5
17	5761.5	39	5783.5	61	5805.5	83	5827.5
18	5762.5	40	5784.5	62	5806.5	84	5828.5
19	5763.5	41	5785.5	63	5807.5	85	5829.5
20	5764.5	42	5786.5	64	5808.5	/	/
21	5765.5	43	5787.5	65	5809.5	/	/
22	5766.5	44	5788.5	66	5810.5	/	/

5.3. MAXIMUM POWER

SRD 5GHz	Frequency (MHz)	Maximum Average Conducted Power (dBm)
1.4 MHz Mode	5725 ~ 5850	20.10
3 MHz Mode		19.96
10 MHz Mode		29.98
20 MHz Mode		29.82
40 MHz Mode		29.09

5.4. TEST CHANNEL CONFIGURATION

SRD 5 GHz	Test Channel Number	Frequency
5.8G 1.4 MHz Mode	CH 1(Low Channel), CH 61(MID Channel), CH 120(High Channel)	5728.5 MHz, 5788.5 MHz, 5848.12 MHz
5.8G 3 MHz Mode	CH 1(Low Channel), CH 41(MID Channel), CH 80(High Channel)	5727.5 MHz, 5787.5 MHz, 5847.2 MHz
5.8G 10 MHz Mode	CH 1(Low Channel), CH 58(MID Channel), CH 115(High Channel)	5730.5 MHz, 5787.5 MHz, 5844.5 MHz
5.8G 20 MHz Mode	CH 1(Low Channel), CH 53(MID Channel), CH 105(High Channel)	5735.5 MHz, 5787.5 MHz, 5839.5 MHz
5.8G 40 MHz Mode	CH 1(Low Channel), CH 12, CH43(MID Channel), CH 62, CH 85(High Channel)	5745.5 MHz, 5756.5 MHz, 5787.5 MHz, 5806.5 MHz, 5829.5 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 5727.5 ~ 5848.12 MHz Band		
Test Software		Set up
Modulation Mode	Transmit Antenna Number	Test Software setting value
		NCB: 1.4 MHz/3 MHz/10 MHz/20 MHz/40 MHz
		All Channels
All	All	Default

5.6. WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst case Data Rates declared by the customer:

- SRD 5.8G-1.4 MHz Mode/QPSK
- SRD 5.8G-3 MHz Mode/QPSK
- SRD 5.8G-10 MHz Mode/QPSK
- SRD 5.8G-20 MHz Mode/QPSK
- SRD 5.8G-40 MHz Mode/QPSK

The EUT has 4 separate antennas which correspond to 4 separate antennas: antenna 0, antenna 1, antenna 2, antenna 3 respectively. Antenna 0,1,2,3 support SRD. The EUT support 1TX4RX and 2TX4RX mode. 1TX4RX and 2TX4RX have the same power setting, so only the worst data for 2TX4RX mode were recorded in the report. For 2T4R mode, antenna 0 and antenna 1/ antenna 0 and antenna 3/ antenna 1 and antenna 2/ antenna 2 and antenna 3 used as transmit antennas and all the 4 antennas can use as receive antennas, all the transmit combination(ANT0 and ANT1 / ANT0 and ANT3 / ANT1 and ANT2 / ANT2 and ANT3) had been tested, but only the worst data for ANT0 and ANT1 were recorded in the report.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
0	5725 ~ 5850	Dipole Antenna	3
1	5725 ~ 5850	Dipole Antenna	2.5
2	5725 ~ 5850	Dipole Antenna	2.5
3	5725 ~ 5850	Dipole Antenna	3

The EUT support Space Time Coding(STBC) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the STBC results the Directional Gain was calculated in accordance with the following method.

$$\text{Directional gain} = 10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/NANT] \text{ dBi}$$

Directional gain(ANT0 & ANT1) = 2.76 dBi

Directional gain(ANT0 & ANT3) = 3 dBi

Directional gain(ANT1 & ANT2) = 2.5 dBi

Directional gain(ANT2 & ANT3) = 2.76 dBi

Test Mode	Transmit and Receive Mode	Description
1.4 MHz Mode	☒ 2TX, 4RX	ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna. ANT 0,1, 2, 3 can be used as receiving antenna.
3 MHz Mode	☒ 2TX, 4RX	ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna. ANT 0,1, 2, 3 can be used as receiving antenna.
10 MHz Mode	☒ 2TX, 4RX	ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna. ANT 0,1, 2, 3 can be used as receiving antenna.
20 MHz Mode	☒ 2TX, 4RX	ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna. ANT 0,1, 2, 3 can be used as receiving antenna.
40 MHz Mode	☒ 2TX, 4RX	ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna. ANT 0,1, 2, 3 can be used as receiving antenna.

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E42-80	/
2	AC Adaptor	Lenovo	ADLX65YCC3D	Input: AC 100-240V, 1.8A, 50-60Hz Output: DC 20V, 3.25A, 65.0W Max

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



Note: AC Adaptor only use for AC POWER LINE CONDUCTED EMISSION test.

6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.27,2024	Dec.26,2025
Vector Signal Generator	R&S	SMBV100A	261637	Sep.28, 2024	Sep.27, 2025
Signal Generator	R&S	SMB100A	178553	Sep.28, 2024	Sep.27, 2025
Signal Analyzer	R&S	FSV40	101118	Sep.28, 2024	Sep.27, 2025
Software					
Description	Manufacturer		Name	Version	
For R&S TS 8997 Test System	Rohde & Schwarz		EMC 32	10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.13, 2024	Sep.12, 2025
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.28, 2024	Sep.27, 2025
DC power supply	Keysight	E3642A	MY55159130	Sep.28, 2024	Sep.27, 2025
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.28, 2024	Sep.27, 2025
Attenuator	Aglient	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.27,2024	Dec.26,2025
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.28, 2024	Sep.27, 2025
Two-Line V-Network	R&S	ENV216	101983	Sep.28, 2024	Sep.27, 2025
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.28, 2024	Sep.27, 2025
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.28, 2024	Sep.27, 2025
EMI Measurement Receiver	R&S	ESR26	101377	Sep.28, 2024	Sep.27, 2025
Horn Antenna	TDK	HRN-0118	130940	Dec.10, 2024	Dec.11, 2027
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.28, 2024	Sep.27, 2025
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.28, 2024	Sep.27, 2025
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.28, 2024	Sep.27, 2025
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.8, 2024	Oct.7, 2025
Barometer	Yiyi	Baro	N/A	Oct.10, 2024	Oct.9, 2025
Attenuator	Agilent	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. Set VBW $\geq$ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3°C	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 15.4V

TEST DATE / ENGINEER

Test Date	August 7, 2025	Test By	Bairong Liu
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix G

7.2. 6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 Subpart E		
Test Item	Limit	Frequency Range (MHz)
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850
99 % Occupied Bandwidth	For reporting purposes only.	5725 ~ 5850

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth; section II.D. for 99 % Occupied Bandwidth.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the EBW. For 99 % Occupied Bandwidth: approximately 1 % ~ 5 % of the OBW.
VBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 26 dB Bandwidth: $> 3 \times \text{RBW}$ For 99 % Bandwidth: $> 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3°C	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 15.4V

TEST DATE / ENGINEER

Test Date	August 7, 2025	Test By	Bairong Liu
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B&C

7.3. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

Method PM (Measurement using an RF average power meter):

(i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:

- a. The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
- b. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
- c. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.


(ii) If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in II.B.

(iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(iv) Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log (1/0.25)$ if the duty cycle is 25 %).

Note: Method SA-2 was used for straddle channel output power test, and Method PM was used for testing rest channels

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3°C	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 15.4V

TEST DATE / ENGINEER

Test Date	August 7, 2025	Test By	Bairong Liu
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	30 dBm/500kHz	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.

Connect the EUT to the spectrum analyzer and use the following settings:


For U-NII-3:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Average
Sweep time	Auto

Allow trace to fully stabilize and use the peak search function on the instrument to find the peak of the spectrum and record its value.

Add $10 \log (1/x)$, where x is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3°C	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 15.4V

TEST DATE / ENGINEER

Test Date	August 7, 2025	Test By	Bairong Liu
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E

7.5. FREQUENCY STABILITY

LIMITS

The frequency of the carrier signal shall be maintained within band of operation.

TEST PROCEDURE

1. The EUT was placed inside an environmental chamber as the temperature in the chamber was varied between -10 °C ~ 40 °C (declared by customer).
2. The temperature was incremented by 10 °C intervals and the unit allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.
3. The primary supply voltage is varied from 85 % to 115 % of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	10 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

4. While maintaining a constant temperature inside the environmental chamber, turn the EUT on and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.
5. Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculated the frequency drift.

TEST ENVIRONMENT

	Normal Test Conditions	Extreme Test Conditions
Relative Humidity	20 % ~ 75 %	/
Atmospheric Pressure	100 kPa ~ 102 kPa	/
Temperature	T_N (Normal Temperature): 25.1 °C	T_L (Low Temperature): -10 °C
		T_H (High Temperature): 40 °C
Supply Voltage	V_N (Normal Voltage): DC 15.4 V	V_L (Low Voltage): DC 13.09 V
		V_H (High Voltage): DC 17.71 V

TEST SETUP**TEST ENVIRONMENT**

Temperature	24.3℃	Relative Humidity	62.6%
Atmosphere Pressure	101kPa	Test Voltage	DC 15.4V

TEST DATE / ENGINEER

Test Date	August 7, 2025	Test By	Bairong Liu
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix F

8. RADIATED TEST RESULTS

LIMITS

Refer to CFR 47 FCC §15.205, §15.209 and §15.407 (b).

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

Limits of unwanted/undesirable emission out of the restricted bands refer to CFR 47 FCC §15.407 (b) and ISSED RSS-247 7.3.

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz		
5470~5725 MHz		
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4
Note: *1 beyond 75 MHz or more above of the band edge. *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.		

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)

Sweep	Auto
-------	------

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.G.3 ~ II.G.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 7 GHz):

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (7 GHz ~ 18 GHz):

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):

Note:


1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (26 GHz ~ 40 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	60.1%
Atmosphere Pressure	101kPa	Test Voltage	


TEST DATE / ENGINEER

Test Date	September 3, 2025	Test By	Mason Wang
-----------	-------------------	---------	------------

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	SRD 5G 1.4M PK	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5640.850	18.74	39.86	58.60	68.20	-9.60	peak
2	5725.000	28.69	39.94	68.63	122.20	-53.57	peak

Test Mode:	SRD 5G 1.4M PK	Frequency(MHz):	5728.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5625.460	19.66	39.84	59.50	68.20	-8.70	peak
2	5725.000	37.34	39.94	77.28	122.20	-44.92	peak

Test Mode:	SRD 5G 1.4M PK	Frequency(MHz):	5848.12
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	64.18	40.13	104.31	122.20	-17.89	peak
2	5952.390	19.73	40.34	60.07	68.20	-8.13	peak

Test Mode:	SRD 5G 3M PK	Frequency(MHz):	5727.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5647.310	19.54	39.86	59.40	68.20	-8.80	peak
2	5725.000	58.55	39.94	98.49	122.20	-23.71	peak

Test Mode:	SRD 5G 3M PK	Frequency(MHz):	5847.2
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	54.79	40.13	94.92	122.20	-27.28	peak
2	5956.300	19.89	40.36	60.25	68.20	-7.95	peak

Test Mode:	SRD 5G 10M PK	Frequency(MHz):	5730.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5634.960	24.87	39.85	64.72	68.20	-3.48	peak
2	5725.000	70.13	39.94	110.07	122.20	-12.13	peak

Test Mode:	SRD 5G 10M PK	Frequency(MHz):	5844.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	65.68	40.13	105.81	122.20	-16.39	peak
2	5965.040	21.65	40.37	62.02	68.20	-6.18	peak

Test Mode:	SRD 5G 20M PK	Frequency(MHz):	5735.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5641.040	23.07	39.86	62.93	68.20	-5.27	peak
2	5725.000	61.75	39.94	101.69	122.20	-20.51	peak

Test Mode:	SRD 5G 20M PK	Frequency(MHz):	5839.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	64.25	40.13	104.38	122.20	-17.82	peak
2	5929.160	23.40	40.30	63.70	68.20	-4.50	peak

Test Mode:	SRD 5G 40M PK	Frequency(MHz):	5745.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5647.690	26.15	39.86	66.01	68.20	-2.19	peak
2	5725.000	56.13	39.94	96.07	122.20	-26.13	peak

Test Mode:	SRD 5G 40M PK	Frequency(MHz):	5756.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5647.880	26.26	39.86	66.12	68.20	-2.08	peak
2	5725.000	57.30	39.94	97.24	122.20	-24.96	peak

Test Mode:	SRD 5G 40M PK	Frequency(MHz):	5762.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5647.880	26.64	39.86	66.50	68.20	-1.70	peak
2	5725.000	47.77	39.94	87.71	122.20	-34.49	peak

Test Mode:	SRD 5G 40M PK	Frequency(MHz):	5806.5
Polarity:	Vertical	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	45.95	40.13	86.08	122.20	-36.12	peak
2	5925.250	26.03	40.29	66.32	68.20	-1.88	peak


Test Mode:	SRD 5G 40M PK	Frequency(MHz):	5829.5
Polarity:	Vertical	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	52.83	40.13	92.96	122.20	-29.24	peak
2	5927.090	24.77	40.30	65.07	68.20	-3.13	peak


8.2. SPURIOUS EMISSIONS(1 GHZ~7 GHZ)

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2158.000	47.75	-9.64	38.11	68.20	-30.09	peak
2	3748.000	40.60	-2.99	37.61	74.00	-36.39	peak
3	4900.000	40.46	1.44	41.90	74.00	-32.10	peak
4	5728.500	55.07	4.05	59.12	/	/	fundamental
5	5974.000	40.33	5.28	45.61	68.20	-22.59	peak
6	6868.000	36.68	6.63	43.31	68.20	-24.89	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1516.000	51.55	-11.81	39.74	74.00	-34.26	peak
2	3652.000	41.60	-3.19	38.41	74.00	-35.59	peak
3	4894.000	40.07	1.41	41.48	74.00	-32.52	peak
4	5728.500	58.34	4.05	62.39	/	/	fundamental
5	6040.000	45.26	5.60	50.86	68.20	-17.34	peak
6	6862.000	36.56	6.63	43.19	68.20	-25.01	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5788.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2158.000	48.21	-9.64	38.57	68.20	-29.63	peak
2	3886.000	41.89	-2.71	39.18	74.00	-34.82	peak
3	4804.000	40.25	0.99	41.24	74.00	-32.76	peak
4	5788.500	52.25	4.30	56.55	/	/	fundamental
5	5998.000	42.74	5.42	48.16	68.20	-20.04	peak
6	6856.000	36.40	6.63	43.03	68.20	-25.17	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5788.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1522.000	51.58	-11.78	39.80	74.00	-34.20	peak
2	1888.000	47.94	-10.17	37.77	68.20	-30.43	peak
3	3580.000	42.78	-3.40	39.38	68.20	-28.82	peak
4	4906.000	40.82	1.46	42.28	74.00	-31.72	peak
5	5788.500	52.72	4.30	57.02	/	/	fundamental
6	5998.000	44.65	5.42	50.07	68.20	-18.13	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5848.12
Polarity:	Horizontal	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2164.000	48.91	-9.61	39.30	68.20	-28.90	peak
2	3568.000	40.86	-3.46	37.40	68.20	-30.80	peak
3	4684.000	40.65	0.51	41.16	74.00	-32.84	peak
4	5848.120	50.06	4.61	54.67	/	/	fundamental
5	6058.000	41.25	5.67	46.92	68.20	-21.28	peak
6	6730.000	36.35	6.47	42.82	68.20	-25.38	peak


Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5848.12
Polarity:	Vertical	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1516.000	51.89	-11.81	40.08	74.00	-33.92	peak
2	2422.000	46.45	-8.54	37.91	68.20	-30.29	peak
3	4354.000	42.01	-1.12	40.89	74.00	-33.11	peak
4	4846.000	41.95	1.18	43.13	74.00	-30.87	peak
5	5848.120	55.74	4.61	60.35	/	/	fundamental
6	6058.000	46.72	5.67	52.39	68.20	-15.81	peak


8.3. SPURIOUS EMISSIONS(7 GHZ~18 GHZ)

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	36.13	7.50	43.63	74.00	-30.37	peak
2	10674.000	32.35	14.52	46.87	74.00	-27.13	peak
3	11477.000	30.54	17.46	48.00	74.00	-26.00	peak
4	13919.000	25.51	23.60	49.11	68.20	-19.09	peak
5	17087.000	24.48	23.16	47.64	68.20	-20.56	peak
6	18000.000	20.94	28.51	49.45	74.00	-24.55	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7319.000	35.92	7.50	43.42	74.00	-30.58	peak
2	8199.000	36.03	8.41	44.44	74.00	-29.56	peak
3	9695.000	34.21	13.45	47.66	68.20	-20.54	peak
4	11455.000	29.93	17.38	47.31	74.00	-26.69	peak
5	13688.000	25.99	22.84	48.83	68.20	-19.37	peak
6	17835.000	22.51	26.99	49.50	74.00	-24.50	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5788.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	35.33	7.50	42.83	74.00	-31.17	peak
2	9695.000	33.46	13.45	46.91	68.20	-21.29	peak
3	11510.000	29.76	17.57	47.33	74.00	-26.67	peak
4	13699.000	25.72	22.87	48.59	68.20	-19.61	peak
5	17131.000	23.91	23.39	47.30	68.20	-20.90	peak
6	18000.000	21.04	28.51	49.55	74.00	-24.45	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5788.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8199.000	35.08	8.41	43.49	74.00	-30.51	peak
2	9618.000	33.82	13.31	47.13	68.20	-21.07	peak
3	11477.000	30.62	17.46	48.08	74.00	-25.92	peak
4	13809.000	26.41	23.17	49.58	68.20	-18.62	peak
5	16185.000	25.91	21.50	47.41	74.00	-26.59	peak
6	17923.000	21.68	27.79	49.47	74.00	-24.53	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5848.12
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8386.000	34.96	8.57	43.53	74.00	-30.47	peak
2	9684.000	33.43	13.44	46.87	68.20	-21.33	peak
3	11598.000	29.67	17.88	47.55	74.00	-26.45	peak
4	12676.000	27.77	20.14	47.91	74.00	-26.09	peak
5	13831.000	26.54	23.26	49.80	68.20	-18.40	peak
6	17967.000	21.10	28.21	49.31	74.00	-24.69	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5848.12
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	35.40	7.49	42.89	74.00	-31.11	peak
2	9640.000	33.14	13.36	46.50	68.20	-21.70	peak
3	11697.000	33.79	17.91	51.70	74.00	-22.30	peak
4	12379.000	31.02	19.58	50.60	74.00	-23.40	peak
5	13820.000	25.59	23.22	48.81	68.20	-19.39	peak
6	17923.000	21.99	27.79	49.78	74.00	-24.22	peak

Test Mode:	SRD 5G 3M	Frequency(MHz):	5727.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	35.20	7.50	42.70	74.00	-31.30	peak
2	9849.000	33.23	13.55	46.78	68.20	-21.42	peak
3	11554.000	29.77	17.71	47.48	74.00	-26.52	peak
4	12874.000	26.77	20.50	47.27	68.20	-20.93	peak
5	13831.000	25.42	23.26	48.68	68.20	-19.52	peak
6	17912.000	21.84	27.70	49.54	74.00	-24.46	peak

Test Mode:	SRD 5G 3M	Frequency(MHz):	5727.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	35.15	7.50	42.65	74.00	-31.35	peak
2	9574.000	32.97	13.13	46.10	68.20	-22.10	peak
3	11455.000	33.16	17.38	50.54	74.00	-23.46	peak
4	12478.000	28.84	19.76	48.60	74.00	-25.40	peak
5	13908.000	26.58	23.56	50.14	68.20	-18.06	peak
6	17868.000	22.84	27.29	50.13	74.00	-23.87	peak

Test Mode:	SRD 5G 3M	Frequency(MHz):	5787.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8243.000	34.83	8.44	43.27	74.00	-30.73	peak
2	10256.000	33.20	13.44	46.64	68.20	-21.56	peak
3	11576.000	30.89	17.80	48.69	74.00	-25.31	peak
4	13930.000	26.40	23.63	50.03	68.20	-18.17	peak
5	17010.000	24.64	22.77	47.41	68.20	-20.79	peak
6	17857.000	22.34	27.18	49.52	74.00	-24.48	peak

Test Mode:	SRD 5G 3M	Frequency(MHz):	5787.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8199.000	35.22	8.41	43.63	74.00	-30.37	peak
2	9332.000	35.08	11.82	46.90	74.00	-27.10	peak
3	11774.000	32.14	17.91	50.05	74.00	-23.95	peak
4	13666.000	27.03	22.78	49.81	68.20	-18.39	peak
5	17043.000	24.80	22.94	47.74	68.20	-20.46	peak
6	17934.000	22.91	27.90	50.81	74.00	-23.19	peak

Test Mode:	SRD 5G 3M	Frequency(MHz):	5844.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8617.000	35.47	8.95	44.42	68.20	-23.78	peak
2	9673.000	33.16	13.42	46.58	68.20	-21.62	peak
3	11455.000	31.91	17.38	49.29	74.00	-24.71	peak
4	13864.000	26.71	23.39	50.10	68.20	-18.10	peak
5	16174.000	26.43	21.43	47.86	74.00	-26.14	peak
6	18000.000	21.73	28.51	50.24	74.00	-23.76	peak

Test Mode:	SRD 5G 3M	Frequency(MHz):	5844.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8188.000	34.79	8.40	43.19	74.00	-30.81	peak
2	9761.000	33.20	13.58	46.78	68.20	-21.42	peak
3	11554.000	30.92	17.71	48.63	74.00	-25.37	peak
4	13622.000	28.03	22.66	50.69	68.20	-17.51	peak
5	16988.000	26.03	22.68	48.71	68.20	-19.49	peak
6	17989.000	22.00	28.40	50.40	74.00	-23.60	peak

Test Mode:	SRD 5G 10M	Frequency(MHz):	5730.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8199.000	34.86	8.41	43.27	74.00	-30.73	peak
2	9662.000	33.09	13.39	46.48	68.20	-21.72	peak
3	11488.000	30.34	17.49	47.83	74.00	-26.17	peak
4	13908.000	26.08	23.56	49.64	68.20	-18.56	peak
5	17087.000	25.20	23.16	48.36	68.20	-19.84	peak
6	17813.000	22.84	26.78	49.62	74.00	-24.38	peak

Test Mode:	SRD 5G 10M	Frequency(MHz):	5730.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8386.000	35.00	8.57	43.57	74.00	-30.43	peak
2	9728.000	32.82	13.52	46.34	68.20	-21.86	peak
3	11466.000	31.64	17.42	49.06	74.00	-24.94	peak
4	13985.000	25.56	23.85	49.41	68.20	-18.79	peak
5	17087.000	24.58	23.16	47.74	68.20	-20.46	peak
6	17868.000	22.25	27.29	49.54	74.00	-24.46	peak

Test Mode:	SRD 5G 10M	Frequency(MHz):	5787.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8188.000	34.58	8.40	42.98	74.00	-31.02	peak
2	9662.000	32.99	13.39	46.38	68.20	-21.82	peak
3	11587.000	29.89	17.84	47.73	74.00	-26.27	peak
4	12544.000	29.07	19.83	48.90	74.00	-25.10	peak
5	13842.000	26.45	23.29	49.74	68.20	-18.46	peak
6	17923.000	22.17	27.79	49.96	74.00	-24.04	peak

Test Mode:	SRD 5G 10M	Frequency(MHz):	5787.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	35.35	7.49	42.84	74.00	-31.16	peak
2	9684.000	32.61	13.44	46.05	68.20	-22.15	peak
3	11180.000	31.62	16.19	47.81	74.00	-26.19	peak
4	13798.000	26.38	23.13	49.51	68.20	-18.69	peak
5	16944.000	24.93	22.54	47.47	68.20	-20.73	peak
6	17978.000	21.65	28.31	49.96	74.00	-24.04	peak

Test Mode:	SRD 5G 10M	Frequency(MHz):	5844.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7275.000	35.09	7.49	42.58	74.00	-31.42	peak
2	9739.000	32.60	13.55	46.15	68.20	-22.05	peak
3	11092.000	32.16	15.83	47.99	74.00	-26.01	peak
4	12863.000	27.05	20.51	47.56	68.20	-20.64	peak
5	13699.000	26.63	22.87	49.50	68.20	-18.70	peak
6	17901.000	22.47	27.60	50.07	74.00	-23.93	peak

Test Mode:	SRD 5G 10M	Frequency(MHz):	5844.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7264.000	35.73	7.49	43.22	74.00	-30.78	peak
2	9827.000	33.25	13.61	46.86	68.20	-21.34	peak
3	11510.000	31.02	17.57	48.59	74.00	-25.41	peak
4	12753.000	27.90	20.38	48.28	68.20	-19.92	peak
5	13864.000	26.29	23.39	49.68	68.20	-18.52	peak
6	18000.000	22.15	28.51	50.66	74.00	-23.34	peak

Test Mode:	SRD 5G 20M	Frequency(MHz):	5735.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	35.41	7.50	42.91	74.00	-31.09	peak
2	9838.000	32.68	13.59	46.27	68.20	-21.93	peak
3	11554.000	30.45	17.71	48.16	74.00	-25.84	peak
4	13853.000	26.49	23.34	49.83	68.20	-18.37	peak
5	17043.000	25.19	22.94	48.13	68.20	-20.07	peak
6	17934.000	22.15	27.90	50.05	74.00	-23.95	peak

Test Mode:	SRD 5G 20M	Frequency(MHz):	5735.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7286.000	35.31	7.49	42.80	74.00	-31.20	peak
2	9596.000	33.32	13.26	46.58	68.20	-21.62	peak
3	11466.000	31.74	17.42	49.16	74.00	-24.84	peak
4	13567.000	27.31	22.55	49.86	68.20	-18.34	peak
5	17054.000	25.23	22.99	48.22	68.20	-19.98	peak
6	17912.000	22.65	27.70	50.35	74.00	-23.65	peak

Test Mode:	SRD 5G 20M	Frequency(MHz):	5787.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	35.62	7.50	43.12	74.00	-30.88	peak
2	9662.000	33.25	13.39	46.64	68.20	-21.56	peak
3	11301.000	32.23	16.74	48.97	74.00	-25.03	peak
4	12401.000	28.74	19.64	48.38	74.00	-25.62	peak
5	13853.000	26.34	23.34	49.68	68.20	-18.52	peak
6	17846.000	22.60	27.09	49.69	74.00	-24.31	peak

Test Mode:	SRD 5G 20M	Frequency(MHz):	5787.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8199.000	34.61	8.41	43.02	74.00	-30.98	peak
2	9684.000	32.72	13.44	46.16	68.20	-22.04	peak
3	12181.000	30.18	19.05	49.23	74.00	-24.77	peak
4	13798.000	27.67	23.13	50.80	68.20	-17.40	peak
5	17054.000	26.31	22.99	49.30	68.20	-18.90	peak
6	17934.000	23.05	27.90	50.95	74.00	-23.05	peak

Test Mode:	SRD 5G 20M	Frequency(MHz):	5839.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8199.000	34.94	8.41	43.35	74.00	-30.65	peak
2	10080.000	32.98	13.27	46.25	68.20	-21.95	peak
3	11466.000	30.75	17.42	48.17	74.00	-25.83	peak
4	12544.000	28.10	19.83	47.93	74.00	-26.07	peak
5	13875.000	26.09	23.44	49.53	68.20	-18.67	peak
6	17978.000	21.57	28.31	49.88	74.00	-24.12	peak

Test Mode:	SRD 5G 20M	Frequency(MHz):	5839.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8199.000	34.91	8.41	43.32	74.00	-30.68	peak
2	9783.000	32.60	13.63	46.23	68.20	-21.97	peak
3	11433.000	31.50	17.31	48.81	74.00	-25.19	peak
4	12885.000	27.19	20.51	47.70	68.20	-20.50	peak
5	13688.000	26.98	22.84	49.82	68.20	-18.38	peak
6	18000.000	21.74	28.51	50.25	74.00	-23.75	peak

Test Mode:	SRD 5G 40M	Frequency(MHz):	5745.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	35.13	7.49	42.62	74.00	-31.38	peak
2	9618.000	33.75	13.31	47.06	68.20	-21.14	peak
3	11587.000	30.72	17.84	48.56	74.00	-25.44	peak
4	12852.000	27.70	20.52	48.22	68.20	-19.98	peak
5	13864.000	27.32	23.39	50.71	68.20	-17.49	peak
6	18000.000	22.18	28.51	50.69	74.00	-23.31	peak

Test Mode:	SRD 5G 40M	Frequency(MHz):	5745.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7286.000	36.01	7.49	43.50	74.00	-30.50	peak
2	9651.000	33.23	13.38	46.61	68.20	-21.59	peak
3	11477.000	31.12	17.46	48.58	74.00	-25.42	peak
4	12456.000	28.22	19.73	47.95	74.00	-26.05	peak
5	13633.000	26.67	22.68	49.35	68.20	-18.85	peak
6	17989.000	22.08	28.40	50.48	74.00	-23.52	peak

Test Mode:	SRD 5G 40M	Frequency(MHz):	5787.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7286.000	35.49	7.49	42.98	74.00	-31.02	peak
2	9596.000	33.37	13.26	46.63	68.20	-21.57	peak
3	11466.000	32.10	17.42	49.52	74.00	-24.48	peak
4	12148.000	29.10	18.97	48.07	74.00	-25.93	peak
5	13875.000	26.33	23.44	49.77	68.20	-18.43	peak
6	17978.000	21.42	28.31	49.73	74.00	-24.27	peak

Test Mode:	SRD 5G 40M	Frequency(MHz):	5787.5
Polarity:	Vertical	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	35.90	7.50	43.40	74.00	-30.60	peak
2	9684.000	32.84	13.44	46.28	68.20	-21.92	peak
3	11466.000	32.18	17.42	49.60	74.00	-24.40	peak
4	12511.000	28.75	19.80	48.55	74.00	-25.45	peak
5	14051.000	26.27	23.66	49.93	68.20	-18.27	peak
6	17934.000	22.22	27.90	50.12	74.00	-23.88	peak

Test Mode:	SRD 5G 40M	Frequency(MHz):	5829.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	35.64	7.50	43.14	74.00	-30.86	peak
2	9728.000	32.66	13.52	46.18	68.20	-22.02	peak
3	11400.000	32.13	17.20	49.33	74.00	-24.67	peak
4	12797.000	28.20	20.53	48.73	68.20	-19.47	peak
5	13600.000	27.31	22.60	49.91	68.20	-18.29	peak
6	17857.000	23.27	27.18	50.45	74.00	-23.55	peak


Test Mode:	SRD 5G 40M	Frequency(MHz):	5829.5
Polarity:	Vertical	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7286.000	35.53	7.49	43.02	74.00	-30.98	peak
2	9794.000	32.59	13.64	46.23	68.20	-21.97	peak
3	11301.000	31.44	16.74	48.18	74.00	-25.82	peak
4	12412.000	28.30	19.65	47.95	74.00	-26.05	peak
5	13831.000	26.73	23.26	49.99	68.20	-18.21	peak
6	17978.000	21.90	28.31	50.21	74.00	-23.79	peak


8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0094	76.16	-101.35	-25.19	48.05	-73.24	peak
2	0.0171	69.38	-101.36	-31.98	42.94	-74.92	peak
3	0.0286	65.46	-101.38	-35.92	38.47	-74.39	peak
4	0.0400	61.98	-101.43	-39.45	35.56	-75.01	peak
5	0.0606	60.45	-101.52	-41.07	31.95	-73.02	peak
6	0.1345	56.59	-101.68	-45.09	25.03	-70.12	peak

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1595	74.36	-101.65	-27.29	23.55	-50.84	peak
2	0.1869	71.54	-101.70	-30.16	22.17	-52.33	peak
3	0.2366	65.78	-101.78	-36.00	20.12	-56.12	peak
4	0.3069	61.93	-101.86	-39.93	17.86	-57.79	peak
5	0.3487	60.41	-101.91	-41.50	16.75	-58.25	peak
6	0.4540	56.96	-102.02	-45.06	14.46	-59.52	peak


Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6671	62.25	-62.10	0.15	31.12	-30.97	peak
2	1.5380	58.35	-62.03	-3.68	23.86	-27.54	peak
3	2.6737	55.64	-61.65	-6.01	29.54	-35.55	peak
4	5.2705	54.54	-61.45	-6.91	29.54	-36.45	peak
5	11.8513	54.06	-60.88	-6.82	29.54	-36.36	peak
6	29.3213	52.30	-60.02	-7.72	29.54	-37.26	peak


8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18488.000	48.15	-5.26	42.89	74.00	-31.11	peak
2	19336.000	49.54	-5.58	43.96	74.00	-30.04	peak
3	20312.000	49.02	-5.56	43.46	74.00	-30.54	peak
4	22024.000	48.04	-4.46	43.58	74.00	-30.42	peak
5	23664.000	47.32	-3.18	44.14	74.00	-29.86	peak
6	25448.000	46.33	-1.76	44.57	74.00	-29.43	peak


Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Vertical	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18440.000	48.82	-5.32	43.50	74.00	-30.50	peak
2	19480.000	49.46	-5.56	43.90	74.00	-30.10	peak
3	21168.000	47.71	-4.80	42.91	74.00	-31.09	peak
4	22888.000	48.03	-3.55	44.48	74.00	-29.52	peak
5	24568.000	47.60	-2.33	45.27	74.00	-28.73	peak
6	25592.000	44.99	-1.35	43.64	74.00	-30.36	peak


8.6. SPURIOUS EMISSIONS(26 GHZ~40 GHZ)

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	26490.000	52.79	-4.74	48.05	74.00	-25.95	peak
2	29332.000	49.16	-0.93	48.23	74.00	-25.77	peak
3	32762.000	49.45	-1.21	48.24	74.00	-25.76	peak
4	35366.000	46.40	2.59	48.99	74.00	-25.01	peak
5	37228.000	44.73	3.14	47.87	74.00	-26.13	peak
6	39958.000	44.08	5.12	49.20	74.00	-24.80	peak


Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Vertical	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	26546.000	51.84	-4.76	47.08	74.00	-26.92	peak
2	29472.000	47.34	-0.71	46.63	74.00	-27.37	peak
3	31530.000	47.80	-1.21	46.59	74.00	-27.41	peak
4	33798.000	46.37	0.46	46.83	74.00	-27.17	peak
5	37200.000	44.61	3.16	47.77	74.00	-26.23	peak
6	39006.000	43.62	4.37	47.99	74.00	-26.01	peak


8.7. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Vertical	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	52.3100	41.17	-15.05	26.12	40.00	-13.88	QP
2	152.2200	48.54	-13.32	35.22	43.50	-8.28	QP
3	216.2400	46.28	-12.95	33.33	46.00	-12.67	QP
4	359.8000	33.91	-9.55	24.36	46.00	-21.64	QP
5	633.3400	30.43	-5.64	24.79	46.00	-21.21	QP
6	986.4200	27.38	-0.32	27.06	54.00	-26.94	QP

Test Mode:	SRD 5G 1.4M	Frequency(MHz):	5728.5
Polarity:	Horizontal	Test Voltage:	DC 15.4V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	52.3100	37.63	-15.05	22.58	40.00	-17.42	QP
2	153.1900	37.68	-13.25	24.43	43.50	-19.07	QP
3	216.2400	41.59	-12.95	28.64	46.00	-17.36	QP
4	312.2700	40.96	-11.03	29.93	46.00	-16.07	QP
5	475.2300	38.22	-7.91	30.31	46.00	-15.69	QP
6	944.7100	30.79	-0.79	30.00	46.00	-16.00	QP

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.407(a)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass


10. TEST DATA


10.1. APPENDIX A: EMISSION BANDWIDTH

10.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Verdict
SRD 1.4M	Ant0	5728.5	2.53	5727.18	5729.72	PASS
	Ant1	5728.5	2.54	5727.17	5729.71	PASS
	Ant0	5788.5	2.56	5787.16	5789.72	PASS
	Ant1	5788.5	2.54	5787.17	5789.71	PASS
	Ant0	5848.12	2.53	5846.79	5849.31	PASS
	Ant1	5848.12	2.59	5846.77	5849.36	PASS
SRD 3M	Ant0	5727.5	3.01	5726.11	5729.12	PASS
	Ant1	5727.5	2.96	5726.14	5729.11	PASS
	Ant0	5787.5	2.96	5786.13	5789.09	PASS
	Ant1	5787.5	2.98	5786.14	5789.12	PASS
	Ant0	5847.2	2.96	5845.82	5848.78	PASS
	Ant1	5847.2	2.96	5845.84	5848.80	PASS
SRD 10M	Ant0	5730.5	14.44	5722.90	5737.34	PASS
	Ant1	5730.5	14.20	5723.30	5737.50	PASS
	Ant0	5787.5	13.28	5781.34	5794.62	PASS
	Ant1	5787.5	13.32	5781.58	5794.90	PASS
	Ant0	5844.5	11.36	5838.42	5849.78	PASS
	Ant1	5844.5	12.80	5838.14	5850.94	PASS
SRD 20M	Ant0	5735.5	18.92	5726.10	5745.02	PASS
	Ant1	5735.5	18.76	5726.06	5744.82	PASS
	Ant0	5787.5	19.36	5777.66	5797.02	PASS
	Ant1	5787.5	19.12	5777.90	5797.02	PASS
	Ant0	5839.5	18.92	5830.06	5848.98	PASS
	Ant1	5839.5	19.04	5829.98	5849.02	PASS
SRD 40M	Ant0	5745.5	37.68	5726.70	5764.38	PASS
	Ant1	5745.5	37.68	5726.70	5764.38	PASS
	Ant0	5756.5	37.84	5737.62	5775.46	PASS
	Ant1	5756.5	37.84	5737.70	5775.54	PASS
	Ant0	5762.5	38.00	5743.62	5781.62	PASS
	Ant1	5762.5	37.92	5743.62	5781.54	PASS
	Ant0	5787.5	37.52	5768.70	5806.22	PASS
	Ant1	5787.5	37.44	5768.78	5806.22	PASS
	Ant0	5806.5	38.00	5787.54	5825.54	PASS
	Ant1	5806.5	38.00	5787.54	5825.54	PASS
	Ant0	5829.5	37.60	5810.78	5848.38	PASS
	Ant1	5829.5	37.60	5810.70	5848.30	PASS

10.1.2. Test Graphs







SRD 1.4M_Ant1_5788.5




SRD 1.4M_Ant0_5848.12




SRD 1.4M_Ant1_5848.12




SRD 3M_Ant0_5727.5




SRD 3M_Ant1_5727.5




SRD 3M_Ant0_5787.5




SRD 3M_Ant1_5787.5




SRD 3M_Ant0_5847.2




SRD 3M_Ant1_5847.2




SRD 10M_Ant0_5730.5




SRD 10M_Ant1_5730.5




SRD 10M_Ant0_5787.5




SRD 10M_Ant1_5787.5




SRD 10M_Ant0_5844.5




SRD 10M_Ant1_5844.5




SRD 20M_Ant0_5735.5




SRD 20M_Ant1_5735.5




SRD 20M_Ant0_5787.5




SRD 20M_Ant1_5787.5




SRD 20M_Ant0_5839.5




SRD 20M_Ant1_5839.5




SRD 40M_Ant0_5745.5




SRD 40M_Ant1_5745.5




SRD 40M_Ant0_5756.5




SRD 40M_Ant1_5756.5




SRD 40M_Ant0_5762.5




SRD 40M_Ant1_5762.5




SRD 40M_Ant0_5787.5




SRD 40M_Ant1_5787.5




SRD 40M_Ant0_5806.5



SRD 40M_Ant1_5806.5



SRD 40M_Ant0_5829.5




SRD 40M_Ant1_5829.5


10.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

10.2.1. Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
SRD 1.4M	Ant0	5728.5	1.163	5727.9166	5729.0794	PASS
	Ant1	5728.5	1.431	5727.7368	5729.1673	PASS
	Ant0	5788.5	1.155	5787.9246	5789.0794	PASS
	Ant1	5788.5	1.431	5787.7288	5789.1593	PASS
	Ant0	5848.12	1.155	5847.5446	5848.6994	PASS
	Ant1	5848.12	1.451	5847.3408	5848.7913	PASS
SRD 3M	Ant0	5727.5	2.194	5726.4031	5728.5969	PASS
	Ant1	5727.5	2.194	5726.4151	5728.6089	PASS
	Ant0	5787.5	2.194	5786.4031	5788.5969	PASS
	Ant1	5787.5	2.194	5786.4151	5788.6089	PASS
	Ant0	5847.2	2.188	5846.1031	5848.2909	PASS
	Ant1	5847.2	2.194	5846.1151	5848.3089	PASS
SRD 10M	Ant0	5730.5	9.63	5725.7048	5735.3352	PASS
	Ant1	5730.5	9.99	5725.4650	5735.4550	PASS
	Ant0	5787.5	12.507	5781.1863	5793.6938	PASS
	Ant1	5787.5	10.589	5782.0654	5792.6548	PASS
	Ant0	5844.5	9.59	5839.7448	5849.3352	PASS
	Ant1	5844.5	9.59	5839.7448	5849.3352	PASS
SRD 20M	Ant0	5735.5	17.942	5726.5889	5744.5310	PASS
	Ant1	5735.5	17.902	5726.6289	5744.5310	PASS
	Ant0	5787.5	18.062	5778.5090	5796.5709	PASS
	Ant1	5787.5	18.142	5778.4690	5796.6109	PASS
	Ant0	5839.5	18.102	5830.4690	5848.5709	PASS
	Ant1	5839.5	18.102	5830.5090	5848.6109	PASS
SRD 40M	Ant0	5745.5	36.124	5727.5979	5763.7218	PASS
	Ant1	5745.5	36.044	5727.5979	5763.6419	PASS
	Ant0	5756.5	36.044	5738.5180	5774.5619	PASS
	Ant1	5756.5	35.964	5738.5979	5774.5619	PASS
	Ant0	5762.5	36.124	5744.5180	5780.6419	PASS
	Ant1	5762.5	36.044	5744.5180	5780.5619	PASS
	Ant0	5787.5	41.958	5766.2413	5808.1993	PASS
	Ant1	5787.5	41.558	5767.0405	5808.5989	PASS
	Ant0	5806.5	36.044	5788.5180	5824.5619	PASS
	Ant1	5806.5	36.044	5788.5180	5824.5619	PASS
	Ant0	5829.5	37.083	5810.8786	5847.9615	PASS
	Ant1	5829.5	36.284	5811.4381	5847.7218	PASS

10.2.2. Test Graphs







SRD 1.4M_Ant1_5788.5




SRD 1.4M_Ant0_5848.12




SRD 1.4M_Ant1_5848.12




SRD 3M_Ant0_5727.5




SRD 3M_Ant1_5727.5




SRD 3M_Ant0_5787.5




SRD 3M Ant1 5787.5




SRD 3M Ant0 5847.2




SRD 3M Ant1 5847.2




SRD 10M_Ant0_5730.5




SRD 10M_Ant1_5730.5




SRD 10M_Ant0_5787.5



SRD 10M_Ant1_5787.5



SRD 10M_Ant0_5844.5



SRD 10M_Ant1_5844.5