



FCC TEST REPORT

For

ComJoT LLC

POC radio/4G Network intercom

Test Model: CJ-1UV

Prepared for : ComJoT LLC
Address : 915 St Louis St, New Orleans, LA, 70112, United States

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 10, 2025
Number of tested samples : 2
Sample No. : A250121024-1, A250121024-2
Serial number : Prototype
Date of Test : March 10, 2025 ~ August 15, 2025
Date of Report : August 15, 2025



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



FCC TEST REPORT FCC Part 90	
Report Reference No.	: LCSA06144206EJ
Date of Issue	: August 15, 2025
Testing Laboratory Name	: Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure	: Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name	: ComJoT LLC
Address	: 915 St Louis St, New Orleans, LA, 70112, United States
Test Specification	
Standard	: FCC CFR Title 47 Part 2, Part 90
Test Report Form No.	: LCSEMC-1.0
TRF Originator	: Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	: Dated 2011-03
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description	: POC radio/4G Network intercom
Trade Mark	: ComJoTRadios
Test Model	: CJ-1UV
Ratings	: Please Refer to Page 6
Result	: Pass

Compiled by:

Li Huan/ Administrator

Supervised by:

Jack Liu/ Technique principal

Approved by:

Gavin Liang/ Manager



**RADIO -- TEST REPORT****Test Report No. : LCSEA06144206EJ**August 15, 2025
Date of issue

Test Model..... : CJ-1UV

EUT..... : POC radio/4G Network intercom

Applicant..... : ComJoT LLC

Address..... : 915 St Louis St, New Orleans, LA, 70112, United States

Telephone..... : /

Fax..... : /

Manufacturer..... : Shenzhen Anysecu Technology Co., Ltd.Address..... : Room2413, Bld.2B, COFCO Xiangyun, Longcheng,
Longgang, Shenzhen, Guangdong, China

Telephone..... : /

Fax..... : /

Factory..... : Shenzhen Anysecu Technology Co., Ltd.Address..... : Room2413, Bld.2B, COFCO Xiangyun, Longcheng,
Longgang, Shenzhen, Guangdong, China

Telephone..... : /

Fax..... : /

Test Result**Pass**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	August 15, 2025	Initial Issue	--





TABLE OF CONTENTS

Test Report Description

Page

1.GENERAL INFORMATION	7
1.1. DESCRIPTION OF DEVICE (EUT)	7
1.2. SUPPORT EQUIPMENT LIST	9
1.3. EXTERNAL I/O CABLE	9
1.4. DESCRIPTION OF TEST FACILITY	9
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
1.6. MEASUREMENT UNCERTAINTY	10
1.7. DESCRIPTION OF TEST MODES	10
2.SYSTEM TEST CONFIGURATION	11
2.1. TEST STANDARDS	11
2.2. EUT CONFIGURATION	11
2.3. EUT EXERCISE	11
2.4. TEST SAMPLE	11
3.SYSTEM TEST CONFIGURATION	12
3.1. JUSTIFICATION	12
3.2. EUT EXERCISE SOFTWARE	12
3.3. SPECIAL ACCESSORIES	12
3.4. BLOCK DIAGRAM/SCHEMATICS	12
3.5. EQUIPMENT MODIFICATIONS	12
3.6. TEST SETUP	12
4.SUMMARY OF TEST RESULT	13
5.TEST CONDITIONS AND RESULTS	14
5.1. MAXIMUM TRANSMITTER POWER	14
5.1.1 Test Applicable	14
5.1.2 Test Procedure	14
5.1.3 Test Configuration	14
5.1.4 Test Results	14
5.2. OCCUPIED BANDWIDTH AND EMISSION MASK TEST	20
5.2.1 Test Applicable	20
5.2.2 Test Configuration	20
5.2.3 Test Procedure	20
5.2.4 Test Results	21
5.3. TRANSMITTER RADIATED SPURIOUS EMISSION	31
5.3.1 Test Applicable	31
5.3.2 Test Configuration	31
5.3.3 Test Arrangement	32
5.3.4 Test Procedure	32
5.3.5 Limit	33
5.3.5 Test Results	33
5.4. SPURIOUS EMISSION ON ANTENNA PORT	36
5.4.1 Test Applicable	36
5.4.2 Test Procedure	36
5.4.3 Test Configuration	36
5.4.4 Limit	36
5.4.5 Test Results	37
5.5. FREQUENCY STABILITY TEST	40
5.5.1 Test Applicable	40
5.5.2 Test Procedure	40
5.5.3 Test Configuration	40
5.5.4 Test Limits	40
5.5.5 Test Results	41
5.6. TRANSIENT FREQUENCY BEHAVIOR	42
5.6.1 Test Applicable	42



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5.6.2 Test Configuration.....	42
5.6.3 Test Procedure	42
5.6.4 Test Results.....	43
5.7. FCC § 2.1047 - MODULATION CHARACTERISTIC	44
5.7.1 Test Applicable.....	44
Applicable Standard.....	44
Test Procedure	44
Test Mode: Transmitting	44
12.5kHz:	45
12.5kHz.....	46
.....	46

6.LIST OF MEASURING EQUIPMENT	47
-------------------------------------	----

7.TEST SETUP PHOTOGRAPHS OF EUT.....	48
--------------------------------------	----

8.EXTERIOR PHOTOGRAPHS OF THE EUT	48
---	----

9.INTERIOR PHOTOGRAPHS OF THE EUT	48
---	----





1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Ratings	: Input: 5V $\pm$ 3000mA For AC Adapter Input: 100-240V~, 50/60Hz, 0.5A Max Adapter Output: 5V $\pm$ 3000mA DC 7.6V by Rechargeable Li-ion Battery, 3000mAh
Hardware Version	: H18_6762_4XE254_V1.1
Software Version	: H18V_V1.1
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	: V5.0
Antenna Description	: PIFA Antenna, 0.69dBi (max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 0.69dBi (max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 0.69dBi (max.)
2G	:
Support Band	: ☒ GSM 850 (U.S.-Band) ☒ PCS 1900 (U.S.-Band)
Release Version	: R99
GPRS Class	: Class 12
EGPRS Class	: Class 12
Type Of Modulation	: GMSK for GSM/GPRS; GMSK/8PSK for EGPRS





Antenna Description : PIFA Antenna
-1.7dBi (max.) For GSM 850
2.0dBi (max.) For PCS 1900

3G :

Support Band : ☒ WCDMA Band II (U.S.-Band)
☒ WCDMA Band IV (U.S.-Band)
☒ WCDMA Band V (U.S.-Band)

Release Version : R9

Type Of Modulation : QPSK,16QAM

Antenna Description : PIFA Antenna
2.0dBi (max.) For WCDMA Band II
1.6dBi (max.) For WCDMA Band IV
-1.7dBi (max.) For WCDMA Band V

LTE :

Support Band : ☒ E-UTRA Band 2(U.S.-Band)
☒ E-UTRA Band 4(U.S.-Band)
☒ E-UTRA Band 5(U.S.-Band)
☒ E-UTRA Band 7(U.S.-Band)
☒ E-UTRA Band 12(U.S.-Band)
☒ E-UTRA Band 17(U.S.-Band)
☒ E-UTRA Band 66(U.S.-Band)

LTE Release Version : R9

Type Of Modulation : QPSK/16QAM

Antenna Description : PIFA Antenna
2.0dBi (max.) For E-UTRA Band 2
1.6dBi (max.) For E-UTRA Band 4
1.3dBi (max.) For E-UTRA Band 5
-1.7dBi (max.) For E-UTRA Band 7
1.0dBi (max.) For E-UTRA Band 12
1.0dBi (max.) For E-UTRA Band 17
1.0dBi (max.) For E-UTRA Band 66

Power Class : Class 3

NFC :

Operating Frequency : 13.56MHz

Modulation Type : ASK

Antenna Description : PIFA Antenna, 1.0dBi(Max.)

PMR :

Operating Frequency : 400~470MHz

Channel Separation : Analog Voice 12.5KHz
Digital Voice/Data 12.5KHz

Modulation Type : FM for Analog Voice
4FSK for Digital Voice/Digital Data

Emission Designator : 11K0F3D for FM Modulation at 12.5KHz Channel Separation





7K60FXD for Digital data
7K60FXW for Digital data/Voice
Rated Output Power : High Power 2W; Lower Power 1W
Antenna Description : External Antenna, 0dBi(Max.)
GPS function : Support and only RX
Extreme temp. : -30°C to +50°C
Tolerance
Extreme vol. Limits : 6.7VDC to 8.7VDC (nominal: 7.6VDC)

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen Sunshine Technological Co., Ltd.	Switching Power Supply	XSD-05030 00SUSU	---	FCC

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
Type-C USB Port	1	USB Cable: 0.8m, unshielded
Antenna Port	1	N/A

1.4. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The sites are constructed in conformance with the requirements of ANSI C63.4 (2014) and CISPR Publication 22.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics" and is documented in the Shenzhen LCS Compliance Testing Laboratory Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.





1.6. Measurement Uncertainty

Test Item	Uncertainty	Note
Frequency error	30 Hz	(1)
Transmitter power conducted	0.62 dB	(1)
Transmitter power Radiated	2.67 dB	(1)
Conducted spurious emission 9KHz-12.75 GHz	1.22 dB	(1)
Conducted Emission 9KHz-30MHz	1.63 dB	(1)
Radiated spurious emission 30~1000MHz	3.10 dB	(1)
Radiated spurious emission 1~18GHz	3.80 dB	(1)
Radiated spurious emission 18-40GHz	3.90 dB	(1)
Occupied Bandwidth	35Hz	(1)
Emission Mask	1.25dB	(1)
Transmitter Frequency Behavior	6.8%	(1)

(1) . This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under typical operating condition. As, test modes selected as below by the technical parameters of the EUT:

Operation Mode	Description of operation mode	Additional information
TM1	4FSK+BW12.5KHz+TX	The EUT is set with 4FSK modulation and 12.5KHz bandwidth at maximum rated power for transmitter, powered by DC 7.60V power
TM2	4FSK+BW12.5KHz+TX	The EUT is set with 4FSK modulation and 12.5KHz bandwidth at minimum rated power for transmitter, powered by DC 7.60V power
TM3	FM+BW12.5KHz+TX	The EUT is set with FM modulation and 12.5KHz bandwidth at maximum rated power for transmitter, powered by DC 7.60V power
TM4	FM+BW12.5KHz+TX	The EUT is set with FM modulation and 12.5KHz bandwidth at minimum rated power for transmitter, powered by DC 7.60V power





2. SYSTEM TEST CONFIGURATION

2.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 90](#): PRIVATE LAND MOBILE RADIO SERVICES.

[ANSI/TIA-603-E-2016](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): Unintentional Radiators

[FCC Part 2](#): FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[ANSI C63.26:2015](#): American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services.

[ANSI C63.4:2014](#): Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2.2. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.3. EUT Exercise

The EUT has been tested under typical operating condition and The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.4. Test Sample

The application provides 1 sample to meet requirement;

Sample Number	Description
Sample 1	continuous transmit



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

N/ A

3.3. Special Accessories

N/ A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.





4. SUMMARY OF TEST RESULT

Transmitter Requirements				
FCC General Rules Part (47CFR)	Description of Test	Test Sample	Result	Remark
2.1046 90.205	Maximum Transmitter Power	Sample 1	Compliant	Note 1
2.1047 (a) 90.207	Modulation Characteristics - Audio Frequency Response	Sample 1	Compliant	Note 1
2.1047 (b) 90.207	Modulation Characteristics - Modulation Limiting	Sample 1	Compliant	Note 1
2.1049 90.210	Occupied Bandwidth Tests; Emission Mask	Sample 1	Compliant	Note 1
2.1055 90.213	Frequency Stability	Sample 1	Compliant	Note 1
90.214	Transient Frequency Behavior	Sample 1	Compliant	Note 1
2.1053 90.210	Transmitter Radiated Spurious Emission	Sample 1	Compliant	Note 1
2.1051 90.210	Spurious Emission on Antenna Port	Sample 1	Compliant	Note 1

Remark:

1. Note 1 – Test results inside test report;
2. Note 2 – N/A* - Not Applicable for this device. Because it is digital device.





5. TEST CONDITIONS AND RESULTS

5.1. Maximum Transmitter Power

5.1.1 Test Applicable

Per FCC Part 2.1046 and Part 90.205: Maximum ERP is dependent upon the station's antenna HAAT and required service area

5.1.2 Test Procedure


Measurements shall be made to establish the radio frequency power delivered by the transmitter the standard output termination. The power output shall be monitored and recorded and no adjustment shall be made to the transmitter after the test has begun, except as noted bellow:

If the power output is adjustable, measurements shall be made for the highest and lowest power levels.

The EUT connect to the Receiver through 20 dB attenuator.

Measurement with Spectrum Analyzer conducted external power supply with 7.2V stabilized supply voltage.

5.1.3 Test Configuration



5.1.4 Test Results

Temperature	24.4℃	Humidity	52.6%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage

Modulation Type	Channel Separation	Operation Mode	Test Channel	Test Frequency (MHz)	Test Results (dBm)	Limit (dBm)
Digital 4FSK	12.5KHz	TM1	L	406.1125	31.298	33±1
			M 1	430.1125	32.090	33±1
			M 2	453.2125	32.838	33±1
			M 3	459.625	32.734	33±1
			M 4	465.625	32.589	33±1
			H	469.9875	32.298	33±1
	12.5KHz	TM2	L	406.1125	28.507	30±1
			M 1	430.1125	29.297	30±1
			M 2	453.2125	29.983	30±1
			M 3	459.625	29.941	30±1
			M 4	465.625	29.740	30±1
			H	469.9875	29.441	30±1
FM	12.5KHz	TM3	L	406.1125	32.498	33±1
			M 1	430.1125	32.652	33±1
			M 2	453.2125	31.863	33±1
			M 3	459.625	31.581	33±1
			M 4	465.625	31.280	33±1
			H	469.9875	31.108	33±1
	12.5KHz	TM4	L	406.1125	27.359	30±1
			M 1	430.1125	28.465	30±1



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



			M 2	453.2125	29.137	30±1
			M 3	459.625	29.125	30±1
			M 4	465.625	29.032	30±1
			H	469.9875	28.912	30±1
Limit	The limit is dependent upon the station's antenna HAAT and required service area.					
Test Results	PASS					


Note: The high rated power level is 2W(33dBm), and low rated power level is 1W(30dBm).
The output power shall not exceed by more than ± 1 dBm the manufacturer's rated output power for the particular transmitter specifically listed on the authorization





Remark:

1. Please refer to following plot.







Transmitter Power



TM2

TM2





406.1125 MHz

430.1125 MHz



453.2125 MHz

459.625 MHz



465.625 MHz

469.9875 MHz







Transmitter Power



TM3

TM3





406.1125 MHz

430.1125 MHz



453.2125 MHz

459.625 MHz



465.625 MHz

469.9875 MHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




Transmitter Power

TM4




406.1125 MHz


TM4




430.1125 MHz




453.2125 MHz



459.625 MHz



465.625 MHz



469.9875 MHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




5.2. Occupied Bandwidth and Emission Mask Test

5.2.1 Test Applicable

- (a). Occupied Bandwidth: The EUT was connected to the audio signal generator and the spectrum analyser via the main RF connector, and through an appropriate attenuator. The EUT was controlled to transmit its maximum power. Then the bandwidth of 99% power can be measured by the spectrum analyser.
- (b). Emission Mask B: For transmitters that are equipped with an audio low-pass filter pursuant to §90.211(a), the power of any emission must be below the unmodulated carrier power (P) as follows:
- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25dB.
 - (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35dB.
 - (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.
- (c). Emission Mask D, 12.5 kHz channel bandwidth equipment: For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:
- (1) On any frequency from the centre of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
 - (2) On any frequency removed from the centre of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
 - (3) On any frequency removed from the centre of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

5.2.2 Test Configuration



5.2.3 Test Procedure

- 1 Set EUT as normal operation.
- 2 Set SPA Centre Frequency = fundamental frequency, RBW=300Hz, VBW= 1 KHz, span =50 KHz .
- 3 Set SPA Max hold. Mark peak, Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.





5.2.4 Test Results

Temperature	24.4℃	Humidity	52.6%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage

Occupied Bandwidth

Modulation Type	Channel Separation	Operation Mode	Test Channel	Test Frequency (MHz)	Occupied Bandwidth (KHz)	
					99%	26dB
4FSK	12.5 KHz	TM1	L	406.1125	7.740	9.868
			M 1	430.1125	7.899	9.637
			M 2	453.2125	7.943	9.853
			M 3	459.625	7.749	9.585
			M 4	465.625	7.951	9.943
			H	469.9875	7.973	10.220
4FSK	12.5 KHz	TM2	L	406.1125	7.793	9.601
			M 1	430.1125	7.974	9.903
			M 2	453.2125	8.042	9.986
			M 3	459.625	7.822	9.935
			M 4	465.625	7.911	10.420
			H	469.9875	7.973	9.741
FM	12.5 KHz	TM3	L	406.1125	9.515	11.050
			M 1	430.1125	9.584	11.050
			M 2	453.2125	9.515	11.040
			M 3	459.625	9.540	11.050
			M 4	465.625	9.533	11.050
			H	469.9875	9.530	11.040
FM	12.5 KHz	TM4	L	406.1125	9.462	11.100
			M 1	430.1125	9.547	11.030
			M 2	453.2125	9.508	11.040
			M 3	459.625	9.377	11.040
			M 4	465.625	9.492	11.030
			H	469.9875	9.398	10.940
Limit			11.25KHz for 12.5KHz Channel Separation			
Test Results			PASS			

Remark:

2. Please refer to following plots.







99% and 26dB Bandwidth



TM1

TM1





406.1125 MHz

430.1125 MHz



453.2125 MHz

459.625 MHz



465.625 MHz

469.9875 MHz







99% and 26dB Bandwidth



TM2

TM2





406.1125 MHz

430.1125 MHz



453.2125 MHz

459.625 MHz



465.625 MHz

469.9875 MHz







99% and 26dB Bandwidth



TM3

TM3





406.1125 MHz

430.1125 MHz



453.2125 MHz

459.625 MHz



465.625 MHz

469.9875 MHz







99% and 26dB Bandwidth



TM4

TM4





406.1125 MHz

430.1125 MHz



453.2125 MHz

459.625 MHz



465.625 MHz

469.9875 MHz





Temperature	24.4°C	Humidity	52.6%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage

Emission Mask

Modulation Type	Channel Separation	Operation Mode	Test Channel	Test Frequency (MHz)	Applicable Mask	RBW (Hz)
4FSK	12.5 KHz	TM1	L	406.1125	D	100
			M 1	430.1125	D	100
			M 2	453.2125	D	100
			M 3	459.625	D	100
			M 4	465.625	D	100
			H	469.9875	D	100
4FSK	12.5 KHz	TM2	L	406.1125	D	100
			M 1	430.1125	D	100
			M 2	453.2125	D	100
			M 3	459.625	D	100
			M 4	465.625	D	100
			H	469.9875	D	100
FM	12.5 KHz	TM3	L	406.1125	D	300
			M 1	430.1125	D	300
			M 2	453.2125	D	300
			M 3	459.625	D	300
			M 4	465.625	D	300
			H	469.9875	D	300
FM	12.5 KHz	TM4	L	406.1125	D	300
			M 1	430.1125	D	300
			M 2	453.2125	D	300
			M 3	459.625	D	300
			M 4	465.625	D	300
			H	469.9875	D	300
Test Results			PASS			


Remark:

2. Please refer to following plots.





Emission Mask







Emission Mask



TM2

TM2





406.1125 MHz

430.1125 MHz



453.2125 MHz

459.625 MHz



465.625 MHz

469.9875 MHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com


Scan code to check authenticity




Emission Mask

TM3

TM3




Date: 21.MAY.2025 14:40:25




Date: 21.MAY.2025 14:50:22

406.1125 MHz

430.1125 MHz




Date: 21.MAY.2025 15:00:14




Date: 21.MAY.2025 15:09:06

453.2125 MHz

459.625 MHz



Date: 21.MAY.2025 15:17:37



Date: 21.MAY.2025 15:26:33

465.625 MHz


469.9875 MHz






Emission Mask

TM4




Date: 21.MAY.2025 14:43:48

TM4




Date: 21.MAY.2025 14:52:46

406.1125 MHz




Date: 21.MAY.2025 15:02:47

430.1125 MHz




Date: 21.MAY.2025 15:11:43

453.2125 MHz



Date: 21.MAY.2025 15:19:39

459.625 MHz



Date: 21.MAY.2025 15:28:53

465.625 MHz



469.9875 MHz



5.3. Transmitter Radiated Spurious Emission

5.3.1 Test Applicable


According to the ANSI C63.26:2015 test method, and according to Section 90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with 12.5 KHz channel bandwidth:

- 1 On any frequency removed from the centre of the authorized bandwidth f_0 to 5.625 KHz removed from f_0 : Zero dB
- 2 On any frequency removed from the centre of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 5.625 KHz but no more than 12.5 KHz: At least 7.27dB
- 3 On any frequency removed from the centre of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 12.5 KHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.


For transmitters designed to transmit with 25 KHz channel separation and equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as following:

- 1 On any frequency removed from the assigned frequency by more than 50 percent, but no more than 100 percent of the authorized bandwidth: At least 25 dB.
- 2 On any frequency removed from the assigned frequency by more than 100 percent, but no more than 250 percent of the authorized bandwidth: At least 35 dB.
- 3 On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log(P)$ dB.

5.3.2 Test Configuration



5.3.3 Test Arrangement



5.3.4 Test Procedure

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in six channels were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100 KHz, VBW=300 KHz for 30MHz to 1GHz, and the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. An amplifier should be connected to the Signal Source output port. And the cable should be connecting between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$





The measurement results are amending as described below:

$$\text{Power (EIRP)} = P_{\text{Mea}} - P_{\text{cl}} - G_a$$

6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15 \text{ dBi}$.

5.3.5 Limit

Modulation Type: 4FSK

FCC Part 90.210:

For 12.5 kHz bandwidth:

On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz at least:

Calculation: Limit (dBm) = $\text{EL} - 50 - 10 \log(\text{TP}) = -20 \text{ dBm}$

Notes: EL is the emission level of the Output Power expressed in dBm.

For 25 kHz bandwidth:

On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 62.5 kHz at least:

Calculation: Limit (dBm) = $\text{EL} - 43 - 10 \log_{10}(\text{TP}) = -13 \text{ dBm}$

Notes: EL is the emission level of the Output Power expressed in dBm.

Note: 1. In general, the worst case attenuation requirement shown above was applied.

2. The measurement frequency range from 9 KHz to 5 GHz.

3. *** means that the emission level is too low to be measured or at least 20 dB down than the limit.

4. ERP for below 1GHz and EIRP above 1GHz.

5.3.5 Test Results

Temperature	24.4°C	Humidity	52.6%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage

Remark:

1. Measured at TM1 to TM4, recorded worst case at TM1;

2. Please refer to following page.

3. All the modes have been tested and recorded worst mode in the report.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Modulation Type: 4FSK							
Operation Mode: TM1				Channel Separation:12.5KHz			
				Test Frequency:406.1125MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak EIRP (dBm)	Limit (dBm)	Polarization
906.34	-42.38	5.26	9.88	2.15	-35.61	-20.00	H
1359.50	-54.20	6.11	11.36	2.15	-46.80	-20.00	H
1812.66	-48.32	7.01	11.42	2.15	-41.76	-20.00	H
906.33	-50.49	5.26	9.88	2.15	-43.72	-20.00	V
1359.48	-52.51	6.11	11.36	2.15	-45.11	-20.00	V
1812.62	-58.23	7.01	11.42	2.15	-51.67	-20.00	V

Modulation Type: 4FSK							
Operation Mode: TM1				Channel Separation:12.5KHz			
				Test Frequency:430.1125MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak EIRP (dBm)	Limit (dBm)	Polarization
820.32	-42.38	5.26	9.88	2.15	-35.61	-20.00	H
1230.57	-53.04	6.11	11.36	2.15	-45.64	-20.00	H
1640.61	-48.51	7.01	11.42	2.15	-41.95	-20.00	H
820.30	-48.86	5.26	9.88	2.15	-42.09	-20.00	V
1230.48	-51.51	6.11	11.36	2.15	-44.11	-20.00	V
1640.62	-57.82	7.01	11.42	2.15	-51.26	-20.00	V

Modulation Type: 4FSK							
Operation Mode: TM1				Channel Separation:12.5KHz			
				Test Frequency: 453.2125MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak EIRP (dBm)	Limit (dBm)	Polarization
906.35	-42.36	5.39	9.38	2.15	-35.59	-20.00	H
1359.53	-54.12	5.67	11.02	2.15	-46.72	-20.00	H
1812.66	-48.39	6.59	10.98	2.15	-41.83	-20.00	H
906.33	-50.52	5.39	9.38	2.15	-43.75	-20.00	V
1359.43	-52.47	5.67	11.02	2.15	-45.07	-20.00	V
1812.62	-58.24	6.59	10.98	2.15	-51.68	-20.00	V

Modulation Type: 4FSK							
Operation Mode: TM1				Channel Separation:12.5KHz			
				Test Frequency: 459.624MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak EIRP (dBm)	Limit (dBm)	Polarization
906.30	-42.37	5.39	9.38	2.15	-35.60	-20.00	H
1359.47	-54.20	5.67	11.02	2.15	-46.80	-20.00	H
1812.57	-48.30	6.59	10.98	2.15	-41.74	-20.00	H
906.39	-50.42	5.39	9.38	2.15	-43.65	-20.00	V
1359.43	-52.50	5.67	11.02	2.15	-45.10	-20.00	V
1812.52	-58.32	6.59	10.98	2.15	-51.76	-20.00	V





Modulation Type: 4FSK							
Operation Mode: TM1				Channel Separation:12.5KHz			
				Test Frequency: 465.625MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak EIRP (dBm)	Limit (dBm)	Polarization
939.36	-42.47	5.28	9.37	2.15	-35.70	-20.00	H
1408.99	-53.62	5.62	10.9	2.15	-46.22	-20.00	H
1878.66	-46.49	6.73	10.83	2.15	-39.93	-20.00	H
939.35	-49.60	5.28	9.31	2.15	-42.83	-20.00	V
1408.99	-51.77	5.84	11.01	2.15	-44.37	-20.00	V
1878.56	-56.55	6.75	11.06	2.15	-49.99	-20.00	V

Modulation Type: 4FSK							
Operation Mode: TM1				Channel Separation:12.5KHz			
				Test Frequency: 469.9875MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak EIRP (dBm)	Limit (dBm)	Polarization
939.36	-42.49	5.28	9.37	2.15	-35.72	-20.00	H
1408.92	-53.60	5.62	10.9	2.15	-46.20	-20.00	H
1878.56	-46.44	6.73	10.83	2.15	-39.88	-20.00	H
939.30	-49.68	5.28	9.31	2.15	-42.91	-20.00	V
1408.99	-51.84	5.84	11.01	2.15	-44.44	-20.00	V
1878.66	-56.49	6.75	11.06	2.15	-49.93	-20.00	V

Notes:

- 1). Measuring frequencies from 9 KHz~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz;
- 2). Radiated emissions measured in frequency range from 9 KHz~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode;
- 3). Peak EIRP = P_{Mea} + Path Loss + Antenna Gain + Correction Value (2.15).





5.4. Spurious Emission on Antenna Port

5.4.1 Test Applicable


The same as Section 5.3

5.4.2 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set to 100 kHz. Sufficient scans were taken to show any out of band emission up to 10th. Harmonic for the lower and the highest frequency range. Set RBW 1KHz, VBW 3KHz in the frequency band 9KHz to 150KHz, set RBW 10KHz, VBW 30 KHz in the frequency band 150KHz to 30 MHz, set RBW 100 kHz, VBW 300 kHz in the frequency band 30MHz to 1GHz, while set RBW=1MHz, VBW=3MHz from the 1GHz to 10th Harmonic.

The audio input was set to 0 to get the unmodulated carrier, the resulting picture is print out for each channel separation.

5.4.3 Test Configuration



5.4.4 Limit

Modulation Type: 4FSK

FCC Part and 90.210:

For 12.5 kHz bandwidth:

On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz at least:

Calculation: Limit (dBm) = EL - 50 - 10log (TP) = -20 dBm

For 25 kHz bandwidth:

On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 62.5 kHz at least:

Calculation: Limit (dBm) = EL - 43 - 10log (TP) = -13 dBm

Notes: EL is the emission level of the Output Power expressed in dBm.

Note: 1. In general, the worst case attenuation requirement shown above was applied.

2. The measurement frequency range from 9 KHz to 6GHz.





5.4.5 Test Results

Temperature	22.6°C	Humidity	53.7%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage

Operation Mode	Test Channel	Test Frequency (MHz)	Measured Frequency Range	Spurious RF Conducted Emission (dBc)	Limits (dBc)	Verdict
TM1	L	406.1125	9 KHz – 6 GHz	<-20	-20	PASS
	M 1	430.1125	9 KHz – 6 GHz	<-20		
	M 2	453.2125	9 KHz – 6 GHz	<-20		
	M 3	459.625	9 KHz – 6 GHz	<-20		
	M 4	465.625	9 KHz – 6 GHz	<-20		
	H	469.9875	9 KHz – 6 GHz	<-20		


Remark:

1. Measured at TM1 to TM4, recorded worst case at TM1 ;
2. Please refer to following plot.
3. All the modes have been tested and recorded worst mode in the report.






Spurious Emission on Antenna Port TM1 /406.1125 MHz




30 MHz – 1 GHz




1 GHz – 5 GHz

TM1 /430.1125 MHz




30 MHz – 1 GHz




1 GHz – 5 GHz

TM1 /453.2125 MHz



30 MHz – 1 GHz



1 GHz – 5 GHz



Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com


Scan code to check authenticity



TM1 /459.625 MHz




30 MHz – 1 GHz




1 GHz – 5 GHz

TM1 /465.625 MHz




30 MHz – 1 GHz




1 GHz – 5 GHz

TM1 /469.9875 MHz



30 MHz – 1 GHz



1 GHz – 5 GHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5.5. Frequency Stability Test


5.5.1 Test Applicable

- 1 According to FCC Part 2 Section 2.1055 (a) (1), the frequency stability shall be measured with variation of ambient temperature from -30°C to +60°C centigrade.
- 2 According to FCC Part 2 Section 2.1055 (e) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
- 3 Vary primary supply voltage from 85 to 115 percent of the nominal value.
- 4 According to §90.213, the frequency stability limit is 2.5 ppm for 12.5KHz and 5.0ppm for 25KHz channel separation

5.5.2 Test Procedure

The EUT was set in the climate chamber and connected to an external DC power supply and AC power supply. The RF output was directly connected to Spectrum Analyzer ESCI3. The coupling loss of the additional cables was recorded and taken in account for all the measurements. After temperature stabilization (approx. 20 min for each stage), the frequency for the lower, the middle and the highest frequency range was recorded. For Frequency stability Vs. Voltage the EUT was connected to a DC power supply or AC power supply and the voltage was adjusted in the required ranges. The result was recorded.

5.5.3 Test Configuration



5.5.4 Test Limits

According to 90.213, Transmitters used must have minimum frequency stability as specified in the following table.

Frequency Range	Channel Bandwidth	Frequency Tolerance (ppm)		
		Fixed and Base Station	Mobile Stations	
			> 2W	≤ 2W
150-174MHz	6.25	1.0	2.0	2.0
	12.5	2.5	5.0	5.0
	25	5.0	5.0	50.0*
421-512MHz	6.25	0.5	1.0	1.0
	12.5	1.5	2.5	2.5
	25	2.5	5.0	5.0

* Stations operating in the 154.45 MHz or the 173.2 to 173.4 MHz bands must have a frequency stability of 5 ppm.

* Paging transmitters operating on paging-only frequencies must operate with frequency stability of 5 ppm in the 150-174 MHz band and 1.5 ppm in the 421-512 MHz band.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5.5.5 Test Results

Temperature	24.4℃	Humidity	52.6%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage

Operation Mode	Channel Separation	Test conditions		Frequency error (ppm)		
		Voltage(V)	Temp (℃)	406.1125	430.1125	453.2125
TM1	12.5KHz	7.6 V	-30	0.001	0.013	-0.002
			-20	0.000	0.012	0.000
			-10	0.000	0.002	-0.002
			0	-0.017	-0.012	-0.002
			10	0.019	0.021	0.015
			20	0.017	0.005	0.000
			30	0.002	0.004	-0.009
			40	-0.011	0.009	-0.002
			50	0.009	0.000	-0.018
		6.7(85% Rated)	20	-0.022	-0.007	-0.004
		8.7(115% Rated)	20	-0.002	0.003	0.002
Limit			2.5ppm			
Test Results			PASS			

Operation Mode	Channel Separation	Test conditions		Frequency error (ppm)		
		Voltage(V)	Temp (°C)	459.625	465.625	469.9875
TM1	12.5KHz	7.6 V	-30	-0.007	0.008	0.004
			-20	0.014	0.003	-0.009
			-10	0.000	0.001	-0.008
			0	-0.003	0.007	0.010
			10	0.004	-0.014	0.014
			20	-0.006	0.017	-0.004
			30	-0.002	-0.004	-0.010
			40	0.001	0.018	0.000
			50	0.003	0.000	-0.008
		6.7(85% Rated)	20	0.003	0.013	0.003
		8.7(115% Rated)	20	-0.012	-0.019	0.015
Limit			2.5ppm			
Test Results			PASS			

Remark:

1. Measured at TM1 to TM4, recorded worst case at TM1.
2. All the modes have been tested and recorded worst mode in the report.





5.6. Transient Frequency Behavior


5.6.1 Test Applicable

Section 90.214

Transient frequencies must be within the maximum frequency difference limits during the time intervals indicated:

Time intervals ^{1, 2}	Maximum frequency difference ³	All equipment	
		1500 to 174 MHz	421 to 512 MHz
Transient Frequency Behavior for Equipment Designed to Operate on 25KHz Channels			
t ₁ ⁴	± 25.0KHz	5.0ms	10.0ms
t ₁	± 12.5KHz	20.0ms	25.0ms
t ₃ ⁴	± 25.0KHz	5.0ms	10.0ms
Transient Frequency Behavior for Equipment Designed to Operate on 12.5KHz Channels			
t ₁ ⁴	±12.5KHz	5.0ms	10.0ms
t ₁	± 6.25KHz	20.0ms	25.0ms
t ₃ ⁴	± 12.5KHz	5.0ms	10.0ms
Transient Frequency Behavior for Equipment Designed to Operate on 6.25KHz Channels			
t ₁ ⁴	±6.25KHz	5.0ms	10.0ms
t ₁	± 3.125KHz	20.0ms	25.0ms
t ₃ ⁴	± 6.25KHz	5.0ms	10.0ms
1. t_{on} is the instant when a 1 KHz test signal is completely suppressed, including any capture time due to phasing. t₁ is the time period immediately following t_{on}. t₂ is the time period immediately following t₁. t₃ is the time period from the instant when the transmitter is turned off until t_{off}. t_{off} is the instant when 1 KHz test signal starts to rise. 2. During the time from the end of t₂ to the beginning of t₃, the frequency difference must not exceed the limits specified in 90.213. 3. Difference between the actual transmitter frequency and the assigned transmitter frequency. 4. If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency for this time period.			

5.6.2 Test Configuration



5.6.3 Test Procedure

According to TIA/EIA-603 2.2.19 requirement.






5.6.4 Test Results

Temperature	24.4°C	Humidity	52.6%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage

Measured at TM1 to TM4, recorded worst case at TM1.

Modulation Type: 4FSK





5.7. FCC §2.1047 - MODULATION CHARACTERISTIC

5.7.1 Test Applicable

Section 90.214

Transient frequencies must be within the maximum frequency difference limits during the time intervals indicated:

Applicable Standard

FCC §2. 1047

(a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.

(b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Procedure

Test Method: TIA-603-E 2.2.3

Test Data

Environmental Conditions

Temperature	24.4℃	Humidity	52.6%
Test Engineer	Jay Luo	Test Voltage	Normal Voltage


Test Mode: Transmitting

Test Result: Compliance. please refer to the following tables.




**Audio Frequency Response – High Power****12.5kHz:**

Carrier Frequency: 453.2125 MHz



**MODULATION LIMITING – High Power****12.5kHz**

Carrier Frequency: 453.2125 MHz





6. LIST OF MEASURING EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRVS	100444	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
2	Power Sensor	R&S	NRP-Z81	100458	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
3	Power Sensor	R&S	U2021	10057	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
4	Test Software	Tonscend	JS1120-2	/	N/A	N/A
5	RF Control Unit	Tonscend	JS0806-2	N/A	2024-11-08	2025-11-07
6	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2024-10-08	2025-10-07
7	DC Power Supply	Agilent	E3642A	N/A	2024-10-08	2025-10-07
8	EMI Test Software	AUDIX	E3	/	N/A	N/A
9	3m Semi Anechoic Chamber	Maorui	966	/	2023-10-12	2026-10-11
10	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2024-07-13	2027-07-12
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2024-08-03	2027-08-02
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2024-07-13	2027-07-12
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2024-07-13	2027-07-12
15	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2024-07-30	2027-07-29
16	EMI Test Receiver	R&S	ESR 7	101181	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
18	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2024-10-08	2025-10-07
19	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2024-10-08	2025-10-07
20	6dB Attenuator	/	100W/6dB	1172040	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
21	3dB Attenuator	/	2N-3dB	/	2024-10-08	2025-10-07
22	EMI Test Receiver	R&S	ESPI	101940	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
23	Artificial Mains	R&S	ENV216	101479	2024-06-06	2025-06-05
					2025-05-23	2026-05-22
24	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2024-06-06	2025-06-05
					2025-05-22	2026-05-21
25	EMI Test Software	Farad	EZ	/	N/A	N/A
26	Antenna Mast	Max-Full	MFA-515BSN	1308572	N/A	N/A
27	Pulse Limiter	R&S	ESH3-Z2	102750	2024-06-06	2025-06-05
					2025-05-23	2026-05-22



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----

