



RF Exposure Evaluation

For

TOALL Design Consulting (Shanghai) Co., Ltd

ata05 Humanized Teleoperated Robot

Test Model: ATA MPM-05

Prepared for : TOALL Design Consulting (Shanghai) Co., Ltd
Address : Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : June 17, 2025
Number of tested samples : 2
Sample No. : A250612026-1, A250612026-2
Serial number : Prototype
Date of Test : June 17, 2025 ~ August 28, 2025
Date of Report : August 29, 2025



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: (+86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



RF Exposure Evaluation	
Report Reference No.	LCSA06165039ED
Date of Issue	August 29, 2025
Testing Laboratory Name	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name	TOALL Design Consulting (Shanghai) Co., Ltd
Address	Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai, China
Test Specification	
Standard	FCC KDB publication 447498 D01 General RF Exposure Guidance v06 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091
Test Report Form No.	TRF-4-E-215 A/0
TRF Originator	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description : ata05 Humanized Teleoperated Robot	
Trade Mark	AIONIOS
Test Model	ATA MPM-05
Ratings	Please Refer to Page 6
Result	Pass

Compiled by:

Li Huan/ Administrator

Supervised by:

Jack Liu / Technique principal

Approved by:

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



RF Exposure Evaluation

Test Report No. : LCSA06165039ED	<u>August 29, 2025</u> Date of issue
---	---

EUT.....	: ata05 Humanized Teleoperated Robot
Test Model.....	: ATA MPM-05
Applicant.....	: TOALL Design Consulting (Shanghai) Co., Ltd
Address.....	: Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: TOALL Design Consulting (Shanghai) Co., Ltd
Address.....	: Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Kuender (Suzhou) Plastic Tech. Co., Ltd.
Address.....	: NO.9 Si-Ming RD, Wujiang City Jiangsu P.R.C
Telephone.....	: /
Fax.....	: /

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	August 29, 2025	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. Product Information.....	6
2. Evaluation Method.....	7
3. Limit.....	7
4. MPE Calculation Method.....	8
5. Antenna Information.....	8
6. Conducted Power.....	9
7. Manufacturing Tolerance.....	10
8. Measurement Results.....	13
9. Conclusion.....	14
10. Description of Test Facility.....	14
11. Measurement Uncertainty.....	14



**1. Product Information**

EUT	: ata05 Humanized Teleoperated Robot
Test Model	: ATA MPM-05
Ratings	: Input: DC 5V, 1.5A DC 3.7V by Rechargeable Li-ion Battery, 5200mAh
Hardware Version	: EC501_MB_V2.0
Software Version	: /
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 0.68dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 1.60dBi(Max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 1.60dBi(Max.)
Radar	:
Frequency Range	: 24.115GHz
Channel Number	: 1 Channel
Antenna Description	: Internal Antenna, 0.36dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.	





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density





4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/ External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Internal	Internal Antenna	2400MHz ~ 2500MHz 5000MHz ~ 6000MHz	2.4GWIFI: 0.68dBi 5GWIFI: 1.60dBi	WIFI Antenna



**6. Conducted Power****[2.4G WIFI]**

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	1	2412	13.96
	6	2437	13.08
	11	2462	13.47
IEEE 802.11g	1	2412	12.55
	6	2437	11.49
	11	2462	12.01
IEEE 802.11n HT20	1	2412	12.97
	6	2437	12.06
	11	2462	12.36
IEEE 802.11n HT40	3	2422	13.42
	6	2437	12.42
	9	2452	13.24

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	36	5180	9.77
	40	5200	9.33
	48	5240	9.13
11N20 SISO	36	5180	10.26
	40	5200	10.06
	48	5240	9.43
11N40 SISO	38	5190	9.49
	46	5230	8.87
11AC20 SISO	36	5180	10.3
	40	5200	9.67
	48	5240	8.96
11AC40 SISO	38	5190	10.35
	46	5230	9.53





[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	149	5745	12.4
	157	5785	11.55
	165	5825	11.65
11N20 SISO	149	5745	13.28
	157	5785	12.54
	165	5825	12.57
11N40 SISO	151	5755	12.09
	159	5795	11.29
11AC20 SISO	149	5745	13.25
	157	5785	12.56
	165	5825	12.7
11AC40 SISO	151	5755	12.06
	159	5795	11.29

Test Procedure

TX frequency range: 24.115GHz

Device category: Portable device (Distance: 20cm)

Max. Field Strength: 80.94dBuV/m @3m

EIRP=E-104.8+20logD=80.94-104.8+20log3=-14.32dBm

Maximum Conducted Output Power: -14.32dBm

7. Manufacturing Tolerance

[2.4G WIFI]

IEEE 802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	11.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	12.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0





[5.2G WIFI]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	10.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	9.0	8.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	9.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[5.8G WIFI]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	





[Radar]

Frequency(GHz)	24.115
Target (dBm)	-14.0
Tolerance ±(dB)	1.0





8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	14.0	25.1189	0.68	1.1695	0.0058	1.0000
IEEE 802.11g	13.0	19.9526	0.68	1.1695	0.0046	1.0000
IEEE 802.11n HT20	13.0	19.9526	0.68	1.1695	0.0046	1.0000
IEEE 802.11n HT40	14.0	25.1189	0.68	1.1695	0.0058	1.0000

[5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	10.0	10.0000	1.60	1.4454	0.0029	1.0000
IEEE 802.11n HT20	11.0	12.5893	1.60	1.4454	0.0036	1.0000
IEEE 802.11n HT40	10.0	10.0000	1.60	1.4454	0.0029	1.0000
IEEE 802.11ac VHT20	11.0	12.5893	1.60	1.4454	0.0036	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	1.60	1.4454	0.0036	1.0000

[5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	1.60	1.4454	0.0057	1.0000
IEEE 802.11n HT20	14.0	25.1189	1.60	1.4454	0.0072	1.0000
IEEE 802.11n HT40	13.0	19.9526	1.60	1.4454	0.0057	1.0000
IEEE 802.11ac VHT20	14.0	25.1189	1.60	1.4454	0.0072	1.0000
IEEE 802.11ac VHT40	13.0	19.9526	1.60	1.4454	0.0057	1.0000

[Radar]

Modulation Type	Maximum EIRP		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
FMCW	-13.0	0.0501	0	1.0000	0.00001	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.





8.2 Simultaneous Transmission MPE Evaluation

The EUT equipped with one 2.4GWIFI/5.2GWIFI/5.8GWIFI antenna, one Radar antenna. so need consider simultaneous transmission;
According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Simultaneous Transmission				
5.8GWIFI Antenna Max MPE ratios	Radar Antenna Max MPE ratios	Σ MPE ratios	Limit	Results
0.0072	0.00001	0.00721	1.0	Pass

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

11. Measurement Uncertainty

2.4GWIFI/5GWIFI:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

-----THE END OF REPORT-----

