

RF Exposure Evaluation
For
TOALL Design Consulting (Shanghai) Co., Ltd
ata05 Humanized Teleoperated Robot
Test Model: ATA MPM-05

Prepared for : TOALL Design Consulting (Shanghai) Co., Ltd
Address : Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai, China

Prepared by : Guangzhou LCS Compliance Testing Laboratory Ltd.
Address : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

Tel : (+86) 020-39166689
Fax : (+86) 020-39166619
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : February 05, 2026
Number of tested samples : 2
Sample No. : A250623055-1, A250623055-2
Serial number : Prototype
Date of Test : February 05, 2026 ~ April 01, 2026
Date of Report : April 02, 2026


RF Exposure Evaluation	
Report Reference No.	LCSC02056007ED
Date of Issue	April 02, 2026
Testing Laboratory Name	Guangzhou LCS Compliance Testing Laboratory Ltd.
Address	No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
Testing Location/ Procedure	Full application of Harmonised standards ☒ Partial application of Harmonised standards ☐ Other standard testing method ☐
Applicant's Name	TOALL Design Consulting (Shanghai) Co., Ltd
Address	Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai, China
Test Specification	
Standard	FCC KDB publication 447498 D01 General RF Exposure Guidance v06 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091
Test Report Form No.	TRF-4-E-215 A/0
TRF Originator	Guangzhou LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description	ata05 Humanized Teleoperated Robot
Trade Mark	AIONIOS
Test Model	ATA MPM-05
Ratings	Please Refer to Page 6
Result	Pass

Compiled by:



Lifeng Le / Administrators

Supervised by:



Justin Zhu/ Technique Director

Approved by:



Gavin Liang/ Manager

RF Exposure Evaluation

Test Report No. : LCSC02056007ED	<u>April 02, 2026</u> Date of issue
---	--

EUT.....	: ata05 Humanized Teleoperated Robot
Test Model.....	: ATA MPM-05
Applicant.....	: TOALL Design Consulting (Shanghai) Co., Ltd
Address.....	: Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai,
	: China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: TOALL Design Consulting (Shanghai) Co., Ltd
Address.....	: Room 225, No.501, Jiujiang Road, Huangpu District, Shanghai,
	: China
Telephone.....	: /
Fax.....	: /
Factory.....	: Kuender (Suzhou) Plastic Tech. Co., Ltd.
Address.....	: NO.9 Si-Ming RD, Wujiang City Jiangsu P.R.C
Telephone.....	: /
Fax.....	: /

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	April 02, 2026	Initial Issue	---

TABLE OF CONTENTS

Description	Page
1. Product Information.....	6
2. Evaluation Method.....	7
3. Limit.....	7
4. MPE Calculation Method.....	8
5. Antenna Information.....	8
6. Conducted Power.....	9
7. Manufacturing Tolerance.....	10
8. Measurement Results.....	13
9. Conclusion.....	14
10. Description of Test Facility.....	14
11. Measurement Uncertainty.....	14

1. Product Information

EUT	: ata05 Humanized Teleoperated Robot
Test Model	: ATA MPM-05
Ratings	: Input: DC 5V, 1.5A DC 3.7V by Rechargeable Li-ion Battery, 5200mAh
Hardware Version	: EC501_MB_V2.0
Software Version	: /
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 0.68dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 1.60dBi(Max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 1.60dBi(Max.)
Radar	:
Frequency Range	: 24.115GHz
Channel Number	: 1 Channel
Antenna Description	: Internal Antenna, 0.36dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.	

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/ External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Internal	Internal Antenna	2400MHz ~ 2500MHz 5000MHz ~ 6000MHz	2.4GWIFI: 0.68dBi 5GWIFI: 1.60dBi	WIFI Antenna

6. Conducted Power**[2.4G WIFI]**

Mode	Channel	Frequency (MHz)	Max Conducted Output Power (dBm)
IEEE 802.11b	1	2412	13.75
	6	2437	11.90
	11	2462	13.80
IEEE 802.11g	1	2412	11.90
	6	2437	10.82
	11	2462	12.61
IEEE 802.11n HT20	1	2412	13.35
	6	2437	11.31
	11	2462	13.00
IEEE 802.11n HT40	3	2422	12.99
	6	2437	11.77
	9	2452	11.60

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	36	5180	9.40
	40	5200	9.73
	48	5240	10.19
11N20 SISO	36	5180	9.52
	40	5200	9.52
	48	5240	10.38
11N40 SISO	38	5190	10.25
	46	5230	10.49
11AC20 SISO	36	5180	9.75
	40	5200	9.58
	48	5240	10.05
11AC40 SISO	38	5190	10.01
	46	5230	10.39

[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	149	5745	11.88
	157	5785	11.53
	165	5825	11.34
11N20 SISO	149	5745	12.14
	157	5785	11.62
	165	5825	11.40
11N40 SISO	151	5755	12.48
	159	5795	11.96
11AC20 SISO	149	5745	11.73
	157	5785	11.75
	165	5825	11.37
11AC40 SISO	151	5755	11.73
	159	5795	11.38

Test Procedure

TX frequency range: 24.115GHz

Device category: Portable device (Distance: 20cm)

Max. Field Strength: 94.51dBuV/m @3m

EIRP=E-104.8+20logD=94.51-104.8+20log3=-0.75dBm

Maximum Conducted Output Power: 0dBm

7. Manufacturing Tolerance

[2.4G WIFI]

IEEE 802.11b (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	11.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.0	10.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	11.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0

[5.2G WIFI]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[5.8G WIFI]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	11.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[Radar]

Frequency(GHz)	24.115
Target (dBm)	0
Tolerance ±(dB)	1.0

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	14.0	25.1189	0.68	1.1695	0.0058	1.0000
IEEE 802.11g	13.0	19.9526	0.68	1.1695	0.0046	1.0000
IEEE 802.11n HT20	14.0	25.1189	0.68	1.1695	0.0058	1.0000
IEEE 802.11n HT40	13.0	19.9526	0.68	1.1695	0.0046	1.0000

[5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	11.0	12.5893	1.60	1.4454	0.0036	1.0000
IEEE 802.11n HT20	11.0	12.5893	1.60	1.4454	0.0036	1.0000
IEEE 802.11n HT40	11.0	12.5893	1.60	1.4454	0.0036	1.0000
IEEE 802.11ac VHT20	11.0	12.5893	1.60	1.4454	0.0036	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	1.60	1.4454	0.0036	1.0000

[5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	12.0	15.8489	1.60	1.4454	0.0046	1.0000
IEEE 802.11n HT20	13.0	19.9526	1.60	1.4454	0.0057	1.0000
IEEE 802.11n HT40	13.0	19.9526	1.60	1.4454	0.0057	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	1.60	1.4454	0.0046	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	1.60	1.4454	0.0046	1.0000

[Radar]

Modulation Type	Maximum EIRP		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
FMCW	1.0	1.2589	0	1.0000	0.0003	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The EUT equipped with one 2.4GWIFI/5.2GWIFI/5.8GWIFI antenna, one Radar antenna. so need consider simultaneous transmission;
According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Simultaneous Transmission				
2.4GWIFI Antenna Max MPE ratios	Radar Antenna Max MPE ratios	Σ MPE ratios	Limit	Results
0.0058	0.0003	0.0061	1.0	Pass

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882

11. Measurement Uncertainty

2.4GWIFI/5GWIFI:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

-----THE END OF REPORT-----