



Report No.: PTC25112101701E-FC03

FCC TEST REPORT

FCC ID: 2BQG6-PW-5

Product	:	tracker wheel
Model Name	:	PW-5, PW-5T, PW-5H, PW-4, PW-6, PW-6H, PW-4T, PW-4H
Brand	:	N/A
Report No.	:	PTC25112101701E-FC03
Prepared for		
QUZHOU SANMAX HARDWARE TECHNOLOGY CO., LTD		
Room 36, No. 2 Juhai Rd., Qujiang District, Quzhou City, Zhejiang Province, China		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



TEST RESULT CERTIFICATION

Applicant's name : QUZHOU SANMAX HARDWARE TECHNOLOGY CO., LTD

Address : Room 36, No. 2 Juhai Rd., Qujiang District, Quzhou City, Zhejiang Province, China

Manufacture's name : QUZHOU SANMAX HARDWARE TECHNOLOGY CO., LTD

Address : Room 36, No. 2 Juhai Rd., Qujiang District, Quzhou City, Zhejiang Province, China

Product name : tracker wheel

Model name : PW-5, PW-5T, PW-5H, PW-4, PW-6, PW-6H, PW-4T, PW-4H

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Nov. 26, 2025 to Dec. 14, 2025

Date of Issue : Dec. 14, 2025

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7
4.5 EIRP POWER	8
4.6 TEST RESULT	8



Report No.: PTC25112101701E-FC03

2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC CFR47 Part 1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	tracker wheel
Model Name	:	PW-5
Additional model	:	PW-5T, PW-5H, PW-4, PW-6, PW-6H, PW-4T, PW-4H
Operation Frequency	:	BLE: 2402-2480MHz Lora: 902.3-914.9MHz
Number of Channel	:	BLE: 40 channels Lora: 64 Channels
Type of Modulation	:	BLE: GFSK Lora: FSK
Antenna installation	:	BLE: Ceramic antenna Lora: FPC Antenna
Antenna Gain	:	BLE: 5.19 dBi Lora: 1.34 dBi
Power supply	:	Battery: Li-ion Battery: ER18505M Rated Voltage: 3.6V Rated Capacity: 3500mAh 12.6Wh
Hardware Version	:	N/A
Software Version	:	N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2} \theta\varphi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



4.5 EIRP power

Freq. (MHz)	Field strength(max)(dBuV/m)	EIRP (max) (dBm)
902.3	89.68	-5.52
908.7	89.79	-5.41
914.9	89.47	-5.73
Note: $EIRP = E - 104.8 + 20 \log D$, Where E is the electric field strength in dBuV/m EIRP is the equivalent isotropically radiated power in dBm d is the specified measurement distance in m where $D=3$, $EIRP = E - 95.2$.		

4.6 Test Result

Item	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
908.7MHz	1.36	-5.41	-5.41±1	0.362243	0.000098	0.605800	Pass
2402MHz(BLE)	3.30	0.83	0.83±1	1.524053	0.001002	1.000000	Pass

Simultaneous MPE Evaluation:

The device can't support simultaneous transmitter.

*****THE END REPORT*****