

TEST REPORT

Applicant: Ladybird IoT LTD

Address: Holywell Park, Ashby Road, Charnwood Building LE
113AQ, LOUGHBOROUGH, United Kingdom

Product Name: LADYBIRD

FCC ID: 2BQGDLB

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to
C63.10a-2024*
KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: 2502U32383E-RF-00B

Report Date: 2025/9/17

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Reviewed By: Alice Tan

Title: RF Engineer

Pedro Yun

Approved By: Pedro Yun

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	5
1.4 EQUIPMENT MODIFICATIONS	5
2. SUMMARY OF TEST RESULTS	6
3. DESCRIPTION OF TEST CONFIGURATION	7
3.1 OPERATION FREQUENCY DETAIL	7
3.2 EUT OPERATION CONDITION	7
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	7
3.4 SUPPORT CABLE LIST AND DETAILS	7
3.5 BLOCK DIAGRAM OF TEST SETUP	8
3.6 TEST FACILITY	9
3.7 MEASUREMENT UNCERTAINTY	9
4. REQUIREMENTS AND TEST PROCEDURES	10
4.1 AC LINE CONDUCTED EMISSIONS	10
4.1.1 Applicable Standard	10
4.1.2 EUT Setup	11
4.1.3 EMI Test Receiver Setup	11
4.1.4 Test Procedure	12
4.1.5 Corrected Result& Margin Calculation	12
4.1.6 Test Result	12
4.2 RADIATION SPURIOUS EMISSIONS	13
4.2.1 Applicable Standard	13
4.2.2 EUT Setup	13
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	15
4.2.4 Test Procedure	15
4.2.5 Corrected Result & Margin Calculation	16
4.2.6 Test Result	16
4.3 MINIMUM 6 DB BANDWIDTH	17
4.3.1 Applicable Standard	17
4.3.2 EUT Setup	17
4.3.3 Test Procedure	17
4.3.4 Test Result	17
4.4 MAXIMUM CONDUCTED OUTPUT POWER	18
4.4.1 Applicable Standard	18
4.4.2 EUT Setup	18
4.4.3 Test Procedure	18
4.4.4 Test Result	18
4.5 MAXIMUM POWER SPECTRAL DENSITY	19

4.5.1 Applicable Standard	19
4.5.2 EUT Setup	19
4.5.3 Test Procedure	19
4.5.4 Test Result	19
4.6 CONDUCTED SPURIOUS EMISSION	20
4.6.1 Applicable Standard	20
4.6.2 EUT Setup	20
4.6.3 Test Procedure	20
4.6.4 Test Result	20
4.7 DUTY CYCLE	21
4.7.1 EUT Setup	21
4.7.2 Test Procedure	21
4.7.3 Judgment	21
4.8 ANTENNA REQUIREMENT	22
4.8.1 Applicable Standard	22
4.8.2 Judgment	22
5. Test DATA AND RESULTS	23
5.1 AC LINE CONDUCTED EMISSIONS	23
5.2 RADIATION SPURIOUS EMISSIONS	24
5.3 6dB EMISSION BANDWIDTH	33
5.4 MAXIMUM CONDUCTED OUTPUT POWER	35
5.5 POWER SPECTRAL DENSITY	37
5.6 CONDUCTED SPURIOUS EMISSION	39
5.7 DUTY CYCLE	41
EXHIBIT A - EUT PHOTOGRAPHS	42
EXHIBIT B - TEST SETUP PHOTOGRAPHS	43
EXHIBIT C - RF EXPOSURE EVALUATION	44
MAXIMUM PERMISSIBLE EXPOSURE (MPE)	44

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2502U32383E-RF-00B	Original Report	2025/9/17

1. GENERAL INFORMATION

1.1 General Description Of Equipment under Test

EUT Name:	LADYBIRD
EUT Model:	S
Operation Frequency:	903-914.2 MHz
Maximum Peak Output Power (Conducted):	9.4 dBm
Modulation Type:	CSS
Rated Input Voltage:	DC 4.5V from 3*1.5V battery (Two groups 4.5V batteries are connected in parallel)
Serial Number:	35HW-2
EUT Received Date:	2025/6/28
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail ▲

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Dipole	50	902-928MHz	2.0dBi
The design of compliance with §15.203:			
☒ Unit uses a permanently attached antenna.			
☐ Unit uses a unique coupling to the intentional radiator.			
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.			

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC Line Conducted Emissions	Not applicable
FCC §15.205,§15.209,§15.247(d)	Radiated Spurious Emission	Compliant
FCC §15.247(a)(2)	6dB Emission Bandwidth	Compliant
FCC §15.247(b)(1)	Maximum Conducted Output Power	Compliant
FCC §15.247(d)	Conducted Spurious Emission	Compliant
FCC §15.247(e)	Power Spectral Density	Compliant
FCC §15.203	Antenna Requirement	Compliant
FCC §15.247(i), §1.1310&§2.1091	Maximum Permissible Exposure(MPE)	Compliant
Note 1: Not applicable, the device was powered by battery when operating.		
Note 2: For Radiated Spurious Emissions 9kHz~1GHz, the maximum output power mode and channel was tested.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	903	5	909.4
2	904.6	6	911
3	906.2	7	912.6
4	907.8	8	914.2

Note: The above frequencies in bold were performed the test.

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:	MurataLoRaModuleTestTool(v0.0.02)		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
Lora	10	10	10


3.3 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Unknown	Water Sensor	Unknown	EMWS-001
Unknown	Light Sensor	Unknown	EMLS-005

3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	no	no	2	Water Sensor	EUT
DC Cable	no	no	2	Light Sensor	EUT

3.5 Block Diagram of Test Setup



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz: 5.47 dB, 26.5GHz~40GHz: 5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground[protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Result& Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor=attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions


4.2.1 Applicable Standard



FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2.2 EUT Setup

9kHz-30MHz:



30MHz~1GHz:**Above 1GHz:**

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz-150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz-30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30 MHz-1000 MHz	Peak	120 kHz	500 kHz	/	PK
	QP	/	/	120 kHz	QP

Above 1GHz:

Pre-scan:

Frequency Range	Measurement	RBW	Video B/W	Detector
Above 1 GHz	Peak	1MHz	3 MHz	PK
	AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was required in Quasi-peak measurement for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average measurement, peak and Average measurement for frequencies above 1 GHz.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

4.2.5 Corrected Result & Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in μ V/m

E_{Log} is the field strength of the emission, in dB μ V/m

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{limit-measure} = E_{limit-Standard} + 40 \times \log_{10} (d_{standard}/d_{measure})$$

The basic equation is as follows:

$$\text{Result} = \text{Reading} + \text{Factor}$$

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Result}$$

4.2.6 Test Result

Please refer to section 5.2.


4.3 Minimum 6 dB Bandwidth

4.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

4.3.2 EUT Setup



4.3.3 Test Procedure

According to ANSI C63.10-2020 Section 11.8

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

4.3.4 Test Result

Please refer to section 5.3.


4.4 Maximum Conducted Output Power

4.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.4.3 Test Procedure

According to ANSI C63.10-2020 Section 11.9.1.1

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Set span $\geq [3 \times \text{RBW}]$.
- Sweep time = No faster than coupled (auto) time.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

4.4.4 Test Result

Please refer to section 5.4.


4.5 Maximum power spectral density

4.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.5.3 Test Procedure

According to ANSI C63.10-2020 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span > 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

4.5.4 Test Result

Please refer to section 5.5.


4.6 Conducted Spurious Emission

4.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.6.2 EUT Setup



4.6.3 Test Procedure

According to ANSI C63.10-2020 Section 11.11


- Set the center frequency and span to encompass frequency range to be measured.
 - Set the RBW = 100 kHz.
 - Set the VBW $\geq [3 \times \text{RBW}]$.
 - Detector = peak.
 - Sweep time = No faster than coupled (auto) time.
 - Trace mode = max hold.
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum amplitude level.
- Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

4.6.4 Test Result

Please refer to section 5.6.

4.7 Duty Cycle

4.7.1 EUT Setup



4.7.2 Test Procedure

According to ANSI C63.10-2020 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.7.3 Judgment

Report only, please refer to section 5.7.

4.8 Antenna Requirement

4.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.8.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Not applicable, the device was powered by battery when operating.

5.2 Radiation Spurious Emissions

1)9kHz - 1GHz

Serial Number:	35HW-2	Test Date:	2025/7/23
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Ethan Wu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	40	ATM Pressure: (kPa)	99.6
----------------------	------	---------------------------	----	---------------------------	------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-2	2024/4/16	2027/4/15
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2025/7/1	2026/6/30
Sonoma	Amplifier	310N	372193	2024/8/16	2025/8/15
R&S	EMI Test Receiver	ESCI	100224	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Please refer to the below plots.

Note: Low channel was tested.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Project No.: 2502U32383E-RF


Serial No.: 35HW-2

Polarization: Parallel

Tester: Ethan Wu

Test Mode: Transmitting


Note: RBW:200Hz,VBW:1kHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.014	56.52	0.12	56.64	124.77	68.13	Peak
2	0.022	55.73	-1.58	54.15	120.74	66.59	Peak
3	0.024	55.32	-2.00	53.32	119.89	66.57	Peak
4	0.026	55.28	-2.38	52.90	119.19	66.29	Peak
5	0.039	55.26	-4.05	51.21	115.69	64.48	Peak
6	0.053	53.76	-5.16	48.60	113.17	64.57	Peak

Project No.: 2502U32383E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: RBW:9kHz,VBW:30kHz

Serial No.: 35HW-2
Tester: Ethan Wu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.150	67.20	-12.10	55.10	104.08	48.98	Peak
2	0.595	80.55	-25.47	55.08	72.08	17.00	Peak
3	1.227	75.07	-30.19	44.88	65.66	20.78	Peak
4	1.762	72.03	-31.63	40.40	69.54	29.14	Peak
5	2.422	69.57	-32.46	37.11	69.54	32.43	Peak
6	11.257	65.44	-33.73	31.71	69.54	37.83	Peak

30MHz-1GHz

Project No.: 2502U32383E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: RBW:100kHz,VBW:300kHz


Serial No.: 35HW-2
Tester: Ethan Wu



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	34.85	43.38	-7.12	36.26	40.00	3.74	QP
2	83.35	49.32	-16.64	32.68	40.00	7.32	QP
3	94.67	52.40	-15.33	37.07	43.50	6.43	QP
4	143.17	50.42	-10.90	39.52	43.50	3.98	QP
5	215.92	52.49	-12.21	40.28	43.50	3.22	QP
6	287.05	51.81	-9.71	42.10	46.00	3.90	QP

Project No.: 2502U32383E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: RBW:100kHz,VBW:300kHz

Serial No.: 35HW-2
Tester: Ethan Wu



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	38.08	46.12	-9.49	36.63	40.00	3.37	QP
2	83.35	49.29	-16.64	32.65	40.00	7.35	Peak
3	94.67	52.03	-15.33	36.70	43.50	6.80	Peak
4	143.17	48.72	-10.90	37.82	43.50	5.68	QP
5	191.67	48.07	-12.30	35.77	43.50	7.73	Peak
6	468.12	41.41	-4.66	36.75	46.00	9.25	Peak

2) 1-10GHz:

Serial Number:	35HW-2		Test Date:	2025/7/23	
Test Site:	Chamber B		Test Mode:	Transmitting	
Tester:	Alan Xie		Test Result:	Pass	
Environmental Conditions:					
Temperature: (°C)	24.9	Relative Humidity: (%)	42	ATM Pressure: (kPa)	99.6
Test Equipment List and Details:					
Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2024/11/17	2025/11/16
AH	Preamplifier	PAM-0118P	469	2025/4/11	2026/4/10
R&S	Spectrum Analyzer	FSV40	101944	2024/9/6	2025/9/5
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2024/8/27	2025/8/26
E-Microwave	Band Rejection Filter	OBF-ZP-902-928-SMAF	OE01902428	2025/6/6	2026/6/5

* Statement of Traceability: Bay Area Compliance Laboratories Corp.(Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below plots.


1-10GHz:

Low Channel, Horizontal

Project No.: 2502U32383E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: Lora_500k low channel 903MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1063.30	50.11	-11.50	38.61	74.00	35.39	Peak

Low Channel, Vertical

Project No.: 2502U32383E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: Lora_500k low channel 903MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1062.64	55.38	-11.50	43.88	74.00	30.12	Peak

Project No.: 2502U32383E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: Lora_500k low channel 903MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1806.00	48.87	-13.56	35.31	74.00	38.69	Peak
2	2709.00	47.27	-12.20	35.07	74.00	38.93	Peak
3	3612.00	46.60	-9.95	36.65	74.00	37.35	Peak
4	9893.86	48.51	1.58	50.09	74.00	23.91	Peak

Project No.: 2502U32383E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: Lora_500k low channel 903MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1806.00	47.46	-13.56	33.90	74.00	40.10	Peak
2	2709.00	47.36	-12.20	35.16	74.00	38.84	Peak
3	3612.00	48.20	-9.95	38.25	74.00	35.75	Peak
4	9921.70	49.35	1.62	50.97	74.00	23.03	Peak

Middle Channel, Horizontal

Project No.: 2502U32383E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: Lora_500k middle channel 907.8MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35MH-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1062.40	50.38	-11.50	38.88	74.00	35.12	Peak

Middle Channel, Vertical

Project No.: 2502U32383E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: Lora_500k middle channel 907.8MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 35MH-2
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1061.80	55.50	-11.50	44.00	74.00	30.00	Peak

Project No.: 2502U32383E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: Lora_500k middle channel 907.8MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 35MH-2
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1815.60	49.97	-13.60	36.37	74.00	37.63	Peak
2	2723.40	47.27	-12.19	35.08	74.00	38.92	Peak
3	3631.20	46.13	-9.89	36.24	74.00	37.76	Peak
4	9284.86	49.72	0.63	50.35	74.00	23.65	Peak

Project No.: 2502U32383E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: Lora_500k middle channel 907.8MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35MH-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1815.60	47.99	-13.60	34.39	74.00	39.61	Peak
2	2723.40	47.18	-12.19	34.99	74.00	39.01	Peak
3	3631.20	46.56	-9.89	36.67	74.00	37.33	Peak
4	9994.78	48.57	1.78	50.35	74.00	23.65	Peak

High Channel, Horizontal

Project No.: 2502U32383E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: Lora_500k high channel 914.2MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1062.28	50.30	-11.50	38.80	74.00	35.20	Peak

High Channel, Vertical

Project No.: 2502U32383E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: Lora_500k high channel 914.2MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1061.92	55.80	-11.50	44.30	74.00	29.70	Peak

Project No.: 2502U32383E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: Lora_500k high channel 914.2MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1828.40	46.53	-13.66	32.87	74.00	41.13	Peak
2	2742.60	47.29	-12.15	35.14	74.00	38.86	Peak
3	3656.80	46.75	-9.81	36.94	74.00	37.06	Peak
4	9923.44	48.82	1.62	50.44	74.00	23.56	Peak

Project No.: 2502U32383E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: Lora_500k high channel 914.2MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 35HW-2
Tester: Alan Xie

Date: 2025-07-23



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1828.40	46.63	-13.66	32.97	74.00	41.03	Peak
2	2742.60	47.78	-12.15	35.63	74.00	38.37	Peak
3	3656.80	46.59	-9.81	36.78	74.00	37.22	Peak
4	9921.70	48.65	1.62	50.27	74.00	23.73	Peak

5.3 6dB Emission Bandwidth

Serial No.:	35HW-2	Test Date:	2025/8/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Conor Fu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	27.1	Relative Humidity: (%)	48	ATM Pressure: (kPa)	100.9
-----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2024/9/5	2025/9/4
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/6/6	2026/6/5
Micro-Coax	Coaxial Cable	UFB205A	323308-024	2025/6/1	2026/5/31

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Test Channel	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
Lowest	903	0.801	≥0.5
Middle	907.8	0.801	≥0.5
Highest	914.2	0.801	≥0.5

Low Channel




ProjectNo.:2502U32383E-RF Tester:Conor Fu
Date: 15.AUG.2025 19:25:51

Middle Channel



ProjectNo.:2502U32383E-RF Tester:Conor Fu
Date: 15.AUG.2025 19:30:15

High Channel



ProjectNo.:2502U32383E-RF Tester:Conor Fu
Date: 15.AUG.2025 19:32:09

5.4 Maximum Conducted Output Power

Serial No.:	35HW-2	Test Date:	2025/7/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Conor Fu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.8	Relative Humidity: (%)	51	ATM Pressure: (kPa)	100.1
-------------------------------	------	---------------------------------------	----	--------------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2024/9/5	2025/9/4
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/6/6	2026/6/5
Micro-Coax	Coaxial Cable	UFB205A	323308-024	2025/6/1	2026/5/31

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Test Channel	Test Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Limit (dBm)
Lowest	903	9.40	≤30
Middle	907.8	9.26	≤30
Highest	914.2	9.13	≤30

Low Channel




ProjectNo.:2502U32383E-RF Tester:Conor Fu
Date: 11.JUL.2025 10:30:27

Middle Channel



ProjectNo.:2502U32383E-RF Tester:Conor Fu
Date: 11.JUL.2025 10:31:50

High Channel



ProjectNo.:2502U32383E-RF Tester:Conor Fu
Date: 11.JUL.2025 10:33:10

5.5 Power Spectral Density

Serial No.:	35HW-2	Test Date:	2025/7/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Conor Fu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.8	Relative Humidity: (%)	51	ATM Pressure: (kPa)	100.1
-----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2024/9/5	2025/9/4
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/6/6	2026/6/5
Micro-Coax	Coaxial Cable	UFB205A	323308-024	2025/6/1	2026/5/31

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Test Channel	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
Lowest	903	2.87	≤8.00
Middle	907.8	2.60	≤8.00
Highest	914.2	2.67	≤8.00


Low Channel



Middle Channel



High Channel



5.6 Conducted Spurious Emission

Serial No.:	35HW-2	Test Date:	2025/9/17
Test Site:	RF	Test Mode:	Transmitting
Tester:	Conor Fu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	27.6	Relative Humidity: (%)	62	ATM Pressure: (kPa)	100.6
-----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2025/7/28	2026/7/27
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/6/6	2026/6/5
Micro-Coax	Coaxial Cable	UFB205A	323308-024	2025/6/1	2026/5/31

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Note: The maximum path attenuation of 30MHz-10GHz was added into the offset.

Low Channel 1




ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:29:36

Low Channel 2




ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:30:58

Low Channel_3




ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:32:33

Middle Channel_1




ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:33:33

Middle Channel_1




ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:34:12

High Channel_1




ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:35:15

High Channel_2



ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:38:06

High Channel_3



ProjectNo.:2502U32383E-RFTester:Conor Fu
Date: 17.SEP.2025 15:38:29

5.7 Duty Cycle

Serial No.:	35HW-2	Test Date:	2025/7/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Conor Fu	Test Result:	N/A

Environmental Conditions:

Temperature: (°C):	26.8	Relative Humidity: (%)	51	ATM Pressure: (kPa)	100.1
-----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2024/9/5	2025/9/4
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/6/6	2026/6/5
Micro-Coax	Coaxial Cable	UFB205A	323308-024	2025/6/1	2026/5/31

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Frequency (MHz)	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW Setting (kHz)
907.8	100	100	100.00	/	0.01

Middle Channel




EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2502U32383E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2502U32383E-RF-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2502U32383E-RF-00B-TSP TEST SETUP PHOTOGRAPHS.

EXHIBIT C - RF EXPOSURE EVALUATION

Maximum Permissible Exposure (MPE)

Applicable Standard

According to subpart §1.1310,15.247(i) systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain [▲]		Conducted output power including Tune-up Tolerance [▲]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Lora-FHSS	902.3-914.9	2.0	1.58	9.5	8.91	20.00	0.003	0.6
Lora-DTS	903-914.2	2.0	1.58	9.5	8.91	20.00	0.003	0.6

Note:

The Antenna Gain and Conducted output power including Tune-up Tolerance provided by manufacturer.

Lora-FHSS and Lora-DTS can't transmit simultaneously.

Result: The device meet FCC MPE at 20 cm distance

***** END OF REPORT *****