



REPORT No.: SZ26060442E01

TEST REPORT

APPLICANT : DAMASCO TRADING LLC

PRODUCT NAME : Smart phone

MODEL NAME : M500, M400, M350

BRAND NAME : DAMASCO

FCC ID : 2BQHT-MOBM400

STANDARD(S) : 47 CFR Part 15 Subpart B

RECEIPT DATE : 2026-07-06

TEST DATE : 2026-07-14 to 2026-07-30

ISSUE DATE : 2026-08-07



Edited by: Chen Bilian
Chen Bilian(Rapporteur)

Approved by: Xiao Xiong
Xiao Xiong(Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information.....	3
1.2. Equipment Under Test (EUT) Description	3
2. Test Results.....	7
2.1. Applied Reference Documents	7
2.2. EUT Setup and Operating Conditions.....	8
3. 47 CFR Part 15B Requirements.....	10
3.1. Conducted Emission	10
3.2. Radiated Emission	14
Annex A Test Uncertainty	21
Annex B Testing Laboratory Information	22
Notes	25

Change History		
Version	Date	Reason for Change
1.0	2026-08-07	First edition

Note: the latest revision of the report supersedes all previous version.



1. Technical Information

Note: Provide by applicant

1.1. Applicant and Manufacturer Information

Applicant:	DAMASCO TRADING LLC
Applicant Address:	3847 NE 168TH ST APT 3C NORTH MIAMI BEACH 33160 FLORIDA USA
Manufacturer:	DAMASCO TRADING LLC
Manufacturer Address:	3847 NE 168TH ST APT 3C NORTH MIAMI BEACH 33160 FLORIDA USA

1.2. Equipment Under Test (EUT) Description

Product Name:	Smart phone
EUT No.:	26#
Hardware Version:	V1.0
Software Version:	M500: M500-16 M400: M400-16 M350: M350-16
Tx Frequency:	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 40: 2300 MHz ~ 2400 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 66: 1710 MHz ~ 1780 MHz Bluetooth: 2402 MHz ~ 2480 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/ac/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz;



MORLAB



	Model No.:	TM680H1
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	6800mAh
	Rated Voltage:	3.85V
	Charge Limit:	4.45V
	Manufacturer:	Guangdong Highpower New Energy Technology Co., Ltd
	Battery 2 (for M350)	
	Brand Name:	N/A
	Model No.:	TM490H3
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	4900mAh
	Rated Voltage:	3.85V
	Charge Limit:	4.4V
	Manufacturer 1:	Guangdong Highpower New Energy Technology Co., Ltd
	Manufacturer 2:	Guangdong Fenghua New Energy Co.,Ltd.
	USB Cable	
	Model:	TP-C0020-B1
	Manufacturer:	Guangdong Wivtak Technology Co., Ltd.

Note:

1. According to the certificate holder, they declared that the product name: Smart phone, with model name: M500, M400, M350. This phone series includes four SKUs (SKU2, SKU1, SKU3, and SKU4), with three model numbers in total to meet different market demands. Specifically, SKU1 and SKU2 share the same model number M500, SKU3 is designated as model M400, and SKU4 is designated as model M350. The differences among the four SKUs are detailed below, with SKU2 serving as the primary test model.
 - 1) SKU1 vs. SKU2: Memory difference. SKU2 is equipped with 64+4 GB DDR3 memory, while SKU1 is equipped with 128+4 GB DDR4 memory.
 - 2) SKU3 vs. SKU2: Rear camera and adapter difference. SKU2 is equipped with a 50 MP rear camera and a 45 W adapter, while SKU3 is equipped with a 13 MP rear camera and a 15 W adapter.



- 3) SKU4 vs. SKU2: Differences in memory, rear camera, battery, and adapter. SKU2 is equipped with 64+4 GB DDR3 memory, a 50 MP rear camera, a 6800 mAh battery, and a 45 W adapter, while SKU4 is equipped with 32+3 GB DDR3 memory, a 13 MP rear camera, a 4900 mAh battery, and a 15 W adapter.

Each SKU also includes primary and secondary source materials. The secondary source materials are as follows: PMU chip, PCB, charging IC, memory, shielding cover, MIC, LCM, camera, AI key, fingerprint module, battery, speaker, earpiece, motor, card holder, housing, FPC, auxiliary materials, etc. Except for the memory, all other materials are identical in specifications and are pin-to-pin compatible, with only the manufacturer differing.

The main test model name is SKU2 (M500), all models have been tested. Only the result for M500 was recorded in this report. For the Conducted Emission, only the worst case [SKU3 (M400), secondary source] is recorded in this report. For the Radiated Emission, only the worst case [SKU2 (M500), primary source] is recorded in this report.

2. There are two kinds of adapters, both adapters have been tested. For the Conducted Emission, only the worst case (Adapter 2) is recorded in this report. For the Radiated Emission, only the worst case (Adapter 1) is recorded in this report.
3. The declarations of EUT presented in the report are provided by applicant, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to specification or user's manual supplied by the applicant.



2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.107	Conducted Emission	2026.07.30	Wang Yapeng	PASS	/
2	15.109	Radiated Emission	2026.07.14 to 2026.07.20	Wang Deyong	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".



2.2. EUT Setup and Operating Conditions

Note: All of the following test modes are tested in all the test items.

Test Item	
Mode 1 :	EUT + GSM850 Idle + Bluetooth Idle + 2.4G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 2 :	EUT + GSM1900 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 3 :	EUT + WCDMA Band II Idle + Bluetooth Idle + 2.4G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 4 :	EUT + WCDMA Band IV Idle + Bluetooth Idle + 5G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 5 :	EUT + WCDMA Band V Idle + Bluetooth Idle + 2.4G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 6 :	EUT + LTE Band 2 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 7 :	EUT + LTE Band 4 Idle + Bluetooth Idle + 2.4G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 8 :	EUT + LTE Band 5 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 9 :	EUT + LTE Band 7 Idle + Bluetooth Idle + 2.4G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 10 :	EUT + LTE Band 13 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 11 :	EUT + LTE Band 26 Idle + Bluetooth Idle + 2.4G WLAN Idle + GPS Rx + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 12 :	EUT + LTE Band 38 Idle + Bluetooth Idle + 5G WLAN Idle + Galileo Rx + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 13 :	EUT + LTE Band 40 Idle + Bluetooth Idle + 2.4G WLAN Idle + BDS Rx + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 14 :	EUT + LTE Band 41 Idle + Bluetooth Idle + 5G WLAN Idle + GLONASS Rx + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 15 :	EUT + LTE Band 66 Idle + Bluetooth Idle + 2.4G WLAN Idle + FM Rx + Battery + AC Adapter + USB Cable + Earphone + SIM Card
Mode 16 :	EUT + WCDMA Band V Idle + Bluetooth Idle + 2.4G WLAN Idle + Battery + USB Cable + Earphone + SIM Card + Notebook + Data Transmission Mode
Mode 17 :	EUT + LTE Band 2 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card + Rear Camera Mode



Mode 18 :	EUT + LTE Band 5 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card + Front Camera Mode
Mode 19 :	EUT + LTE Band 7 Idle + Bluetooth Idle + 2.4G WLAN Idle + Battery + AC Adapter + USB Cable + Earphone + SIM Card + Play 1kHz Color Bar Video
Mode 20 :	EUT + LTE Band 13 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + SIM Card + Type-C Earphone + Play 1kHz Color Bar Video
Mode 21 :	EUT + WCDMA Band IV Idle + Bluetooth Idle + 5G WLAN Idle + Battery + USB Cable + Earphone + SIM Card + Mobile Phone + OTG Reverse Charging Mode
Mode 22 :	EUT + LTE Band 5 Idle + Bluetooth Idle + 5G WLAN Idle + Battery + SIM Card + Notebook + Notebook Adapter + USB Cable + Earphone + Indirect Supply Mode
Remark: The above test mode in boldface (Mode 17) was the worst case of conducted emission test, only the test data of this mode was reported. The above test mode in boldface (Mode 18) was the worst case of radiated emission test, only the test data of this mode was reported.	

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

3. 47 CFR Part 15B Requirements

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor,



and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.

3.1.3. Test Result

Set RBW=9 kHz, VBW=30 kHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}] = U_R [\text{dB}\mu\text{V}] + L_{\text{Cable loss}} [\text{dB}] + A_{\text{Factor}} [\text{dB}]$$


U_R : Receiver Reading

A_{Factor} : Voltage Division Factor of LISN


$L_{\text{Cable loss}}$: Correction Factor Contains Pulse Limiter and Cable

During the test, the total correction Factor $L_{\text{Cable loss}}$ and A_{Factor} were built in test software.

A. Test Plot and Suspicious Points:



No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quasi-peak	Average	Quasi-peak	Average		
1	0.4650	41.12	29.58	56.60	46.60	Line	PASS
2	0.5505	47.16	36.91	56.00	46.00		PASS
3	0.5865	44.46	33.83	56.00	46.00		PASS
4	0.6496	42.76	33.51	56.00	46.00		PASS
5	1.1040	40.29	29.30	56.00	46.00		PASS
6	21.9926	41.00	28.03	60.00	50.00		PASS



No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quasi-peak	Average	Quasi-peak	Average		
1	0.5415	47.00	41.33	56.00	46.00	Neutral	PASS
2	0.6090	40.64	34.49	56.00	46.00		PASS
3	0.6540	41.21	35.92	56.00	46.00		PASS
4	1.0185	38.70	32.78	56.00	46.00		PASS
5	1.1356	37.60	31.59	56.00	46.00		PASS
6	21.6144	35.52	23.48	60.00	50.00		PASS



3.2. Radiated Emission

3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency Range (MHz)	Field Strength Limitation at 3m Measurement Dist	
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dB $\mu\text{V/m}$ is calculated by 20log Emission Level($\mu\text{V/m}$).


3.2.2. Frequency Range of Measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

3.2.3. Test Setup

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on variable-height antenna master tower.

For the test Antenna:

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

For measurements below 1GHz the resolution bandwidth is set to 120 kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video bandwidth is set to 3MHz for peak measurements and as applicable for average measurements.

3.2.4. Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions which (6GHz-30GHz) are attenuated more than 20 dB below the permissible value need not be reported.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R \text{ [dB}\mu\text{V]} + A_T \text{ [dB]} + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna


U_R : Receiver Reading

G_{preamp} : Preamplifier Gain


A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.




No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	40.3800	24.70	N.A	N.A	N.A	40.00	N.A	V	PASS
2	54.6405	20.55	N.A	N.A	N.A	40.00	N.A	V	PASS
3	105.7646	26.49	N.A	N.A	N.A	43.50	N.A	V	PASS
4	158.9259	18.85	N.A	N.A	N.A	43.50	N.A	V	PASS
5	228.1908	24.51	N.A	N.A	N.A	46.00	N.A	V	PASS
6	383.9884	31.87	N.A	N.A	N.A	46.00	N.A	V	PASS



No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1136.5000	N.A	N.A	30.74	74.00	N.A	54.00	V	PASS
2	1861.0000	N.A	N.A	28.07	74.00	N.A	54.00	V	PASS
3	2399.5000	N.A	N.A	34.51	74.00	N.A	54.00	V	PASS
4	3714.0000	N.A	N.A	36.00	74.00	N.A	54.00	V	PASS
5	4833.0000	N.A	N.A	40.44	74.00	N.A	54.00	V	PASS
6	5552.5000	N.A	N.A	42.22	74.00	N.A	54.00	V	PASS



No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	33.8804	24.45	N.A	N.A	N.A	40.00	N.A	H	PASS
2	86.9447	23.11	N.A	N.A	N.A	40.00	N.A	H	PASS
3	104.3094	23.62	N.A	N.A	N.A	43.50	N.A	H	PASS
4	219.4599	30.81	N.A	N.A	N.A	46.00	N.A	H	PASS
5	227.6088	31.01	N.A	N.A	N.A	46.00	N.A	H	PASS
6	383.9884	40.09	N.A	N.A	N.A	46.00	N.A	H	PASS



No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1136.5000	N.A	N.A	29.66	74.00	N.A	54.00	H	PASS
2	2356.0000	N.A	N.A	33.55	74.00	N.A	54.00	H	PASS
3	3235.0000	N.A	N.A	34.51	74.00	N.A	54.00	H	PASS
4	3925.5000	N.A	N.A	37.95	74.00	N.A	54.00	H	PASS
5	4945.0000	N.A	N.A	41.45	74.00	N.A	54.00	H	PASS
6	5927.5000	N.A	N.A	42.30	74.00	N.A	54.00	H	PASS



Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	9kHz-150kHz	2.1dB
	150kHz-30MHz	2.8dB

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	30MHz-200MHz	4.3dB
	200MHz-1000MHz	4.4dB
	1GHz-6GHz	4.7dB
	6GHz-18GHz	5.2dB
	18GHz-40GHz	5.3dB



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory:	The FCC designation number is CN1192. Test firm registration number is 226174. (Shenzhen Morlab Communications Technology Co., Ltd.)
---------------------------------------	--

4. Test Software Utilized

Model	Version Number	Producer
TS+ -[JS32-RE]	Version 2.5.0.6	Tonscend
TS+ -[JS32-CE]	Version 2.5.0.0	Tonscend

**5. Test Equipments Utilized**

Description	Model	Serial No.	Manufacturer	Cal. Date	Due. Date
Bi-Log Antenna	VULB 9163	9163-519	SCHWARZBECK	2025/8/18	2026/8/17
Horn Antenna	BBHA 9120D	01774	SCHWARZBECK	2026/5/30	2027/5/29
Horn Antenna	BBHA9170	BBHA9170 #773	SCHWARZBECK	2026/5/30	2027/5/29
Receiver	N9038A	MY541300 16	Agilent	2025/12/26	2026/12/25
Preamplifier	S020180L3203	61171/611 72	LUCIX CORP.	2026/5/7	2027/5/6
Preamplifier	S10M100L3802	46732	LUCIX CORP.	2026/5/7	2027/5/6
Preamplifier	DCLNA0118-40 C-S	DS77209	Decentest	2026/5/7	2027/5/6
RF Coaxial Cable	PE330	MRE001	Pasternack	N/A	N/A
RF Coaxial Cable	CLU18	MRE002	Pasternack	N/A	N/A
RF Coaxial Cable	CLU18	MRE003	Pasternack	N/A	N/A
RF Coaxial Cable	N/A	EMC-CE-0 0514	N/A	N/A	N/A
Receiver	ESPI	101052	R&S	2026/5/7	2027/5/6
LISN	ENV 216	103131	R&S	2026/3/18	2027/3/17
INTELLIGENT PURE SINE-WAVE POWER SUPPLY	TPS 500B	1008004	EVERFINE	2025/9/11	2026/9/10
System Simulator	CMW500	152038	R&S	2025/9/3	2026/9/2

6. Ancillary Equipment Utilized

Description	Model	Serial No.	Manufacturer
Radiated Emission			
Mobile Phone	RMX3193	VGSKUKT85TLFBMPJ	Realme
Type-C Earphone	CM33	N/A	HUAWEI
Earphone	N/A	N/A	OPPO
Notebook	X14	AMGMPPM1604001372	HONOR



REPORT No.: SZ26060442E01

SIM Card	N/A	N/A	China Mobile
Conducted Emission			
Earphone	N/A	N/A	OPPO
SIM Card	N/A	N/A	China Mobile
Notebook	E740C I3-6006U	BJB2017040	Lenovo
Notebook adapter	SA10M42787 LC FRU	ADLX45NDC3A	Lenovo



Notes

1. The report shall have report stamp or our company stamp.
2. The report shall be invalid without all the signatures of the editor and approver.
3. The report shall not be changed.
4. Any objections must be raised to Morlab within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

5. Conformity declaration:

- ☒ Morlab issues a statement of conformity based on the corresponding standards (default)
- ☐ Morlab issues a statement of conformity based on the applicant requirement

6. Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the testing standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule).

_____ END OF REPORT _____