


4.5 Power Spectral Density


Test Requirement:	FCC Part15 E Section 15.407, RSS-247 §6.2
Test Method:	KDB 789033 D02 General UNII Test Procedures New Rules v02r01
Limit:	FCC: 1. $\leq 11.00 \text{ dBm/MHz}$ for 5150MHz-5250MHz, 5250-5350MHz and 5470-5725 MHz 2. $\leq 30.00 \text{ dBm/500KHz}$ for 5725MHz-5850MHz IC: 1. For the 5.15-5.25 GHz, The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band. 2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test procedure:	1) Create an average power spectrum for the EUT operating mode being tested by following the instructions in section E)2) for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power..." 2) Use the peak search function on the instrument to find the peak of the spectrum. 3) Make the following adjustments to the peak value of the spectrum, if applicable: a) If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum. b) If Method SA-3 Alternative was used and the linear mode was used in step E)2)g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging. 4) The result is the PSD.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data**Band 1 (5150-5250 MHz) SISO:**


Condition	Antenna	Modulation	Frequency (MHz)	PSD(dBm/MHz)	Duty factor(dB)	Total PSD(dBm/MHz)	limit(dBm)	Result
NVNT	ANT1	802.11a	5180.00	0.53	0.12	0.65	11	Pass
NVNT	ANT1	802.11a	5200.00	0.30	0.18	0.48	11	Pass
NVNT	ANT1	802.11a	5240.00	0.20	0.12	0.32	11	Pass
NVNT	ANT1	802.11n(HT20)	5180.00	-1.00	0.20	-0.80	11	Pass
NVNT	ANT1	802.11n(HT20)	5200.00	0.07	0.13	0.20	11	Pass
NVNT	ANT1	802.11n(HT20)	5240.00	0.29	0.13	0.42	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5180.00	-1.31	0.20	-1.11	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5200.00	0.47	0.13	0.60	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5240.00	0.80	0.13	0.93	11	Pass
NVNT	ANT1	802.11n(HT40)	5190.00	-4.01	0.39	-3.62	11	Pass
NVNT	ANT1	802.11n(HT40)	5230.00	-4.42	0.26	-4.17	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5190.00	-4.97	0.26	-4.71	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5230.00	-4.40	0.26	-4.14	11	Pass
NVNT	ANT1	802.11ac(VHT80)	5210.00	-10.16	0.75	-9.41	11	Pass




Power Spectral Density NVNT_ANT1_802_11a_5180





Power Spectral Density NVNT_ANT1_802_11a_5200




Power Spectral Density NVNT_ANT1_802_11a_5240




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5200




Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5180




Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5240



Power Spectral Density NVNT_ANT1_802_11n(HT40)_5230



Power Spectral Density_NVNT_ANT1_802_11ac(VHT40)_5230



Band 2 (5260-5320 MHz) SISO:

Condition	Antenna	Modulation	Frequency (MHz)	PSD(dBm/MHz)	Duty factor(dB)	Total PSD(dBm/MHz)	limit(dBm)	Result
NVNT	ANT1	802.11a	5260.00	0.42	0.12	0.54	11	Pass
NVNT	ANT1	802.11a	5300.00	0.19	0.12	0.31	11	Pass
NVNT	ANT1	802.11a	5320.00	0.60	0.18	0.78	11	Pass
NVNT	ANT1	802.11n(HT20)	5260.00	0.04	0.13	0.17	11	Pass
NVNT	ANT1	802.11n(HT20)	5300.00	-0.44	0.13	-0.31	11	Pass
NVNT	ANT1	802.11n(HT20)	5320.00	-0.60	0.20	-0.40	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5260.00	-0.15	0.20	0.05	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5300.00	0.01	0.13	0.14	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5320.00	0.14	0.13	0.27	11	Pass
NVNT	ANT1	802.11n(HT40)	5270.00	-4.38	0.26	-4.12	11	Pass
NVNT	ANT1	802.11n(HT40)	5310.00	-4.38	0.26	-4.12	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5270.00	-5.44	0.26	-5.18	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5310.00	-4.13	0.39	-3.74	11	Pass
NVNT	ANT1	802.11ac(VHT80)	5290.00	-9.51	0.48	-9.03	11	Pass





Power Spectral Density NVNT_ANT1_802_11a_5260





Power Spectral Density NVNT_ANT1_802_11a_5300





Power Spectral Density NVNT_ANT1_802_11a_5320





Power Spectral Density NVNT_ANT1_802_11n(HT20)_5300





Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5260





Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5320



Power Spectral Density NVNT_ANT1_802_11n(HT40)_5310



Power Spectral Density_NVNT_ANT1_802_11ac(VHT40)_5310




Band 4 (5725 – 5850 MHz) SISO:

Condition	Antenna	Modulation	Frequency (MHz)	PSD _{SA} (dBm/RBW)	Duty factor(dB)	RB factor(dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
NVNT	ANT1	802.11a	5745.00	-4.16	0.18	-0	-4.07	30	Pass
NVNT	ANT1	802.11a	5785.00	-4.39	0.12	-0	-4.36	30	Pass
NVNT	ANT1	802.11a	5825.00	-4.75	0.12	-0	-4.71	30	Pass
NVNT	ANT1	802.11n(HT20)	5745.00	-3.46	0.13	-0	-3.41	30	Pass
NVNT	ANT1	802.11n(HT20)	5785.00	-4.82	0.13	-0	-4.78	30	Pass
NVNT	ANT1	802.11n(HT20)	5825.00	-5.37	0.20	-0	-5.25	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5745.00	-4.41	0.13	-0	-4.37	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5785.00	-3.63	0.13	-0	-3.58	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5825.00	-5.55	0.13	-0	-5.51	30	Pass
NVNT	ANT1	802.11n(HT40)	5755.00	-8.64	0.39	-0	-8.34	30	Pass
NVNT	ANT1	802.11n(HT40)	5795.00	-9.86	0.26	-0	-9.68	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5755.00	-9.02	0.26	-0	-8.84	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5795.00	-10.54	0.26	-0	-10.37	30	Pass
NVNT	ANT1	802.11ac(VHT80)	5775.00	-12.76	0.51	-0	-12.34	30	Pass




Power_Spectral_Density_NVNT_ANT1_802_11a_5745




Power_Spectral_Density_NVNT_ANT1_802_11a_5785




Power_Spectral_Density_NVNT_ANT1_802_11a_5825




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5785




Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5745




Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5825



Power Spectral Density NVNT_ANT1_802_11n(HT40)_5795




Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5795



4.6 Band Edge

Test Requirement:	FCC Part15 E Section 15.407 and 15.205, RSS-Gen §8.9																								
Test Method:	ANSI C63.10:2020																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>AV</td><td>1MHz</td><td>3MHz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	AV	1MHz	3MHz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	AV	1MHz	3MHz	Average Value																					
Limit:	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>68.2</td><td>Peak Value</td></tr></table> Undesirable emission limits: (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band. (3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	68.2	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	68.2	Peak Value																							
Test Procedure:	a. The EUT was placed on the top of a rotating table 1.5 m above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values																								

	of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test setup:	Above 1GHz 
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remark:

According to KDB 789033 D02 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:

$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2,$

For example, if $\text{EIRP} = -27\text{dBm}$

$E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$

Measurement Data:**Band1**

Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.06	-13.16	42.90	68.20	-25.30	PK
V	5150.00	57.37	-13.16	44.21	68.20	-23.99	PK
Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.26	-13.16	32.10	54.00	-21.90	AV
V	5150.00	47.45	-13.16	34.29	54.00	-19.71	AV
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	53.81	-12.62	41.19	68.20	-27.01	PK
V	5350.00	57.48	-12.62	44.86	68.20	-23.34	PK
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.01	-12.62	32.39	54.00	-21.61	AV
V	5350.00	45.85	-12.62	33.23	54.00	-20.77	AV

Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.51	-13.16	43.35	68.20	-24.85	PK
V	5150.00	55.76	-13.16	42.60	68.20	-25.60	PK
Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.60	-13.16	31.44	54.00	-22.56	AV
V	5150.00	45.87	-13.16	32.71	54.00	-21.29	AV
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.71	-12.62	44.09	68.20	-24.11	PK
V	5350.00	56.97	-12.62	44.35	68.20	-23.85	PK
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.10	-12.62	34.48	54.00	-19.52	AV
V	5350.00	47.56	-12.62	34.94	54.00	-19.06	AV

Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.74	-13.16	41.58	68.20	-26.62	PK
V	5150.00	56.36	-13.16	43.20	68.20	-25.00	PK
Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.38	-13.16	33.22	54.00	-20.78	AV
V	5150.00	49.25	-13.16	36.09	54.00	-17.91	AV
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.84	-12.62	42.22	68.20	-25.98	PK
V	5350.00	58.47	-12.62	45.85	68.20	-22.35	PK
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	48.08	-12.62	35.46	54.00	-18.54	AV
V	5350.00	45.56	-12.62	32.94	54.00	-21.06	AV

Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.37	-13.16	43.21	68.20	-24.99	PK
V	5150.00	55.36	-13.16	42.20	68.20	-26.00	PK
Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.13	-13.16	31.97	54.00	-22.03	AV
V	5150.00	47.54	-13.16	34.38	54.00	-19.62	AV
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.04	-12.62	41.42	68.20	-26.78	PK
V	5350.00	58.73	-12.62	46.11	68.20	-22.09	PK
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.21	-12.62	32.59	54.00	-21.41	AV
V	5350.00	46.34	-12.62	33.72	54.00	-20.28	AV

Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	57.02	-13.16	43.86	68.20	-24.34	PK
V	5150.00	57.05	-13.16	43.89	68.20	-24.31	PK
Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.51	-13.16	31.35	54.00	-22.65	AV
V	5150.00	46.96	-13.16	33.80	54.00	-20.20	AV
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.19	-12.62	41.57	68.20	-26.63	PK
V	5350.00	54.82	-12.62	42.20	68.20	-26.00	PK
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.73	-12.62	35.11	54.00	-18.89	AV
V	5350.00	45.41	-12.62	32.79	54.00	-21.21	AV

Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.31	-13.16	42.15	68.20	-26.05	PK
V	5150.00	58.24	-13.16	45.08	68.20	-23.12	PK
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.84	-13.16	32.68	54.00	-21.32	AV
V	5150.00	49.24	-13.16	36.08	54.00	-17.92	AV
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.70	-12.62	44.08	68.20	-24.12	PK
V	5350.00	58.11	-12.62	45.49	68.20	-22.71	PK
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.87	-12.62	33.25	54.00	-20.75	AV
V	5350.00	46.32	-12.62	33.70	54.00	-20.30	AV

Band2

Mode:		802.11a		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	53.95	-13.16	40.79	68.20	-27.41	PK
V	5150.00	58.58	-13.16	45.42	68.20	-22.78	PK
Mode:		802.11a		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.43	-13.16	31.27	54.00	-22.73	AV
V	5150.00	47.84	-13.16	34.68	54.00	-19.32	AV
Mode:		802.11a		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	57.61	-12.62	44.99	68.20	-23.21	PK
V	5350.00	54.92	-12.62	42.30	68.20	-25.90	PK
Mode:		802.11a		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	48.00	-12.62	35.38	54.00	-18.62	AV
V	5350.00	49.05	-12.62	36.43	54.00	-17.57	AV

Mode:		802.11n(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.39	-13.16	41.23	68.20	-26.97	PK
V	5150.00	56.13	-13.16	42.97	68.20	-25.23	PK
Mode:		802.11n(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.70	-13.16	33.54	54.00	-20.46	AV
V	5150.00	48.91	-13.16	35.75	54.00	-18.25	AV
Mode:		802.11n(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.56	-12.62	42.94	68.20	-25.26	PK
V	5350.00	56.45	-12.62	43.83	68.20	-24.37	PK
Mode:		802.11n(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	48.02	-12.62	35.40	54.00	-18.60	AV
V	5350.00	48.58	-12.62	35.96	54.00	-18.04	AV

Mode:		802.11ac(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.36	-13.16	41.20	68.20	-27.00	PK
V	5150.00	56.14	-13.16	42.98	68.20	-25.22	PK
Mode:		802.11ac(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.39	-13.16	31.23	54.00	-22.77	AV
V	5150.00	46.69	-13.16	33.53	54.00	-20.47	AV
Mode:		802.11ac(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.78	-12.62	44.16	68.20	-24.04	PK
V	5350.00	60.00	-12.62	47.38	68.20	-20.82	PK
Mode:		802.11ac(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.74	-12.62	35.12	54.00	-18.88	AV
V	5350.00	49.70	-12.62	37.08	54.00	-16.92	AV

Mode:		802.11n(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.52	-13.16	42.36	68.20	-25.84	PK
V	5150.00	55.34	-13.16	42.18	68.20	-26.02	PK
Mode:		802.11n(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	48.19	-13.16	35.03	54.00	-18.97	AV
V	5150.00	46.42	-13.16	33.26	54.00	-20.74	AV
Mode:		802.11n(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.77	-12.62	42.15	68.20	-26.05	PK
V	5350.00	57.09	-12.62	44.47	68.20	-23.73	PK
Mode:		802.11n(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.04	-12.62	33.42	54.00	-20.58	AV
V	5350.00	46.16	-12.62	33.54	54.00	-20.46	AV


Mode:		802.11ac(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.83	-13.16	41.67	68.20	-26.53	PK
V	5150.00	57.72	-13.16	44.56	68.20	-23.64	PK
Mode:		802.11ac(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.28	-13.16	34.12	54.00	-19.88	AV
V	5150.00	47.06	-13.16	33.90	54.00	-20.10	AV
Mode:		802.11ac(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.58	-12.62	41.96	68.20	-26.24	PK
V	5350.00	56.91	-12.62	44.29	68.20	-23.91	PK
Mode:		802.11ac(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	48.11	-12.62	35.49	54.00	-18.51	AV
V	5350.00	46.48	-12.62	33.86	54.00	-20.14	AV

Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.18	-13.16	42.02	68.20	-26.18	PK
V	5150.00	58.63	-13.16	45.47	68.20	-22.73	PK
Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.77	-13.16	32.61	54.00	-21.39	AV
V	5150.00	48.76	-13.16	35.60	54.00	-18.40	AV
Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.56	-12.62	41.94	68.20	-26.26	PK
V	5350.00	56.31	-12.62	43.69	68.20	-24.51	PK
Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.36	-12.62	31.74	54.00	-22.26	AV
V	5350.00	48.59	-12.62	35.97	54.00	-18.03	AV


Band4

Condition	Antenna	Modulation	TX_Frequency (MHz)	Frequency Area(MHz)	Frequency(MHz)	Amplitude(dBm)	Limit(dBm)	Result
NVNT	ANT1	802.11a	LCH	5565-5655	5648.430	-48.94	-27.00	Pass
NVNT	ANT1	802.11a	LCH	5655-5700	5681.865	-48.91	-4.91	Pass
NVNT	ANT1	802.11a	LCH	5700-5720	5715.600	-39.45	14.37	Pass
NVNT	ANT1	802.11a	LCH	5720-5725	5721.640	-34.63	19.34	Pass
NVNT	ANT1	802.11a	HCH	5850-5855	5854.360	-39.95	17.06	Pass
NVNT	ANT1	802.11a	HCH	5855-5875	5862.240	-44.46	13.57	Pass
NVNT	ANT1	802.11a	HCH	5875-5920	5900.965	-49.08	-11.35	Pass
NVNT	ANT1	802.11a	HCH	5920-6005	5930.880	-46.16	-27.00	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5565-5655	5574.090	-49.27	-27.00	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5655-5700	5665.575	-48.49	-18.31	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5700-5720	5718.380	-36.08	15.15	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5720-5725	5722.815	-33.38	22.02	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5850-5855	5853.475	-37.91	19.08	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5855-5875	5856.260	-40.43	15.25	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5875-5920	5894.305	-48.94	-5.87	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5920-6005	5964.710	-46.23	-27.00	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5565-5655	5618.820	-49.06	-27.00	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5655-5700	5689.065	-48.75	1.01	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5700-5720	5719.920	-37.32	15.58	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5720-5725	5722.015	-34.41	20.19	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5850-5855	5853.215	-38.97	19.67	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5855-5875	5855.460	-40.41	15.47	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5875-5920	5914.600	-49.11	-22.56	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5920-6005	5926.630	-44.12	-27.00	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5595-5655	5646.480	-49.25	-27.00	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5655-5700	5696.445	-40.94	7.08	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5700-5720	5717.340	-32.55	14.86	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5720-5725	5721.930	-27.87	20.00	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5850-5855	5854.365	-43.00	17.05	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5855-5875	5861.280	-44.98	13.84	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5875-5920	5911.315	-48.49	-19.86	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5920-5955	5934.840	-43.68	-27.00	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5595-5655	5653.800	-48.28	-27.00	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5655-5700	5691.945	-46.33	3.38	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5700-5720	5717.940	-33.37	15.02	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5720-5725	5721.550	-32.48	19.13	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5850-5855	5854.950	-43.17	15.71	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5855-5875	5858.440	-45.02	14.64	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5875-5920	5893.450	-48.42	-5.17	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5920-5955	5922.030	-45.61	-27.00	Pass



Bandedge_NVNT_ANT1_802_11a_5745





Bandedge_NVNT_ANT1_802_11a_5825





Bandedge_NVNT_ANT1_802_11n(HT20)_5745





Bandedge_NVNT_ANT1_802_11ac(VHT20)_5745

**Bandedge_NVNT_ANT1_802_11ac(VHT20)_5825****Bandedge_NVNT_ANT1_802_11n(HT40)_5755**





Bandedge_NVNT_ANT1_802_11ac(VHT40)_5755



4.7 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen §8.9				
Test Method:	ANSI C63.10:2020				
Test Frequency Range:	30MHz to 40GHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		AV	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		74.0		Peak Value
54.0			Average Value		
Test Procedure:	Substitution method was performed to determine the actual ERP emission levels of the EUT. The following test procedure as below:				
	1>.Below 1GHz test procedure:				
	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
	2>.Above 1GHz test procedure:				
	1. On the test site as test setup graph above,the EUT shall be placed at the 1.5m support on the turntable and in the position closest to normal use as declared by the provider. 2. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter.The output of the test antenna shall be connected to the measuring receiver. 3. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the				

	transmitter under test. - The test antenna shall be raised and lowered from 1m to 4m until a maximum signal level is detected by the measuring receiver. Then the turntable should be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. - Repeat step 4 for test frequency with the test antenna polarized horizontally. - Remove the transmitter and replace it with a substitution antenna - Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a nonradiating cable. With the antennas at both ends vertically polarized, and with the signal generator tuned to a particular test frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output. - Repeat step 7 with both antennas horizontally polarized for each test frequency. - Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps 7 and 8 by the power loss in the cable between the generator and the antenna, and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna by the following formula: $\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$ where: Pg is the generator output power into the substitution antenna.
Test setup:	Below 1GHz  Above 1GHz

	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data:**Below 1GHz**

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
33.82	12.78	13.61	26.39	40	-13.61	Vertical
54.95	13.52	13.73	27.25	40	-12.75	Vertical
121.08	16.64	12.70	29.35	43.5	-14.15	Vertical
172.22	11.70	13.17	24.87	43.5	-18.63	Vertical
441.04	16.36	18.82	35.18	46	-10.82	Vertical
860.53	12.57	27.44	40.00	46	-6.00	Vertical
64.78	11.43	12.72	24.15	40	-15.85	Horizontal
100.20	14.27	10.68	24.95	43.5	-18.55	Horizontal
270.04	14.02	14.09	28.10	46	-17.90	Horizontal
350.55	13.43	16.38	29.81	46	-16.19	Horizontal
627.40	13.55	23.36	36.91	46	-9.09	Horizontal
955.60	10.84	28.75	39.59	46	-6.41	Horizontal

Above 1GHz:**802.11a 5180MHz**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.81	41.95	-5.59	36.36	68.20	-31.84	Vertical
15540.62	32.06	-1.02	31.04	74.00	-42.96	Vertical
10360.73	42.79	-5.63	37.16	68.20	-31.04	Horizontal
15540.05	32.67	-1.00	31.66	74.00	-42.34	Horizontal

802.11a 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.23	42.23	-5.63	36.60	68.20	-31.60	Vertical
15540.08	32.79	-1.03	31.75	74.00	-42.25	Vertical
10360.94	42.83	-5.67	37.16	68.20	-31.04	Horizontal
15540.80	32.44	-1.03	31.41	74.00	-42.59	Horizontal

802.11a 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.56	41.98	-5.64	36.34	68.20	-31.86	Vertical
15540.46	32.92	-0.97	31.95	74.00	-42.05	Vertical
10360.29	42.90	-5.64	37.26	68.20	-30.94	Horizontal
15540.10	32.19	-1.03	31.16	74.00	-42.84	Horizontal

802.11n(HT20) 5180MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.62	42.28	-5.61	36.67	68.20	-31.53	Vertical
15540.24	32.41	-0.96	31.44	74.00	-42.56	Vertical
10360.06	41.82	-5.66	36.16	68.20	-32.04	Horizontal
15540.94	33.15	-0.99	32.16	74.00	-41.84	Horizontal

802.11n(HT20) 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.28	42.42	-5.65	36.78	68.20	-31.42	Vertical
15540.94	33.17	-1.00	32.16	74.00	-41.84	Vertical
10360.02	41.97	-5.62	36.35	68.20	-31.85	Horizontal
15540.84	33.06	-0.96	32.09	74.00	-41.91	Horizontal

802.11n(HT20) 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.98	42.57	-5.65	36.93	68.20	-31.27	Vertical
15540.12	32.72	-0.97	31.76	74.00	-42.24	Vertical
10360.89	42.57	-5.59	36.98	68.20	-31.22	Horizontal
15540.41	32.91	-0.97	31.93	74.00	-42.07	Horizontal

802.11ac(HT20) 5180MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.49	42.56	-5.66	36.90	68.20	-31.30	Vertical
15540.59	32.97	-0.97	32.00	74.00	-42.00	Vertical
10360.75	42.18	-5.67	36.51	68.20	-31.69	Horizontal
15540.37	32.61	-0.96	31.65	74.00	-42.35	Horizontal

802.11ac(HT20) 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.59	42.18	-5.66	36.51	68.20	-31.69	Vertical
15540.79	33.13	-1.01	32.11	74.00	-41.89	Vertical
10360.57	43.04	-5.63	37.42	68.20	-30.78	Horizontal
15540.10	32.94	-0.97	31.97	74.00	-42.03	Horizontal

802.11ac(HT20) 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.86	42.07	-5.64	36.44	68.20	-31.76	Vertical
15540.81	32.39	-0.97	31.41	74.00	-42.59	Vertical
10360.45	42.51	-5.62	36.89	68.20	-31.31	Horizontal
15540.15	32.67	-0.97	31.70	74.00	-42.30	Horizontal

802.11n(HT40) 5190MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.53	42.79	-5.61	37.18	68.20	-31.02	Vertical
15540.03	31.99	-1.03	30.97	74.00	-43.03	Vertical
10360.71	42.84	-5.64	37.20	68.20	-31.00	Horizontal
15540.66	32.86	-1.04	31.82	74.00	-42.18	Horizontal

802.11n(HT40) 5230MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.66	41.86	-5.65	36.21	68.20	-31.99	Vertical
15540.40	32.20	-0.99	31.21	74.00	-42.79	Vertical
10360.63	42.92	-5.62	37.30	68.20	-30.90	Horizontal
15540.85	32.36	-1.01	31.35	74.00	-42.65	Horizontal

802.11ac(HT40) 5190MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.21	42.38	-5.63	36.75	68.20	-31.45	Vertical
15540.91	32.62	-1.00	31.62	74.00	-42.38	Vertical
10360.04	42.75	-5.67	37.08	68.20	-31.12	Horizontal
15540.35	32.66	-1.04	31.62	74.00	-42.38	Horizontal

802.11ac(HT40) 5230MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10361.00	41.87	-5.64	36.23	68.20	-31.97	Vertical
15540.94	32.61	-0.96	31.65	74.00	-42.35	Vertical
10360.76	42.32	-5.66	36.66	68.20	-31.54	Horizontal
15540.12	32.98	-0.97	32.00	74.00	-42.00	Horizontal

802.11ac(HT80) 5210MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.68	42.52	-5.67	36.86	68.20	-31.34	Vertical
15540.51	33.02	-1.01	32.01	74.00	-41.99	Vertical
10360.56	42.03	-5.66	36.38	68.20	-31.82	Horizontal
15540.92	32.21	-0.98	31.23	74.00	-42.77	Horizontal

Note:

1. Level = Read Level + Factor

Factor = Antenna Factor+ Cable loss- Preamp Factor.

2. The test trace is same as the ambient noise (the test frequency range: 18GHz~40GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

4. This Report only show the test plots of the worst case (U-NII-1).

4.8 Frequency stability

Test Standard	15.407(f), RSS-Gen §6.11
Test limit	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.
Test results:	Pass

Measurement Data:

Mode	Voltage (V)	FHL (5180MHz)	Deviation (KHz)	FHH (5240MHz)	Deviation (KHz)
Band 1 (5150-5250 MHz)	DC 10.8V	5179.998	2	5239.994	6
	DC 12.0V	5179.998	2	5239.993	7
	DC 13.2V	5179.998	2	5239.994	6
Mode	Voltage (V)	FHL (5260MHz)	Deviation (KHz)	FHH (5320MHz)	Deviation (KHz)
Band 2 (5250-5350 MHz)	DC 10.8V	5259.992	8	5319.991	9
	DC 12.0V	5259.994	6	5319.995	5
	DC 13.2V	5259.995	5	5319.992	8
Mode	Voltage (V)	FHL (5745MHz)	Deviation (KHz)	FHH (5825MHz)	Deviation (KHz)
Band 4 (5725-5850 MHz)	DC 10.8V	5744.994	6	5824.994	6
	DC 12.0V	5744.997	3	5824.995	5
	DC 13.2V	5744.992	8	5824.996	4

Mode	Temperature (°C)	FHL (5180MHz)	Deviation (KHz)	FHH (5240MHz)	Deviation (KHz)
Band 1 (5150-5250 MHz)	-10°C	5179.999	1	5239.995	5
	0°C	5179.998	2	5239.992	8
	+10°C	5179.992	8	5239.996	4
	+20°C	5179.992	8	5239.998	2
	+30°C	5179.993	7	5239.992	8
	+40°C	5179.994	6	5239.994	6
	+50°C	5179.995	5	5239.991	9
Mode	Temperature (°C)	FHL (5260MHz)	Deviation (KHz)	FHH (5320MHz)	Deviation (KHz)
Band 2 (5250-5350 MHz)	-10°C	5259.991	9	5319.998	0.001
	0°C	5259.999	1	5319.995	0.004
	+10°C	5259.996	4	5319.993	0.006
	+20°C	5259.995	5	5319.992	0.007
	+30°C	5259.995	5	5319.995	0.004
	+40°C	5259.992	8	5319.996	0.003
	+50°C	5259.991	9	5319.993	0.006
	-10°C	5259.999	1	5319.992	0.007
Mode	Temperature (°C)	FHL (5745MHz)	Deviation (KHz)	FHH (5825MHz)	Deviation (KHz)
Band 4 (5725-5850 MHz)	-10°C	5744.994	6	5824.997	3
	0°C	5744.992	8	5824.993	7
	+10°C	5744.998	2	5824.999	1
	+20°C	5744.993	7	5824.992	8
	+30°C	5744.994	6	5824.996	4
	+40°C	5744.999	1	5824.996	4
	+50°C	5744.997	3	5824.995	5

5 Photos Of Test Setup

Reference to the **appendix I Test Setup Photo** for details.

6 Photos Of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

-----END OF REPORT-----

