FCC TEST REPORT

FCC ID: 2BQIE-KF58

Report No.	:	SSP25060151-1E
Applicant	:	Shenzhen Weichenshi Technology Co., Ltd
Product Name	:	Industrial AIO Computer
Model Name	:	KF58, KF28, KF38, KF78, KF88, KF218, KF238, KF248, KF278, KF328, KF26, KF36, KF56, KF76, KF86, KF216, KF236, KF246, KF276, KF326
Test Standard	:	FCC Part 15.247
Date of Issue	:	2025-07-15

Shenzhen CCUT Quality Technology Co., Ltd.
1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant.....:	Shenzhen Weichenshi Technology Co., Ltd
Address of Applicant.....:	Room 301, No.28, Lutianyuan Road, Dongfang Community, Songgang Street, Baoan District, Shenzhen China
Manufacturer.....:	Shenzhen Weichenshi Technology Co., Ltd
Address of Manufacturer.....:	Room 301, No.28, Lutianyuan Road, Dongfang Community, Songgang Street, Baoan District, Shenzhen China
Product Name.....:	Industrial AIO Computer
Brand Name.....:	
Main Model.....:	KF58
Series Models.....:	KF28, KF38, KF78, KF88, KF218, KF238, KF248, KF278, KF328, KF26, KF36, KF56, KF76, KF86, KF216, KF236, KF246, KF276, KF326
Test Standard.....:	FCC Part 15 Subpart C ANSI C63.10-2013
Date of Test .....:	2025-06-11 to 2025-07-15
Test Result.....:	PASS
Tested By .....:	Choco Qiu (Choco Qiu)
Reviewed By.....:	Lieber Ouyang (Lieber Ouyang)
Authorized Signatory.....:	Lahm Peng (Lahm Peng)

Shenzhen CCUT Quality Technology Co., Ltd. APPROVED

Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.

CONTENTS

1. General Information **6**
1.1 Product Information 6
1.2 Test Setup Information 7
1.3 Compliance Standards 8
1.4 Test Facilities 8
1.5 List of Measurement Instruments 9
1.6 Measurement Uncertainty 10
2. Summary of Test Results **11**
3. Antenna Requirement **12**
3.1 Standard and Limit 12
3.2 Test Result 12
4. Conducted Emissions **13**
4.1 Standard and Limit 13
4.2 Test Procedure 13
4.3 Test Data and Results 14
5. Radiated Emissions **17**
5.1 Standard and Limit 17
5.2 Test Procedure 17
5.3 Test Data and Results 19
6. Band-edge Emissions(Radiated) **23**
6.1 Standard and Limit 23
6.2 Test Procedure 23
6.3 Test Data and Results 23
Pass ..... 错误！未定义书签。
Pass ..... 错误！未定义书签。
7. Frequency Hopping System **25**
7.1 Standard and Limit 25
7.2 Test Procedure 25
7.3 Test Data and Results 26
8. Dwell Time **27**
8.1 Standard and Limit 27
8.2 Test Procedure 27
8.3 Test Data and Results 28
9. Maximum Peak Conducted Output Power **31**
9.1 Standard and Limit 31
9.2 Test Procedure 31
9.3 Test Data and Results 31
10. Occupied Bandwidth(-20dB) **34**
10.1 Standard and Limit 34
10.2 Test Procedure 34
10.3 Test Data and Results 34
11. Carrier Frequencies Separation **38**
11.1 Standard and Limit 38
11.2 Test Procedure 38
11.3 Test Data and Results 38
12. Number of Hopping Channel **41**
12.1 Standard and Limit 41
12.2 Test Procedure 41
12.3 Test Data and Results 41
13. Band-edge Emission(Conducted) **43**
13.1 Standard and Limit 43
13.2 Test Procedure 43
13.3 Test Data and Results 43
14. Conducted RF Spurious Emissions **49**
14.1 Standard and Limit 49
14.2 Test Procedure 49

14.3 Test Data and Results 49

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-07-15	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Industrial AIO Computer
Trade Name:	
Main Model:	KF58
Series Models:	KF28, KF38, KF78, KF88, KF218, KF238, KF248, KF278, KF328, KF26, KF36, KF56, KF76, KF86, KF216, KF236, KF246, KF276, KF326
Rated Voltage:	DC 12V
Power Adapter:	Input: AC 100-240V/50-60Hz, Output: DC 12V/3A
Test Sample No:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer. Note 2: Differences between models are only in name, but they share the same circuit and electronic structure, declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	Bluetooth BR/EDR
Operating Frequency:	2402MHz ~ 2480MHz
RF Output Power:	2.33dBm (Conducted)
Number of Channel:	79
Channel Separation:	1MHz
Modulation:	GFSK, Pi/4 DQPSK, 8DPSK
Antenna Gain:	2.32dBi
Type of Antenna:	Internal antenna
Type of Device:	☐ Portable Device ☒ Mobile Device ☐ Modular Device

1.2 Test Setup Information

List of Test Modes		
Test Mode	Description	Remark
TM1	Lowest Channel	2402MHz(DH5/2DH5/3DH5)
TM2	Middle Channel	2441MHz(DH5/2DH5/3DH5)
TM3	Highest Channel	2480MHz(DH5/2DH5/3DH5)
TM4	Hopping	2402MHz~2480MHz
TM5	Playing with charging	Bluetooth playing

List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-

List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
AC/DC ADAPTER	Shenzhen Jiuzhou Power Technology Co., Ltd	J482-1203000DI	-
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	21	2422	41	2442	61	2462
02	2403	22	2423	42	2443	62	2463
03	2404	23	2424	43	2444	63	2464
04	2405	24	2425	44	2445	64	2465
05	2406	25	2426	45	2446	65	2466
~	~	~	~	~	~	~	~
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18	2419	38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461		

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	**Shenzhen CCUT Quality Technology Co., Ltd.** 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Test Cable	N/A	Cable 5	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Attenuator	QUANJUDA	6dB	220731	2024-08-07	2025-08-06
Test Cable	N/A	Cable 1	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 2	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 3	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 4	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 8	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 9	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06
RF Test Software	MWRFTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThlnkPad E15 Gen 3	SPPOZ22485	N/A	N/A

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(a)(1), (g), (h)	Frequency Hopping System	Passed
FCC Part 15.247(a)(1)(iii)	Dwell Time	Passed
FCC Part 15.247(b)(1)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.215(c)	Occupied Bandwidth(-20dB)	Passed
FCC Part 15.247(a)(1)	Carrier Frequencies Separation	Passed
FCC Part 15.247(a)(1)(iii)	Number of Hopping Channel	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit

According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50
Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz Note 2: The lower limit applies at the band edges		

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver
Attenuation: 10dB
Start Frequency: 0.15MHz
Stop Frequency: 30MHz
IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

All of the GFSK, π/4 DQPSK and 8DPSK modes have been tested, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case GFSK_2402MHz as below:
Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions	
Tested Mode:	TM5
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1635	39.88	9.78	49.66	65.28	-15.62	QP	P
2	0.1635	23.19	9.78	32.97	55.28	-22.31	AVG	P
3 *	0.5100	34.23	9.77	44.00	56.00	-12.00	QP	P
4	0.5100	21.83	9.77	31.60	46.00	-14.40	AVG	P
5	1.2119	32.98	9.74	42.72	56.00	-13.28	QP	P
6	1.2119	19.64	9.74	29.38	46.00	-16.62	AVG	P
7	3.3180	32.81	9.79	42.60	56.00	-13.40	QP	P
8	3.3180	19.89	9.79	29.68	46.00	-16.32	AVG	P
9	6.6840	34.49	9.80	44.29	60.00	-15.71	QP	P
10	6.6840	21.01	9.80	30.81	50.00	-19.19	AVG	P
11	20.7149	31.77	9.82	41.59	60.00	-18.41	QP	P
12	20.7149	21.50	9.82	31.32	50.00	-18.68	AVG	P

Test Plots and Data of Conducted Emissions	
Tested Mode:	TM5
Test Voltage:	AC 120V/60Hz
Test Power Line:	Live
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1814	38.53	9.70	48.23	64.42	-16.19	QP	P
2	0.1814	24.46	9.70	34.16	54.42	-20.26	AVG	P
3 *	0.5054	37.31	9.70	47.01	56.00	-8.99	QP	P
4	0.5054	25.57	9.70	35.27	46.00	-10.73	AVG	P
5	1.7430	33.91	9.69	43.60	56.00	-12.40	QP	P
6	1.7430	21.63	9.69	31.32	46.00	-14.68	AVG	P
7	4.8479	35.50	9.73	45.23	56.00	-10.77	QP	P
8	4.8479	22.92	9.73	32.65	46.00	-13.35	AVG	P
9	12.5295	28.97	9.70	38.67	60.00	-21.33	QP	P
10	12.5295	18.27	9.70	27.97	50.00	-22.03	AVG	P
11	20.4630	24.00	9.73	33.73	60.00	-26.27	QP	P
12	20.4630	13.82	9.73	23.55	50.00	-26.45	AVG	P

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:

Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54
Note: The more stringent limit applies at transition frequencies.	

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range blew 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.

b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.

c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1GHz, 100 kHz for f < 1 GHz, 10kHz for f < 30MHz
VBW ≥ RBW, Sweep = auto
Detector function = peak
Trace = max hold

d) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.

e) For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

All of the GFSK, π/4 DQPSK and 8DPSK modes have been tested, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case GFSK_2402MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)	
Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	148.4410	47.93	-15.98	31.95	43.50	-11.55	QP
2	207.1225	54.44	-19.54	34.90	43.50	-8.60	QP
3 *	374.6225	54.02	-15.15	38.87	46.00	-7.13	QP
4	501.1790	47.47	-13.35	34.12	46.00	-11.88	QP
5	625.0780	46.24	-11.15	35.09	46.00	-10.91	QP
6	779.6067	46.79	-9.05	37.74	46.00	-8.26	QP

Radiated Emission Test Data (30MHz to 1GHz)	
Tested Mode:	TM1
Test Antenna Polarization:	Vertical
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.4508	43.56	-16.39	27.17	40.00	-12.83	QP
2	148.4410	48.44	-15.98	32.46	43.50	-11.04	QP
3	181.2834	47.95	-18.34	29.61	43.50	-13.89	QP
4	345.5951	44.03	-15.63	28.40	46.00	-17.60	QP
5	483.9094	48.18	-13.46	34.72	46.00	-11.28	QP
6 *	625.0780	49.00	-11.15	37.85	46.00	-8.15	QP

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK_2402MHz)							
4804	76.35	-14.72	61.63	74	-12.37	H	PK
4804	62.02	-14.72	47.3	54	-6.7	H	AV
7206	65.42	-8.41	57.01	74	-16.99	H	PK
7206	46.14	-8.41	37.73	54	-16.27	H	AV
4804	73.02	-14.72	58.3	74	-15.7	V	PK
4804	57.77	-14.72	43.05	54	-10.95	V	AV
7206	62.79	-8.41	54.38	74	-19.62	V	PK
7206	50.78	-8.41	42.37	54	-11.63	V	AV
Middle Channel (GFSK_2441MHz)							
4882	76.71	-14.64	62.07	74	-11.93	H	PK
4882	61.69	-14.64	47.05	54	-6.95	H	AV
7323	63.63	-8.28	55.35	74	-18.65	H	PK
7323	49.41	-8.28	41.13	54	-12.87	H	AV
4882	74.58	-14.64	59.94	74	-14.06	V	PK
4882	60.21	-14.64	45.57	54	-8.43	V	AV
7323	64.83	-8.28	56.55	74	-17.45	V	PK
7323	49.27	-8.28	40.99	54	-13.01	V	AV
Highest Channel (GFSK_2480MHz)							
4960	76.44	-14.53	61.91	74	-12.09	H	PK
4960	60.17	-14.53	45.64	54	-8.36	H	AV
7440	64.25	-8.13	56.12	74	-17.88	H	PK
7440	45.75	-8.13	37.62	54	-16.38	H	AV
4960	74.15	-14.53	59.62	74	-14.38	V	PK
4960	60.46	-14.53	45.93	54	-8.07	V	AV
7440	62.49	-8.13	54.36	74	-19.64	V	PK
7440	46.43	-8.13	38.3	54	-15.7	V	AV

Note 1: All of the GFSK, π/4 DQPSK and 8DPSK modes have been tested. This EUT was tested in 3 orthogonal positions and the worst case position data of GFSK was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 20 dB with respect to the limits.

6. Band-edge Emissions(Radiated)

6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

All of the GFSK, π/4 DQPSK and 8DPSK modes have been tested, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case GFSK as below:

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK_2402MHz)							
2310	65.33	-21.34	43.99	74	-30.01	H	PK
2310	49.48	-21.34	28.14	54	-25.86	H	AV
2390	64.22	-20.96	43.26	74	-30.74	H	PK
2390	52.78	-20.96	31.82	54	-22.18	H	AV
2400	68.03	-20.91	47.12	74	-26.88	H	PK
2400	54.17	-20.91	33.26	54	-20.74	H	AV
2310	66.89	-21.34	45.55	74	-28.45	V	PK
2310	52.02	-21.34	30.68	54	-23.32	V	AV
2390	65.18	-20.96	44.22	74	-29.78	V	PK
2390	50.59	-20.96	29.63	54	-24.37	V	AV
2400	68.62	-20.91	47.71	74	-26.29	V	PK
2400	55.05	-20.91	34.14	54	-19.86	V	AV
Highest Channel (GFSK_2480MHz)							
2483.50	69.29	-20.51	48.78	74	-25.22	H	PK
2483.50	55.89	-20.51	35.38	54	-18.62	H	AV
2500	65.28	-20.43	44.85	74	-29.15	H	PK
2500	50.1	-20.43	29.67	54	-24.33	H	AV
2483.50	67.57	-20.51	47.06	74	-26.94	V	PK
2483.50	54.12	-20.51	33.61	54	-20.39	V	AV
2500	64.02	-20.43	43.59	74	-30.41	V	PK
2500	50.36	-20.43	29.93	54	-24.07	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit

7. Frequency Hopping System

7.1 Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

7.2 Test Procedure

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

7.3 Test Data and Results

Pseudorandom Frequency Hopping Sequence Table as below:
Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8. Dwell Time

8.1 Standard and Limit

According to 15.247 (a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed..

8.2 Test Procedure

1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Spectrum Setting: RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
3) Use video trigger with the trigger level set to enable triggering only on full pulses.
4) Sweep Time is more than once pulse time.
5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
6) Measure the maximum time duration of one single pulse.
7) Set the EUT for packet transmitting.
8) Measure the maximum time duration of one single pulse.
9) The EUT was set to the Hopping Mode for Dwell Time Test.



Test Setup Block Diagram

8.3 Test Data and Results

Test Mode	Data Packet	Channel (MHz)	Pulse Duration (ms)	Dwell Time (ms)	Limit (ms)	Result
GFSK	1-DH5	2402	2.905	302.12	<400	Pass
	1-DH5	2441	2.905	319.55	<400	Pass
	1-DH5	2480	2.903	316.427	<400	Pass
Pi/4 DQPSK	2-DH5	2402	2.892	349.932	<400	Pass
	2-DH5	2441	2.892	309.444	<400	Pass
	2-DH5	2480	2.91	323.01	<400	Pass
8DPSK	3-DH5	2402	2.894	277.824	<400	Pass
	3-DH5	2441	2.91	273.54	<400	Pass
	3-DH5	2480	2.908	308.248	<400	Pass

Note:

1. A period time = 0.4 (s) * 79 = 31.6(s)
2. DH1 time slot = Pulse Duration * (1600/(2*79)) * A period time
   DH3 time slot = Pulse Duration * (1600/(4*79)) * A period time
   DH5 time slot = Pulse Duration * (1600/(6*79)) * A period time
3. For GFSK, π/4-DQPSK and 8DPSK: The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

GFSK(DH5)	Pi/4 DQPSK (2DH5)
Burst(2402) 	Burst(2402) 
Burst(2441) 	Burst(2441)
Burst(2480) 	Burst(2480)

8DPSK (3DH5)
Burst(2402)
Burst(2441)
Burst(2480)


9. Maximum Peak Conducted Output Power

9.1 Standard and Limit

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

9.2 Test Procedure

1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 2MHz, VBW = 6MHz, Sweep = Auto, Detector = Peak.
4) Measure the highest amplitude appearing on spectral display and mark the value.
5) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

9.3 Test Data and Results

Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
GFSK	2402	-0.14	21	Pass
	2441	-1.16	21	Pass
	2480	-2.7	21	Pass
Pi/4 DQPSK	2402	2.17	21	Pass
	2441	1.12	21	Pass
	2480	-0.49	21	Pass
8DPSK	2402	2.33	21	Pass
	2441	1.19	21	Pass
	2480	-0.43	21	Pass

GFSK	Pi/4 DQPSK
2402MHz	2402MHz
	
2441MHz	2441MHz
	
2480MHz	2480MHz
	

8DPSK
2402MHz 
2441MHz 
2480MHz 

10. Occupied Bandwidth(-20dB)

10.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

10.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.
1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto.
4) Set a reference level on the measuring instrument equal to the highest peak value.
5) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
6) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

10.3 Test Data and Results

Test Mode	Test Channel (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
GFSK	2402	0.943	0.848
	2441	0.936	0.854
	2480	0.943	0.853
Pi/4 DQPSK	2402	1.282	1.174
	2441	1.324	1.180
	2480	1.281	1.178
8DPSK	2402	1.32	1.180
	2441	1.281	1.176
	2480	1.3	1.176

GFSK	Pi/4 DQPSK
2402MHz  	2402MHz 
2441MHz  	2441MHz 
2480MHz  	2480MHz 

8DPSK

2402MHz



2441MHz



2480MHz



11. Carrier Frequencies Separation

11.1 Standard and Limit

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

11.2 Test Procedure

1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto, Detector = Peak.
4) By using the Max Hold function, record the separation of two adjacent channels.
5) Measure the frequency difference of these two adjacent channels by spectrum analyzer mark function. and then plot the result on the screen of the spectrum analyzer.
6) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

11.3 Test Data and Results

Test Mode	Test Channel	Test Freq. 1 (MHz)	Test Freq. 2 (MHz)	CFS (MHz)	Limit (MHz)
GFSK	Lowest	2401.83	2403.004	1.174	0.629
	Middle	2441.004	2441.996	0.992	0.624
	Highest	2478.974	2479.966	0.992	0.629
Pi/4 DQPSK	Lowest	2402.124	2403.014	0.89	0.855
	Middle	2440.996	2441.91	0.914	0.883
	Highest	2478.902	2480.014	1.112	0.854
8DPSK	Lowest	2401.99	2403.168	1.178	0.88
	Middle	2440.922	2442.002	1.08	0.854
	Highest	2478.908	2479.914	1.006	0.867

Note: CFS(Channel Frequency Separation) = Test Freq. 2 - Test Freq. 1

GFSK	Pi/4 DQPSK
Lowest	Lowest
	
Middle	Middle
Highest	Highest
	

8DPSK
Lowest 
Middle
Highest