

SAR Exemption Evaluation Report

Applicant Zhongshan Polono Electronic Technology Co., Ltd.
FCC ID 2BQIW-PM240C
Product Thermal Printer
Model PM240; PM240C
Report No. EFTA26030143-IE-08-S1
Issue Date May 14, 2026

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **KDB 447498 D01 General RF Exposure Guidance v06**. The test results show that the equipment tested can demonstrate compliance with the requirements as documented in this report.



Prepared by: Wei Fangying



Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility	3
1.3	Testing Location.....	3
1.4	Laboratory Environment	3
2	Description of Equipment Under Test	4
3	Evaluation Standard	6
4	Maximum Tune up Tolerance	7
5	Standalone SAR Test Exclusion Considerations	8
	ANNEX A: The EUT Appearance	9

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Zhongshan Polono Electronic Technology Co., Ltd.
Applicant address	4th and 5th floors, Building 2, 4th and 5th floors, Building 3, No.132, Tanlong North Road, Tanzhou Town, Zhongshan city, China
Manufacturer	Zhongshan Polono Electronic Technology Co., Ltd.
Manufacturer address	4th and 5th floors, Building 2, 4th and 5th floors, Building 3, No.132, Tanlong North Road, Tanzhou Town, Zhongshan city, China

General Technologies

EUT Description		
Model	PM240; PM240C	
Lab Internal SN	Conducted	260313-03-035
	Radiated	260313-03-030
Hardware Version	0.0.1	
Software Version	0.0.5	
Date of Testing	March 12, 2026 ~ April 13, 2026	
Date of Sample Received	March 12, 2026	
EUT Accessory		
Type C cord	Manufacturer: Zhuhai Huashitong Electronics Co., Ltd. Model:/	
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.		

Wireless Technology and Frequency Range

Wireless Technology		Modulation	Operating Mode	Tx (MHz)
Bluetooth	2.4G	Version 5.1 BR/EDR + LE		2402 ~2480

3 Evaluation Standard

KDB 447498 D01 General RF Exposure Guidance v06

4 Maximum Tune up Tolerance

Band	Maximum Tune up Tolerance	
	(dBm)	(mW)
Bluetooth	1.00	1.26

5 Standalone SAR Test Exclusion Considerations

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Band	Configuration	Frequency (MHz)	Distance (mm)	MAX Tune Up (dBm)	Calculation Value	SAR test exclusion thresholds	Routine Evaluation
Bluetooth	Body SAR	2480	0	1.00	0.40	3.00	No
	Extremity SAR	2480	0	1.00	0.20	7.50	No

Note:

1. As described above, according to KDB 447498 D01, if the calculated result is less than or equal to 3.0 for 1-g SAR and less than or equal to 7.5 for 10-g extremity SAR, the device is exempt from SAR testing.
2. Calculation Value= $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}]$
3. Based on SAR test exclusion, all values meet the SAR test exclusion thresholds and are exempt from routine evaluation.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****