TEST REPORT

Report No.:	BCTC2505932380E
Applicant:	Runius Design AB
Product Name:	SPAZA REFILL MACHINE
Test Model:	71
Tested Date:	2025-05-26 to 2025-06-10
Issued Date:	2025-06-10

Shenzhen BCTC Testing Co., Ltd.

FCC ID: 2BQLW-71

Product Name:	SPAZA REFILL MACHINE
Trademark:	SPAZA®
Model/Type reference:	71
Prepared For:	Runius Design AB
Address:	Industriv. 1, 17148 Solna, Sweden
Manufacturer:	Runius Design AB
Address:	Industriv. 1, 17148 Solna, Sweden
Prepared By:	Shenzhen BCTC Testing Co., Ltd.
Address:	1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date:	2025-05-21
Sample tested Date:	2025-05-26 to 2025-06-10
Issue Date:	2025-06-10
Report No.:	BCTC2505932380E
Test Standards:	FCC Part15.247 ANSI C63.10-2013
Test Results:	PASS
Remark:	This is WIFI-2.4GHz band radio test report.

Tested by:

Lei Chen

Lei Chen/Project Handler

Approved by:

Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration Page
1. Version 5
2. Test Summary 6
3. Measurement Uncertainty 7
4. Product Information And Test Setup 8
4.1 Product Information 8
4.2 Test Setup Configuration 8
4.3 Support Equipment 8
4.4 Channel List 9
4.5 Test Mode 9
4.6 Table Of Parameters Of Text Software Setting 10
5. Test Facility And Test Instrument Used 11
5.1 Test Facility 11
5.2 Test Instrument Used 11
6. Conducted Emissions 13
6.1 Block Diagram Of Test Setup 13
6.2 Limit 13
6.3 Test Procedure 13
6.4 EUT Operating Conditions 13
6.5 Test Result 14
7. Radiated Emissions 16
7.1 Block Diagram Of Test Setup 16
7.2 Limit 17
7.3 Test Procedure 18
7.4 EUT Operating Conditions 19
7.5 Test Result 19
8. Radiated Band Emission Measurement And Restricted Bands Of Operation 26
8.1 Block Diagram Of Test Setup 26
8.2 Limit 26
8.3 Test Procedure 27
8.4 EUT operating Conditions 27
8.5 Test Result 28
9. Power Spectral Density Test 30
9.1 Block Diagram Of Test Setup 30
9.2 Limit 30
9.3 Test Procedure 30
9.4 EUT Operating Conditions 30
9.5 Test Result 31
10. Bandwidth Test 38
10.1 Block Diagram Of Test Setup 38
10.2 Limit 38
10.3 Test Procedure 38
10.4 EUT Operating Conditions 38

10.5 Test Result 39
11. Peak Output Power Test 46
11.1 Block Diagram Of Test Setup 46
11.2 Limit 46
11.3 Test Procedure 46
11.4 EUT Operating Conditions 46
11.5 Test Result 47
12. 100 KHz Bandwidth Of Frequency Band Edge 48
12.1 Block Diagram Of Test Setup 48
12.2 Limit 48
12.3 Test Procedure 48
12.4 EUT Operating Conditions 48
12.5 Test Result 49
13. Duty Cycle Of Test Signal 69
13.1 Standard Requirement 69
13.2 Formula 69
13.3 Test Procedure 69
13.4 Test Result 69
14. Antenna Requirement 72
14.1 Limit 72
14.2 Test Result 72
15. EUT Photographs 73
16. EUT Test Setup Photographs 74

(Note: N/A means not applicable)

1. Version

Report No.	Issue Date	Description	Approved
BCTC2505932380E	2025-06-10	Original	Valid

2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Conducted Emission	15.207	PASS
2	6dB Bandwidth	15.247 (a)(2)	PASS
3	Peak Output Power	15.247 (b)	PASS
4	Radiated Spurious Emission	15.247 (d)	PASS
5	Power Spectral Density	15.247 (e)	PASS
6	Restricted Band of Operation	15.205	PASS
7	Band Edge (Out of Band Emissions)	15.247 (d)	PASS
8	Antenna Requirement	15.203	PASS
9	Duty Cycle	/	/

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	Power Spectral Density	U=1.19dB
10	Peak Output Power	U=0.31dB
11	Occupied Bandwidth/Frequency Range	U=3.46%
12	humidity uncertainty	U=5.3%
13	Temperature uncertainty	U=0.59℃

4. Product Information And Test Setup

4.1 Product Information

Model/Type reference:	71
Model differences:	N/A
Hardware Version:	V 1.0
Software Version:	V 6.1.3
Operation Frequency:	802.11b/g/n20MHz:2412~2462 MHz 802.11n40MHz:2422~2452 MHz
Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n Up to 150Mbps
Type of Modulation:	OFDM/DSSS
Number Of Channel	802.11b/g/n20MHz:11 CH 802.11n40MHz: 7 CH
Antenna installation:	PCB antenna
Antenna Gain:	4.4 dBi Remark: ☒ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. ☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
Ratings:	AC 100-240V 50/60Hz

4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	SPAZA REFILL MACHINE	SPAZA®	71	N/A	EUT

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

Channel List for 802.11b/g/n(20)					
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
01	2412	02	2417	03	2422
04	2427	05	2432	06	2437
07	2442	08	2447	09	2452
10	2457	11	2462		

Channel List for 802.11n(40)					
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
03	2422	04	2427	05	2432
06	2437	07	2442	08	2447
09	2452				

4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For All Mode	Description	Modulation Type
Mode 1	CH 01	802.11b
Mode 2	CH 06	
Mode 3	CH 11	
Mode 4	CH 01	802.11g
Mode 5	CH 06	
Mode 6	CH 11	
Mode 7	CH 01	802.11n20
Mode 8	CH 06	
Mode 9	CH 11	
Mode 10	CH 03	802.11n40
Mode 11	CH 06	
Mode 12	CH 09	
Mode 13	WIFI Linking	

Note:
(1) The measurements are performed at all Bit Rate of Transmiter, the worst data was reported.

4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	**EspRFTestTool_v4.6_Manual**		
Frequency	2412 MHz	2437 MHz	2462 MHz
Parameters	DEF	DEF	DEF
Frequency	2422MHz	2437MHz	2452MHz
Parameters	DEF	DEF	DEF

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.
FCC Test Firm Registration Number: 712850
A2LA certificate registration number is: CN1212
ISED Registered No.: 23583
ISED CAB identifier: CN0017

5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	**Manufacturer**	**Model#**	**Serial#**	**Last Cal.**	**Next Cal.**
Receiver	R&S	ESR	102075	May 08, 2025	May 07, 2026
LISN	R&S	ENV216	101375	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 14, 2025	May 13, 2026

RF Conducted Test					
Equipment	**Manufacturer**	**Model#**	**Serial#**	**Last Cal.**	**Next Cal.**
Power meter	Keysight	E4419	\	May 14, 2025	May 13, 2026
Power Sensor (AV)	Keysight	E9300A	\	May 14, 2025	May 13, 2026
Signal Analyzer20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 14, 2025	May 13, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Radio frequency control box	MAIWEI	MW100-RFCB	\	\	\
Software	MAIWEI	MTS 8310	\	\	\

Radiated Emissions Test (966 Chamber01)					
Equipment	**Manufacturer**	**Model#**	**Serial#**	**Last Cal.**	**Next Cal.**
966 chamber	ChengYu	966 Room	966	May 15, 2023	May 14, 2026
Receiver	R&S	ESR	102075	May 08, 2025	May 07, 2026
Receiver	R&S	ESRP	101154	May 14, 2025	May 13, 2026
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 14, 2025	May 13, 2026
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 24, 2025	May 23, 2026
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 24, 2025	May 23, 2026
Amplifier	SKET	LAPA_01G18 G-45dB	SK202104090 1	May 14, 2025	May 13, 2026
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 24, 2025	May 23, 2026
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35-HG	2034381	May 24, 2025	May 23, 2026
Horn Antenna(18G Hz-40GHz)	Schwarzbeck	BBHA9170	00822	May 24, 2025	May 23, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

FREQUENCY (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00
Notes: 1. *Decreasing linearly with logarithm of frequency. 2. The lower limit shall apply at the transition frequencies.		

6.3 Test Procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

a. The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
b. The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
c. For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	23 ℃	Relative Humidity:	54%
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 13	Test Voltage :	AC 120V/60Hz



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.1635	37.94	20.07	58.01	65.28	-7.27	QP
2		0.1635	24.40	20.07	44.47	55.28	-10.81	AVG
3		0.1859	37.13	20.07	57.20	64.22	-7.02	QP
4	*	0.1859	27.34	20.07	47.41	54.22	-6.81	AVG
5		0.9284	9.95	20.09	30.04	56.00	-25.96	QP
6		0.9284	2.43	20.09	22.52	46.00	-23.48	AVG
7		5.3158	5.12	20.15	25.27	60.00	-34.73	QP
8		5.3158	-11.80	20.15	8.35	50.00	-41.65	AVG
9		15.3330	9.78	20.31	30.09	60.00	-29.91	QP
10		15.3330	-5.72	20.31	14.59	50.00	-35.41	AVG
11		18.2310	15.05	20.32	35.37	60.00	-24.63	QP
12		18.2310	0.43	20.32	20.75	50.00	-29.25	AVG

Temperature:	23 ℃	Relative Humidity:	54%
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 13	Test Voltage :	AC 120V/60Hz



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1	*	0.1590	37.31	20.07	57.38	65.52	-8.14	QP
2		0.1590	26.75	20.07	46.82	55.52	-8.70	AVG
3		0.3300	23.95	20.07	44.02	59.45	-15.43	QP
4		0.3300	11.62	20.07	31.69	49.45	-17.76	AVG
5		0.7214	17.65	20.09	37.74	56.00	-18.26	QP
6		0.7214	4.31	20.09	24.40	46.00	-21.60	AVG
7		3.3540	6.06	20.13	26.19	56.00	-29.81	QP
8		3.3540	-7.38	20.13	12.75	46.00	-33.25	AVG
9		13.2720	12.15	20.26	32.41	60.00	-27.59	QP
10		13.2720	-2.63	20.26	17.63	50.00	-32.37	AVG
11		19.3781	17.76	20.33	38.09	60.00	-21.91	QP
12		19.3781	3.29	20.33	23.62	50.00	-26.38	AVG

7. Radiated Emissions

7.1 Block Diagram Of Test Setup

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency	Field Strength	Distance	Field Strength Limit at 3m Distance	
(MHz)	uV/m	(m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:
(1) The limit for radiated test was performed according to FCC PART 15C.
(2) The tighter limit applies at the band edges.
(3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

7.3 Test Procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Spectrum Parameter	Setting
1-25GHz	RBW 1 MHz /VBW 1 MHz for Peak, RBW 1 MHz / VBW 10Hz for Average

Below 1GHz test procedure as below:
a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Above 1GHz test procedure as below:
g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
Note:
Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

Above 1GHz test procedure as below:
a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
g. Test the EUT in the lowest channel, the Highest channel.
Note:
Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	24.8 ℃	Relative Humidity:	60%
Pressure:	101KPa	Test Voltage :	AC 120V/60Hz
Test Mode:	Mode 1-12	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

Between 30MHz – 1GHz

Temperature:	24.8 ℃	Relative Humidity:	60%
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 3 (the worst mode)	Test Voltage :	AC 120V/60Hz



Remark:
1.Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	59.2325	37.04	-15.15	21.89	40.00	-18.11	QP
2		104.5361	33.43	-16.25	17.18	43.50	-26.32	QP
3		202.1005	39.51	-15.66	23.85	43.50	-19.65	QP
4		242.5252	39.76	-14.50	25.26	46.00	-20.74	QP
5		407.5144	38.48	-10.69	27.79	46.00	-18.21	QP
6		706.6998	26.65	-5.61	21.04	46.00	-24.96	QP

Temperature:	24.8 ℃	Relative Humidity:	60%
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 3 (the worst mode)	Test Voltage :	AC 120V/60Hz



Remark:
1.Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		31.7313	42.03	-16.32	25.71	40.00	-14.29	QP
2	*	46.6664	47.35	-14.17	33.18	40.00	-6.82	QP
3		62.1928	45.41	-15.85	29.56	40.00	-10.44	QP
4		195.8220	43.94	-16.03	27.91	43.50	-15.59	QP
5		344.3854	33.84	-11.68	22.16	46.00	-23.84	QP
6		706.6998	27.00	-5.61	21.39	46.00	-24.61	QP

Between 1GHz – 25GHz

802.11b

Polar (H/V)	Fre-quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure-ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low channel:2412MHz							
V	4824.00	64.51	-19.95	44.56	74.00	-29.44	PK
V	4824.00	57.31	-19.95	37.36	54.00	-16.64	AV
V	7236.00	66.07	-14.14	51.93	74.00	-22.07	PK
V	7236.00	55.52	-14.14	41.38	54.00	-12.62	AV
H	4824.00	64.68	-19.95	44.73	74.00	-29.27	PK
H	4824.00	54.16	-19.95	34.21	54.00	-19.79	AV
H	7236.00	67.13	-14.14	52.99	74.00	-21.01	PK
H	7236.00	58.25	-14.14	44.11	54.00	-9.89	AV
Middle channel:2437MHz							
V	4874.00	64.99	-19.85	45.14	74.00	-28.86	PK
V	4874.00	58.00	-19.85	38.15	54.00	-15.85	AV
V	7311.00	68.29	-13.93	54.36	74.00	-19.64	PK
V	7311.00	54.84	-13.93	40.91	54.00	-13.09	AV
H	4874.00	67.57	-19.85	47.72	74.00	-26.28	PK
H	4874.00	57.57	-19.85	37.72	54.00	-16.28	AV
H	7311.00	68.02	-13.93	54.09	74.00	-19.91	PK
H	7311.00	59.88	-13.93	45.95	54.00	-8.05	AV
High channel:2462MHz							
V	4924.00	65.67	-19.75	45.92	74.00	-28.08	PK
V	4924.00	54.68	-19.75	34.93	54.00	-19.07	AV
V	7386.00	67.68	-13.72	53.96	74.00	-20.04	PK
V	7386.00	58.79	-13.72	45.07	54.00	-8.93	AV
H	4924.00	68.17	-19.75	48.42	74.00	-25.58	PK
H	4924.00	54.62	-19.75	34.87	54.00	-19.13	AV
H	7386.00	65.26	-13.72	51.54	74.00	-22.46	PK
H	7386.00	58.74	-13.72	45.02	54.00	-8.98	AV

Remark:
1. Measurement = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier,
Over= Measurement – Limit
2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Fre-quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure-ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low channel:2412MHz							
V	4824.00	66.16	-19.95	46.21	74.00	-27.79	PK
V	4824.00	59.97	-19.95	40.02	54.00	-13.98	AV
V	7236.00	68.44	-14.14	54.30	74.00	-19.70	PK
V	7236.00	57.70	-14.14	43.56	54.00	-10.44	AV
H	4824.00	64.52	-19.95	44.57	74.00	-29.43	PK
H	4824.00	56.85	-19.95	36.90	54.00	-17.10	AV
H	7236.00	66.20	-14.14	52.06	74.00	-21.94	PK
H	7236.00	59.06	-14.14	44.92	54.00	-9.08	AV
Middle channel:2437MHz							
V	4874.00	69.34	-19.85	49.49	74.00	-24.51	PK
V	4874.00	59.67	-19.85	39.82	54.00	-14.18	AV
V	7311.00	69.70	-13.93	55.77	74.00	-18.23	PK
V	7311.00	55.41	-13.93	41.48	54.00	-12.52	AV
H	4874.00	65.89	-19.85	46.04	74.00	-27.96	PK
H	4874.00	58.10	-19.85	38.25	54.00	-15.75	AV
H	7311.00	67.22	-13.93	53.29	74.00	-20.71	PK
H	7311.00	58.03	-13.93	44.10	54.00	-9.90	AV
High channel:2462MHz							
V	4924.00	66.92	-19.75	47.17	74.00	-26.83	PK
V	4924.00	54.05	-19.75	34.30	54.00	-19.70	AV
V	7386.00	69.24	-13.72	55.52	74.00	-18.48	PK
V	7386.00	56.05	-13.72	42.33	54.00	-11.67	AV
H	4924.00	64.56	-19.75	44.81	74.00	-29.19	PK
H	4924.00	54.49	-19.75	34.74	54.00	-19.26	AV
H	7386.00	68.04	-13.72	54.32	74.00	-19.68	PK
H	7386.00	57.73	-13.72	44.01	54.00	-9.99	AV

Remark:
1. Measurement = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier,
Over= Measurement – Limit
2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n20

Polar (H/V)	Fre-quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure-ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low channel:2412MHz							
V	4824.00	69.45	-19.95	49.50	74.00	-24.50	PK
V	4824.00	58.28	-19.95	38.33	54.00	-15.67	AV
V	7236.00	66.47	-14.14	52.33	74.00	-21.67	PK
V	7236.00	59.56	-14.14	45.42	54.00	-8.58	AV
H	4824.00	64.36	-19.95	44.41	74.00	-29.59	PK
H	4824.00	55.26	-19.95	35.31	54.00	-18.69	AV
H	7236.00	68.98	-14.14	54.84	74.00	-19.16	PK
H	7236.00	56.93	-14.14	42.79	54.00	-11.21	AV
Middle channel:2437MHz							
V	4874.00	66.58	-19.85	46.73	74.00	-27.27	PK
V	4874.00	58.74	-19.85	38.89	54.00	-15.11	AV
V	7311.00	64.01	-13.93	50.08	74.00	-23.92	PK
V	7311.00	57.54	-13.93	43.61	54.00	-10.39	AV
H	4874.00	68.81	-19.85	48.96	74.00	-25.04	PK
H	4874.00	57.69	-19.85	37.84	54.00	-16.16	AV
H	7311.00	69.53	-13.93	55.60	74.00	-18.40	PK
H	7311.00	57.47	-13.93	43.54	54.00	-10.46	AV
High channel:2462MHz							
V	4924.00	66.64	-19.75	46.89	74.00	-27.11	PK
V	4924.00	56.67	-19.75	36.92	54.00	-17.08	AV
V	7386.00	66.46	-13.72	52.74	74.00	-21.26	PK
V	7386.00	57.64	-13.72	43.92	54.00	-10.08	AV
H	4924.00	68.28	-19.75	48.53	74.00	-25.47	PK
H	4924.00	58.25	-19.75	38.50	54.00	-15.50	AV
H	7386.00	67.63	-13.72	53.91	74.00	-20.09	PK
H	7386.00	55.03	-13.72	41.31	54.00	-12.69	AV

Remark:
1. Measurement = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier,
Over= Measurement – Limit
2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n40

Polar (H/V)	Fre-quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure-ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low channel:2422MHz							
V	4844.00	69.63	-19.91	49.72	74.00	-24.28	PK
V	4844.00	58.62	-19.91	38.71	54.00	-15.29	AV
V	7266.00	66.72	-14.06	52.66	74.00	-21.34	PK
V	7266.00	56.00	-14.06	41.94	54.00	-12.06	AV
H	4844.00	64.76	-19.91	44.85	74.00	-29.15	PK
H	4844.00	56.06	-19.91	36.15	54.00	-17.85	AV
H	7266.00	67.26	-14.06	53.20	74.00	-20.80	PK
H	7266.00	55.40	-14.06	41.34	54.00	-12.66	AV
Middle channel:2437MHz							
V	4874.00	69.74	-19.85	49.89	74.00	-24.11	PK
V	4874.00	55.88	-19.85	36.03	54.00	-17.97	AV
V	7311.00	68.74	-13.93	54.81	74.00	-19.19	PK
V	7311.00	59.98	-13.93	46.05	54.00	-7.95	AV
H	4874.00	69.01	-19.85	49.16	74.00	-24.84	PK
H	4874.00	54.23	-19.85	34.38	54.00	-19.62	AV
H	7311.00	68.42	-13.93	54.49	74.00	-19.51	PK
H	7311.00	56.16	-13.93	42.23	54.00	-11.77	AV
High channel:2452MHz							
V	4904.00	69.72	-19.79	49.93	74.00	-24.07	PK
V	4904.00	58.99	-19.79	39.20	54.00	-14.80	AV
V	7356.00	64.76	-13.80	50.96	74.00	-23.04	PK
V	7356.00	54.29	-13.80	40.49	54.00	-13.51	AV
H	4904.00	68.75	-19.79	48.96	74.00	-25.04	PK
H	4904.00	54.44	-19.79	34.65	54.00	-19.35	AV
H	7356.00	66.82	-13.80	53.02	74.00	-20.98	PK
H	7356.00	59.01	-13.80	45.21	54.00	-8.79	AV

Remark:
1. Measurement = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier,
Over= Measurement – Limit
2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8. Radiated Band Emission Measurement And Restricted Bands Of Operation

8.1 Block Diagram Of Test Setup

Radiated Emission Test-Up Frequency Above 1GHz



8.2 Limit

FCC Part15 C Section 15.209 and 15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:
(1) The limit for radiated test was performed according to FCC PART 15C.
(2) The tighter limit applies at the band edges.
(3) Emission level (dBuV/m)=20log Emission level (uV/m).

8.3 Test Procedure

Receiver Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Above 1GHz test procedure as below:
a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
g. Test the EUT in the lowest channel, the Highest channel.
Note:
Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

8.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

8.5 Test Result

	Polar (H/V)	Fre-quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure-ment (dBuV/m)	Measure-ment (dBuV/m)		Over	Result
					PK	PK	AV	PK	
802.11b	Low Channel 2412MHz								
	H	2310.00	70.83	-25.67	45.16	74.00	54.00	-28.84	PASS
	H	2390.00	72.98	-25.43	47.55	74.00	54.00	-26.45	PASS
	V	2310.00	70.25	-25.67	44.58	74.00	54.00	-29.42	PASS
	V	2390.00	71.65	-25.43	46.22	74.00	54.00	-27.78	PASS
	High Channel 2462MHz								
	H	2483.50	75.13	-25.15	49.98	74.00	54.00	-24.02	PASS
	H	2500.00	75.92	-25.10	50.82	74.00	54.00	-23.18	PASS
	V	2483.50	75.85	-25.15	50.70	74.00	54.00	-23.30	PASS
	V	2500.00	74.42	-25.10	49.32	74.00	54.00	-24.68	PASS
802.11g	Low Channel 2412MHz								
	H	2310.00	74.96	-25.67	49.29	74.00	54.00	-24.71	PASS
	H	2390.00	75.61	-25.43	50.18	74.00	54.00	-23.82	PASS
	V	2310.00	73.56	-25.67	47.89	74.00	54.00	-26.11	PASS
	V	2390.00	77.15	-25.43	51.72	74.00	54.00	-22.28	PASS
	High Channel 2462MHz								
	H	2483.50	72.29	-25.15	47.14	74.00	54.00	-26.86	PASS
	H	2500.00	75.24	-25.10	50.14	74.00	54.00	-23.86	PASS
	V	2483.50	74.66	-25.15	49.51	74.00	54.00	-24.49	PASS
	V	2500.00	74.07	-25.10	48.97	74.00	54.00	-25.03	PASS

Remark:
1. Measurement = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier,
Over= Measurement – Limit
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.
3 In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

	Polar (H/V)	Fre-quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure-ment (dBuV/m)	Measure-ment (dBuV/m)		Over	Result
					PK	PK	AV	PK	
802.11 n20	Low Channel 2412MHz								
	H	2310.00	70.85	-25.67	45.18	74.00	54.00	-28.82	PASS
	H	2390.00	72.50	-25.43	47.07	74.00	54.00	-26.93	PASS
	V	2310.00	73.02	-25.67	47.35	74.00	54.00	-26.65	PASS
	V	2390.00	73.19	-25.43	47.76	74.00	54.00	-26.24	PASS
	High Channel 2462MHz								
	H	2483.50	74.72	-25.15	49.57	74.00	54.00	-24.43	PASS
	H	2500.00	75.14	-25.10	50.04	74.00	54.00	-23.96	PASS
	V	2483.50	71.11	-25.15	45.96	74.00	54.00	-28.04	PASS
	V	2500.00	69.33	-25.10	44.23	74.00	54.00	-29.77	PASS
802.11 n40	Low Channel 2422MHz								
	H	2310.00	70.52	-25.67	44.85	74.00	54.00	-29.15	PASS
	H	2390.00	72.51	-25.43	47.08	74.00	54.00	-26.92	PASS
	V	2310.00	76.63	-25.67	50.96	74.00	54.00	-23.04	PASS
	V	2390.00	77.98	-25.43	52.55	74.00	54.00	-21.45	PASS
	High Channel 2452MHz								
	H	2483.50	77.34	-25.15	52.19	74.00	54.00	-21.81	PASS
	H	2500.00	73.96	-25.10	48.86	74.00	54.00	-25.14	PASS
	V	2483.50	72.95	-25.15	47.80	74.00	54.00	-26.20	PASS
	V	2500.00	73.53	-25.10	48.43	74.00	54.00	-25.57	PASS

Remark:
1. Measurement = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier,
Over= Measurement – Limit
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.
3 In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

9. Power Spectral Density Test

9.1 Block Diagram Of Test Setup



9.2 Limit

FCC Part15 (15.247) , Subpart C				
Section	**Test Item**	**Limit**	**Frequency Range (MHz)**	**Result**
15.247 (e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

9.3 Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

9.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.
Note: Power Spectral Density(dBm)=Reading+Cable Loss

9.5 Test Result

Temperature:	26℃	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz	Remark:	N/A

Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/10kHz)	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	-15.06	-20.29	8	Pass
NVNT	b	2437	-14.56	-19.79	8	Pass
NVNT	b	2462	-14.22	-19.45	8	Pass
NVNT	g	2412	-19.48	-24.71	8	Pass
NVNT	g	2437	-18.8	-24.03	8	Pass
NVNT	g	2462	-18.58	-23.81	8	Pass
NVNT	n20	2412	-19.45	-24.68	8	Pass
NVNT	n20	2437	-18.91	-24.14	8	Pass
NVNT	n20	2462	-18.77	-24	8	Pass
NVNT	n40	2422	-21.78	-27.01	8	Pass
NVNT	n40	2437	-22.32	-27.55	8	Pass
NVNT	n40	2452	-21.95	-27.18	8	Pass
Note: Correction Factor = 10log(3KHz/RBW in measurement) =-5.23 Power Spectral Density (dBm/3kHz)= Power Spectral Density (dBm/10kHz)-5.23						

Test Graphs

PSD NVNT b 2412MHz

PSD NVNT b 2437MHz

PSD NVNT b 2462MHz

PSD NVNT g 2412MHz



PSD NVNT g 2437MHz



PSD NVNT g 2462MHz



PSD NVNT n20 2412MHz



PSD NVNT n20 2437MHz



PSD NVNT n20 2462MHz



PSD NVNT n40 2422MHz



PSD NVNT n40 2437MHz



PSD NVNT n40 2452MHz



10. Bandwidth Test

10.1 Block Diagram Of Test Setup

10.2 Limit

FCC Part15 (15.247) , Subpart C				
Section	**Test Item**	**Limit**	**Frequency Range (MHz)**	**Result**
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

10.3 Test Procedure

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

10.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.
Note: Power Spectral Density(dBm)=Reading+Cable Loss

10.5 Test Result

Temperature:	26℃	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz	Remark:	N/A

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	9.514	0.5	Pass
NVNT	b	2437	9.513	0.5	Pass
NVNT	b	2462	10.011	0.5	Pass
NVNT	g	2412	16.538	0.5	Pass
NVNT	g	2437	16.52	0.5	Pass
NVNT	g	2462	16.472	0.5	Pass
NVNT	n20	2412	17.625	0.5	Pass
NVNT	n20	2437	17.6	0.5	Pass
NVNT	n20	2462	17.633	0.5	Pass
NVNT	n40	2422	34.252	0.5	Pass
NVNT	n40	2437	34.195	0.5	Pass
NVNT	n40	2452	34.513	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz



-6dB Bandwidth NVNT b 2437MHz



-6dB Bandwidth NVNT b 2462MHz



-6dB Bandwidth NVNT g 2412MHz



-6dB Bandwidth NVNT g 2437MHz



-6dB Bandwidth NVNT g 2462MHz



-6dB Bandwidth NVNT n20 2412MHz



-6dB Bandwidth NVNT n20 2437MHz



-6dB Bandwidth NVNT n20 2462MHz



-6dB Bandwidth NVNT n40 2422MHz



-6dB Bandwidth NVNT n40 2437MHz



-6dB Bandwidth NVNT n40 2452MHz



11. Peak Output Power Test

11.1 Block Diagram Of Test Setup



11.2 Limit

FCC Part15 (15.247) , Subpart C				
Section	**Test Item**	**Limit**	**Frequency Range (MHz)**	**Result**
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

11.3 Test Procedure

a. The EUT was directly connected to the Power meter

11.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.
Note: Power Spectral Density(dBm)=Reading+Cable Loss

11.5 Test Result

Temperature:	26℃	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz	Remark:	N/A

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	6.36	30	Pass
NVNT	b	2437	6.8	30	Pass
NVNT	b	2462	7.1	30	Pass
NVNT	g	2412	5.36	30	Pass
NVNT	g	2437	5.94	30	Pass
NVNT	g	2462	6.1	30	Pass
NVNT	n20	2412	4.09	30	Pass
NVNT	n20	2437	4.68	30	Pass
NVNT	n20	2462	4.84	30	Pass
NVNT	n40	2422	3.35	30	Pass
NVNT	n40	2437	3.32	30	Pass
NVNT	n40	2452	3.48	30	Pass

12. 100 KHz Bandwidth Of Frequency Band Edge

12.1 Block Diagram Of Test Setup



12.2 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

12.3 Test Procedure

Using the following spectrum analyzer setting:
a) Set the RBW = 100KHz.
b) Set the VBW = 300KHz.
c) Sweep time = auto couple.
d) Detector function = peak.
e) Trace mode = max hold.
f) Allow trace to fully stabilize.

12.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.
Note: Power Spectral Density(dBm)=Reading+Cable Loss

12.5 Test Result

Test Graphs

Band Edge NVNT b 2412MHz

Band Edge NVNT b 2412MHz Emission



Band Edge NVNT b 2462MHz

Band Edge NVNT b 2462MHz Emission



Band Edge NVNT g 2412MHz



Band Edge NVNT g 2412MHz Emission



Band Edge NVNT g 2462MHz



Band Edge NVNT g 2462MHz Emission



Band Edge NVNT n20 2412MHz



Band Edge NVNT n20 2412MHz Emission



Band Edge NVNT n20 2462MHz



Band Edge NVNT n20 2462MHz Emission



Band Edge NVNT n40 2422MHz



Band Edge NVNT n40 2422MHz Emission



Band Edge NVNT n40 2452MHz

Band Edge NVNT n40 2452MHz Emission



Test Graphs

Tx. Spurious NVNT b 2412MHz

Tx. Spurious NVNT b 2412MHz Emission



Tx. Spurious NVNT b 2437MHz

Tx. Spurious NVNT b 2437MHz Emission



Tx. Spurious NVNT b 2462MHz

Tx. Spurious NVNT b 2462MHz Emission



Tx. Spurious NVNT g 2412MHz



Tx. Spurious NVNT g 2412MHz Emission



Tx. Spurious NVNT g 2437MHz



Tx. Spurious NVNT g 2437MHz Emission



Tx. Spurious NVNT g 2462MHz



Tx. Spurious NVNT g 2462MHz Emission



Tx. Spurious NVNT n20 2412MHz



Tx. Spurious NVNT n20 2412MHz Emission



Tx. Spurious NVNT n20 2437MHz



Tx. Spurious NVNT n20 2437MHz Emission



Tx. Spurious NVNT n20 2462MHz



Tx. Spurious NVNT n20 2462MHz Emission



Tx. Spurious NVNT n40 2422MHz

Tx. Spurious NVNT n40 2422MHz Emission



Tx. Spurious NVNT n40 2437MHz



Tx. Spurious NVNT n40 2437MHz Emission



Tx. Spurious NVNT n40 2452MHz



Tx. Spurious NVNT n40 2452MHz Emission



13. Duty Cycle Of Test Signal

13.1 Standard Requirement

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

13.2 Formula

Duty Cycle = Ton / (Ton+Toff)

13.3 Test Procedure

1.Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak

13.4 Test Result

Condition	Mode	Frequency (MHz)	Duty Cycle (%)
NVNT	b	2412	100
NVNT	g	2412	100
NVNT	n20	2412	100
NVNT	n40	2422	100

Test Graphs

Duty Cycle NVNT b 2412MHz



Duty Cycle NVNT g 2412MHz



Duty Cycle NVNT n20 2412MHz



Duty Cycle NVNT n40 2422MHz



14. Antenna Requirement

14.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

14.2 Test Result

The EUT antenna is PCB antenna, antenna connector type is IPEX, fulfill the requirement of this section.

15. EUT Photographs

EUT Photo 1

EUT Photo 2

NOTE: Appendix-Photographs Of EUT Constructional Details.

16. EUT Test Setup Photographs

Conducted Emissions Photo

Radiated Measurement Photos



BCTC
倍 测 检 测

STATEMENT

1. The equipment lists are traceable to the national reference standards.

2. The test report can not be partially copied unless prior written approval is issued from our lab.

3. The test report is invalid without the "special seal for inspection and testing".

4. The test report is invalid without the signature of the approver.

5. The test process and test result is only related to the Unit Under Test.

6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.

7. The quality system of our laboratory is in accordance with ISO/IEC17025.

8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:
1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

※※※※※ END ※※※※※