



Shenzhen XINHENGYANG Technology Co., Ltd

SPECIFICATION

Customer Name: _____

Product Model: CEILING-MOUNTED AP ER3075

Customer P/N : 3701000711

XINHENGYANG P/N: CP. 21. 0000346

SPECIFICATIONS: WiFi-6G-CH2/FPC/L=170MM white

Production date: 2025. 10. 15

Sample Version: R1

XINHENGYANG		
FICTION	DQE	R&D
Customer		
PUR	QC	R&D

Manufacturer: Shenzhen Xinhengyang Technology Co., LTD

Address: 1 / F, Building B, Aerospace micromotor Building, No.7 Langshan No.2

Road, Xili Street, Nanshan District, Shenzhen

Tel: 0755-83600916 Email: gc@xhy-2008.com

Network address: <https://www.xhy-2008.com>

R & D, production and sales of professional wireless terminal antenna



Directory Index

1、	Cover	1
2、	Index	2
3、	Change history	3
4、	The basic parameters	4
5、	TestEquipment & Conditions	5
6、	Performance testing	6-9
7、	Product Drawing	10
8、	RoHS	11
9、	Product packaging instructions	11



3、Change history

Number	Effective date	Change record
R1	2025.10.15	Initial release



4、The basic parameters

A. Electrical Characteristics	
Frequency	5925MHz-7125MHz
VSWR	< 2.0
Avg Efficiency	>50%
Impedance	50 Ohm
Polarization	Linear
Peak Gain	5.28dBi
B. Material & Mechanical	
Material of Radiator	FPC Black
Cable Type	Φ1.37 L=170MM±3.0MM white
Connector Type	One
Dimension	19.9MM*13.0MM±0.15MM FPC Black
C. Environmental	
Operation Temperature	- 20 °C ~ + 60 °C
Storage Temperature	- 20 °C ~ + 60 °C


5、 Introduction:

Microwave darkroom and no reflection chamber, absorbing short wave darkroom dark room. Microwave darkroom by electromagnetic shielding room, filtering and isolation, grounding device, the ventilation duct, indoor distribution system, monitoring system, ceiling wave material part. It is based on the wave absorbing material as the lining of the shield room, it can absorb the most of the electromagnetic energy into the six wall is a better simulation of the free space conditions.

The main working principle of microwave anechoic chamber is according to the electromagnetic wave in the medium from the low magnetic guide magnetic direction of propagation rules, absorbing materials to guide the electromagnetic wave using high permeability, through resonance, a substantial absorption of electromagnetic wave radiation energy, by coupling the electromagnetic energy into heat energy.

main performance:

Frequency range:400MHz ~ 6GHz ceiling reflected wave loss materials: 400MHz ~ 6GHz is equal to or more than 15dB (microwave absorbing material by composite wave absorbing materials, namely tapered containing carbon sponge suction wave material paste in ferrite).



6、Performance Test report

Those specifications were specially defined for CEILING-MOUNTED AP ER3075 model.

6.1、Prototype position:



6.2、VSWR


1. Measuring Method

A 50 Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the VSWR.

Keeping this jig away from metal at least 20cm





2. Measurement frequency points and VSWR value

WiFi-6G-CH2



6.3、2D/3D field pattern diagram


WiFi 6G-CH2-
6500MHz



6.4、Passive efficiency & Gain

5925MHz-7125MHz					
WiFi 6E-CH2					
Frequency (MHz)	Gain (dBi)	Efficiency (%)	Frequency (MHz)	Gain (dBi)	Efficiency (%)
5925.0	3.59	60.51	6550.0	3.65	53.42
5950.0	3.26	57.49	6600.0	2.36	56.76
6000.0	3.83	62.96	6650.0	3.70	58.16
6050.0	3.61	60.89	6700.0	3.32	55.40
6100.0	2.96	59.38	6750.0	3.64	68.95
6150.0	3.22	60.72	6800.0	3.89	55.41
6200.0	4.13	57.99	6850.0	3.80	56.61
6250.0	4.24	59.54	6900.0	3.63	61.99
6300.0	4.16	57.20	6950.0	3.90	54.91
6350.0	4.58	55.49	7000.0	5.28	68.02
6400.0	3.80	52.22	7050.0	3.90	59.36
6450.0	3.31	59.41	7100.0	3.70	51.57
6500.0	3.26	54.75	7125.0	4.60	54.93

7、Product Drawing





8、RoHS

Antenna CP.21.0000346 meets RoHS requirements See electronic file for details.

9、Product packaging instructions

A. packing should meet the moistureproof, vibration, pressure and mildew proof, etc.

B. the smallest packing unit logo must have the manufacturer trademarks, product model, name, code and quantity.

C. in the attached packing list, certificate of approval, and the factory inspection report.

*****END*****