



**中认信通**

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



# TEST REPORT

**Applicant:** SmartEase Ltd.

Address: 3107 Iris Avenue Suite 200, Boulder, Colorado, United States

**FCC ID:** 2BQWOG03

**Product Name:** Smart wireless intercom audio ski goggles

**Standard(s):** 47 CFR Part 95 Subpart B  
ANSI C63.26-2015

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number:** 2503V71118E-RF-00C

**Date Of Issue:** 2025/12/5

**Reviewed By:** Calvin Chen

Title: RF Test Supervisor

**Approved By:** Sun Zhong

Title: Manager

**Test Laboratory:** China Certification ICT Co., Ltd (Dongguan)

Room 101 & 201, Building 2, 256 Pingdong Road, Dalang Town,  
Dongguan City, Guangdong, China

Tel: +86-769-83085888

[www.ccttt.com.cn](http://www.ccttt.com.cn)

**Test Facility**

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the Room 101 & 201, Building 2, 256 Pingdong Road, Dalang Town, Dongguan City, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

**Declarations**

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Each test item follows the test standard(s) without deviation.

# CONTENTS

|                                                                     |           |
|---------------------------------------------------------------------|-----------|
| <b>DOCUMENT REVISION HISTORY .....</b>                              | <b>5</b>  |
| <b>1. GENERAL INFORMATION .....</b>                                 | <b>6</b>  |
| <b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b> | <b>6</b>  |
| <b>1.2 DESCRIPTION OF TEST CONFIGURATION.....</b>                   | <b>7</b>  |
| 1.2.1 EUT Operation Condition:.....                                 | 7         |
| 1.2.2 Support Equipment List and Details .....                      | 7         |
| 1.2.3 Support Cable List and Details .....                          | 7         |
| 1.2.4 Block Diagram of Test Setup.....                              | 7         |
| <b>1.3 MEASUREMENT UNCERTAINTY .....</b>                            | <b>8</b>  |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                             | <b>9</b>  |
| <b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>                    | <b>10</b> |
| <b>3.1 FRS FREQUENCY ACCURACY .....</b>                             | <b>10</b> |
| 3.1.1 Applicable Standard.....                                      | 10        |
| 3.1.2 EUT Setup Block Diagram .....                                 | 10        |
| 3.1.3 Test Procedure .....                                          | 10        |
| <b>3.2 FRS TRANSMIT POWER.....</b>                                  | <b>11</b> |
| 3.2.1 Applicable Standard.....                                      | 11        |
| 3.2.2 EUT Setup Block Diagram .....                                 | 11        |
| 3.2.3 Test Procedure .....                                          | 11        |
| <b>3.3 FRS EMISSION TYPES.....</b>                                  | <b>12</b> |
| 3.3.1 Applicable Standard.....                                      | 12        |
| 3.3.2 Judgment.....                                                 | 12        |
| <b>3.4 FRS AUTHORIZED BANDWIDTH AND EMISSION MASK.....</b>          | <b>13</b> |
| 3.4.1 Applicable Standard.....                                      | 13        |
| 3.4.2 EUT Setup Block Diagram .....                                 | 13        |
| 3.4.3 Test Procedure .....                                          | 13        |
| <b>3.5 FRS MODULATION LIMITS .....</b>                              | <b>15</b> |
| 3.5.1 Applicable Standard.....                                      | 15        |
| 3.5.2 EUT Setup Block Diagram .....                                 | 15        |
| 3.5.3 Test Procedure .....                                          | 15        |
| <b>3.6 FRS UNWANTED EMISSIONS LIMITS.....</b>                       | <b>16</b> |
| 3.6.1 Applicable Standard.....                                      | 16        |
| 3.6.2 Test setup: .....                                             | 17        |
| 3.6.3 Test Procedure: .....                                         | 18        |
| <b>3.7 FRS ADDITIONAL REQUIREMENTS .....</b>                        | <b>19</b> |
| 3.7.1 Applicable Standard.....                                      | 19        |
| 3.7.2 Judgment.....                                                 | 19        |
| <b>4. TEST DATA AND RESULTS .....</b>                               | <b>20</b> |
| <b>4.1 FRS FREQUENCY ACCURACY .....</b>                             | <b>20</b> |
| <b>4.2 FRS TRANSMIT POWER.....</b>                                  | <b>22</b> |

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>4.3 FRS AUTHORIZED BANDWIDTH AND EMISSION MASK .....</b> | <b>24</b> |
| <b>4.4 FRS MODULATION LIMITS .....</b>                      | <b>26</b> |
| <b>4.5 RADIATED SPURIOUS EMISSION .....</b>                 | <b>29</b> |
| <b>5. EUT PHOTOGRAPHS .....</b>                             | <b>31</b> |
| <b>6. TEST SETUP PHOTOGRAPHS .....</b>                      | <b>32</b> |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number      | Description of Revision | Date of Revision |
|-----------------|--------------------|-------------------------|------------------|
| 1.0             | 2503V71118E-RF-00C | Original Report         | 2025/12/5        |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

|                                        |                                                                           |
|----------------------------------------|---------------------------------------------------------------------------|
| <b>EUT Name:</b>                       | Smart wireless intercom audio ski goggles                                 |
| <b>EUT Model:</b>                      | G03                                                                       |
| <b>Modulation Type:</b>                | FM                                                                        |
| <b>Emission Designator:</b>            | 11K0F3E                                                                   |
| <b>Maximum Output Power:<br/>(ERP)</b> | 462.5500-462.7250MHz: 24.98dBm<br>467.5625-467.7125MHz: 24.74dBm          |
| <b>Rated Input Voltage:</b>            | 3.7Vdc from battery or 5Vdc from USB                                      |
| <b>Sample Number:</b>                  | 37C6-1(for RF Conducted Test)<br>37C6-2(Radiated Spurious Emissions Test) |
| <b>EUT Received Date:</b>              | 2025/8/11                                                                 |
| <b>EUT Received Status:</b>            | Good                                                                      |

### Operation Frequency Detail:

| Channel Number | Frequency (MHz) | Channel Number | Frequency (MHz) |
|----------------|-----------------|----------------|-----------------|
| 1              | 462.5625        | 12             | 467.6625        |
| 2              | 462.5875        | 13             | 467.6875        |
| 3              | 462.6125        | 14             | 467.7125        |
| 4              | <b>462.6375</b> | 15             | 462.5500        |
| 5              | 462.6625        | 16             | 462.5750        |
| 6              | 462.6875        | 17             | 462.6000        |
| 7              | 462.7125        | 18             | 462.6250        |
| 8              | 467.5625        | 19             | 462.6500        |
| 9              | 467.5875        | 20             | 462.6750        |
| 10             | 467.6125        | 21             | 462.7000        |
| 11             | <b>467.6375</b> | 22             | 462.7250        |

Per C63.26-2015, section 5.1, the frequency in bold was performed the test.

### Antenna Information Detail ▲:

| Antenna Type | Antenna Connector | input impedance (Ohm) | Frequency Range (MHz) | Antenna Gain       |
|--------------|-------------------|-----------------------|-----------------------|--------------------|
| Monopole     | Integral          | 50                    | 410-470               | 0.77 dBi(-1.38dBd) |

### Accessory Information:

| Accessory Description | Manufacturer | Model | Parameters |
|-----------------------|--------------|-------|------------|
| /                     | /            | /     | /          |

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

|                                 |                                                                                                    |
|---------------------------------|----------------------------------------------------------------------------------------------------|
| <b>EUT Operation Mode:</b>      | The system was configured for testing in Engineering Mode, which was provided by the manufacturer. |
| <b>Equipment Modifications:</b> | No                                                                                                 |
| <b>EUT Exercise Software:</b>   | No                                                                                                 |


### 1.2.2 Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| /            | /           | /     | /             |

### 1.2.3 Support Cable List and Details

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To |
|-------------------|----------------|--------------|------------|-----------|----|
| /                 | /              | /            | /          | /         | /  |

### 1.2.4 Block Diagram of Test Setup



### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

| Parameter                                | Measurement Uncertainty                                                                                                 |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Occupied Channel Bandwidth               | ±5 %                                                                                                                    |
| RF output power, conducted               | ±0.61dB                                                                                                                 |
| Unwanted Emissions, radiated             | 30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB,<br>6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB |
| Unwanted Emissions, conducted            | ±1.26 dB                                                                                                                |
| Temperature                              | ±1 °C                                                                                                                   |
| Humidity                                 | ±5%                                                                                                                     |
| DC and low frequency voltages            | ±0.4%                                                                                                                   |
| Duty Cycle                               | 1%                                                                                                                      |
| RF Frequency                             | ±0.082 ×10 <sup>-6</sup>                                                                                                |
| Audio Frequency/Low Pass Filter Response | 4.02%                                                                                                                   |
| Modulation Limiting                      | 1.19%                                                                                                                   |

## 2. SUMMARY OF TEST RESULTS

| Standard/Rule(s)     | Description of Test           | Results   |
|----------------------|-------------------------------|-----------|
| §2.1055(d), §95.565  | FRS Frequency Accuracy        | Compliant |
| §2.1046, FCC §95.567 | FRS transmit Power            | Compliant |
| §95.571              | FRS Emission Types            | Compliant |
| §2.1049, §95.573     | FRS Authorized Bandwidth      | Compliant |
| §95.579              | Emission Mask                 | Compliant |
| §2.1047, §95.575     | FRS Modulation Limits         | Compliant |
| §2.1053, §95.579     | FRS Unwanted Emissions Limits | Compliant |
| §95.587              | FRS Additional Requirements   | Compliant |

### 3. REQUIREMENTS AND TEST PROCEDURES


#### 3.1 FRS Frequency Accuracy

##### 3.1.1 Applicable Standard

FCC §95.565

Each FRS transmitter type must be designed such that the carrier frequencies remain within  $\pm 2.5$  parts-per-million of the channel center frequencies specified in §95.563 during normal operating conditions.

##### 3.1.2 EUT Setup Block Diagram



##### 3.1.3 Test Procedure

C63.26-2015, Clause 5.6

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage. The operating carrier frequency shall be set up in accordance with the manufacturer's published operation and instruction manual prior to the commencement of these tests. No adjustment of any frequency determining circuit element shall be made subsequent to this initial set-up. Frequency stability is tested:

a) At 10 °C intervals of temperatures between -30 °C and +50 °C at the manufacturer's rated supply voltage, and

b) At +20 °C temperature and  $\pm 15\%$  supply voltage variations. If a product is specified to operate over a range of input voltage then the -15% variation is applied to the lowermost voltage and the +15% is applied to the uppermost voltage. During the test all necessary settings, adjustments and control of the EUT have to be performed without disturbing the test environment, i.e., without opening the environmental chamber. The frequency stabilities can be maintained to a lesser temperature range provided that the transmitter is automatically inhibited from operating outside the lesser temperature range. For handheld equipment that is only capable of operating from internal batteries and the supply voltage cannot be varied, the frequency stability tests shall be performed at the nominal battery voltage and the battery end point voltage specified by the manufacturer. An external supply voltage can be used and set at the internal battery nominal voltage, and again at the battery operating end point voltage which shall be specified by the equipment manufacturer.

If an unmodulated carrier is not available, the mean frequency of a modulated carrier can be obtained by using a frequency counter with gating time set to an appropriately large multiple of bit periods (gating time depending on the required accuracy). Full details on the choice of values shall be included in the test report.


### 3.2 FRS Transmit Power

#### 3.2.1 Applicable Standard

FCC §95.567

Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

#### 3.2.2 EUT Setup Block Diagram



Note: The insertion loss of the RF cable, Coaxial Attenuators, DC Block was offset into the Spectrum Analyzer.

#### 3.2.3 Test Procedure

C63.26-2015, Clause 5.2.3.3

This procedure can be used to measure the peak power in either a CW-like or noise-like narrowband RF signal. The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW  $\geq 3 \times$  RBW.

- a) Set the RBW  $\geq$  OBW.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Set span  $\geq 2 \times$  OBW.
- d) Sweep time  $\geq 10 \times$  (number of points in sweep)  $\times$  (transmission symbol period).
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the peak amplitude level

ERP=Conducted Output Power+ Antenna Gain(dBd)

### **3.3 FRS Emission Types**

#### **3.3.1 Applicable Standard**

FCC §95.571

Each FRS transmitter type must be designed such that it can transmit only the following emission types: F3E, G3E, F2D, and G2D.

#### **3.3.2 Judgment**

Emission type is F3E.

### 3.4 FRS Authorized Bandwidth and Emission Mask

#### 3.4.1 Applicable Standard

FCC §95.573

Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5 kHz.

FCC § 95.579

Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) *Attenuation requirements.* The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

(1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.


(2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.

(3)  $43 + 10 \log (P)$  dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) *Measurement bandwidths.* The power of unwanted emissions in the frequency bands specified in paragraphs (a)(1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a)(3) is measured with a reference bandwidth of at least 30 kHz.

(c) *Measurement conditions.* The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

#### 3.4.2 EUT Setup Block Diagram



Note: The insertion loss of the RF cable, Coaxial Attenuators, DC Block was offset into the Spectrum Analyzer.

#### 3.4.3 Test Procedure

C63.26-2015, Clause 5.4.4

The OBW is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

The following procedure shall be used for measuring (99%) power bandwidth:

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of  $1.5 \times \text{OBW}$  is sufficient).

b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set  $\geq 3 \times \text{RBW}$ .

c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.

NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances.

d) Set the detection mode to peak, and the trace mode to max-hold.

e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.

f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

According to ANSI C63.26-2015 Section 5.7.3:

f) See Annex I for example emission mask plots.


### 3.5 FRS Modulation Limits

#### 3.5.1 Applicable Standard

FCC §95.575

Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

#### 3.5.2 EUT Setup Block Diagram



**Modulation limiting Test and Audio frequency response Test**

#### 3.5.3 Test Procedure

##### C63.26-2015, Clause 5.3.2 Modulation limiting test methodology

Modulation limiting is the ability of a transmitter circuit to limit the transmitter from producing deviations in excess of a rated system deviation.

- a) Connect the equipment as illustrated in Figure 1.
- b) Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
- c) Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 0.25$  Hz to  $\geq 15000$  Hz. Turn the de-emphasis function off.
- d) Apply a 1000 Hz modulating signal to the transmitter from the audio frequency generator, and adjust the level to obtain 60% of full rated system deviation. This is the 0 dB reference level.
- e) Increase the level from the audio generator by 20 dB in 5 dB increments recording the deviation as measured from the test receiver in each step. Verify that the audio level used to make the OBW measurement is included in the sweep.
- f) Repeat for step e) at 300 Hz, 2500 Hz and 3000 Hz at a minimum using the 0 dB reference level obtained in step d).
- g) Set the test receiver to measure peak negative deviation and repeat step d) through step f).
- h) The values recorded in step f) and step g) are the modulation limiting.
- i) Plot the data set as a percentage of deviation relative to the 0 dB reference point versus input voltage.

##### C63.26-2015, Clause 5.3.3.2 Audio frequency response test methodology—Constant Input

- a) Connect the equipment as illustrated in Figure 3.
- b) Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 50$  Hz to  $\geq 15\ 000$  Hz. Turn the de-emphasis function off.
- c) Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
- d) Apply a 1000 Hz tone and adjust the audio frequency generator to produce 20% of the rated system deviation.
- e) Set the test receiver to measure rms deviation and record the deviation reading as DEVREF.
- f) Set the audio frequency generator to the desired test frequency between 300 Hz and 3000 Hz.

### 3.6 FRS Unwanted Emissions Limits

#### 3.6.1 Applicable Standard

FCC §95.579

Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) *Attenuation requirements.* The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

(1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.

(2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.

(3)  $43 + 10 \log (P)$  dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) *Measurement bandwidths.* The power of unwanted emissions in the frequency bands specified in paragraphs (a)(1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a)(3) is measured with a reference bandwidth of at least 30 kHz.

(c) *Measurement conditions.* The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

### 3.6.2 Test setup:




Figure 6—Test site-up for radiated ERP and/or EIRP measurements




Figure 7—Substitution method set-up for radiated emission

### 3.6.3 Test Procedure:

#### ANSI C63.26-2015 Section 5.5.3

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
  - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
  - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
  - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
  - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
  - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
- e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
- f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
- g) For each emission that was detected and measured in the initial test [i.e., in step b) and step c)]:
  - 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
  - 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c).
  - 3) Record the output power level of the signal generator when equivalence is achieved in step 2).
- h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
- i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:
 
$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
 where
 

|       |                                          |
|-------|------------------------------------------|
| $P_e$ | = equivalent emission power in dBm       |
| $P_s$ | = source (signal generator) power in dBm |

 NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.
- j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:  $\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}$ . If necessary, the antenna gain can be calculated from calibrated antenna factor information
- k) Provide the complete measurement results as a part of the test report.

### 3.7 FRS Additional Requirements

#### 3.7.1 Applicable Standard

FCC §95.587

Each FRS transmitter type must be designed to meet the following additional requirements.

(a) *Transmit frequency capability*. FRS transmitter types must not be capable of transmitting on any frequency or channel other than those listed in §95.563.

(b) *Antenna*. The antenna of each FRS transmitter type must meet the following requirements.

(1) The antenna must be a non-removable integral part of the FRS transmitter type.

(2) The gain of the antenna must not exceed that of a half-wave dipole antenna.

(3) The antenna must be designed such that the electric field of the emitted waves is vertically polarized when the unit is operated in the normal orientation.

(c) *Digital data transmissions*. FRS transmitter types having the capability to transmit digital data must be designed to meet the following requirements.

(1) FRS units may transmit digital data containing location information, or requesting location information from one or more other FRS or GMRS units, or containing a brief text message to another specific FRS or GMRS unit or units.

(2) Digital data transmissions may be initiated by a manual action or command of the operator or on an automatic or periodic basis, and FRS units may be designed to automatically respond with location data upon receiving an interrogation request from another

(3) Digital data transmissions must not exceed one second in duration.

(4) Digital data transmissions must not be sent more frequently than one digital data transmission within a thirty-second period, except that an FRS unit may automatically respond to more than one interrogation request received within a thirty-second period.

(d) *Packet mode*. FRS transmitter types must not be capable of transmitting data in the store-and-forward packet operation mode.

(e) Effective September 30, 2019, no person shall manufacture or import hand-held portable radio equipment capable of operating under this subpart (FRS) and other licensed or licensed-by-rule services in this chapter (part 15 unlicensed equipment authorizations are permitted if consistent with part 15 rules).

#### 3.7.2 Judgment

Transmit frequency capability: Compliance, please refer to section 1.1.

Antenna: Compliant, please refer to section 1.1.

Digital Data transmissions: Not Applicable, no digital modulation function.

Packet mode: Not Applicable, no digital modulation function.

No capable of FRS combined other licensed: Compliance, Only FRS function

**Result: Compliant.**

## 4. TEST DATA AND RESULTS

### 4.1 FRS Frequency Accuracy

|                |          |              |              |
|----------------|----------|--------------|--------------|
| Sample Number: | 37C6-1   | Test Date:   | 2025/12/1    |
| Test Site:     | RF       | Test Mode:   | Transmitting |
| Tester:        | Chin Qin | Test Result: | Pass         |

#### Environmental Conditions:

|                      |      |                              |    |                        |     |
|----------------------|------|------------------------------|----|------------------------|-----|
| Temperature:<br>(°C) | 24.2 | Relative<br>Humidity:<br>(%) | 50 | ATM Pressure:<br>(kPa) | 101 |
|----------------------|------|------------------------------|----|------------------------|-----|

#### Test Equipment List and Details:

| Manufacturer | Description               | Model             | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|---------------------------|-------------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum<br>Analyzer      | FSV40             | 101591           | 2025/3/31           | 2026/3/30               |
| YINSAIGE     | Coaxial Cable             | SS402             | SJ0100003        | Each time           | N/A                     |
| BIRD         | Coaxial<br>Attenuator     | 300-WA-FFN-<br>30 | 1171762          | Each time           | N/A                     |
| GLOBAL       | TEMP&HUMI<br>Test Chamber | BTH-150-40        | 30174            | 2025/8/1            | 2026/7/31               |
| UNI-T        | Digital<br>Multimeter     | UT39A+            | C250343896       | 2025/7/18           | 2026/7/17               |
| GWINSTEK     | DC Power<br>Supply        | SPS3610           | D33251           | N/A                 | N/A                     |

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

| Test Frequency (MHz) | Temperature (°C) | Voltage (Vdc) | Measured Frequency (MHz) | Frequency Error (ppm) | limit (ppm) |
|----------------------|------------------|---------------|--------------------------|-----------------------|-------------|
| 462.6375             | -30              | 3.7           | 462.6373445              | -0.34                 | $\leq 2.5$  |
|                      | -20              | 3.7           | 462.6373925              | -0.23                 | $\leq 2.5$  |
|                      | -10              | 3.7           | 462.6375485              | 0.10                  | $\leq 2.5$  |
|                      | 0                | 3.7           | 462.6375825              | 0.18                  | $\leq 2.5$  |
|                      | 10               | 3.7           | 462.6376975              | 0.43                  | $\leq 2.5$  |
|                      | 20               | 3.7           | 462.6377825              | 0.61                  | $\leq 2.5$  |
|                      | 30               | 3.7           | 462.6378825              | 0.83                  | $\leq 2.5$  |
|                      | 40               | 3.7           | 462.6379055              | 0.88                  | $\leq 2.5$  |
|                      | 50               | 3.7           | 462.6380345              | 1.16                  | $\leq 2.5$  |
|                      | 20               | 3.5           | 462.6373525              | -0.32                 | $\leq 2.5$  |
|                      | 20               | 4.1           | 462.6381135              | 1.33                  | $\leq 2.5$  |

| Test Frequency (MHz) | Temperature (°C) | Voltage (Vdc) | Measured Frequency (MHz) | Frequency Error (ppm) | limit (ppm) |
|----------------------|------------------|---------------|--------------------------|-----------------------|-------------|
| 467.6375             | -30              | 3.7           | 467.6372815              | -0.47                 | $\leq 2.5$  |
|                      | -20              | 3.7           | 467.6374485              | -0.11                 | $\leq 2.5$  |
|                      | -10              | 3.7           | 467.6374945              | -0.01                 | $\leq 2.5$  |
|                      | 0                | 3.7           | 467.6376245              | 0.27                  | $\leq 2.5$  |
|                      | 10               | 3.7           | 467.6377145              | 0.46                  | $\leq 2.5$  |
|                      | 20               | 3.7           | 467.6377725              | 0.58                  | $\leq 2.5$  |
|                      | 30               | 3.7           | 467.6377775              | 0.59                  | $\leq 2.5$  |
|                      | 40               | 3.7           | 467.6379205              | 0.90                  | $\leq 2.5$  |
|                      | 50               | 3.7           | 467.6379775              | 1.02                  | $\leq 2.5$  |
|                      | 20               | 3.5           | 467.6373175              | -0.39                 | $\leq 2.5$  |
|                      | 20               | 4.1           | 467.6381305              | 1.35                  | $\leq 2.5$  |

Note: the operation voltage was declared by manufacturer<sup>▲</sup>.

**4.2 FRS Transmit Power**

|                |          |              |              |
|----------------|----------|--------------|--------------|
| Sample Number: | 37C6-1   | Test Date:   | 2025/12/1    |
| Test Site:     | RF       | Test Mode:   | Transmitting |
| Tester:        | Chin Qin | Test Result: | Pass         |

**Environmental Conditions:**

|                      |      |                              |    |                        |     |
|----------------------|------|------------------------------|----|------------------------|-----|
| Temperature:<br>(°C) | 24.2 | Relative<br>Humidity:<br>(%) | 50 | ATM Pressure:<br>(kPa) | 101 |
|----------------------|------|------------------------------|----|------------------------|-----|

**Test Equipment List and Details:**

| Manufacturer | Description                | Model         | Serial Number | Calibration Date | Calibration Due Date |
|--------------|----------------------------|---------------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer          | FSV40         | 101591        | 2025/3/31        | 2026/3/30            |
| YINSAIGE     | Coaxial Cable              | SS402         | SJ0100003     | Each time        | N/A                  |
| BIRD         | Coaxial Attenuator         | 300-WA-FFN-30 | 1171762       | Each time        | N/A                  |
| HP           | RF Communications Test Set | 8920A         | 3438A05209    | 2025/9/23        | 2026/9/22            |


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

| Test Frequency (MHz)                           | Conducted Output power (dBm) | Antenna Gain (dBd) | ERP (dBm) | ERP Limit (dBm) |
|------------------------------------------------|------------------------------|--------------------|-----------|-----------------|
| 462.6375                                       | 26.36                        | -1.38              | 24.98     | ≤33             |
| 467.6375                                       | 26.12                        | -1.38              | 24.74     | ≤27             |
| ERP=Conducted Output Power + Antenna Gain(dBd) |                              |                    |           |                 |


Conducted Output power

462.6375 MHz



ProjectNo.:2503V71118E-RF Tester:Chin Qin  
Date: 1.DEC.2025 21:07:11

467.6375 MHz



ProjectNo.:2503V71118E-RF Tester:Chin Qin  
Date: 1.DEC.2025 21:41:57

**4.3 FRS Authorized Bandwidth And Emission Mask**

|                |          |              |              |
|----------------|----------|--------------|--------------|
| Sample Number: | 37C6-1   | Test Date:   | 2025/12/1    |
| Test Site:     | RF       | Test Mode:   | Transmitting |
| Tester:        | Chin Qin | Test Result: | Pass         |

**Environmental Conditions:**

|                      |      |                              |    |                        |     |
|----------------------|------|------------------------------|----|------------------------|-----|
| Temperature:<br>(°C) | 24.2 | Relative<br>Humidity:<br>(%) | 50 | ATM Pressure:<br>(kPa) | 101 |
|----------------------|------|------------------------------|----|------------------------|-----|

**Test Equipment List and Details:**

| Manufacturer | Description                | Model         | Serial Number | Calibration Date | Calibration Due Date |
|--------------|----------------------------|---------------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer          | FSV40         | 101591        | 2025/3/31        | 2026/3/30            |
| YINSAIGE     | Coaxial Cable              | SS402         | SJ0100003     | Each time        | N/A                  |
| BIRD         | Coaxial Attenuator         | 300-WA-FFN-30 | 1171762       | Each time        | N/A                  |
| HP           | RF Communications Test Set | 8920A         | 3438A05209    | 2025/9/23        | 2026/9/22            |

*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

**Test Data:**

| Test Frequency<br>(MHz) | 99% Occupied<br>Bandwidth<br>(kHz) | 20 dB<br>Bandwidth<br>(kHz) | Limit<br>(kHz) |
|-------------------------|------------------------------------|-----------------------------|----------------|
| 462.6375                | 10                                 | 10.319                      | ≤12.5          |
| 467.6375                | 10                                 | 10.285                      | ≤12.5          |

Note:

Emission bandwidth was based on calculation method instead of measurement.

Emission Designator

Per CFR 47 §2.201& §2.202, BW = 2M + 2D

**For FM Mode (Channel Spacing: 12.5 kHz)**


Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$

F3E portion of the designator represents an FM voice transmission

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.



**4.4 FRS Modulation Limits**

|                |          |              |              |
|----------------|----------|--------------|--------------|
| Sample Number: | 37C6-1   | Test Date:   | 2025/12/1    |
| Test Site:     | RF       | Test Mode:   | Transmitting |
| Tester:        | Chin Qin | Test Result: | Pass         |

**Environmental Conditions:**

|                      |      |                              |    |                        |     |
|----------------------|------|------------------------------|----|------------------------|-----|
| Temperature:<br>(°C) | 24.2 | Relative<br>Humidity:<br>(%) | 50 | ATM Pressure:<br>(kPa) | 101 |
|----------------------|------|------------------------------|----|------------------------|-----|

**Test Equipment List and Details:**


| Manufacturer | Description                      | Model         | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|----------------------------------|---------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum<br>Analyzer             | FSV40         | 101591           | 2025/3/31           | 2026/3/30               |
| YINSAIGE     | Coaxial Cable                    | SS402         | SJ0100003        | Each time           | N/A                     |
| BIRD         | Coaxial<br>Attenuator            | 300-WA-FFN-30 | 1171762          | Each time           | N/A                     |
| HP           | RF<br>Communications<br>Test Set | 8920A         | 3438A05209       | 2025/9/23           | 2026/9/22               |

*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

**Test Data:**


**Test Data:**  
**MODULATION LIMITING**

| Carrier Frequency: 467.6375 MHz, Channel Spacing: 12.5kHz |                         |               |                         |               |                          |               |                          |               |                          |               |             |
|-----------------------------------------------------------|-------------------------|---------------|-------------------------|---------------|--------------------------|---------------|--------------------------|---------------|--------------------------|---------------|-------------|
| Audio Frequency(Hz)                                       | DEVIATION (@+0dB) [kHz] |               | DEVIATION (@+5dB) [kHz] |               | DEVIATION (@+10dB) [kHz] |               | DEVIATION (@+15dB) [kHz] |               | DEVIATION (@+20dB) [kHz] |               | Limit [kHz] |
|                                                           | Peak Positive           | Peak Negative | Peak Positive           | Peak Negative | Peak Positive            | Peak Negative | Peak Positive            | Peak Negative | Peak Positive            | Peak Negative |             |
| 300                                                       | 0.332                   | 0.334         | 0.567                   | 0.560         | 0.643                    | 0.637         | 0.670                    | 0.669         | 0.627                    | 0.631         | 2.5         |
| 1000                                                      | 1.500                   | 1.500         | 1.949                   | 1.962         | 1.935                    | 1.947         | 2.014                    | 2.044         | 1.995                    | 2.029         | 2.5         |
| 2500                                                      | 2.070                   | 2.235         | 2.088                   | 2.250         | 2.083                    | 2.247         | 2.119                    | 2.291         | 2.127                    | 2.296         | 2.5         |
| 3000                                                      | 2.072                   | 2.194         | 2.122                   | 2.240         | 2.109                    | 2.254         | 2.162                    | 2.293         | 2.175                    | 2.307         | 2.5         |



**Audio Frequency Response**  
Carrier Frequency: 467.6375 MHz

| Audio Frequency (Hz) | Response Attenuation (dB) |
|----------------------|---------------------------|
| 300                  | -13.77                    |
| 400                  | -9.67                     |
| 500                  | -7.03                     |
| 600                  | -5.11                     |
| 700                  | -3.68                     |
| 800                  | -2.39                     |
| 900                  | -1.05                     |
| 1000                 | 0.00                      |
| 1200                 | 1.29                      |
| 1400                 | 2.73                      |
| 1600                 | 3.83                      |
| 1800                 | 4.39                      |
| 2000                 | 5.56                      |
| 2200                 | 5.86                      |
| 2400                 | 6.70                      |
| 2600                 | 7.24                      |
| 2800                 | 7.58                      |
| 3000                 | 7.74                      |
| 3125                 | 5.23                      |



#### 4.5 Radiated Spurious Emission

|                |                       |              |                       |
|----------------|-----------------------|--------------|-----------------------|
| Sample Number: | 37C6-2                | Test Date:   | 2025/11/26-2025/11/28 |
| Test Site:     | 966-2,966-1           | Test Mode:   | Transmitting          |
| Tester:        | Roinin Fu, Peter Rong | Test Result: | Pass                  |

##### Environmental Conditions:

|                      |           |                           |       |                           |             |
|----------------------|-----------|---------------------------|-------|---------------------------|-------------|
| Temperature:<br>(°C) | 22.4-23.6 | Relative Humidity:<br>(%) | 35-39 | ATM<br>Pressure:<br>(kPa) | 101.4-101.7 |
|----------------------|-----------|---------------------------|-------|---------------------------|-------------|

##### Test Equipment List and Details:

| Manufacturer    | Description                       | Model                 | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------------------------|-----------------------|---------------|------------------|----------------------|
| Sunol Sciences  | Antenna                           | JB6                   | A082520-5     | 2023/12/1        | 2026/11/30           |
| R&S             | EMI Test Receiver                 | ESR3                  | 102724        | 2025/2/14        | 2026/2/13            |
| TIMES MICROWAVE | Coaxial Cable                     | LMR-600-UltraFlex     | C-0100-03     | 2024/12/3        | 2025/12/2            |
| TIMES MICROWAVE | Coaxial Cable                     | LMR-600-UltraFlex     | C-0370-01     | 2024/12/3        | 2025/12/2            |
| XQY             | Coaxial Cable                     | XQY-CMR400UF-NJ-NJ-7M | 24056379      | 2025/6/4         | 2026/6/3             |
| EMCO            | Adjustable Dipole Antenna         | 3121C                 | 9109-756      | N/A              | N/A                  |
| MICRO-COAX      | Coaxial Cable                     | UFA210B-0-0720-300300 | 99G1448       | 2025/7/14        | 2026/7/13            |
| Agilent         | Signal Generator                  | E8247C                | MY43321352    | 2025/1/9         | 2026/1/8             |
| ETS-Lindgren    | Horn Antenna                      | 3115                  | 9912-5985     | 2023/12/6        | 2026/12/5            |
| R&S             | Spectrum Analyzer                 | FSV40                 | 101591        | 2025/3/31        | 2026/3/30            |
| MICRO-COAX      | Coaxial Cable                     | UFA210A-1-1200-70U300 | 217423-008    | 2025/1/10        | 2026/1/9             |
| MICRO-COAX      | Coaxial Cable                     | UFA210A-1-2362-300300 | 235780-001    | 2025/1/10        | 2026/1/9             |
| A.H             | Pre-amplifier                     | PAM-0118P             | 628           | 2025/10/31       | 2026/10/30           |
| AH              | Double Ridge Guide Horn Antenna   | SAS-571               | 1396          | 2023/2/22        | 2026/2/21            |
| Decentest       | Multiplex Switch Test Control Set | DT7220SCU             | DQ77925       | 2025/8/4         | 2026/8/3             |
| Decentest       | Filter Switch Unit                | DT7220FSU             | DQ77928       | 2025/8/4         | 2026/8/3             |

**\* Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

##### Test Data:

Please refer to the below table and plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

| Frequency<br>(MHz)     | Polar<br>(H/V) | Receiver<br>Reading<br>(dBμV) | Substituted Method            |                              |                    | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|------------------------|----------------|-------------------------------|-------------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
|                        |                |                               | Substituted<br>Level<br>(dBm) | Antenna<br>Gain<br>(dBd/dBi) | Cable Loss<br>(dB) |                            |                |                |
| frequency:462.6375 MHz |                |                               |                               |                              |                    |                            |                |                |
| 925.275                | H              | 43.93                         | -24.22                        | 0.00                         | 0.62               | -24.84                     | -13.00         | 11.84          |
| 925.275                | V              | 39.16                         | -26.47                        | 0.00                         | 0.62               | -27.09                     | -13.00         | 14.09          |
| 1387.950               | H              | 79.95                         | -41.18                        | 8.19                         | 0.73               | -33.72                     | -13.00         | 20.72          |
| 1387.950               | V              | 78.35                         | -42.87                        | 8.19                         | 0.73               | -35.41                     | -13.00         | 22.41          |
| 1850.600               | H              | 74.06                         | -46.41                        | 8.92                         | 0.89               | -38.38                     | -13.00         | 25.38          |
| 1850.600               | V              | 72.38                         | -48.01                        | 8.92                         | 0.89               | -39.98                     | -13.00         | 26.98          |
| 2313.250               | H              | 53.21                         | -65.46                        | 9.29                         | 0.98               | -57.15                     | -13.00         | 44.15          |
| 2313.250               | V              | 55.63                         | -62.82                        | 9.29                         | 0.98               | -54.51                     | -13.00         | 41.51          |
| 2775.900               | H              | 49.66                         | -66.59                        | 9.84                         | 1.05               | -57.80                     | -13.00         | 44.80          |
| 2775.900               | V              | 48.77                         | -67.37                        | 9.84                         | 1.05               | -58.58                     | -13.00         | 45.58          |
| 3238.550               | H              | 46.95                         | -66.12                        | 10.30                        | 1.16               | -56.98                     | -13.00         | 43.98          |
| 3238.550               | V              | 49.02                         | -63.80                        | 10.30                        | 1.16               | -54.66                     | -13.00         | 41.66          |
| 3701.200               | H              | 51.26                         | -62.72                        | 10.60                        | 1.25               | -53.37                     | -13.00         | 40.37          |
| 3701.200               | V              | 54.29                         | -59.67                        | 10.60                        | 1.25               | -50.32                     | -13.00         | 37.32          |
| 4163.850               | H              | 46.09                         | -66.87                        | 10.80                        | 1.30               | -57.37                     | -13.00         | 44.37          |
| 4163.850               | V              | 46.73                         | -66.20                        | 10.80                        | 1.30               | -56.70                     | -13.00         | 43.70          |
| 4626.500               | H              | 47.21                         | -65.18                        | 10.75                        | 1.41               | -55.84                     | -13.00         | 42.84          |
| 4626.500               | V              | 47.86                         | -64.41                        | 10.75                        | 1.41               | -55.07                     | -13.00         | 42.07          |
| frequency:467.6375MHz  |                |                               |                               |                              |                    |                            |                |                |
| 935.275                | H              | 46.09                         | -21.82                        | 0.00                         | 0.66               | -22.48                     | -13.00         | 9.48           |
| 935.275                | V              | 40.64                         | -24.80                        | 0.00                         | 0.66               | -25.46                     | -13.00         | 12.46          |
| 1402.913               | H              | 81.31                         | -39.98                        | 8.23                         | 0.71               | -32.46                     | -13.00         | 19.46          |
| 1402.913               | V              | 79.70                         | -41.63                        | 8.23                         | 0.71               | -34.11                     | -13.00         | 21.11          |
| 1870.550               | H              | 73.42                         | -46.96                        | 8.94                         | 0.89               | -38.91                     | -13.00         | 25.91          |
| 1870.550               | V              | 73.69                         | -46.50                        | 8.94                         | 0.89               | -38.45                     | -13.00         | 25.45          |
| 2338.188               | H              | 62.93                         | -55.48                        | 9.30                         | 0.97               | -47.15                     | -13.00         | 34.15          |
| 2338.188               | V              | 52.47                         | -65.71                        | 9.30                         | 0.97               | -57.38                     | -13.00         | 44.38          |
| 2805.825               | H              | 49.58                         | -66.62                        | 9.89                         | 1.04               | -57.77                     | -13.00         | 44.77          |
| 2805.825               | V              | 48.20                         | -67.89                        | 9.89                         | 1.04               | -59.04                     | -13.00         | 46.04          |
| 3273.463               | H              | 49.65                         | -63.25                        | 10.31                        | 1.16               | -54.10                     | -13.00         | 41.10          |
| 3273.463               | V              | 50.94                         | -61.72                        | 10.31                        | 1.16               | -52.57                     | -13.00         | 39.57          |
| 3741.100               | H              | 51.19                         | -62.20                        | 10.64                        | 1.23               | -52.79                     | -13.00         | 39.79          |
| 3741.100               | V              | 50.37                         | -62.94                        | 10.64                        | 1.23               | -53.53                     | -13.00         | 40.53          |
| 4208.738               | H              | 46.98                         | -66.00                        | 10.77                        | 1.33               | -56.56                     | -13.00         | 43.56          |
| 4208.738               | V              | 47.01                         | -65.93                        | 10.77                        | 1.33               | -56.49                     | -13.00         | 43.49          |
| 4676.375               | H              | 45.40                         | -66.64                        | 10.81                        | 1.41               | -57.24                     | -13.00         | 44.24          |
| 4676.375               | V              | 46.67                         | -65.35                        | 10.81                        | 1.41               | -55.95                     | -13.00         | 42.95          |

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

## 5. EUT PHOTOGRAPHS

---

Please refer to the attachment 2503V71118E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2503V71118E-RF-INP EUT INTERNAL PHOTOGRAPHS.

## **6. TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2503V71118E-RF-00C-TSP TEST SETUP PHOTOGRAPHS.

**===== END OF REPORT =====**