

FCC RADIO TEST REPORT

FCC ID: 2BQY7-M64510

Product : IoT Module

Trade Mark : N/A

Model Name : MQC2066-5-46-0U

Family Model : MQC2066-0-46-0U, MQC2066-0-40-0U,
MQC2066-5-40-0U, MQC6856-1-46-0U,
MQC6856-5-46-0U, MQC6856-1-40-0U,
MQC6856-5-40-0U

Report No. : N25082902703E

Issue Date: Nov. 27, 2025

Prepared for

METICOMM PTE. LTD.

15 UPPER CIRCULAR ROAD, #06-01, SINGAPORE 058413

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District,
Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name** METICOMM PTE. LTD.

Address 15 UPPER CIRCULAR ROAD, #06-01, SINGAPORE 058413

Manufacturer's Name METICOMM PTE. LTD.

Address 15 UPPER CIRCULAR ROAD, #06-01, SINGAPORE 058413

Product description

Product name..... IoT Module

Trade Mark N/A

Model and/or type reference MQC2066-5-46-0U

Family Model..... MQC2066-0-46-0U, MQC2066-0-40-0U, MQC2066-5-40-0U,
MQC6856-1-46-0U, MQC6856-5-46-0U, MQC6856-1-40-0U,
MQC6856-5-40-0U

Test Sample Number S2508290070-1#

Standards FCC Part 15 Subpart ETest procedure ANSI C63.10-2020+COR.1-2023;
KDB 789033 D02 General UNII Test Procedures New Rules v02r01
KDB 662911 D01 Multiple Transmitter Output v02r01
KDB 987594 D02 U-NII 6GHz EMC Measurement v01r01

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements.. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Aug. 29, 2025 ~ Nov. 27, 2025

Date of Issue..... Nov. 27, 2025

Test Result..... **Pass**Prepared By : Kieron Luo
Kieron Luo
(Project Engineer)Reviewed By : Aaron Cheng
Aaron Cheng
(Supervisor)Approved By : Alex Li
Alex Li
(Manager)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 FACILITIES AND ACCREDITATIONS	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	15
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	16
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	17
3 . TEST REQUIREMENTS	19
3.1 CONDUCTED EMISSION MEASUREMENT	19
3.1.1 APPLICABLE STANDARD	19
3.1.2 CONFORMANCE LIMIT	19
3.1.3 TEST CONFIGURATION	19
3.1.4 TEST PROCEDURE	19
3.1.5 TEST RESULTS	20
3.2 RADIATED EMISSION MEASUREMENT	22
3.2.1 APPLICABLE STANDARD	22
3.2.2 CONFORMANCE LIMIT	22
3.2.3 MEASURING INSTRUMENTS	22
3.2.4 TEST CONFIGURATION	23
3.2.5 TEST PROCEDURE	24
3.2.6 TEST RESULTS (9KHZ – 30 MHZ)	25
3.2.7 TEST RESULTS (30MHZ – 1GHZ)	26
3.2.8 TEST RESULTS (1GHZ-18GHZ)	28
3.2.9 TEST RESULTS (18GHZ-40GHZ)	32
SPURIOUS EMISSION IN BANDEDGE	34
3.3 EIRP POWER SPECTRAL DENSITY TEST	38
3.3.1 APPLIED PROCEDURES / LIMIT	38
3.3.2 TEST PROCEDURE	38
3.3.3 DEVIATION FROM STANDARD	39
3.3.4 TEST SETUP	39
3.3.5 EUT OPERATION CONDITIONS	39
3.3.6 TEST RESULTS	40
3.4 26DB & 99% EMISSION BANDWIDTH	41
3.4.1 APPLIED PROCEDURES / LIMIT	41
3.4.2 TEST PROCEDURE	41

Table of Contents

	Page
3.4.3 EUT OPERATION CONDITIONS	42
3.4.4 TEST RESULTS	42
3.5 IN-BAND EMISSIONS	43
3.5.1 APPLIED PROCEDURES / LIMIT	43
3.5.2 TEST PROCEDURE	43
3.5.3 DEVIATION FROM STANDARD	43
3.5.4 TEST SETUP	43
3.5.5 EUT OPERATION CONDITIONS	43
3.5.6 TEST RESULTS	44
3.6 MAXIMUM EIRP OUTPUT POWER	45
3.6.1 PPLIED PROCEDURES / LIMIT	45
3.6.2 TEST PROCEDURE	45
3.6.3 DEVIATION FROM STANDARD	45
3.6.4 TEST SETUP	45
3.6.5 EUT OPERATION CONDITIONS	45
3.6.6 TEST RESULTS	46
3.7 OPERATIONAL RESTRICTIONS FOR 6 GHZ U-NII DEVICES.	47
3.7.1 APPLICABLE STANDARD	47
3.7.2 TEST RESULTS	47
3.8 CONTENTION BASED PROTOCOL	48
3.8.1 LIMIT OF CONTENTION BASED PROTOCOL	48
3.8.2TEST PROCEDURES	49
3.8.3TEST SETUP	50
3.8.4TEST RESULTS	50
3.9 FREQUENCY STABILITY	50
4. ANTENNA REQUIREMENT	50
4.1 STANDARD REQUIREMENT	50
4.2 EUT ANTENNA	50
5. TEST RESULT	50

Revision History

Report No.	Version	Description	Issued Date
N25082902703E	Rev.02	Initial issue of report	Nov. 27, 2025

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.407(b)(9)	AC Power Line Conducted Emissions	PASS	
15.407(b)(6)	Unwanted Emissions	PASS	
15.407(b)(7)	In-Band Emissions	PASS	
2.1049	99% Occupied Bandwidth	PASS	
15.407(a)(11)	26 dB Emission Bandwidth	PASS	
15.407(a)(8)	Maximum E.I.R.P Output Power	PASS	
15.407(a)(8)	E.I.R.P Power Spectral Density	PASS	
15.407(d)(6)	Contention Based Protocol	PASS	
15.407(g)	Frequency Stability	PASS	
15.203	Antenna Requirement	PASS	

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier: CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^{\circ}\text{C}$
8	Humidity	$\pm 2\%$
9	Occupied bandwidth	$\pm 4.7\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	IoT Module	
Trade Mark	N/A	
Model Name	MQC2066-5-46-0U	
Family Model	MQC2066-0-46-0U, MQC2066-0-40-0U, MQC2066-5-40-0U, MQC6856-1-46-0U, MQC6856-5-46-0U, MQC6856-1-40-0U, MQC6856-5-40-0U	
Model Difference	The difference between MQC2066-5-46-0U and MQC2066-0-46-0U lies in their Bluetooth interfaces. The difference between MQC2066-5-46-0U and MQC2066-5-40-0U lies in the presence or absence of an adapter board. The only difference between 6856 and 2066 is the model name.	
FCC ID	2BQY7-M64510	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11ax (20MHz channel bandwidth); ☒ 802.11ax (40MHz channel bandwidth); ☒ 802.11ax (80MHz channel bandwidth); ☒ 802.11ax (160MHz channel bandwidth);
	Modulation	OFDMA (QPSK/BPSK/16QAM/64QAM/256QAM)
	Operating Frequency Range	☒ 5955-7115MHz for 802.11ax(20MHz); ☒ 5965-7085MHz for 802.11ax(40MHz); ☒ 5985-7025MHz for 802.11ax(80MHz); ☒ 6025-6985MHz for 802.11ax(160MHz);
	Number of Channels	☒ 59 channels for ax 20; ☒ 29 channels for ax 40; ☒ 14 channels for ax 80; ☒ 7 channels for ax 160;
	Function:	☐ Low-power Dual Client ☐ Low-power Indoor Access Point ☐ Subordinate Indoor Device ☒ Low-power Indoor Client ☐ Standard Power Access Point ☐ Standard Client ☐ Fixed Client
	Smart system	☒ MIMO for 802.11ax
	Antenna Type	External Antenna
	Antenna Gain	Antenna 1: 4.5dBi; Antenna 2: 4.5dBi
	Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual. The EUT is categorized as an Low-power Indoor Client (6XD) operating in the 5.925-7.125 GHz band. It will only operate under the control of a Low-power Indoor (LPI) access point (6ID).	
Ratings	DC 3.3V	
Adapter	N/A	
Battery	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual	
HW Version	N/A	
SW Version	N/A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.

20MHz					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5955	81	6355	161	6755
5	5975	85	6375	165	6775
9	5995	89	6395	169	6795
13	6015	93	6415	173	6815
17	6035	97	6435	177	6835
21	6055	101	6455	181	6855
25	6075	105	6475	185	6875
29	6095	109	6495	189	6895
33	6115	113	6515	193	6915
37	6135	117	6535	197	6935
41	6155	121	6555	201	6955
45	6175	125	6575	205	6975
49	6195	129	6595	209	6995
53	6215	133	6615	213	7015
57	6235	137	6635	217	7035
61	6255	141	6655	221	7055
65	6275	145	6675	225	7075
69	6295	149	6695	229	7095
73	6315	153	6715	233	7115
77	6335	157	6735		

40MHz					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	5965	83	6365	163	6765
11	6005	91	6405	171	6805
19	6045	99	6445	179	6845
27	6085	107	6485	187	6885
35	6125	115	6525	195	6925
43	6165	123	6565	203	6965
51	6205	131	6605	211	7005
59	6245	139	6645	219	7045
67	6285	147	6685	227	7085
75	6325	155	6725		

80MHz					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
7	5985	87	6385	167	6785
23	6065	103	6465	183	6865
39	6145	119	6545	199	6945
55	6225	135	6625	215	7025
71	6305	151	6705		

160MHz					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
15	6025	111	6505	207	6985
47	6185	143	6665		
79	6345	175	6825		

- 1). CH111, CH115, CH119, CH175, CH185, CH187, CH183 is straddle channels.
3. 6G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
802.11ax	1TX, 1RX
802.11ax	1TX/2TX, 1RX/2RX

For 6GHz mode, antennas 1 and 2 are transmitting, each with a same directional gain.
 For MIMO mode,
 $\text{Directional gain} = [G_{\text{ANT}} + 10 \log(N_{\text{ANT}})] \text{dBi} = 4.5 + 10 * \log 2 = 7.51 \text{dBi}$

Note:

$G_{\text{ANT1}} = G_{\text{ANT2}} = 4.5 \text{dBi}$

N_{ANT} means the number of Antennas.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11ax 20 CH1/ CH45/ CH 93/ CH97/ CH105/ CH 113/ CH117/ CH149/ CH 181/ CH185/ CH189/ CH 209/ CH233 For SISO&MIMO
Mode 3	802.11ax 40 CH3/ CH 43/ CH 91/ CH99/ CH 107/ CH 115/ CH123/ CH 147/ CH 179/ CH187/ CH 195/ CH 211/ CH227 For SISO&MIMO
Mode 4	802.11ax 80 CH 7/ CH 39/ CH 87/ CH 103/ CH 119/ CH 135/ CH 151/ CH 167/ CH 183/ CH 199/ CH 215 For SISO&MIMO
Mode 5	802.11ax 160 CH 15/ CH 47/ CH 79/ CH 111/ CH 143/ CH 175/ CH 207 For SISO&MIMO

For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11ax 20 CH1/ CH45/ CH 93/ CH97/ CH105/ CH 113/ CH117/ CH149/ CH 181/ CH185/ CH189/ CH 209/ CH233 For SISO&MIMO
Mode 3	802.11ax 40 CH3/ CH 43/ CH 91/ CH99/ CH 107/ CH 115/ CH123/ CH 147/ CH 179/ CH187/ CH 195/ CH 211/ CH227 For SISO&MIMO
Mode 4	802.11ax 80 CH 7/ CH 39/ CH 87/ CH 103/ CH 119/ CH 135/ CH 151/ CH 167/ CH 183/ CH 199/ CH 215 For SISO&MIMO
Mode 5	802.11ax 160 CH 15/ CH 47/ CH 79/ CH 111/ CH 143/ CH 175/ CH 207 For SISO&MIMO

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (3) In ax mode, RU allocation is not supported and it is a full carrier. Only the HE SU PPDU format operational mode.
- (4) CH111, CH115, CH119, CH175, CH185, CH187, CH183 is straddle channels.

The EUT support MIMO modes, transmit mode what describe as following:

Mode	Tx / Rx
802.11ax (20MHz,40MHz,80MHz,160MHz)	2TX, 2RX

For 6GHz band, 802.11ax(20/40/80/160) has MIMO mode, Antenna 1,2 are simultaneous transmissions.
Note: Most devices can operate with one spatial stream (NSS = 1, where NSS is the number of spatial streams) even if they also are capable of more spatial streams. The worst case directional gain will occur when NSS = 1; therefore, it is especially important to ensure that the device complies with all emission limits for the case of NSS = 1 (or with the lowest possible value of NSS, if the device always uses spatial multiplexing).

Note:

1. There are a total of two motherboards, namely A55B1_MB motherboard and A55B1_MB motherboard. Both motherboards have undergone testing and evaluation. But the report will only show the worst data.
2. 802.11ax only support full RU.

**Power Setting
For SISO Mode**

Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax20	5955	MCS0	7
		6175	MCS0	7
		6415	MCS0	7
		6435	MCS0	6
		6475	MCS0	6
		6515	MCS0	6
		6535	MCS0	8
		6695	MCS0	8
		6855	MCS0	8
		6875	MCS0	8
		6995	MCS0	7
		7115	MCS0	7

Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax40	5965	MCS0	7
		6165	MCS0	7
		6405	MCS0	7
		6445	MCS0	7
		6485	MCS0	7
		6525	MCS0	7
		6565	MCS0	8
		6685	MCS0	8
		6845	MCS0	8
		6885	MCS0	8
		6965	MCS0	8
		7085	MCS0	8

Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax80	5985	MCS0	13
		6145	MCS0	14
		6385	MCS0	12
		6465	MCS0	12
		6545	MCS0	14
		6625	MCS0	14
		6785	MCS0	14
		6865	MCS0	14
		6945	MCS0	14
		7025	MCS0	13

Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax160	6025	MCS0	10
		6185	MCS0	10
		6345	MCS0	10
		6505	MCS0	12
		6665	MCS0	14
		6825	MCS0	14
		6985	MCS0	13

MIMO Mode

Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax20	5955	MCS0	3
		6175	MCS0	3
		6415	MCS0	3
		6435	MCS0	2
		6475	MCS0	2
		6515	MCS0	2
		6535	MCS0	3
		6695	MCS0	3
		6855	MCS0	4
		6875	MCS0	3
		6995	MCS0	3
		7115	MCS0	3


Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax40	5965	MCS0	4
		6165	MCS0	4
		6405	MCS0	4
		6445	MCS0	4
		6485	MCS0	4
		6525	MCS0	4
		6565	MCS0	4
		6685	MCS0	4
		6845	MCS0	4
		6885	MCS0	4
		6965	MCS0	4
		7085	MCS0	4

Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax80	5985	MCS0	10
		6145	MCS0	10
		6385	MCS0	10
		6465	MCS0	8
		6545	MCS0	6
		6625	MCS0	6
		6785	MCS0	7
		6865	MCS0	6
		6945	MCS0	6
		7025	MCS0	7


Band	Modulation mode	Frequency(MHz)	Rate	Normal Power setting
6GHz	802.11ax160	6025	MCS0	10
		6185	MCS0	10
		6345	MCS0	10
		6505	MCS0	10
		6665	MCS0	9
		6825	MCS0	9
		6985	MCS0	10

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2. EUT built-in battery-powered, the battery is fully-charged.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Manufacturer	Model/Type No.	Series No.	Note
AE-1	IoT Module	METICOMM PTE. LTD.	MQC2064-5-46-0U	N/A	EUT
AE-2	Notebook	HUAWEI	FLMH-16	N/A	Peripherals
AE-3	Adapter	HUAWEI	HW-200325CP3	N/A	Peripherals
AE-4	Mainframe	Yingchi	YM-503	N/A	Peripherals
AE-5	Adapter	Yingchi	DC-908-1204000	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	0.5m
C-2	RF Cable	YES	NO	0.1m
C-3	Power Cable	NO	NO	1.0m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2025.04.24	2026.04.23	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025.04.17	2026.04.16	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2025.04.17	2026.04.16	1 year
4	Test Receiver	R&S	ESPI7	101318	2025.04.17	2026.04.16	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2025.04.17	2026.04.16	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2025.04.17	2026.04.16	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	MWRFTest	MW100-PD	MW2021043	2025.04.17	2026.04.16	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2023.05.06	2026.05.05	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2025.04.17	2026.04.16	1 year
2	LISN	R&S	ENV216	101313	2025.04.16	2026.04.15	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2025.04.16	2026.04.15	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFTest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. TEST REQUIREMENTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020+COR.1-2023 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


3.1.5 TEST RESULTS

EUT :	IoT Module	Model Name :	MQC2066-5-46-0U
Temperature :	24.8°C	Relative Humidity :	64.3%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 3.3V from Adapter AC 120V/60Hz	Test Mode :	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1620	11.66	10.02	21.68	65.36	-43.68	peak
0.1620	-1.90	10.02	8.12	55.36	-47.24	AVG
0.2980	10.01	10.22	20.23	60.30	-40.07	peak
0.2986	1.06	10.22	11.28	50.28	-39.00	AVG
1.2980	6.70	12.39	19.09	56.00	-36.91	peak
1.2940	-6.56	12.37	5.81	46.00	-40.19	AVG
2.5780	9.65	9.82	19.47	56.00	-36.53	peak
2.5780	-1.19	9.82	8.63	46.00	-37.37	AVG
5.4140	7.30	9.90	17.20	60.00	-42.80	peak
5.4140	-4.24	9.90	5.66	50.00	-44.34	AVG
11.0340	11.89	10.08	21.97	60.00	-38.03	peak
11.0340	0.30	10.08	10.38	50.00	-39.62	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




Note: The test report records only the worst-case test values.

EUT :	IoT Module	Model Name :	MQC2066-5-46-0U
Temperature :	24.8℃	Relative Humidity :	64.3%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 3.3V from Adapter AC 120V/60Hz	Test Mode :	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1607	14.43	9.99	24.42	65.43	-41.01	peak
0.1607	2.45	9.99	12.44	55.43	-42.99	AVG
0.4711	9.46	10.64	20.10	56.49	-36.39	peak
0.4711	-0.35	10.64	10.29	46.49	-36.20	AVG
1.0500	8.18	11.82	20.00	56.00	-36.00	peak
1.0500	-3.94	11.82	7.88	46.00	-38.12	AVG
3.9100	7.77	9.79	17.56	56.00	-38.44	peak
3.8860	-4.11	9.79	5.68	46.00	-40.32	AVG
15.4380	10.61	10.30	20.91	60.00	-39.09	peak
15.4380	0.91	10.30	11.21	50.00	-38.79	AVG
21.3460	10.18	10.26	20.44	60.00	-39.56	peak
21.3460	-2.05	10.26	8.21	50.00	-41.79	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



Note: The test report records only the worst-case test values.

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(b) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(10): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2020+COR.1-2023. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020+COR.1-2023 and CAN/CSA-CEI/IEC CISPR 22. This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHZ – 30 MHZ)

EUT:	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHZ – 1GHZ)

EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	25.7 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 4 (802.11ax20 MIMO)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	50.0566	9.20	19.67	28.87	40.00	-11.13	peak
V	66.7325	9.85	17.26	27.11	40.00	-12.89	peak
V	172.5987	13.20	15.61	28.81	43.50	-14.69	peak
V	210.7860	8.48	18.23	26.71	43.50	-16.79	peak
V	495.9344	9.29	24.50	33.79	46.00	-12.21	peak
V	824.5968	8.54	29.98	38.52	46.00	-7.48	peak

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit




Note: The test report records only the worst-case test values.

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBUV)	(dB)	(dBUV/m)	(dBUV/m)	(dB)	
H	48.3317	7.85	19.70	27.55	40.00	-12.45	peak
H	110.1816	8.23	17.79	26.02	43.50	-17.48	peak
H	211.5264	8.86	18.24	27.10	43.50	-16.40	peak
H	337.2155	7.79	21.51	29.30	46.00	-16.70	peak
H	609.9217	8.73	26.47	35.20	46.00	-10.80	peak
H	779.6067	8.84	29.42	38.26	46.00	-7.74	peak

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note: The test report records only the worst-case test values.

3.2.8 TEST RESULTS (1GHZ-18GHZ)

EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 2/3/4/5 MIMO		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5955 MHz)-Above 1G									
Vertical	7189	49.83	5.43	36.59	37.14	54.71	68.2	-13.49	Pk
Vertical	10142	49.90	6.06	37.98	34.79	59.15	68.2	-9.05	Pk
Vertical	11910	52.00	6.77	37.7	32.33	64.14	74	-9.86	Pk
Vertical	11910	33.99	6.77	37.7	32.33	46.13	54	-7.87	AV
Horizontal	7188	47.91	5.43	36.59	37.14	52.79	68.2	-15.41	Pk
Horizontal	10141	48.51	6.06	37.98	34.77	57.78	68.2	-10.42	Pk
Horizontal	11910	51.83	6.77	37.7	32.33	63.97	74	-10.03	Pk
Horizontal	11910	34.68	6.77	37.7	32.33	46.82	54	-7.18	AV
middle Channel (6175 MHz)-Above 1G									
Vertical	7165	53.66	5.42	37.11	36.94	59.25	68.2	-8.95	Pk
Vertical	10400	50.54	6.14	38.3	32.45	62.53	68.2	-5.67	Pk
Vertical	12350	54.55	6.92	38.6	30.88	69.19	74	-4.81	Pk
Vertical	12350	29.59	6.92	38.6	30.88	44.23	54	-9.77	AV
Horizontal	7163	53.10	5.42	37.06	36.96	58.62	68.2	-9.58	Pk
Horizontal	10400	46.66	6.14	38.3	32.45	58.65	68.2	-9.55	Pk
Horizontal	12350	52.89	6.92	38.6	30.88	67.53	74	-6.47	Pk
Horizontal	12350	32.59	6.92	38.6	30.88	47.23	54	-6.77	AV
High Channel (6415 MHz)-Above 1G									
Vertical	7268	45.62	5.45	36.12	35.84	51.35	74	-22.65	Pk
Vertical	7268	34.44	5.45	36.12	35.84	40.17	54	-13.83	AV
Vertical	12830	42.64	7.06	40.25	28.91	61.04	68.2	-7.16	Pk
Vertical	15720	43.06	7.65	38.76	32.22	57.25	74	-16.75	Pk
Vertical	15720	32.44	7.65	38.76	32.22	46.63	54	-7.37	AV
Horizontal	7268	50.94	5.45	36.15	35.77	56.77	74	-17.23	Pk
Horizontal	7268	40.14	5.45	36.15	35.77	45.97	54	-8.03	AV
Horizontal	12830	42.68	7.06	40.25	28.91	61.08	68.2	-7.12	Pk
Horizontal	15720	48.60	7.65	38.76	32.22	62.79	74	-11.21	Pk
Horizontal	15720	34.26	7.65	38.76	32.22	48.45	54	-5.55	AV

Note:"802.11ax20 MIMO" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

All modes have been test, just the 802.11ax20 MIMO worst mode has been recorded in the report.

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (6435 MHz)-Above 1G									
Vertical	7189	48.16	5.43	36.49	37.18	52.90	68.2	-15.30	Pk
Vertical	12870	44.72	7.07	40.05	28.89	62.95	68.2	-5.25	Pk
Vertical	15543	51.65	7.62	38.73	30.4	67.60	74	-6.40	Pk
Vertical	15543	30.29	7.62	38.73	30.4	46.24	54	-7.76	AV
Horizontal	7184	48.61	5.43	36.59	37.14	53.49	68.2	-14.71	Pk
Horizontal	12870	42.84	7.07	40.05	28.89	61.07	68.2	-7.13	Pk
Horizontal	15544	49.00	7.62	38.72	30.42	64.92	74	-9.08	Pk
Horizontal	15544	32.85	7.62	38.72	30.42	48.77	54	-5.23	AV
middle Channel (6475 MHz)-Above 1G									
Vertical	7166	50.21	5.42	37.11	36.94	55.80	68.2	-12.40	Pk
Vertical	12950	44.73	7.1	39.65	28.85	62.63	68.2	-5.57	Pk
Vertical	15651	48.01	7.64	38.46	31.59	62.52	74	-11.48	Pk
Vertical	15651	33.82	7.64	38.46	31.59	48.33	54	-5.67	AV
Horizontal	7163	48.18	5.42	37.06	36.96	53.70	68.2	-14.50	Pk
Horizontal	12950	44.65	7.1	39.65	28.85	62.55	68.2	-5.65	Pk
Horizontal	15660	49.08	7.64	38.52	31.67	63.57	74	-10.43	Pk
Horizontal	15660	35.17	7.64	38.52	31.67	49.66	54	-4.34	AV
High Channel (6515 MHz)-Above 1G									
Vertical	7291	49.69	5.45	36.46	35.02	56.58	74	-17.42	Pk
Vertical	7291	33.81	5.45	36.46	35.02	40.70	54	-13.30	AV
Vertical	13030	45.10	7.12	39.58	29.06	62.74	68.2	-5.46	Pk
Vertical	17720	42.54	8.15	45.08	28.93	66.84	74	-7.16	Pk
Vertical	17720	24.17	8.15	45.08	28.93	48.47	54	-5.53	AV
Horizontal	7288	50.87	5.45	36.35	35.29	57.38	74	-16.62	Pk
Horizontal	7288	34.62	5.45	36.35	35.29	41.13	54	-12.87	AV
Horizontal	13030	44.89	7.12	39.58	29.06	62.53	68.2	-5.67	Pk
Horizontal	17720	42.97	8.15	45.08	28.93	67.27	74	-6.73	Pk
Horizontal	17720	24.58	8.15	45.08	28.93	48.88	54	-5.12	AV

Note:"802.11ax20 MIMO" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

All modes have been test, just the 802.11ax20 MIMO worst mode has been recorded in the report.

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (6535 MHz)-Above 1G									
Vertical	7174	47.99	5.42	36.75	37.08	53.08	68.2	-15.12	Pk
Vertical	13070	43.96	7.12	39.82	29.38	61.52	68.2	-6.68	Pk
Vertical	16140	49.64	7.75	38.92	30.81	65.50	74	-8.50	Pk
Vertical	16140	32.14	7.75	38.92	30.81	48.00	54	-6.00	AV
Horizontal	7173	46.75	5.43	36.59	37.14	51.63	68.2	-16.57	Pk
Horizontal	13070	45.71	7.12	39.82	29.38	63.27	68.2	-4.93	Pk
Horizontal	16140	48.46	7.75	38.92	30.81	64.32	74	-9.68	Pk
Horizontal	16140	33.00	7.75	38.92	30.81	48.86	54	-5.14	AV
middle Channel (6695 MHz)-Above 1G									
Vertical	7165	57.86	5.42	37.11	36.94	63.45	68.2	-4.75	Pk
Vertical	10413	50.77	6.15	38.33	32.41	62.84	68.2	-5.36	Pk
Vertical	13390	49.78	7.19	40.76	30.03	67.70	74	-6.30	Pk
Vertical	13390	30.22	7.19	40.76	30.03	48.14	54	-5.86	AV
Horizontal	7163	56.77	5.42	37.06	36.96	62.29	68.2	-5.91	Pk
Horizontal	10414	49.98	6.15	38.33	32.41	62.05	68.2	-6.15	Pk
Horizontal	13390	50.56	7.19	40.76	30.03	68.48	74	-5.52	Pk
Horizontal	13390	29.89	7.19	40.76	30.03	47.81	54	-6.19	AV
High Channel (6855 MHz)-Above 1G									
Vertical	7523	47.76	5.51	36.76	34.13	55.90	74	-18.10	Pk
Vertical	7523	37.55	5.51	36.76	34.13	45.69	54	-8.31	AV
Vertical	13710	44.73	7.25	40.56	29.66	62.88	68.2	-5.32	Pk
Vertical	15739	48.16	7.66	38.72	32.4	62.14	74	-11.86	Pk
Vertical	15739	34.77	7.66	38.72	32.41	48.74	54	-5.26	AV
Horizontal	7527	48.53	5.51	36.75	34.11	56.68	74	-17.32	Pk
Horizontal	7527	37.44	5.51	36.75	34.11	45.59	54	-8.41	AV
Horizontal	13710	44.81	7.25	40.56	29.66	62.96	68.2	-5.24	Pk
Horizontal	15740	49.07	7.66	38.72	32.41	63.04	74	-10.96	Pk
Horizontal	15740	33.15	7.66	38.72	32.43	47.10	54	-6.90	AV

Note:"802.11ax20 MIMO" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

All modes have been test, just the 802.11ax20 MIMO worst mode has been recorded in the report.

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (6895 MHz)-Above 1G									
Vertical	7152	48.71	5.42	37.17	36.92	54.38	68.2	-13.82	Pk
Vertical	13750	42.67	7.27	41.04	30.91	60.07	68.2	-8.13	Pk
Vertical	15840	49.17	7.67	38.11	31.89	63.06	74	-10.94	Pk
Vertical	15840	34.03	7.67	38.12	31.92	47.90	54	-6.10	AV
Horizontal	7186	49.10	5.43	36.59	37.14	53.98	68.2	-14.22	Pk
Horizontal	13750	45.13	7.27	41.04	30.91	62.53	68.2	-5.67	Pk
Horizontal	15840	51.37	7.67	38.12	31.92	65.24	74	-8.76	Pk
Horizontal	15840	35.82	7.67	38.12	31.92	49.69	54	-4.31	AV
middle Channel (6995 MHz)-Above 1G									
Vertical	7167	48.30	5.42	37.11	36.94	53.89	68.2	-14.31	Pk
Vertical	13990	44.23	7.31	40.75	29.2	63.09	68.2	-5.11	Pk
Vertical	15963	46.67	7.69	37.65	28.72	63.29	74	-10.71	Pk
Vertical	15961	32.12	7.69	37.64	28.77	48.68	54	-5.32	AV
Horizontal	7165	48.77	5.42	37.06	36.96	54.29	68.2	-13.91	Pk
Horizontal	13990	42.69	7.31	40.75	29.2	61.55	68.2	-6.65	Pk
Horizontal	15960	46.17	7.69	37.64	28.8	62.70	74	-11.30	Pk
Horizontal	15961	31.48	7.69	37.64	28.77	48.04	54	-5.96	AV
High Channel (7115 MHz)-Above 1G									
Vertical	7633	44.84	5.54	36.86	35.55	51.69	74	-22.31	Pk
Vertical	7633	33.79	5.54	36.86	35.55	40.64	54	-13.36	AV
Vertical	14230	43.75	7.35	40.19	27.82	63.47	68.2	-4.73	Pk
Vertical	15472	49.82	7.61	39.14	29.51	67.06	74	-6.94	Pk
Vertical	15472	31.01	7.61	39.14	29.51	48.25	54	-5.75	AV
Horizontal	7686	47.76	5.55	37.24	36.63	53.92	74	-20.08	Pk
Horizontal	7686	35.10	5.55	37.24	36.63	41.26	54	-12.74	AV
Horizontal	14230	43.82	7.35	40.19	27.82	63.54	68.2	-4.66	Pk
Horizontal	15471	47.07	7.61	39.14	29.5	64.32	74	-9.68	Pk
Horizontal	15470	31.53	7.61	39.14	29.49	48.79	54	-5.21	AV

Note:"802.11ax20 MIMO" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

All modes have been test, just the 802.11ax20 MIMO worst mode has been recorded in the report.

3.2.9 TEST RESULTS (18GHz-40GHz)

EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	N/A
Test Mode :	N/A		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	23163.400	58.88	-7.40	51.48	68.20	-16.72	peak
2	29492.067	61.19	-7.82	53.37	68.20	-14.83	peak
3	31237.400	60.54	-5.81	54.73	74.00	-19.27	peak
4	31237.400	48.96	-5.81	43.15	54.00	-10.85	AVG
5	35440.133	59.58	2.72	62.30	68.20	-5.90	peak
6	36453.600	59.97	0.86	60.83	74.00	-13.17	peak
7 *	36453.600	49.54	0.86	50.40	54.00	-3.60	AVG
8	39785.133	53.27	3.10	56.37	68.20	-11.83	peak

High Channel (7115 MHz)-Above 1G Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	25223.333	57.60	-4.17	53.43	68.20	-14.77	peak
2	31403.867	59.74	-5.73	54.01	74.00	-19.99	peak
3	34881.333	58.34	3.43	61.77	68.20	-6.43	peak
4	35314.733	59.24	2.83	62.07	68.20	-6.13	peak
5	35514.200	59.33	2.64	61.97	68.20	-6.23	peak
6	36448.467	61.56	0.85	62.41	74.00	-11.59	peak
7 *	36448.467	49.65	0.85	50.50	54.00	-3.50	AVG

Note:

1. All the modulation modes have been tested, The report just record the worst data mode. The worst mode is 802.11ax 20 7115MHz.
2. Factor= Antenna Factor + Cable Loss - Preamp Factor
3. Level=Reading value+Factor

SPURIOUS EMISSION IN BANDEDGE


EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 2/3/4/5(MIMO Mode)		

802.11ax20 MIMO Mode 5955MHz

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	5881.922	53.13	1.01	54.14	74.00	-19.86	peak
V	5882.560	45.33	1.02	46.35	54.00	-7.65	AVG

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit




Note: The test report records only the worst-case test values.
See Annex 5.7 for test data at the antenna port

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5879.275	53.36	1.00	54.36	74.00	-19.64	peak
H	5881.195	45.20	1.01	46.21	54.00	-7.79	AVG

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit




Note: The test report records only the worst-case test values.
See Annex 5.7 for test data at the antenna port

802.11ax20 MIMO Mode 7115MHz

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	7250.000	50.84	3.16	54.00	74.00	-20.00	peak
V	7250.000	44.40	3.16	47.56	54.00	-6.44	AVG

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit




Note: The test report records only the worst-case test values.
See Annex 5.7 for test data at the antenna port

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	7250.000	52.02	3.16	55.18	74.00	-18.82	peak
H	7250.000	43.88	3.16	47.04	54.00	-6.96	AVG

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note: The test report records only the worst-case test values.
See Annex 5.7 for test data at the antenna port

3.3 EIRP POWER SPECTRAL DENSITY TEST

3.3.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)(8)

For client devices operating under the control of an indoor access point in the 5.925–7.125 GHz bands, the maximum power spectral density must not exceed -1 dBm e.i.r.p. in any 1-megahertz band, and the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm.

3.3.2 TEST PROCEDURE

For devices operating in the bands 5.925–7.125 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(8).

The following test procedures apply:

1. Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
2. Set RBW = 1MHz
3. Set VBW ≥ 3 RBW.
4. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
5. Sweep time = auto.
6. Detector = power averaging (rms)
7. Trace average at least 100 traces in power averaging (rms) mode;
8. Add $10 \log (1/x)$, where x is the duty cycle

3.3.3 DEVIATION FROM STANDARD

No deviation.

3.3.4 TEST SETUP

Refer to section 3.2.4 of this report.

3.3.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULTS

EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 2/3/4/5(MIMO Mode)		

Test data reference attachment.

3.4 26DB & 99% EMISSION BANDWIDTH

3.4.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)(11)


The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.

3.4.2 TEST PROCEDURE

- a) Set RBW = approximately 1%~5 of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.
6. Use the 99 % power bandwidth function of the instrument (if available).



3.4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.4 TEST RESULTS

EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 2/3/4/5(MIMO Mode)		

Test data reference attachment.

3.5 IN-BAND EMISSIONS

3.5.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(b)(7)

For transmitters operating within the 5.925-7.125 GHz bands: Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB.


3.5.2 TEST PROCEDURE

- a) Set the span to encompass the entire 26 dB EBW of the signal.
- b) Set RBW = same RBW used for 26 dB EBW measurement.
- c) Set VBW $\geq 3 \times$ RBW
- d) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$
- e) Detector = RMS (i.e., power averaging).
- f) Trace mode = max hold.
- g) Sweep = auto couple.
- h) Trace average at least 100 traces in power averaging (rms) mode.

3.5.3 DEVIATION FROM STANDARD

No deviation.

3.5.4 TEST SETUP



3.5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.5.6 TEST RESULTS

EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 2/3/4/5(MIMO Mode)		

Test data reference attachment.

3.6 MAXIMUM EIRP OUTPUT POWER

3.6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)(8)

For client devices operating under the control of an indoor access point in the 5.925–7.125 GHz bands, the maximum power spectral density must not exceed -1 dBm e.i.r.p. in any 1-megahertz band, and the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm.

3.6.2 TEST PROCEDURE

For devices operating in the bands 5.925–7.125 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(4)(8).

The following test procedures apply:

1. Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
2. Set RBW = 1MHz
3. Set VBW $\geq$ 3 RBW.
4. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
5. Sweep time = auto.
6. Detector = power averaging (rms)
7. Trace average at least 100 traces in power averaging (rms) mode;
8. Add $10 \log (1/x)$, where x is the duty cycle

3.6.3 DEVIATION FROM STANDARD

No deviation.

3.6.4 TEST SETUP

Refer to section 3.2.4 of this report.

3.6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6.6 TEST RESULTS

EUT :	IoT Module	Model Name. :	MQC2066-5-46-0U
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 2/3/4/5(MIMO Mode)		

Test data reference attachment.

3.7 OPERATIONAL RESTRICTIONS FOR 6 GHZ U-NII DEVICES.

3.7.1 APPLICABLE STANDARD

According to FCC §15.407(d)(2)(3)(5)(6)

Operation of transmitters in the 5.925–7.125 GHz band is prohibited for control of or communications with unmanned aircraft systems.

Transmitters operating under the provisions of paragraphs (a)(5), (a)(6), and (a)(8) of this section are limited to indoor locations.

In the 5.925–7.125 GHz band, client devices, except fixed client devices, must operate under the control of a standard power access point, indoor access point or subordinate devices; Subordinate devices must operate under the control of an indoor access point. In all cases, an exception exists for transmitting brief messages to an access point when attempting to join its network after detecting a signal that confirms that an access point is operating on a particular channel. Access points and subordinate devices may connect to other access points or subordinate devices. Client devices are prohibited from connecting directly to another client device.

Indoor access points, subordinate devices and client devices operating in the 5.925–7.125 GHz band must employ a contention-based protocol.

3.7.2 TEST RESULTS

EUT :	VR All-in-one-Headset	Model Name. :	Crystal
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V

Declaration by applicant all restrictions are meet the FCC §15.407(d)(2)(3)(5)(6) requirements.

3.8 CONTENTION BASED PROTOCOL

3.8.1 LIMIT OF CONTENTION BASED PROTOCOL

According to FCC §15.407(d)(6)

Indoor access points, subordinate devices and client devices operating in the 5.925-7.125 GHz band must employ a contention-based protocol.

FCC KDB 987594 D02 U-NII 6GHz EMC Measurement v01r01

Unlicensed low-power indoor devices must detect co-channel radio frequency power that is at least -62 dBm or lower. Upon detection of energy in the band, unlicensed low power indoor devices must vacate the channel and stay off the channel as long as detected radio frequency power is equal to or greater than the threshold (-62 dBm). The -62 dBm (or lower) threshold is referenced to a 0 dBi antenna gain. To ensure incumbent operations are reliably detected in the band, low power indoor devices must detect RF energy throughout their intended operating channel. For example, an 802.11 device that plans to transmit a 40 MHz- wide signal (on a primary 20 MHz channel and a secondary 20 MHz channel) must detect energy throughout the entire 40 MHz channel. Additionally, low-power indoor devices must detect co-channel energy with 90% or greater certainty.

Table 1. Criteria to determine number of times detection threshold test may be performed

If	Number of Tests	Placement of Incumbent Transmission
$BW_{EUT} \leq BW_{Inc}$	Once	Tune incumbent and EUT transmissions ($f_{c1} = f_{c2}$)
$BW_{Inc} < BW_{EUT} \leq 2BW_{Inc}$	Once	Incumbent transmission is contained within BW_{EUT}
$2BW_{Inc} < BW_{EUT} \leq 4BW_{Inc}$	Twice. Incumbent transmission is contained within BW_{EUT}	Incumbent transmission is located as closely as possible to the lower edge and upper edge, respectively, of the EUT channel
$BW_{EUT} > 4BW_{Inc}$	Three times	Incumbent transmission is located as closely as possible to the lower edge of the EUT channel, in the middle of EUT channel, and as closely as possible to the upper edge of the EUT channel

where:

BW_{EUT} : Transmission bandwidth of EUT signal

BW_{Inc} : Transmission bandwidth of the simulated incumbent signal (10 MHz wide AWGN signal)

f_{c1} : Center frequency of EUT transmission

f_{c2} : Center frequency of simulated incumbent signal




Figure 1. Two possible scenarios where a) center frequency of EUT transmission falls within incumbent's bandwidth, or b) outside of it

3.8.2 TEST PROCEDURES

The testing follows FCC KDB 987594 D02 U-NII 6GHz EMC Measurement v01r01.

Section I) Contention Based Protocol

Conducted method Step-by-Step Procedure, Conducted Setup

1. Configure the EUT to transmit with a constant duty cycle.
2. Set the operating parameters of the EUT including power level, operating frequency, modulation and bandwidth.
3. Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT.
4. Connect the output port of the EUT to the signal analyzer 2, as shown in test setup Figure 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.
5. Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters set at step two.
6. Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10 MHz-wide AWGN signal. Use Table 1 to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.
7. Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT as shown in test setup Figure 2.
8. Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.
9. Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.
10. (Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.
11. Refer to Table 1 to determine number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step 5, choose a different center frequency for the AWGN signal and repeat the process.
12. For the contention-based protocol test where only one channel in each supported sub-band needs to be tested. The narrowest and widest bandwidth in each channel shall be measured EUT was driven in MIMO mode, the interferer level was injected to both chains to monitor the performance, while the interferer level is determined according the lowest antenna gain among both antennas (i.e, lower interferer level)

3.8.3 TEST SETUP




Figure 2. Contention-based protocol test setup, conducted method Step-by-Step Procedure, Conducted Setup

3.8.4 TEST RESULTS

Test data reference attachment.

3.9 FREQUENCY STABILITY

Section 15.407(g) specifies that U-NII devices are required to ensure frequency stability. It is required that that the emissions are maintained within the band of operation under all conditions of normal operation as specified in the user's manual. The grantee is responsible for ensuring that the EUT meets Section 15.407(g) requirements; however, the applications for equipment certification are not required to include test reports with explicit demonstration of compliance.

4. ANTENNA REQUIREMENT

4.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 EUT ANTENNA

The EUT have a permanent attached External antenna. It comply with the standard requirement.

5. TEST RESULT

Refer to attachment

END OF REPORT