

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE 1M	2.402	-2.21	0.60	-2±1	-1	0.79	<5	0.24622	3.0	YES
	2.440	-2.72	0.53	-2±1	-1	0.79	<5	0.24816	3.0	YES
	2.480	-4.03	0.40	-4±1	-3	0.50	<5	0.15785	3.0	YES
BLE 2M	2.402	-2.17	0.61	-2±1	-1	0.79	<5	0.24622	3.0	YES
	2.440	-2.69	0.54	-2±1	-1	0.79	<5	0.24816	3.0	YES
	2.480	-4.02	0.40	-4±1	-3	0.50	<5	0.15785	3.0	YES

Conclusion:

For the max result : $0.2 \leq 3.0$ for 1g SAR, SAR is not required.

Signature:

Alex Li

Date: 2025-12-18

NAME AND TITLE (Please print or type): Alex Li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China