



## Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street,  
Bao'an District, Shenzhen, China

### TEST REPORT

#### FCC PART 15 SUBPART E 15.407

Report Reference No. ....: CTA25091900503

FCC ID. ....: 2BQZB-G1618-05

Compiled by

( position+printed name+signature)...: File administrators Zoey Cao

Supervised by

( position+printed name+signature)...: Project Engineer Ace Chai

Approved by

( position+printed name+signature)...: RF Manager Eric Wang

Date of issue .....: Oct. 16, 2025

Testing Laboratory Name .....: Shenzhen CTA Testing Technology Co., Ltd.

Address .....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community,  
Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name .....: Shenzhen GPD Technology Co., Ltd.

Address .....: 1006, Block 4D, Software Industry Base, High-Tech Industrial Park,  
Shenzhen, 518000, China

Test specification .....:

Standard .....: FCC Part 15 Subpart E 15.407

TRF Originator .....: Shenzhen CTA Testing Technology Co., Ltd.

**Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....: Handheld PC gaming console

Trade Mark .....: N/A

Manufacturer.....: Shenzhen GPD Technology Co., Ltd.

Model/Type reference.....: G1618-05

Listed Models.....: N/A

Modulation .....: OFDM/ OFDMA

Frequency.....: From 5180MHz-5240MHz, 5745MHz-5825MHz

Ratings.....: Input: 20V --- 9A

Result.....: PASS

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

## TEST REPORT

Equipment under Test : Handheld PC gaming console

Model /Type : G1618-05

Listed Models : N/A

**Applicant** : **Shenzhen GPD Technology Co., Ltd.**

Address : 1006, Block 4D, Software Industry Base, High-Tech Industrial Park,  
Shenzhen, 518000, China

**Manufacturer** : **Shenzhen GPD Technology Co., Ltd.**

Address : 1006, Block 4D, Software Industry Base, High-Tech Industrial Park,  
Shenzhen, 518000, China

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|     |                                                           |    |
|-----|-----------------------------------------------------------|----|
| 1   | TEST STANDARDS.....                                       | 4  |
| 2   | SUMMARY.....                                              | 5  |
| 2.1 | General Remarks .....                                     | 5  |
| 2.2 | Product Description .....                                 | 5  |
| 2.3 | Equipment Under Test.....                                 | 5  |
| 2.4 | Short description of the Equipment under Test (EUT) ..... | 6  |
| 2.5 | EUT configuration.....                                    | 6  |
| 2.6 | EUT operation mode .....                                  | 6  |
| 2.7 | Block Diagram of Test Setup.....                          | 7  |
| 2.8 | Related Submittal(s) / Grant (s).....                     | 7  |
| 2.9 | Modifications.....                                        | 7  |
| 3   | TEST ENVIRONMENT .....                                    | 8  |
| 3.1 | Address of the test laboratory.....                       | 8  |
| 3.2 | Test Facility .....                                       | 8  |
| 3.3 | Environmental conditions .....                            | 8  |
| 3.4 | Test Description.....                                     | 9  |
| 3.5 | Statement of the measurement uncertainty .....            | 9  |
| 3.1 | Equipments Used during the Test .....                     | 11 |
| 4   | TEST CONDITIONS AND RESULTS .....                         | 12 |
| 4.1 | AC Power Conducted Emission .....                         | 12 |
| 4.2 | Radiated and Conducted Unwanted Emissions.....            | 17 |
| 4.3 | Maximum Conducted Average Output Power .....              | 28 |
| 4.4 | Power Spectral Density .....                              | 31 |
| 4.5 | Emission Bandwidth (26dB Bandwidth) .....                 | 34 |
| 4.6 | Minimum Emission Bandwidth (6dB Bandwidth).....           | 35 |
| 4.7 | Frequency Stability .....                                 | 36 |
| 4.8 | On Time and Duty Cycle .....                              | 38 |
| 4.9 | Antenna Requirement.....                                  | 39 |
| 5   | Test Setup Photos of the EUT .....                        | 40 |
| 6   | Photos of the EUT.....                                    | 41 |

# **1 TEST STANDARDS**

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10-2020 +Cor. 1-2023+ C63.10a-2024+ Errata to C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v02r01

## 2 SUMMARY

### 2.1 General Remarks

|                                |   |               |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Sep. 19, 2025 |
| Testing commenced on           | : | Sep. 19, 2025 |
| Testing concluded on           | : | Oct. 16, 2025 |

### 2.2 Product Description

|                                      |                                                                                                                                                                                                                    |                                    |                      |               |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|----------------------|---------------|
| Product Description:                 | Handheld PC gaming console                                                                                                                                                                                         |                                    |                      |               |
| Model:                               | G1618-05                                                                                                                                                                                                           |                                    |                      |               |
| Power supply:                        | Input: 20V --- 9A                                                                                                                                                                                                  |                                    |                      |               |
| Hardware version:                    | V1.0                                                                                                                                                                                                               |                                    |                      |               |
| Software version:                    | V1.0                                                                                                                                                                                                               |                                    |                      |               |
| Testing sample ID:                   | CTA250919005-1# (Engineer sample)<br>CTA250919005-2# (Normal sample)                                                                                                                                               |                                    |                      |               |
| WIFI                                 |                                                                                                                                                                                                                    |                                    |                      |               |
| Supported type:                      | 20MHz system                                                                                                                                                                                                       | 40MHz system                       | 80MHz system         | 160MHz system |
|                                      | 802.11a<br>802.11n<br>802.11ac<br>802.11ax                                                                                                                                                                         | 802.11n<br>802.11ac<br>802.11ax    | 802.11ac<br>802.11ax | N/A           |
| Operation frequency:                 | 5180MHz-5240MHz<br>5745MHz-5825MHz                                                                                                                                                                                 | 5190MHz-5230MHz<br>5755MHz-5795MHz | 5210MHz<br>5775MHz   | N/A           |
| Modulation:                          | OFDM<br>OFDMA                                                                                                                                                                                                      | OFDM<br>OFDMA                      | OFDM<br>OFDMA        | N/A           |
| Channel number:                      | 9                                                                                                                                                                                                                  | 4                                  | 2                    | N/A           |
| Channel separation:                  | 20MHz                                                                                                                                                                                                              | 40MHz                              | 80MHz                | N/A           |
| Supported partial RU configurations: | Only Support Full RU                                                                                                                                                                                               |                                    |                      |               |
| Antenna type:                        | PIFA Antenna                                                                                                                                                                                                       |                                    |                      |               |
| Antenna gain:                        | ANT1: 4.06 dBi for 5180-5240MHz, 4.20 dBi for 5745-5825MHz<br>ANT2: 2.98 dBi for 5180-5240MHz, 2.01 dBi for 5745-5825MHz                                                                                           |                                    |                      |               |
| MIMO:                                | Directional Gain=10log(((10^(4.06/20)+10^(2.98/20))^2)/2)=6.5dBi for 5.2GWIFI<br>Directional Gain=10log(((10^(4.20/20)+10^(2.01/20))^2)/2)=6.2dBi for 5.8GWIFI<br>Power and PSD Limit= limit- (Directional Gain-6) |                                    |                      |               |

### 2.3 Equipment Under Test

#### Power supply system utilised

Refer to section 2.2

## 2.4 Short description of the Equipment under Test (EUT)

This is a Handheld PC gaming console.

For more details, refer to the user's manual of the EUT.

| Test Software Version | Tools software(DRTU_3.04) |          |          |
|-----------------------|---------------------------|----------|----------|
| Frequency             | 5180 MHz                  | 5220 MHz | 5240 MHz |
| 802.11a               | 3                         | 3        | 3        |
| 802.11n20             | 3                         | 3        | 3        |
| 802.11ac20            | 3                         | 3        | 3        |
| 802.11ax20            | 3                         | 3        | 3        |
| Frequency             | 5190 MHz                  | /        | 5230 MHz |
| 802.11n40             | 3                         | /        | 3        |
| 802.11ac40            | 3                         | /        | 3        |
| 802.11ax40            | 3                         | /        | 3        |
| Frequency             | /                         | 5210 MHz | /        |
| 802.11ac80            | /                         | 3        | /        |
| 802.11ax80            | /                         | 3        | /        |

| Test Software Version | Tools software(DRTU_3.04) |          |          |
|-----------------------|---------------------------|----------|----------|
| Frequency             | 5745 MHz                  | 5785 MHz | 5825 MHz |
| 802.11a               | 3                         | 3        | 3        |
| 802.11n20             | 3                         | 3        | 3        |
| 802.11ac20            | 3                         | 3        | 3        |
| 802.11ax20            | 3                         | 3        | 3        |
| Frequency             | 5755 MHz                  | /        | 5795 MHz |
| 802.11n40             | 3                         | /        | 3        |
| 802.11ac40            | 3                         | /        | 3        |
| 802.11ax40            | 3                         | /        | 3        |
| Frequency             | /                         | 5775 MHz | /        |
| 802.11ac80            | /                         | 3        | /        |
| 802.11ax80            | /                         | 3        | /        |

## 2.5 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

○ - supplied by the manufacturer

● - supplied by the lab

|                                                                |                                                 |
|----------------------------------------------------------------|-------------------------------------------------|
| ● Adapter information<br>(Auxiliary test supplied by test Lab) | Input: AC 100-240V 50/60Hz<br>Output: DC 20V 9A |
|----------------------------------------------------------------|-------------------------------------------------|

## 2.6 EUT operation mode

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

| Operating band               | 20MHz   |                 | 40MHz   |                 | 80MHz   |                 |
|------------------------------|---------|-----------------|---------|-----------------|---------|-----------------|
|                              | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| U-NII 1<br>(5150MHz-5250MHz) | 36      | 5180            | 38      | 5190            | 42      | 5210            |
|                              | 40      | 5200            |         |                 |         |                 |
|                              | 44      | 5220            | 46      | 5230            |         |                 |
|                              | 48      | 5240            |         |                 |         |                 |


Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China  
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

|                              |     |      |     |      |     |      |
|------------------------------|-----|------|-----|------|-----|------|
| U-NII 3<br>(5725MHz-5850MHz) | 149 | 5745 | 151 | 5755 | 155 | 5775 |
|                              | 153 | 5765 |     |      |     |      |
|                              | 157 | 5785 | 159 | 5795 |     |      |
|                              | 161 | 5805 |     |      |     |      |
|                              | 165 | 5825 | --  | --   | --  | --   |

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

## 2.7 Block Diagram of Test Setup



## 2.8 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

## 2.9 Modifications

No modifications were implemented to meet testing criteria.

### 3 TEST ENVIRONMENT

#### 3.1 Address of the test laboratory

**Shenzhen CTA Testing Technology Co., Ltd.**

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 517856    Designation Number: CN1318**

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6534.01**

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### 3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 25 ° C       |
|                       |              |
| Humidity:             | 45 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

Conducted testing:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 25 ° C       |
|                       |              |
| Humidity:             | 44 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

AC Power Conducted Emission

|                       |              |
|-----------------------|--------------|
| Temperature:          | 24 ° C       |
|                       |              |
| Humidity:             | 44 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

### 3.4 Test Description

| FCC Requirement                  |                                            |                       |
|----------------------------------|--------------------------------------------|-----------------------|
| FCC Part 15.207                  | AC Power Conducted Emission                | PASS                  |
| FCC Part 15.407(a)               | Emission Bandwidth(26dBm Bandwidth)        | PASS <sup>Note1</sup> |
| FCC Part 15.407(e)               | Minimum Emission Bandwidth(6dBm Bandwidth) | PASS <sup>Note2</sup> |
| FCC Part 15.407(a)               | Maximum Conducted Output Power             | PASS                  |
| FCC Part 15.407(a)               | Peak Power Spectral Density                | PASS                  |
| FCC Part 15.407(g)               | Frequency Stability                        | PASS                  |
| FCC Part 15.407(b)               | Undesirable emission                       | PASS                  |
| FCC Part 15.407(b)/15.205/15.209 | Radiated Emissions                         | PASS                  |
| FCC Part 15.407(h)               | Dynamic Frequency Selection                | N/A <sup>Note 3</sup> |
| FCC Part 15.203/15.247(b)        | Antenna Requirement                        | PASS                  |

Note 1: Apply to U-NII 1 band.

Note 2: Apply to U-NII 3 band only.

Note 3: This device not work in DFS band.

#### Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                                                                                                                                                                                   | Mode                                              | Data Rate |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|-----------|
| Maximum Conducted Output Power<br>Power Spectral Density<br>Emission Bandwidth(26dBm Bandwidth)<br>Minimum Emission Bandwidth(6dBm Bandwidth)<br>Undesirable emission<br>Frequency Stability | 11a/OFDM                                          | 6 Mbps    |
|                                                                                                                                                                                              | 11n(20MHz),11ac(20MHz)/OFDM,<br>11ax(20MHz)/OFDMA | MCS0      |
|                                                                                                                                                                                              | 11n(40MHz),11ac(40MHz)/OFDM,<br>11ax(40MHz)/OFDMA | MCS0      |
|                                                                                                                                                                                              | 11ac(80MHz)/OFDM,<br>11ax(80MHz)/OFDMA            | MCS0      |

### 3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

| Test                  | Range      | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission     | 9KHz~30MHz | 3.02 dB                 | (1)   |
| Radiated Emission     | 30~1000MHz | 4.06 dB                 | (1)   |
| Radiated Emission     | 1~18GHz    | 5.14 dB                 | (1)   |
| Radiated Emission     | 18-40GHz   | 5.38 dB                 | (1)   |
| Conducted Disturbance | 0.15~30MHz | 2.14 dB                 | (1)   |

**Shenzhen CTA Testing Technology Co., Ltd.**

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China  
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

|                                             |             |         |     |
|---------------------------------------------|-------------|---------|-----|
| Output Peak power                           | 30MHz~18GHz | 0.55 dB | (1) |
| Power spectral density                      | /           | 0.57 dB | (1) |
| Spectrum bandwidth                          | /           | 1.1%    | (1) |
| Radiated spurious emission<br>(30MHz-1GHz)  | 30~1000MHz  | 4.10 dB | (1) |
| Radiated spurious emission<br>(1GHz-18GHz)  | 1~18GHz     | 4.32 dB | (1) |
| Radiated spurious emission<br>(18GHz-40GHz) | 18-40GHz    | 5.54 dB | (1) |
| Time                                        | /           | ±2%     | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


### 3.1 Equipments Used during the Test

| Test Equipment                                              | Manufacturer    | Model No.     | Equipment No. | Calibration Date | Calibration Due Date |
|-------------------------------------------------------------|-----------------|---------------|---------------|------------------|----------------------|
| LISN                                                        | R&S             | ENV216        | CTA-308       | 2025/08/04       | 2026/08/03           |
| LISN                                                        | R&S             | ENV216        | CTA-314       | 2025/07/30       | 2026/07/29           |
| EMI Test Receiver                                           | R&S             | ESPI          | CTA-307       | 2025/07/30       | 2026/07/29           |
| EMI Test Receiver                                           | R&S             | ESCI          | CTA-306       | 2025/07/30       | 2026/07/29           |
| Spectrum Analyzer                                           | Agilent         | N9020A        | CTA-301       | 2025/05/17       | 2026/05/16           |
| Spectrum Analyzer                                           | Agilent         | N9020A        | CTA-301       | 2025/07/30       | 2026/07/29           |
| Vector Signal generator                                     | Agilent         | N5182A        | CTA-305       | 2025/07/30       | 2026/07/29           |
| Analog Signal Generator                                     | R&S             | E4421B        | CTA-304       | 2025/07/30       | 2026/07/29           |
| WIDEBAND RADIO COMMUNICATION TESTER                         | CMW500          | R&S           | CTA-302       | 2025/07/30       | 2026/07/29           |
| Temperature and humidity meter                              | Chigo           | ZG-7020       | CTA-326       | 2025/07/31       | 2026/07/30           |
| Ultra-Broadband Antenna                                     | Schwarzbeck     | VULB9163      | CTA-310       | 2023/10/17       | 2026/10/16           |
| Horn Antenna                                                | Schwarzbeck     | BBHA 9120D    | CTA-309       | 2023/10/13       | 2026/10/12           |
| Loop Antenna                                                | Zhinan          | ZN30900C      | CTA-311       | 2023/10/17       | 2026/10/16           |
| Horn Antenna                                                | Schwarzbeck     | BBHA 9170     | CTA-346       | 2025/05/18       | 2028/05/17           |
| Amplifier                                                   | Schwarzbeck     | BBV9745       | CTA-312       | 2025/07/30       | 2026/07/29           |
| Amplifier                                                   | Tonscend        | TAP-011840    | CTA-313       | 2025/07/30       | 2026/07/29           |
| High-Pass Filter                                            | XingBo          | XBLBQ-GTA18   | CTA-402       | 2025/07/30       | 2026/07/29           |
| High-Pass Filter                                            | XingBo          | XBLBQ-GTA27   | CTA-403       | 2025/07/30       | 2026/07/29           |
| Automatic control unit                                      | Tonscend        | JS0806-2      | CTA-351       | 2025/07/30       | 2026/07/29           |
| Amplifier                                                   | SKET            | LNPA 1840G-50 | CTA-345       | 2025/05/17       | 2026/05/16           |
| Spectrum analyzer                                           | R&S             | FSV40-N       | CTA-344       | 2025/05/17       | 2026/05/16           |
| Attenuator                                                  | XINQY           | 10dB          | N/A           | N/A              | N/A                  |
| Programmable Constant Temperature And Humidity Test Chamber | DONGGUAN JINGYU | HT-H-408      | CTA-053       | 2025/07/30       | 2026/07/29           |
| EMI Test Software                                           | Tonscend        | TS@JS32-RE    | 5.0.0.2       | N/A              | N/A                  |
| EMI Test Software                                           | Tonscend        | TS@JS32-CE    | 5.0.0.1       | N/A              | N/A                  |
| RF Test Software                                            | Tonscend        | TS@JS1120-3   | 3.1.65        | N/A              | N/A                  |
| RF Test Software                                            | Tonscend        | TS@JS1120     | 3.1.46        | N/A              | N/A                  |

## 4 TEST CONDITIONS AND RESULTS

### 4.1 AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a Multi-System Scannerop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### TEST RESULTS


Passed

Please refer to the below test data:

Remark:


1. All modes of 802.11a/n/11ac/11ax were test at Low, Middle, and High channel; only the worst result of a Middle Channel was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

5.2GWIFI:



Polarization:

N



## Final Data List

| NO. | Freq. [MHz] | Factor [dB] | QP Reading[dB μV] | QP Value [dBμV] | QP Limit [dBμV] | QP Margin [dB] | AV Reading [dBμV] | AV Value [dBμV] | AV Limit [dBμV] | AV Margin [dB] | Verdict |
|-----|-------------|-------------|-------------------|-----------------|-----------------|----------------|-------------------|-----------------|-----------------|----------------|---------|
| 1   | 0.1905      | 9.95        | 34.16             | 44.11           | 64.01           | 19.90          | 21.81             | 31.76           | 54.01           | 22.25          | PASS    |
| 2   | 0.6585      | 10.29       | 31.88             | 42.17           | 56.00           | 13.83          | 18.99             | 29.28           | 46.00           | 16.72          | PASS    |
| 3   | 1.671       | 10.42       | 27.72             | 38.14           | 56.00           | 17.86          | 17.03             | 27.45           | 46.00           | 18.55          | PASS    |
| 4   | 5.7705      | 11.02       | 17.42             | 28.44           | 60.00           | 31.56          | 6.45              | 17.47           | 50.00           | 32.53          | PASS    |
| 5   | 16.035      | 12.49       | 24.93             | 37.42           | 60.00           | 22.58          | 15.75             | 28.24           | 50.00           | 21.76          | PASS    |
| 6   | 25.8765     | 13.49       | 22.05             | 35.54           | 60.00           | 24.46          | 15.43             | 28.92           | 50.00           | 21.08          | PASS    |


Note:1). QP Value (dBμV)= QP Reading (dBμV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). QPMargin(dB) = QP Limit (dBμV) - QP Value (dBμV)


4). AVMargin(dB) = AV Limit (dBμV) - AV Value (dBμV)

5.8GWIFI:



Polarization:

N



## Final Data List

| NO. | Freq. [MHz] | Factor [dB] | QP Reading[dB μV] | QP Value [dBμV] | QP Limit [dBμV] | QP Margin [dB] | AV Reading [dBμV] | AV Value [dBμV] | AV Limit [dBμV] | AV Margin [dB] | Verdict |
|-----|-------------|-------------|-------------------|-----------------|-----------------|----------------|-------------------|-----------------|-----------------|----------------|---------|
| 1   | 0.177       | 9.91        | 32.98             | 42.89           | 64.63           | 21.74          | 20.41             | 30.32           | 54.63           | 24.31          | PASS    |
| 2   | 0.447       | 10.21       | 30.33             | 40.54           | 56.93           | 16.39          | 19.18             | 29.39           | 46.93           | 17.54          | PASS    |
| 3   | 1.5675      | 10.42       | 29.98             | 40.40           | 56.00           | 15.60          | 17.51             | 27.93           | 46.00           | 18.07          | PASS    |
| 4   | 3.5745      | 10.72       | 18.67             | 29.39           | 56.00           | 26.61          | 7.54              | 18.26           | 46.00           | 27.74          | PASS    |
| 5   | 16.6425     | 12.57       | 24.35             | 36.92           | 60.00           | 23.08          | 12.86             | 25.43           | 50.00           | 24.57          | PASS    |
| 6   | 26.61       | 13.55       | 21.88             | 35.43           | 60.00           | 24.57          | 16.92             | 30.47           | 50.00           | 19.53          | PASS    |

Note:1). QP Value (dBμV) = QP Reading (dBμV) + Factor (dB)

2). Factor (dB) = insertion loss of LISN (dB) + Cable loss (dB)

3). QPMargin(dB) = QP Limit (dBμV) - QP Value (dBμV)

4). AVMargin(dB) = AV Limit (dBμV) - AV Value (dBμV)

## 4.2 Radiated and Conducted Unwanted Emissions

### Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

### Undesirable emission limits

| Requirement  | Limit(EIRP)     | Limit (Field strength at 3m) <sup>Note1</sup> |
|--------------|-----------------|-----------------------------------------------|
| 15.407(b)(1) | PK:-27(dBm/MHz) | PK:68.2(dBμV/m)                               |
| 15.407(b)(2) |                 |                                               |
| 15.407(b)(3) |                 |                                               |
| 15.407(b)(4) |                 |                                               |

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

### Radiated emission limits

| Frequency (MHz) | Distance (Meters) | Radiated (dBμV/m)                          | Radiated (μV/m)       |
|-----------------|-------------------|--------------------------------------------|-----------------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(\text{KHz}))+40\log(300/3)$ | $2400/F(\text{KHz})$  |
| 0.49-1.705      | 3                 | $20\log(24000/F(\text{KHz}))+40\log(30/3)$ | $24000/F(\text{KHz})$ |
| 1.705-30        | 3                 | $20\log(30)+40\log(30/3)$                  | 30                    |
| 30-88           | 3                 | 40.0                                       | 100                   |
| 88-216          | 3                 | 43.5                                       | 150                   |
| 216-960         | 3                 | 46.0                                       | 200                   |
| Above 960       | 3                 | 54.0                                       | 500                   |

**Conducted measurement Test Procedure:**

The testing follows the ANSI C63.10 Section 12.7.6 and 6.10.4:

The procedure for peak unwanted emissions measurements above 1000 MHz is as follows:

b) Peak emission levels are measured by setting the instrument as follows:

- 1) RBW = 1 MHz.
- 2) VBW  $\geq [3 \times \text{RBW}]$
- 3) Detector = peak.
- 4) Sweep time = No faster than coupled (auto) time.
- 5) Trace mode = max-hold.
- 6) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, then the time required for the trace to stabilize will increase by a factor of approximately  $1 / D$ , where D is the duty cycle. For example, at 50% duty cycle, the measurement time will increase by a factor of two, relative to measurement time for continuous transmission.


**Test Results**

Please refer to FCC Appendix RF Test Data for 5GWIFI


Note: RF Conducted test Offset= cable loss, For conducted spurious emission test, cable loss is the maximum value in the range of test.

**TEST CONFIGURATION**


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz




(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz





### Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type   | Test Distance |
|----------------------|---------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna | 3             |
| 30MHz-1GHz           | Bilog Antenna       | 3             |
| 1GHz-18GHz           | Horn Antenna        | 3             |
| 18GHz-25GHz          | Horn Antenna        | 1             |

- Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting                                                                            | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                       | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                      | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                                   | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz,<br>Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz,<br>Sweep time=Auto | Peak     |

### TEST RESULTS


Remark:


- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- All modes of 802.11a/n/11ac/11ax have been tested for below 1GHz test, only the worst case 802.11a low channel was recorded.
- All modes of 802.11a/n/11ac/11ax have been tested for above 1GHz test, only the worst case 802.11a was recorded.
- Radiated emission test from 9 KHz to 40GHz harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
- Conducted emission test from 30MHz to 40GHz harmonic of fundamental was verified, and emission margin is greater than 20dB in 27GHz to 40GHz and not recorded in this report.

Shenzhen CTA Testing Technology Co., Ltd.


Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China  
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn


5.2G WIFI :  
For 30MHz-1GHz





5.8G WIFI :  
For 30MHz-1GHz





**For 1GHz to 40GHz**

Note: All modes of 802.11a/n/11ac have been tested for above 1GHz test, only the worst case 802.11ac20 MIMO mode was recorded.

**U-NII 1 & 802.11a Mode (above 1GHz)**

| Tested Channel | Frequency (MHz) | Emission Level (dBuV/m) | Detector Mode | ANT Pol | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre amplifier (dB) | Correction Factor (dB/m) |
|----------------|-----------------|-------------------------|---------------|---------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
|                | 5150.00         | 54.75                   | PK            | H       | 68.30          | 13.55       | 58.18            | 33.04                 | 5.45              | 41.92              | -3.43                    |
| 36.00          | 5150.00         | 48.54                   | AV            | H       | 54.00          | 5.46        | 51.97            | 33.04                 | 5.45              | 41.92              | -3.43                    |
| (5180MHz)      | 10360.00        | 51.78                   | PK            | H       | 68.30          | 16.52       | 48.11            | 38.83                 | 10.12             | 45.28              | 3.67                     |
|                | --              | --                      | AV            | H       | --             | --          | --               | --                    | --                | --                 | --                       |
| 44.00          | 10440.00        | 53.82                   | PK            | H       | 68.30          | 14.48       | 50.14            | 38.85                 | 10.13             | 45.3               | 3.68                     |
| (5220MHz)      | --              | --                      | AV            | H       | --             | --          | --               | --                    | --                | --                 | --                       |
| 48.00          | 5350.50         | 47.67                   | PK            | H       | 68.30          | 20.63       | 50.94            | 32.84                 | 5.97              | 42.08              | -3.27                    |
| (5240MHz)      | 10480.00        | 52.93                   | PK            | H       | 68.30          | 15.37       | 49.19            | 38.89                 | 10.19             | 45.34              | 3.74                     |
|                | --              | --                      | AV            | H       | --             | --          | --               | --                    | --                | --                 | --                       |

| Tested Channel | Frequency (MHz) | Emission Level (dBuV/m) | Detector Mode | ANT Pol | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre amplifier (dB) | Correction Factor (dB/m) |
|----------------|-----------------|-------------------------|---------------|---------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
|                | 5150.00         | 55.71                   | PK            | V       | 68.30          | 12.59       | 59.14            | 33.04                 | 5.45              | 41.92              | -3.43                    |
| 36.00          | 5150.00         | 48.72                   | AV            | V       | 54.00          | 5.28        | 52.15            | 33.04                 | 5.45              | 41.92              | -3.43                    |
| (5180MHz)      | 10360.00        | 52.88                   | PK            | V       | 68.30          | 15.42       | 49.21            | 38.83                 | 10.12             | 45.28              | 3.67                     |
|                | --              | --                      | --            | V       | --             | --          | --               | --                    | --                | --                 | --                       |
| 44.00          | 10440.00        | 52.80                   | PK            | V       | 68.30          | 15.50       | 49.12            | 38.85                 | 10.13             | 45.3               | 3.68                     |
| (5220MHz)      | --              | --                      | --            | V       | --             | --          | --               | --                    | --                | --                 | --                       |
| 48.00          | 5350.50         | 47.66                   | PK            | V       | 68.30          | 20.64       | 50.93            | 32.84                 | 5.97              | 42.08              | -3.27                    |
| (5240MHz)      | 10480.00        | 51.97                   | PK            | V       | 68.30          | 16.33       | 48.23            | 38.89                 | 10.19             | 45.34              | 3.74                     |
|                | --              | --                      | AV            | V       | --             | --          | --               | --                    | --                | --                 | --                       |

**U-NII 3 & 802.11a Mode (above 1GHz)**

| Tested    | Frequency | Emission | Detector | Antenna | Limit    | Margin | Raw    | Antenna | Cable  | Pre       | Correction |
|-----------|-----------|----------|----------|---------|----------|--------|--------|---------|--------|-----------|------------|
| Channel   | (MHz)     | Level    | Mode     | Pol     | (dBuV/m) | (dB)   | Value  | Factor  | Factor | amplifier | Factor     |
|           |           | (dBuV/m) |          |         |          |        | (dBuV) | (dB/m)  | (dB)   | (dB)      | (dB/m)     |
|           | 5650.00   | 38.83    | PK       | H       | 68.30    | 29.47  | 41.06  | 33.20   | 5.78   | 41.21     | -2.23      |
|           | 5700.00   | 41.58    | PK       | H       | 105.30   | 63.72  | 43.92  | 33.40   | 5.93   | 41.67     | -2.34      |
|           | 5720.00   | 42.38    | PK       | H       | 110.90   | 68.52  | 45.16  | 33.42   | 6.04   | 42.24     | -2.78      |
| 149.00    | 5725.00   | 44.36    | PK       | H       | 122.30   | 77.94  | 47.14  | 33.42   | 6.04   | 42.24     | -2.78      |
| (5745MHz) | 5850.00   | 48.70    | PK       | H       | 122.30   | 73.60  | 51.10  | 33.90   | 6.49   | 42.79     | -2.40      |
|           | 5855.00   | 45.68    | PK       | H       | 110.90   | 65.22  | 47.97  | 33.90   | 6.74   | 42.93     | -2.29      |
|           | 5875.00   | 46.16    | PK       | H       | 105.30   | 59.14  | 48.26  | 33.97   | 7.02   | 43.09     | -2.10      |
|           | 5925.00   | 46.46    | PK       | H       | 68.30    | 21.84  | 48.23  | 34.17   | 7.33   | 43.27     | -1.77      |
| 149.00    | 11490.00  | 53.52    | PK       | H       | 68.30    | 14.78  | 49.04  | 39.02   | 10.91  | 45.45     | 4.48       |
| (5745MHz) | --        | --       | AV       | H       | --       | --     | --     | --      | --     | --        | --         |
|           | 5650.00   | 39.68    | PK       | H       | 68.30    | 28.62  | 41.91  | 33.20   | 5.78   | 41.21     | -2.23      |
|           | 5700.00   | 41.74    | PK       | H       | 105.30   | 63.56  | 44.08  | 33.40   | 5.93   | 41.67     | -2.34      |
| 157.00    | 5720.00   | 43.23    | PK       | H       | 110.90   | 67.67  | 46.01  | 33.42   | 6.04   | 42.24     | -2.78      |
| (5785MHz) | 5850.00   | 45.58    | PK       | H       | 122.30   | 76.72  | 47.98  | 33.90   | 6.49   | 42.79     | -2.40      |
|           | 5855.00   | 45.87    | PK       | H       | 110.90   | 65.03  | 48.16  | 33.90   | 6.74   | 42.93     | -2.29      |
|           | 5875.00   | 45.88    | PK       | H       | 105.30   | 59.42  | 47.98  | 33.97   | 7.02   | 43.09     | -2.10      |
|           | 5925.00   | 46.24    | PK       | H       | 68.30    | 22.06  | 48.01  | 34.17   | 7.33   | 43.27     | -1.77      |
| 157.00    | 11570.00  | 52.48    | PK       | H       | 68.30    | 15.82  | 48.03  | 38.93   | 10.95  | 45.43     | 4.45       |
| (5785MHz) | --        | --       | AV       | H       | --       | --     | --     | --      | --     | --        | --         |
|           | 5650.00   | 39.80    | PK       | H       | 68.30    | 28.50  | 42.03  | 33.20   | 5.78   | 41.21     | -2.23      |
|           | 5700.00   | 41.76    | PK       | H       | 105.30   | 63.54  | 44.10  | 33.40   | 5.93   | 41.67     | -2.34      |
| 165.00    | 5720.00   | 43.25    | PK       | H       | 110.90   | 67.65  | 46.03  | 33.42   | 6.04   | 42.24     | -2.78      |
| (5825MHz) | 5850.00   | 47.55    | PK       | H       | 122.30   | 74.75  | 49.95  | 33.90   | 6.49   | 42.79     | -2.40      |
|           | 5855.00   | 45.76    | PK       | H       | 110.90   | 65.14  | 48.05  | 33.90   | 6.74   | 42.93     | -2.29      |
|           | 5875.00   | 46.00    | PK       | H       | 105.30   | 59.30  | 48.10  | 33.97   | 7.02   | 43.09     | -2.10      |
|           | 5925.00   | 46.49    | PK       | H       | 68.30    | 21.81  | 48.26  | 34.17   | 7.33   | 43.27     | -1.77      |
| 165.00    | 11650.00  | 52.57    | PK       | H       | 68.30    | 15.73  | 47.99  | 38.83   | 11.16  | 45.41     | 4.58       |
| (5825MHz) | --        | --       | AV       | H       | --       | --     | --     | --      | --     | --        | --         |

| Tested    | Frequency | Emission | Detector | Antenna | Limit    | Margin | Raw    | Antenna | Cable  | Pre       | Correction |
|-----------|-----------|----------|----------|---------|----------|--------|--------|---------|--------|-----------|------------|
| Channel   | (MHz)     | Level    | Mode     | Pol     | (dBuV/m) | (dB)   | Value  | Factor  | Factor | amplifier | Factor     |
|           |           | (dBuV/m) |          |         |          |        | (dBuV) | (dB/m)  | (dB)   | (dB)      | (dB/m)     |
|           | 5650.00   | 39.87    | PK       | V       | 68.30    | 28.43  | 42.10  | 33.20   | 5.78   | 41.21     | -2.23      |
|           | 5700.00   | 41.74    | PK       | V       | 105.30   | 63.56  | 44.08  | 33.40   | 5.93   | 41.67     | -2.34      |
|           | 5720.00   | 42.22    | PK       | V       | 110.90   | 68.68  | 45.00  | 33.42   | 6.04   | 42.24     | -2.78      |
| 149.00    | 5725.00   | 44.35    | PK       | V       | 122.30   | 77.95  | 47.13  | 33.42   | 6.04   | 42.24     | -2.78      |
| (5745MHz) | 5850.00   | 47.63    | PK       | V       | 122.30   | 74.67  | 50.03  | 33.90   | 6.49   | 42.79     | -2.40      |
|           | 5855.00   | 45.91    | PK       | V       | 110.90   | 64.99  | 48.20  | 33.90   | 6.74   | 42.93     | -2.29      |
|           | 5875.00   | 46.15    | PK       | V       | 105.30   | 59.15  | 48.25  | 33.97   | 7.02   | 43.09     | -2.10      |
|           | 5925.00   | 46.16    | PK       | V       | 68.30    | 22.14  | 47.93  | 34.17   | 7.33   | 43.27     | -1.77      |
| 149.00    | 11490.00  | 53.59    | PK       | V       | 68.30    | 14.71  | 49.11  | 39.02   | 10.91  | 45.45     | 4.48       |
| (5745MHz) | --        | --       | AV       | V       | --       | --     | --     | --      | --     | --        | --         |
|           | 5650.00   | 38.90    | PK       | V       | 68.30    | 29.40  | 41.13  | 33.20   | 5.78   | 41.21     | -2.23      |
|           | 5700.00   | 40.87    | PK       | V       | 105.30   | 64.43  | 43.21  | 33.40   | 5.93   | 41.67     | -2.34      |
| 157.00    | 5720.00   | 42.21    | PK       | V       | 110.90   | 68.69  | 44.99  | 33.42   | 6.04   | 42.24     | -2.78      |
| (5785MHz) | 5850.00   | 48.67    | PK       | V       | 122.30   | 73.63  | 51.07  | 33.90   | 6.49   | 42.79     | -2.40      |
|           | 5855.00   | 45.99    | PK       | V       | 110.90   | 64.91  | 48.28  | 33.90   | 6.74   | 42.93     | -2.29      |
|           | 5875.00   | 46.00    | PK       | V       | 105.30   | 59.30  | 48.10  | 33.97   | 7.02   | 43.09     | -2.10      |
|           | 5925.00   | 46.43    | PK       | V       | 68.30    | 21.87  | 48.20  | 34.17   | 7.33   | 43.27     | -1.77      |
| 157.00    | 11570.00  | 53.53    | PK       | V       | 68.30    | 14.77  | 49.08  | 38.93   | 10.95  | 45.43     | 4.45       |
| (5785MHz) | --        | --       | AV       | V       | --       | --     | --     | --      | --     | --        | --         |
|           | 5650.00   | 38.80    | PK       | V       | 68.30    | 29.50  | 41.03  | 33.20   | 5.78   | 41.21     | -2.23      |
|           | 5700.00   | 40.65    | PK       | V       | 105.30   | 64.65  | 42.99  | 33.40   | 5.93   | 41.67     | -2.34      |
| 165.00    | 5720.00   | 42.31    | PK       | V       | 110.90   | 68.59  | 45.09  | 33.42   | 6.04   | 42.24     | -2.78      |
| (5825MHz) | 5850.00   | 46.80    | PK       | V       | 122.30   | 75.50  | 49.20  | 33.90   | 6.49   | 42.79     | -2.40      |
|           | 5855.00   | 45.92    | PK       | V       | 110.90   | 64.98  | 48.21  | 33.90   | 6.74   | 42.93     | -2.29      |
|           | 5875.00   | 46.11    | PK       | V       | 105.30   | 59.19  | 48.21  | 33.97   | 7.02   | 43.09     | -2.10      |
|           | 5925.00   | 46.41    | PK       | V       | 68.30    | 21.89  | 48.18  | 34.17   | 7.33   | 43.27     | -1.77      |
| 165.00    | 11650.00  | 52.63    | PK       | V       | 68.30    | 15.67  | 48.05  | 38.83   | 11.16  | 45.41     | 4.58       |
| (5825MHz) | --        | --       | AV       | V       | --       | --     | --     | --      | --     | --        | --         |

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
5. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80, IEEE 802.11ax HE20, IEEE 802.11ax HE40 and IEEE 802.11ax HE80.

### 4.3 Maximum Conducted Average Output Power

#### Limit

##### **For the band 5.15-5.25 GHz.**

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

**For the 5.25-5.35 GHz and 5.47-5.725 GHz bands**, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz.

**For the band 5.725-5.85 GHz**, the maximum conducted output power over the frequency band of operation shall not exceed 1 W


#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Method PM is Measurement using an RF average power sensor. The procedure for this method is as follows:

1. The testing follows the ANSI C63.10 Section 12.4.3
2. The maximum average conducted output power may be measured using a broadband average RF power sensor.
3. The power sensor shall have a video bandwidth that is greater than or equal to the OBW bandwidth and shall use a fast-responding diode detector.

#### Test Configuration



#### Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI

Total Output Average power(dBm)= Output Average power(dBm)+ Duty Factor(dB)

For MIMO:

## U-NII 1

| Type            | Channel | Output power<br>(dBm)<br>ANT1 | Output<br>power<br>(dBm)<br>ANT2 | Output power<br>(dBm)<br>MIMO | Limit (dBm) | Result |
|-----------------|---------|-------------------------------|----------------------------------|-------------------------------|-------------|--------|
| 802.11n(HT20)   | 36      | 2.9                           | 3.17                             | 6.05                          | 23.4        | Pass   |
|                 | 44      | 2.92                          | 3.19                             | 6.07                          |             |        |
|                 | 48      | 3.1                           | 3.05                             | 6.09                          |             |        |
| 802.11n(HT40)   | 38      | 3.38                          | 3.63                             | 6.52                          | 23.4        | Pass   |
|                 | 46      | 3.52                          | 3.42                             | 6.48                          |             |        |
| 802.11ac(VHT20) | 36      | 3.01                          | 3.12                             | 6.08                          | 23.4        | Pass   |
|                 | 44      | 2.69                          | 3.12                             | 5.92                          |             |        |
|                 | 48      | 3.07                          | 2.95                             | 6.02                          |             |        |
| 802.11ac(VHT40) | 38      | 3.33                          | 3.46                             | 6.41                          | 23.4        | Pass   |
|                 | 46      | 3.64                          | 3.43                             | 6.55                          |             |        |
| 802.11ac(VHT80) | 42      | 3.57                          | 3.64                             | 6.62                          | 23.4        | Pass   |
| 802.11ax(HE20)  | 36      | 3.16                          | 3.2                              | 6.19                          | 23.4        | Pass   |
|                 | 44      | 3.09                          | 3.14                             | 6.13                          |             |        |
|                 | 48      | 3.24                          | 3.07                             | 6.17                          |             |        |
| 802.11ax(HE40)  | 38      | 3.1                           | 3.09                             | 6.11                          | 23.4        | Pass   |
|                 | 46      | 3.28                          | 3.1                              | 6.20                          |             |        |
| 802.11ax(HE80)  | 42      | 3.28                          | 3.36                             | 6.33                          | 23.4        | Pass   |

## U-NII 3

| Type            | Channel | Output power<br>(dBm)<br>ANT1 | Output power<br>(dBm)<br>ANT2 | Output power<br>(dBm)<br>MIMO | Limit<br>(dBm) | Result |
|-----------------|---------|-------------------------------|-------------------------------|-------------------------------|----------------|--------|
| 802.11n(HT20)   | 149     | 2.21                          | 2.25                          | 5.24                          | 29.8           | Pass   |
|                 | 157     | 1.85                          | 1.99                          | 4.93                          |                |        |
|                 | 165     | 1.6                           | 1.8                           | 4.71                          |                |        |
| 802.11n(HT40)   | 151     | 2.6                           | 2.7                           | 5.66                          | 29.8           | Pass   |
|                 | 159     | 2.39                          | 2.42                          | 5.42                          |                |        |
| 802.11ac(VHT20) | 149     | 2.22                          | 2.17                          | 5.21                          | 29.8           | Pass   |
|                 | 157     | 1.97                          | 1.96                          | 4.98                          |                |        |
|                 | 165     | 1.6                           | 1.73                          | 4.68                          |                |        |
| 802.11ac(VHT40) | 151     | 2.69                          | 2.75                          | 5.73                          | 29.8           | Pass   |
|                 | 159     | 2.38                          | 2.47                          | 5.44                          |                |        |
| 802.11ac(VHT80) | 155     | 2.46                          | 2.65                          | 5.57                          | 29.8           | Pass   |
| 802.11ax(HE20)  | 149     | 2.32                          | 2.41                          | 5.38                          | 29.8           | Pass   |
|                 | 157     | 2.02                          | 1.98                          | 5.01                          |                |        |
|                 | 165     | 1.65                          | 1.77                          | 4.72                          |                |        |
| 802.11ax(HE40)  | 151     | 2.32                          | 2.29                          | 5.32                          | 29.8           | Pass   |
|                 | 159     | 2.18                          | 1.96                          | 5.08                          |                |        |
| 802.11ax(HE80)  | 155     | 2.3                           | 2.43                          | 5.38                          | 29.8           | Pass   |

## 4.4 Power Spectral Density

### Limit

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. <sup>note1</sup>

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. <sup>note1</sup>

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. <sup>note1</sup>

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. <sup>note1</sup>

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. <sup>note1, note2</sup>


Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 500KHz for U-NII 3 band.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to encompass the entire EBW.
5. Detector = Average.
6. Sweep time = auto couple.
7. Trace mode = Average hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

### Test Configuration



**Test Results**

Please refer to FCC Appendix RF Test Data for 5GWIFI

Total Power Spectral Density (dBm/MHz)= Power Spectral Density (dBm/MHz)+ Duty Factor (dB)

Remark: P.S.D(dBm/500KHz)= P.S.D(dBm/300KHz)+10 log (500 kHz/300KHz)+Duty factor.

RBW factor = 10 log (500 KHz / 300 KHz) = 2.22 dB

For MIMO:

**U-NII 1**

| Type            | Channel | Power Spectral Density [dBm/MHz] ANT1 | Power Spectral Density [dBm/MHz] ANT2 | Power Spectral Density [dBm/MHz] MIMO | Limit [dBm/MHz] | Result |
|-----------------|---------|---------------------------------------|---------------------------------------|---------------------------------------|-----------------|--------|
| 802.11n(HT20)   | 36      | -5.23                                 | -5.49                                 | -2.35                                 | 10.5            | PASS   |
|                 | 44      | -5.26                                 | -5.52                                 | -2.38                                 |                 |        |
|                 | 48      | -5.09                                 | -5.77                                 | -2.41                                 |                 |        |
| 802.11n(HT40)   | 38      | -8.10                                 | -8.67                                 | -5.37                                 |                 |        |
|                 | 46      | -8.05                                 | -8.52                                 | -5.27                                 |                 |        |
| 802.11ac(HT20)  | 36      | -5.40                                 | -5.62                                 | -2.50                                 |                 |        |
|                 | 44      | -5.77                                 | -5.74                                 | -2.74                                 |                 |        |
|                 | 48      | -4.80                                 | -5.72                                 | -2.23                                 |                 |        |
| 802.11ac(HT40)  | 38      | -8.32                                 | -8.57                                 | -5.43                                 |                 |        |
|                 | 46      | -7.89                                 | -8.77                                 | -5.30                                 |                 |        |
| 802.11ac (HT80) | 42      | -11.21                                | -11.25                                | -8.22                                 |                 |        |
| 802.11ax(HT20)  | 36      | -5.03                                 | -5.71                                 | -2.35                                 |                 |        |
|                 | 44      | -5.52                                 | -5.86                                 | -2.68                                 |                 |        |
|                 | 48      | -5.07                                 | -6.00                                 | -2.50                                 |                 |        |
| 802.11ax(HT40)  | 38      | -8.45                                 | -9.08                                 | -5.74                                 |                 |        |
|                 | 46      | -8.38                                 | -9.22                                 | -5.77                                 |                 |        |
| 802.11ax (HT80) | 42      | -11.37                                | -11.81                                | -8.57                                 |                 |        |

## U-NII 3

| Type            | Channel | Power Spectral Density<br>(dBm/500KHz)<br>ANT1 | Power Spectral Density<br>(dBm/500KHz)<br>ANT2 | Power Spectral Density<br>(dBm/500KHz)<br>MIMO | Limit<br>(dBm) | Result |
|-----------------|---------|------------------------------------------------|------------------------------------------------|------------------------------------------------|----------------|--------|
| 802.11n(HT20)   | 149     | -7.75                                          | -8.84                                          | -5.25                                          | 29.8           | Pass   |
|                 | 157     | -9.03                                          | -8.85                                          | -5.93                                          |                |        |
|                 | 165     | -8.94                                          | -9.27                                          | -6.09                                          |                |        |
| 802.11n(HT40)   | 151     | -11.60                                         | -11.77                                         | -8.67                                          |                |        |
|                 | 159     | -11.50                                         | -11.88                                         | -8.68                                          |                |        |
| 802.11ac(HT20)  | 149     | -8.61                                          | -9.00                                          | -5.79                                          |                |        |
|                 | 157     | -8.21                                          | -9.02                                          | -5.59                                          |                |        |
|                 | 165     | -9.05                                          | -8.98                                          | -6.00                                          |                |        |
| 802.11ac(HT40)  | 151     | -11.13                                         | -11.61                                         | -8.35                                          |                |        |
|                 | 159     | -11.33                                         | -11.92                                         | -8.60                                          |                |        |
| 802.11ac(HT80)  | 155     | -14.61                                         | -14.22                                         | -11.40                                         |                |        |
| 802.11ax(HT20)  | 149     | -8.25                                          | -9.28                                          | -5.72                                          |                |        |
|                 | 157     | -8.77                                          | -9.41                                          | -6.07                                          |                |        |
|                 | 165     | -9.01                                          | -9.86                                          | -6.40                                          |                |        |
| 802.11ax(HT40)  | 151     | -11.94                                         | -12.44                                         | -9.17                                          |                |        |
|                 | 159     | -11.96                                         | -12.37                                         | -9.15                                          |                |        |
| 802.11ax (HT80) | 155     | -14.65                                         | -14.42                                         | -11.52                                         |                |        |

#### 4.5 Emission Bandwidth (26dB Bandwidth)

##### Limit

No Limits for 26dBc Bandwidth

##### Test Procedure

The procedure for this method is as follows:

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max-hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

##### Test Configuration



##### Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI

#### 4.6 Minimum Emission Bandwidth (6dB Bandwidth)

##### Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

##### Test Procedure

The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

##### Test Configuration



##### Test Results


Please refer to FCC Appendix RF Test Data for 5GWIFI

## 4.7 Frequency Stability

### LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

### TEST CONFIGURATION



### TEST PROCEDURE

#### **Frequency Stability under Temperature Variations:**

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

#### **Frequency Stability under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

### TEST RESULTS

| Reference Frequency: 802.11ac channel=36 frequency=5180MHz |                  |                 |          |                              |
|------------------------------------------------------------|------------------|-----------------|----------|------------------------------|
| Voltage ( V )                                              | Temperature (°C) | Frequency error |          | Limit (ppm)                  |
|                                                            |                  | Hz              | ppm      |                              |
| AC 120                                                     | -30              | 110.70          | 0.021371 | Within the band of operation |
|                                                            | -20              | 174.54          | 0.033695 |                              |
|                                                            | -10              | 145.65          | 0.028118 |                              |
|                                                            | 0                | 146.39          | 0.028261 |                              |
|                                                            | 10               | 146.20          | 0.028224 |                              |
|                                                            | 20               | 99.73           | 0.019253 |                              |
|                                                            | 30               | 167.33          | 0.032303 |                              |
|                                                            | 40               | 129.20          | 0.024942 |                              |
|                                                            | 50               | 128.57          | 0.024820 |                              |
| AC 132                                                     | 25               | 195.61          | 0.037763 | Pass                         |
| AC 108                                                     | 25               | 118.53          | 0.022882 |                              |


| Reference Frequency: 802.11ac channel=149 frequency=5745MHz |                  |                 |          |                              |
|-------------------------------------------------------------|------------------|-----------------|----------|------------------------------|
| Voltage ( V )                                               | Temperature (°C) | Frequency error |          | Limit (ppm)                  |
|                                                             |                  | Hz              | ppm      |                              |
| AC 120                                                      | -30              | 135.42          | 0.023572 | Within the band of operation |
|                                                             | -20              | 129.58          | 0.022555 |                              |
|                                                             | -10              | 167.33          | 0.029126 |                              |
|                                                             | 0                | 169.44          | 0.029493 |                              |
|                                                             | 10               | 136.61          | 0.023779 |                              |
|                                                             | 20               | 144.52          | 0.025156 |                              |
|                                                             | 30               | 116.57          | 0.020291 |                              |
|                                                             | 40               | 168.64          | 0.029354 |                              |
|                                                             | 50               | 160.37          | 0.027915 |                              |
| AC 132                                                      | 25               | 150.80          | 0.026249 | Pass                         |
| AC 108                                                      | 25               | 129.69          | 0.022574 |                              |

## 4.8 On Time and Duty Cycle

### Standard Applicable

None; for reporting purpose only.

### TEST CONFIGURATION



### Test Procedures

- 1). Set the Centre frequency of the spectrum analyzer to the transmitting frequency;
- 2). Set the span=0MHz, RBW=8MHz, VBW=8MHz, Sweep time=Auto;
- 3). Detector = peak;
- 4). Trace mode = Single hold.

### TEST RESULTS

Please refer to FCC Appendix RF Test Data for 5GWIFI

## 4.9 Antenna Requirement

### Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):**


(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### Antenna Connected Construction

The PIFA Antenna maximum gain of antenna was ANT1: 4.06 dBi for 5180-5240MHz, 4.20 dBi for 5745-5825MHz, ANT2: 2.98 dBi for 5180-5240MHz, 2.01 dBi for 5745-5825MHz.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen CTA Testing Technology Co., Ltd. does not assume any responsibility.

## 5 Test Setup Photos of the EUT





## 6 Photos of the EUT

Reference to the test report No. CTA25091900501

\*\*\*\*\* End of Report \*\*\*\*\*