



Shenzhen Huaxin Information Technology Service Co., Ltd

101, R & D Building, No.3 guansheng 4th Road, Luhua Community, Guanhu Street, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-21018313 Http: //www.tecovo.net

TEST REPORT

Report No.: HX260624R004

FCC ID.....: 2BR3M-5ZNJL

IC.....: 34542-5ZNJL

Applicant.....: GUANG DONG REMAC SMART TECHNOLOGY CO.,LTD

Address.....: 10 - 1, 10th Floor, Building 1, Shunbei Ruichuang Intelligent Manufacturing Park, No. 10 Bihe Road, Malong Village, Beijiao Town, Foshan, Guangdong, 528000, China (Peoples Republic Of)

Manufacturer.....: GUANG DONG REMAC SMART TECHNOLOGY CO.,LTD

Address.....: 10 - 1, 10th Floor, Building 1, Shunbei Ruichuang Intelligent Manufacturing Park, No. 10 Bihe Road, Malong Village, Beijiao Town, Foshan, Guangdong, 528000, China (Peoples Republic Of)

Product Name.....: Smart Roller Shades P5

Trade Mark.....:  REZE FLOW REMAC AHOME

Model/Type reference.....: 5ZNJL

Listed Model(s): /

Standard.....: RSS-247 Issue 4

Date of receipt of test sample...: Jun. 09, 2026

Date of testing.....: Jun. 10, 2026 ~ Jul. 14, 2026

Date of issue.....: Jul. 14, 2026

Result.....: PASS

Compiled by:

(Printed name + signature) Terry Su



Approved by:

(Printed name + signature) Amy Zhai



Testing Laboratory Name.....: Shenzhen Huaxin Information Technology Service Co., Ltd

Address.....: 101, R & D Building, No.3 guansheng 4th Road, Luhua Community, Guanhu Street, Longhua District, Shenzhen, Guangdong, China

This test report shall not be copied in any form except with the written approval of our laboratory. The customer shall not claim that the product has been endorsed by Shenzhen Huaxin Information Technology Service Co., Ltd. based on this report, The test results in the report are only applicable to the samples tested. Without the signatures of the compiled engineer and the approver, the test report will be invalid. Any objection shall be submitted to Shenzhen Huaxin Information Technology Service Co., Ltd. within 15 days from the date of receiving the report. After this period, it will not be considered. The test report only corresponds to the test sample.



Table of Contents

Page

1. TEST SUMMARY	3
1.1. TEST STANDARDS	3
1.2. REPORT VERSION	3
1.3. TEST DESCRIPTION	4
1.4. TEST FACILITY	5
1.5. MEASUREMENT UNCERTAINTY	5
1.6. ENVIRONMENTAL CONDITIONS	6
2. GENERAL INFORMATION	7
2.1. CLIENT INFORMATION	7
2.2. GENERAL DESCRIPTION OF EUT	7
2.3. ACCESSORY EQUIPMENT INFORMATION	8
2.4. OPERATION STATE	9
2.5. MEASUREMENT INSTRUMENTS LIST	11
3. TEST ITEM AND RESULTS	13
3.1. CONDUCTED EMISSION	13
3.2. RADIATED EMISSION	16
3.3. RADIATED EMISSIONS RESTRICTED BAND	56
3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED)	81
3.5. DTS BANDWIDTH	100
3.6. MAXIMUM CONDUCTED OUTPUT POWER	114
3.7. POWER SPECTRAL DENSITY	116
3.8. DUTY CYCLE	124
3.9. ANTENNA REQUIREMENT	132



1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

[RSS-247 Issue 4](#): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

[ANSI C63.10-2020+COR. 1-2023+C63.10A-2024+ERRATA TO C63.10A-2024](#): American National Standard for Testing Unlicensed Wireless Devices.

[RSS-Gen Issue 5](#): General Requirements for Compliance of Radio Apparatus.

1.2. Report version

Revised No.	Date of issue	Description
01	Jul. 14, 2026	Original



1.3. Test Description

FCC Part 15 Subpart C (15.247) / RSS-247 Issue 4				
Test Item	Standard Section		Result	Test Engineer
	FCC	IC		
Antenna Requirement	15.203&15.247(b)(4)	RSS-Gen 6.8	Pass	Sain Liao
Conducted Emission	15.207	RSS-Gen 8.8	Pass	Ann Lu
Radiated Emissions Restricted Band and Radiated Spurious Emissions	15.205&15.209&15.247(d)	RSS-247 6.6 & RSS-Gen 8.10	Pass	Sain Liao
Conducted Band Edge and Spurious Emissions	15.247(d)	RSS-Gen 8.9 & RSS-Gen 8.10	Pass	Sain Liao
6dB Bandwidth	15.247(a)(2)	RSS-247 6.3.1 (a)	Pass	Sain Liao
Occupied Bandwidth	/	RSS-Gen 6.7	Pass	Sain Liao
Conducted Max Output Power	15.247(b)(3)	RSS-247 6.3.2	Pass	Sain Liao
Power Spectral Density	15.247(e)	RSS-247 6.3.1 (b)	Pass	Sain Liao
Transmitter Radiated Spurious	15.209&15.247(d)	RSS-247 6.6 & RSS-Gen 8.10	Pass	Sain Liao

Note: The measurement uncertainty is not included in the test result.



1.4. Test Facility

Shenzhen Huaxin Information Technology Service Co., Ltd

Add: 101, R & D Building, No.3 guansheng 4th Road, Luhuhu Community, Guanhu Street, Longhua District, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 6855.01

Shenzhen Huaxin Information Technology Service Co., Ltd EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Company Number: 31786, CAB Identifier: CN0147)

Shenzhen Huaxin Information Technology Service Co., Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 31786.

FCC (Registration No.: 932271, Designation Number CN1344)

Shenzhen Huaxin Information Technology Service Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC)Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration NO.: 932271.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Huaxin Information Technology Service Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for Shenzhen Huaxin Information Technology Service Co., Ltd



Test Items	Measurement Uncertainty	Notes
DTS Bandwidth	$\pm 3.70\%$	(1)
Maximum Conducted Output Power	$\pm 0.60\text{dB}$	(1)
Maximum Power Spectral Density Level	$\pm 0.46\text{dB}$	(1)
Band-edge Compliance	$\pm 4.40\text{dB}$	(1)
Conducted Spurious Emissions	$\pm 1.40\text{dB}$	(1)
Conducted Emissions 9kHz~30MHz	$\pm 3.10\text{dB}$	(1)
Radiated Emissions 9kHz~30MHz	$\pm 3.62\text{dB}$	(1)
Radiated Emissions 30~1000MHz	$\pm 4.63\text{dB}$	(1)
Radiated Emissions 1~18GHz	$\pm 4.40\text{dB}$	(1)
Radiated Emissions 18~40GHz	$\pm 4.40\text{dB}$	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.6. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	21°C ~ 27°C
Relative Humidity:	40% ~ 60%
Air Pressure:	101kPa



2. GENERAL INFORMATION

2.1. Client Information

Applicant:	GUANG DONG REMAC SMART TECHNOLOGY CO.,LTD
Address:	10 - 1, 10th Floor, Building 1, Shunbei Ruichuang Intelligent Manufacturing Park, No. 10 Bihe Road, Malong Village, Beijiao Town, Foshan, Guangdong, 528000, China (Peoples Republic Of)
Manufacturer:	GUANG DONG REMAC SMART TECHNOLOGY CO.,LTD
Address:	10 - 1, 10th Floor, Building 1, Shunbei Ruichuang Intelligent Manufacturing Park, No. 10 Bihe Road, Malong Village, Beijiao Town, Foshan, Guangdong, 528000, China (Peoples Republic Of)

2.2. General Description of EUT

Product Name:	Smart Roller Shades P5
Trade Mark:	 REZE FLOW REMAC AHOME
Model/Type reference:	5ZNJL
Listed Model(s):	/
Power supply:	AC 100-240V 50/60Hz
Hardware version:	WIFI module-V1.1 260204
Software version:	WF1.0.8
Samples No.:	YP260709-E001-1
WIFI Specification	
Modulation:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/ n/ ax: OFDM(BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Operation frequency:	802.11b/ g/ n(HT20)/ ax(HE20): 2412MHz~2462MHz 802.11n(HT40)/ ax(HE40): 2422MHz~2452MHz
Channel number:	802.11b/ g/ n(HT20): 11 Channels 802.11n(HT40)/ ax(HE40): 7 Channels
Channel separation:	5MHz
Antenna type:	FPC Antenna
Antenna gain:	3.73dBi



2.3. Accessory Equipment information

Equipment Information			
Name	Model	S/N	Manufacturer
Notebook	MCLG-16	2NZBB24117801340	HUAWEI
Cable Information			
Name	Shielded Type	Ferrite Core	Length
AC In Cable	Without	Without	200cm
Test Software Information			
Name	Versions	/	/
Wifi_Test_Tool_V1.9.0	V1.9.0	/	/



2.4. Operation state

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing, This product does not support MRU, but only supports SU.

Operation Frequency List:

Channel	Frequency (MHz)
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

Note: CH 01~CH 11 for 802.11b/g/n(HT20)/ax(HE20), CH 03~CH 09 for 802.11n(HT40)/ax(HE40).

Power setting

Test Mode	Frequency [MHz]	Power setting (Value)
802.11b	2412	20
	2437	20
	2462	19
802.11g	2412	58
	2437	57
	2462	56
802.11n(HT20)	2412	59
	2437	57
	2462	56
802.11ax(HE20)	2412	60
	2437	59
	2462	59
802.11n(HT40)	2422	57
	2437	56
	2452	55
802.11ax(HE40)	2422	58
	2437	57
	2452	56



RU Type

Bandwidth	20MHz BW	40MHz BW
RU Type	242-tone RU	484-tone RU

Data Rated

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Mode	Data rate (worst mode)
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)/ (HT40)	HT-MCS0
802.11ax(HE20)/ (HE40)	HE-MCS0

Test mode

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.



2.5. Measurement Instruments List

RF Test System - SRD					
Item	Test Equipment	Manufacturer	Model No.	Versions/ Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY51280803	Apr. 08, 2027
2	Wideband Radio Communication Tester	R&S	CMW500	157763	Apr. 08, 2027
3	MXG Vector Signal Generator	Agilent	N5182A	101795	Apr. 08, 2027
4	EXG Analog Signal Generator	Agilent	N5181A	MY47421151	Apr. 08, 2027
5	RF Sensor Unit	Techy	TR1029-2	20220428P009	Apr. 08, 2027
6	High and low temperature test chamber	Asprey	LX-225L	2020091401	Apr. 08, 2027
7	SRD Test Software	TACHOY	RTS	V1.0.0	/
8	2G/3G/4G Test Software	TST	TST-PASS	V2.0	/

Radiated emission					
Item	Test Equipment	Manufacturer	Model No.	Versions/ Serial No.	Calibrated until
1	EMI spectrum receiver	R&S	ESR7	102543	Apr. 09, 2027
2	9*6*6 anechoic chamber	Mao Rui	9*6*6	/	Apr. 09, 2028
3	Spectrum analyzer	R&S	FSV40-N	101795	Apr. 09, 2027
4	Preamplifier	Agilent	8449B	3008A00551	Apr. 08, 2027
5	Preamplifier	HP	8447D	1616A02061	Apr. 09, 2027
6	Preamplifier	SKET	LNPA1840G-50	SK2019040302	Apr. 09, 2027
7	Horn Antenna	SCHWARZBEC K	BBHA9170	00369	Apr. 10, 2028
8	Horn Antenna	A. H. System, Inc	SAS-571	915	Apr. 10, 2028
9	Trilog-Broadband Antenna	SCHWARZBEC K	VULB 9168	01318	Apr. 10, 2028
10	Loop Antenna	SCHWARZBEC K	FMZB1519B	00128	Apr. 08, 2027
11	6dB Fixed Attenuator	SKET	AP_DC01G-2W-N-6 dB	SK2021012803	Apr. 08, 2027
12	RF Cable 0.009~1000MHz	Langjingkeji	N/J-NJ-RG58(1G) 9m	/	Apr. 09, 2027
13	RF Cable 1000~18000MHz	Langjingkeji	N/J-SMAAJ-406(18G) 9m	/	Apr. 09, 2027
14	RF Cable	Langjingkeji	2.92/M-2.92/M-0.5M	/	Apr. 12, 2027
15	RF Cable 18000~40000MHz	Langjingkeji	2.92/M-2.92/M-3M	/	Apr. 12, 2027
16	Test Software	SKET	EMC-I	V1.4.0.1	/
17	Test Software	FARA	EZ-EMC	FA-03A3	/

Conducted emission					
Item	Test Equipment	Manufacturer	Model No.	Versions/ Serial No.	Calibrated until
1	LISN	R&S	ENV216	101291	Apr. 09, 2027
2	LISN	R&S	ESH3-Z5	894981/024	Apr. 09, 2027



3	EMI Test Receiver	R&S	ESR7	102543	Apr. 09, 2027
5	RF Cable	Langjingkeji	N/J-NJ-RG58(1G) 10m	/	Apr. 09, 2027
6	Test Software	SKET	EMC-I	V1.4.0.1	/

Note: 1. The Cal. Interval was one year.

2. The cable loss has calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Conducted Emission


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207/ RSS-Gen 8.8:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration




Test Procedure

1. The EUT was setup according to ANSI C63.10-2020+COR. 1-2023+C63.10A-2024+ERRATA TO C63.10A-2024 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.


**Test Mode:**

Please refer to the clause 2.4.

Test Results



Test Voltage:	AC 120V/60 Hz
Test Mode:	802.11b Mode 2412MHz
Terminal:	Neutral



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector	Polar
1	442.000kHz	22.90	9.80	32.70	57.02	-24.32	QP	N
2	162.000kHz	26.95	9.70	36.65	65.36	-28.71	QP	N
3	194.000kHz	22.89	9.70	32.59	63.86	-31.27	QP	N
4	1.942MHz	14.59	10.00	24.59	56.00	-31.41	QP	N
5	2.322MHz	11.88	10.00	21.88	56.00	-34.12	QP	N
6	27.194MHz	6.53	14.40	20.93	60.00	-39.07	QP	N
7	446.000kHz	17.98	9.80	27.78	46.95	-19.17	AV	N
8	1.674MHz	11.98	9.90	21.88	46.00	-24.12	AV	N
9	326.000kHz	9.96	9.80	19.76	49.55	-29.79	AV	N
10	29.278MHz	2.14	14.90	17.04	50.00	-32.96	AV	N
11	230.000kHz	8.75	9.80	18.55	52.45	-33.90	AV	N
12	12.942MHz	1.77	11.60	13.37	50.00	-36.63	AV	N

Emission Level= Read Level+ Correct Factor



3.2. Radiated Emission

Limit


FCC CFR Title 47 Part 15 Subpart C Section 15.209/ RSS-Gen 8.9:

Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m).


Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10-2020+COR. 1-2023+C63.10A-2024+ERRATA TO C63.10A-2024
 2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
 5. Set to the maximum power setting and enable the EUT transmit continuously.
 6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured
 - (2) Below 30 MHz:
9kHz – 150kHz, RBW=200Hz, VBW $\geq$ RBW, Sweep=auto, Detector function=peak, Trace=max hold;
150kHz – 30MHz, RBW=9kHz, VBW $\geq$ RBW, Sweep=auto, Detector function=peak, Trace=max hold; If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) 30 MHz - 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (4) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW $\geq$ 1/T Peak detector for Average value.
- Note 1: For the 1/T& Duty Cycle please refer to clause 3.8 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result

9 KHz~30 MHz


From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



30MHz-1GHz

Ant. Pol.	Horizontal
Test Mode:	802.11b Mode 2412MHz
Remark:	Only worse case is reported




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Delta dB	Detector	Polar
1*	74.741MHz	12.7	10.2	22.9	40.0	-17.1	QP	Hor
2*	113.663MHz	10.6	11.9	22.5	43.5	-21.0	QP	Hor
3*	162.648MHz	8.5	14.1	22.6	43.5	-20.9	QP	Hor
4*	206.298MHz	12.8	10.6	23.4	43.5	-20.1	QP	Hor
5*	548.829MHz	11.6	19.3	30.9	46.0	-15.1	QP	Hor
6*	913.670MHz	11.9	24.3	36.2	46.0	-9.8	QP	Hor

Remarks:

- 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- 2.Margin value = Level -Limit value



Ant. Pol.	Vertical
Test Mode:	802.11b Mode 2412MHz
Remark:	Only worse case is reported



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Delta dB	Detector	Polar
1*	33.516MHz	11.3	13.3	24.6	40.0	-15.4	QP	Ver
2*	83.956MHz	15.1	9.3	24.4	40.0	-15.6	QP	Ver
3*	113.178MHz	13.1	11.7	24.8	43.5	-18.7	QP	Ver
4*	121.544MHz	14.9	12.2	27.1	43.5	-16.4	QP	Ver
5*	547.010MHz	11.7	19.3	31.0	46.0	-15.0	QP	Ver
6*	903.243MHz	12.2	24.1	36.3	46.0	-9.7	QP	Ver


Remarks:

- Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- Margin value = Level -Limit value



1GHz -3GHz

Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1596.812	46.16	-8.57	37.59	74.00	-36.41	peak
2	1596.812	33.88	-8.57	25.31	54.00	-28.69	AVG
3	1861.282	46.19	-8.00	38.19	74.00	-35.81	peak
4	1861.282	33.19	-8.00	25.19	54.00	-28.81	AVG
5	2125.029	47.95	-5.51	42.44	74.00	-31.56	peak
6 *	2125.029	33.18	-5.51	27.67	54.00	-26.33	AVG


Remarks:


1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor


2. Margin value = Level - Limit value















Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1593.088	45.61	-8.59	37.02	74.00	-36.98	peak
2	1593.088	34.18	-8.59	25.59	54.00	-28.41	AVG
3	2390.761	52.89	-3.28	49.61	74.00	-24.39	peak
4	2390.761	39.25	-3.28	35.97	54.00	-18.03	AVG
5	2582.226	53.19	-4.76	48.43	74.00	-25.57	peak
6 *	2582.226	46.00	-4.76	41.24	54.00	-12.76	AVG


Remarks:


1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value














3GHz -18GHz

Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4824.237	54.40	-17.65	36.75	74.00	-37.25	peak
2	4824.237	49.09	-17.65	31.44	54.00	-22.56	AVG
3	6431.642	51.91	-12.25	39.66	74.00	-34.34	peak
4	6431.642	45.39	-12.25	33.14	54.00	-20.86	AVG
5	17879.462	44.49	7.00	51.49	74.00	-22.51	peak
6 *	17879.462	32.55	7.00	39.55	54.00	-14.45	AVG


Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value











Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	6756.488	47.58	-11.65	35.93	74.00	-38.07	peak
2	6756.488	39.70	-11.65	28.05	54.00	-25.95	AVG
3	11150.943	45.11	-4.31	40.80	74.00	-33.20	peak
4	11150.943	33.69	-4.31	29.38	54.00	-24.62	AVG
5	17851.452	42.88	6.63	49.51	74.00	-24.49	peak
6 *	17851.452	32.46	6.63	39.09	54.00	-14.91	AVG


Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value






Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4843.725	50.94	-17.58	33.36	74.00	-40.64	peak
2	4843.725	45.52	-17.58	27.94	54.00	-26.06	AVG
3	6459.070	49.40	-12.18	37.22	74.00	-36.78	peak
4	6459.070	43.55	-12.18	31.37	54.00	-22.63	AVG
5	14517.584	43.42	-1.29	42.13	74.00	-31.87	peak
6 *	14517.584	33.11	-1.29	31.82	54.00	-22.18	AVG


Remarks:


1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value














18GHz -25GHz

Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20483.250	58.39	-19.44	38.95	74.00	-35.05	peak
2	20483.250	48.05	-19.44	28.61	54.00	-25.39	AVG
3	21819.375	57.86	-19.12	38.74	74.00	-35.26	peak
4	21819.375	46.87	-19.12	27.75	54.00	-26.25	AVG
5	24290.375	57.58	-17.46	40.12	74.00	-33.88	peak
6 *	24290.375	46.41	-17.46	28.95	54.00	-25.05	AVG


Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value



Ant. Pol.	Vertical
Test Mode:	TX 802.11b Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20931.250	57.69	-18.77	38.92	74.00	-35.08	peak
2 *	20931.250	48.11	-18.77	29.34	54.00	-24.66	AVG
3	22519.375	57.73	-19.16	38.57	74.00	-35.43	peak
4	22519.375	47.13	-19.16	27.97	54.00	-26.03	AVG
5	24496.000	56.37	-17.01	39.36	74.00	-34.64	peak
6	24496.000	46.34	-17.01	29.33	54.00	-24.67	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20928.625	57.08	-18.79	38.29	74.00	-35.71	peak
2	20928.625	47.54	-18.79	28.75	54.00	-25.25	AVG
3	23145.875	57.19	-18.73	38.46	74.00	-35.54	peak
4	23145.875	46.51	-18.73	27.78	54.00	-26.22	AVG
5	24578.250	56.21	-17.01	39.20	74.00	-34.80	peak
6 *	24578.250	46.09	-17.01	29.08	54.00	-24.92	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Vertical
Test Mode:	TX 802.11b Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	19659.000	59.41	-20.90	38.51	74.00	-35.49	peak
2	19659.000	49.08	-20.90	28.18	54.00	-25.82	AVG
3	21826.375	57.83	-19.12	38.71	74.00	-35.29	peak
4	21826.375	46.88	-19.12	27.76	54.00	-26.24	AVG
5	23914.125	56.43	-17.66	38.77	74.00	-35.23	peak
6 *	23914.125	46.74	-17.66	29.08	54.00	-24.92	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18991.375	58.79	-20.61	38.18	74.00	-35.82	peak
2	18991.375	48.50	-20.61	27.89	54.00	-26.11	AVG
3	21018.750	56.83	-18.52	38.31	74.00	-35.69	peak
4	21018.750	47.21	-18.52	28.69	54.00	-25.31	AVG
5	24525.750	56.17	-17.00	39.17	74.00	-34.83	peak
6 *	24525.750	45.95	-17.00	28.95	54.00	-25.05	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Vertical
Test Mode:	TX 802.11b Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	19354.500	59.22	-20.82	38.40	74.00	-35.60	peak
2	19354.500	48.56	-20.82	27.74	54.00	-26.26	AVG
3	21263.750	57.23	-18.82	38.41	74.00	-35.59	peak
4 *	21263.750	46.82	-18.82	28.00	54.00	-26.00	AVG
5	23655.125	56.59	-18.29	38.30	74.00	-35.70	peak
6	23655.125	45.84	-18.29	27.55	54.00	-26.45	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	21047.625	57.59	-18.56	39.03	74.00	-34.97	peak
2	21047.625	47.30	-18.56	28.74	54.00	-25.26	AVG
3	22636.625	57.80	-18.93	38.87	74.00	-35.13	peak
4	22636.625	46.58	-18.93	27.65	54.00	-26.35	AVG
5	24132.000	56.48	-17.48	39.00	74.00	-35.00	peak
6 *	24132.000	46.68	-17.48	29.20	54.00	-24.80	AVG


Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value



Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	19974.875	58.99	-20.18	38.81	74.00	-35.19	peak
2	19974.875	48.04	-20.18	27.86	54.00	-26.14	AVG
3	21367.000	57.44	-18.75	38.69	74.00	-35.31	peak
4 *	21367.000	46.81	-18.75	28.06	54.00	-25.94	AVG
5	23248.250	57.28	-18.75	38.53	74.00	-35.47	peak
6	23248.250	46.60	-18.75	27.85	54.00	-26.15	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20543.625	58.20	-19.42	38.78	74.00	-35.22	peak
2	20543.625	47.95	-19.42	28.53	54.00	-25.47	AVG
3	22892.125	57.66	-18.70	38.96	74.00	-35.04	peak
4	22892.125	46.21	-18.70	27.51	54.00	-26.49	AVG
5	24607.125	55.66	-17.02	38.64	74.00	-35.36	peak
6 *	24607.125	45.82	-17.02	28.80	54.00	-25.20	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20500.750	58.42	-19.40	39.02	74.00	-34.98	peak
2	20500.750	47.83	-19.40	28.43	54.00	-25.57	AVG
3	22640.125	57.42	-18.92	38.50	74.00	-35.50	peak
4	22640.125	46.91	-18.92	27.99	54.00	-26.01	AVG
5	24597.500	55.75	-17.02	38.73	74.00	-35.27	peak
6 *	24597.500	46.09	-17.02	29.07	54.00	-24.93	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2452MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20539.250	57.75	-19.41	38.34	74.00	-35.66	peak
2	20539.250	47.85	-19.41	28.44	54.00	-25.56	AVG
3	21826.375	56.79	-19.12	37.67	74.00	-36.33	peak
4	21826.375	47.15	-19.12	28.03	54.00	-25.97	AVG
5	24216.875	56.86	-17.53	39.33	74.00	-34.67	peak
6 *	24216.875	46.01	-17.53	28.48	54.00	-25.52	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2452MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	19935.500	59.17	-20.30	38.87	74.00	-35.13	peak
2	19935.500	48.22	-20.30	27.92	54.00	-26.08	AVG
3	22615.625	57.43	-18.97	38.46	74.00	-35.54	peak
4	22615.625	46.35	-18.97	27.38	54.00	-26.62	AVG
5	24561.625	55.90	-17.01	38.89	74.00	-35.11	peak
6 *	24561.625	45.60	-17.01	28.59	54.00	-25.41	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value


3.3. Radiated Emissions Restricted Band

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d)/ RSS-Gen 8.10:

Restricted Frequency Band (MHz)	(dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

Test Configuration



Test Procedure


1. The EUT was setup and tested according to ANSI C63.10-2020+COR. 1-2023+C63.10A-2024+ERRATA TO C63.10A-2024 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2020+COR. 1-2023+C63.10A-2024+ERRATA TO C63.10A-2024 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.


Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 3.8 Duty Cycle.


Test Mode


Please refer to the clause 2.4.


Test Results







































































3.4. Band edge and Spurious Emissions (Conducted)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d)/ RSS-247 6.6: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Test Configuration



Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW $\geq$ RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test Mode

Please refer to the clause 2.4.



Test Results

**(1) Band edge Conducted Test**

Test Mode	Test Frequency	Ref Level[dBm]	Result[dBm]	Limit[dBm]	Verdict
802.11b	2412	7.262	-41.834	-22.738	PASS
	2462	7.185	-46.355	-22.815	PASS
802.11g	2412	4.798	-30.369	-25.202	PASS
	2462	5.944	-39.753	-24.056	PASS
802.11n(HT20)	2412	5.476	-33.250	-24.524	PASS
	2462	6.070	-43.826	-23.930	PASS
802.11ax(HE20)	2412	5.730	-31.524	-24.270	PASS
	2462	6.532	-40.734	-23.468	PASS
802.11n(HT40)	2422	2.554	-36.459	-27.446	PASS
	2452	2.672	-36.646	-27.328	PASS
802.11ax(HE40)	2422	2.928	-31.037	-27.072	PASS
	2452	3.027	-34.344	-26.973	PASS





802.11b_2412



802.11b_2462



802.11g_2412



802.11g_2462