

# TEST REPORT

**Report No.:** 8333EU012703W3

**Applicant:** JAMO HOLDING LIMITED

**Address:** UNIT 2 UG/F BLOCK E WAH LOK INDUSTRIAL  
CENTRE 31 - 35 SHAN MEI STREET SHA TIN NT,  
HONGKONG, China

**Product Name:** HYG Reflect

**Model No.:** Reflect

**Trademark:** Jamo

**FCC ID:** 2BR3Z-REFLECT

**Test Standard(s):** 47 CFR Part 1 Subpart I Section 1.1310  
47 CFR Part 2, Subpart J, Section 2.1091

**Test Result:** Pass

**Date of Receipt:** Aug. 27, 2025

**Test Date:** Aug. 27, 2025 – Oct. 12, 2025


**Date of Issue:** Dec. 29, 2029

**ISSUED BY:**

SHENZHEN EU TESTING LABORATORY LIMITED



**Prepared by:**



Mikey Zhu/ Engineer

**Reviewed and Approved by:**



Sally Zhang/ Manager

## Revision Record

| Report Version | Issued Date   | Description | Status |
|----------------|---------------|-------------|--------|
| V0             | Dec. 29, 2029 | Original    | Valid  |
|                |               |             |        |
|                |               |             |        |



## Table of Contents

|         |                                     |    |
|---------|-------------------------------------|----|
| 1       | COVER PAGE.....                     | 1  |
| 2       | GENERAL INFORMATION .....           | 4  |
| 2.1     | APPLICANT INFORMATION.....          | 4  |
| 2.2     | MANUFACTURER INFORMATION.....       | 4  |
| 2.3     | FACTORY INFORMATION.....            | 4  |
| 2.4     | GENERAL DESCRIPTION OF E.U.T.....   | 4  |
| 2.5     | TECHNICAL INFORMATION OF E.U.T..... | 5  |
| 3       | TEST SUMMARY .....                  | 6  |
| 3.1     | TEST STANDARD .....                 | 6  |
| 3.2     | TEST VERDICT.....                   | 6  |
| 3.3     | TEST LABORATORY .....               | 6  |
| 4       | TEST CONFIGURATION.....             | 7  |
| 4.1     | TEST ENVIRONMENT .....              | 7  |
| 4.2     | TEST EQUIPMENT .....                | 7  |
| 4.3     | TEST MODE .....                     | 7  |
| 4.4     | MEASUREMENT UNCERTAINTY .....       | 7  |
| 5       | TEST METHODOLOGY.....               | 8  |
| 5.1     | REFERENCE EVALUATION METHOD .....   | 8  |
| 5.2     | TEST SETUP.....                     | 9  |
| 5.3     | EVALUATION RESULT .....             | 10 |
| ANNEX A | TEST SETUP PHOTOS .....             | 11 |

## 2 General Information

### 2.1 Applicant Information

|           |                                                                                                   |
|-----------|---------------------------------------------------------------------------------------------------|
| Applicant | JAMO HOLDING LIMITED                                                                              |
| Address   | UNIT 2 UG/F BLOCK E WAH LOK INDUSTRIAL CENTRE 31 - 35 SHAN MEI STREET SHA TIN NT, HONGKONG, China |

### 2.2 Manufacturer Information

|              |                                                                                                   |
|--------------|---------------------------------------------------------------------------------------------------|
| Manufacturer | JAMO HOLDING LIMITED                                                                              |
| Address      | UNIT 2 UG/F BLOCK E WAH LOK INDUSTRIAL CENTRE 31 - 35 SHAN MEI STREET SHA TIN NT, HONGKONG, China |

### 2.3 Factory Information

|         |                                                                                                   |
|---------|---------------------------------------------------------------------------------------------------|
| Factory | JAMO HOLDING LIMITED                                                                              |
| Address | UNIT 2 UG/F BLOCK E WAH LOK INDUSTRIAL CENTRE 31 - 35 SHAN MEI STREET SHA TIN NT, HONGKONG, China |

### 2.4 General Description of E.U.T.

|                                      |                                                                                                                                                  |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name                         | HYG Reflect                                                                                                                                      |
| Model No. Under Test                 | Reflect                                                                                                                                          |
| List Model No.                       | N/A                                                                                                                                              |
| Description of Model differentiation | N/A                                                                                                                                              |
| Rating(s)                            | Input: 12.0V---3.5A (Adapter Input: 100-240V~, 50/60Hz, 1.5A;<br>Output: 12.0V---3.5A, 42.0W)<br>Wireless Charging Output: 15W Max.              |
| Adapter                              | Model No.: RYZ909C120350VU<br>Input: 100-240V~, 50/60Hz, 1.5A<br>Output: 12.0V---3.5A, 42.0W<br>Manufacturer: SHENZHEN RUI YU TECHNOLOGY CO.,LTD |
| Product Type                         | <input checked="" type="checkbox"/> Mobile<br><input type="checkbox"/> Portable<br><input type="checkbox"/> Fix Location                         |
| Test Sample No.                      | -1/2(Normal Sample), -2/2(Engineering Sample)                                                                                                    |
| Hardware Version                     | V00                                                                                                                                              |
| Software Version                     | MCU: V0.0.3 BT: V 52                                                                                                                             |
| Remark                               | For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.                                |

## 2.5 Technical Information of E.U.T.

|                                   |                                                          |
|-----------------------------------|----------------------------------------------------------|
| Network and Wireless Connectivity | Bluetooth (BDR+EDR)<br>Wireless Power Transmission (WPT) |
|-----------------------------------|----------------------------------------------------------|

The requirement for the following technical information of the EUT was tested in this report:

|                     |                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Technology          | <b>WPT</b>                                                                                                                             |
| Operating Frequency | 110.1-205KHz                                                                                                                           |
| Modulation Type     | FSK                                                                                                                                    |
| Antenna Type        | Inductive Loop Coil Antenna                                                                                                            |
| Antenna Gain(Peak)  | 0 dBi                                                                                                                                  |
| Remark              | The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant. |

### 3 Test Summary

#### 3.1 Test Standard

The tests were performed according to following standards:

| No. | Identity                                 | Document Title                                                                         |
|-----|------------------------------------------|----------------------------------------------------------------------------------------|
| 1   | 47 CFR Part 1 Subpart I Section 1.1310   | Radio frequency radiation exposure limits.                                             |
| 2   | 47 CFR Part 2, Subpart J, Section 2.1091 | Radiofrequency radiation exposure evaluation: mobile devices                           |
| 3   | KDB 680106 D01v04                        | RF exposure consideration for low power consumer wireless power transfer applications. |

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

#### 3.2 Test Verdict

| No. | Description            | FCC Part No.                                                           | Verdict | Remark |
|-----|------------------------|------------------------------------------------------------------------|---------|--------|
| 1   | RF Exposure Evaluation | FCC 1.1310<br>FCC 2.1091<br>KDB 680106 D01 Wireless Power Transfer v04 | Pass    | --     |

#### 3.3 Test Laboratory

|                               |                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Test Laboratory               | Shenzhen EU Testing Laboratory Limited                                                                                 |
| Address                       | 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China |
| Designation Number            | CN1368                                                                                                                 |
| Test Firm Registration Number | 952583                                                                                                                 |

## 4 Test Configuration

### 4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

|                            |                         |                          |
|----------------------------|-------------------------|--------------------------|
| Relative Humidity          | 30% to 60%              |                          |
| Atmospheric Pressure       | 86 kPa to 106 kPa       |                          |
| Temperature                | NT (Normal Temperature) | +15°C to +35°C           |
| Working Voltage of the EUT | NV (Normal Voltage)     | 120VAC, 60Hz for adapter |

### 4.2 Test Equipment

| Equipment                                    | Manufacturer | Model No | Serial No | Cal Date   | Cal Due Date |
|----------------------------------------------|--------------|----------|-----------|------------|--------------|
| Electric and Magnetic Field Probe - Analyzer | Narda        | EHP-200A | EE-405    | 2025/02/14 | 2026/02/13   |

### 4.3 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned bellow was evaluated respectively.

| No. | Description                     | Remark |
|-----|---------------------------------|--------|
| TM1 | Adapter + Wireless Output (15W) |        |
| TM2 | Standby                         |        |

Note:

1. EUT supports all empty load, half load, full load mode were tested, so the all conditions have been tested. It is found that TM1 full load is the worst mode, and the data in the report only reflects the worst mode.

### 4.4 Measurement Uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Test Item                               | Measurement Uncertainty |
|-----------------------------------------|-------------------------|
| Magnetic field measurements(3kHz~10MHz) | ±14.6%                  |
| Electric field measurements(3kHz~10MHz) | ±17.3%                  |

## 5 Test Methodology

### 5.1 Reference Evaluation Method

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

**Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)**


| Frequency range<br>(MHz)                                       | Electric field strength<br>(V/m) | Magnetic field strength<br>(A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |
|----------------------------------------------------------------|----------------------------------|----------------------------------|----------------------------------------|-----------------------------|
| <b>(A) Limits for Occupational/Controlled Exposures</b>        |                                  |                                  |                                        |                             |
| 0.3-3.0                                                        | 614                              | 1.63                             | *(100)                                 | 6                           |
| 3.0-30                                                         | 1842/f                           | 4.89/f                           | *(900/f <sup>2</sup> )                 | 6                           |
| 30-300                                                         | 61.4                             | 0.163                            | 1.0                                    | 6                           |
| 300-1500                                                       | /                                | /                                | f/300                                  | 6                           |
| 1500-100,000                                                   | /                                | /                                | 5                                      | 6                           |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                                  |                                  |                                        |                             |
| 0.3-1.34                                                       | 614                              | 1.63                             | *(100)                                 | 30                          |
| 1.34-30                                                        | 824/f                            | 2.19/f                           | *(180/f <sup>2</sup> )                 | 30                          |
| 30-300                                                         | 27.5                             | 0.073                            | 0.2                                    | 30                          |
| 300-1500                                                       | /                                | /                                | f/1500                                 | 30                          |
| 1500-100,000                                                   | /                                | /                                | 1.0                                    | 30                          |

F=frequency in MHz

\*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

## 5.2 Test Setup



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 20cm measured from the center of the probe(s) to the edge of the device.

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (20cm) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v04.

### 5.3 Evaluation Result

Test Condition: Test Mode 1 operating with client device (1% battery status of client device)

| Test Position | E-field (V/m) |       |                 | H-field (A/m) |       |                 |
|---------------|---------------|-------|-----------------|---------------|-------|-----------------|
|               | Measurement   | Limit | 50% Limit (V/m) | Measurement   | Limit | 50% Limit (A/m) |
| Top           | 3.9725        | 614   | 307             | 0.2184        | 1.63  | 0.815           |
| Bottom        | 4.1316        |       |                 | 0.1392        |       |                 |
| Front         | 2.7653        |       |                 | 0.0448        |       |                 |
| Rear          | 4.8634        |       |                 | 0.0536        |       |                 |
| Left          | 1.6583        |       |                 | 0.1336        |       |                 |
| Right         | 1.6916        |       |                 | 0.1344        |       |                 |

Test Condition: Test Mode 1 operating with client device (50% battery status of client device)

| Test Position | E-field (V/m) |       |                 | H-field (A/m) |       |                 |
|---------------|---------------|-------|-----------------|---------------|-------|-----------------|
|               | Measurement   | Limit | 50% Limit (V/m) | Measurement   | Limit | 50% Limit (A/m) |
| Top           | 5.1854        | 614   | 307             | 0.2176        | 1.63  | 0.815           |
| Bottom        | 4.5119        |       |                 | 0.1968        |       |                 |
| Front         | 3.1701        |       |                 | 0.0600        |       |                 |
| Rear          | 3.4229        |       |                 | 0.0296        |       |                 |
| Left          | 3.8540        |       |                 | 0.0540        |       |                 |
| Right         | 2.5940        |       |                 | 0.0648        |       |                 |

Test Condition: Test Mode 1 operating with client device (99% battery status of client device)

| Test Position | E-field (V/m) |       |                 | H-field (A/m) |       |                 |
|---------------|---------------|-------|-----------------|---------------|-------|-----------------|
|               | Measurement   | Limit | 50% Limit (V/m) | Measurement   | Limit | 50% Limit (A/m) |
| Top           | 4.3570        | 614   | 307             | 0.1608        | 1.63  | 0.815           |
| Bottom        | 3.3919        |       |                 | 0.1432        |       |                 |
| Front         | 0.9533        |       |                 | 0.0312        |       |                 |
| Rear          | 4.0827        |       |                 | 0.1840        |       |                 |
| Left          | 3.9965        |       |                 | 0.1888        |       |                 |
| Right         | 2.8114        |       |                 | 0.1904        |       |                 |


Note 1: E-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT.

Note 2: H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT.

## ANNEX A TEST SETUP PHOTOS

### PHOTO 1

Test Position: Top



## STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---