



EMC TEST REPORT

Product Name: RADIO

Trade mark: KAITO

Model No.: KA600, KA600L, HQ600

FCC ID No.: 2BR4H-KA600

Report No.: CTB25091518105E01

Applicant: Kaito Electronics, Inc.

Address: 5185 Cliffwood Drive, Montclair, CA 91763, USA

Manufacturer: SHENZHEN GARRINI ELECTRONICS CO., LTD

Address: 1906, Block 2, Jiazhou Hao Yuan, South Bin He Da Dao, Futian, Shenzhen, China

Prepared by: Shenzhen CTB Testing Technology Co., Ltd.

Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China

Sample No.: 240925022-3X

Date of Receipt: Sep. 25, 2024

Date of Test(s): Sep. 25, 2024 ~ Sep. 27, 2024

Date of Issue: Sep. 25, 2025

Test Standard(s): 47 CFR Part 15 Subchapter B, ANSI C63.4: 2014

Test Result: Pass

All test data come from the report of No.: CTB240929023EX

In the configuration tested, the EUT complied with the standards specified above.

Compiled by:

Reviewed by:

Approved by:

Blake Cai

Blake Cai

Bin Mei

Bin Mei



Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "★" indicates the testing items were fulfilled by subcontracted lab. "×" indicates the items are not in CNAS accreditation scope.

Table of Contents

1. Description of version	3
2. Test summary	4
3. Measurement uncertainty	5
4. General information	6
4.1. Description of EUT	6
4.2. Description of accessory device	6
4.3. Test conditions	6
4.4. Block diagram of EUT configuration	7
4.5. Operating condition of EUT	7
5. List of Test and Measurement Instruments	8
6. Conducted Emission	10
6.1. Limit	10
6.2. Test setup	10
6.3. EMI test receiver setup	10
6.4. Test procedure	10
6.5. Test results	11
7. Radiated emissions	13
7.1. Limit	13
7.2. Test setup	13
7.3. EMI test receiver setup and spectrum analyzer setup	14
7.4. Test procedure	14
7.5. Corrected Amplitude & Margin Calculation	14
7.6. Test results	15
8. Photographs of test setup	19
9. Photographs of EUT	21

1. Description of version

Report No.	Issue Date	Description	Approved
CTB240929023EX	Sep. 30, 2024	Original	Invalid
CTB25091518105E01	Sep. 25, 2025	Revision	Valid

Note: This report has added the FCC ID number on the basis of the original report CTB240929023EX.

2. Test summary

Test procedures according to the technical standards:

Standard	Test Item	Test Result
§15.107	Conducted Emission	PASS
§15.109	Radiated Emission	PASS

3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

Test Item	Frequency	Expanded Uncertainty (U_{Lab})
No.1 Conducted Emission	150 kHz to 30 MHz	± 3.1 dB
No.2 Conducted Emission	150 kHz to 30 MHz	± 3.2 dB
Radiated Emission	30 MHz to 1000 MHz	± 4.1 dB
Radiated Emission	1000 MHz to 6000 MHz	± 4.8 dB

4. General information

4.1. Description of EUT

Product name	RADIO
Trade mark	KAITO
Model No.	KA600
Serial Model No.	KA600L, HQ600
Model Difference	All models are different. Everything else is the same. Test Sample Model: KA600
Rated Power	1.2W
Rated Voltage& current	DC 5V from adapter or DC 3.6V from Rechargeable Ni-MH Batteries or DC 6V from AA batteries
Highest Internal Frequency	>108MHz
Configuration	☒ Table-top ☐ Floor-standing
Classification	☐ Class A ☒ Class B
The highest frequency of the internal sources of the EUT	☐ below 1.705 MHz, the measurement shall only be made up to 30 MHz. ☐ between 1.705 MHz and 108 MHz, the measurement shall only be made up to 1 GHz. ☐ between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. ☐ between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. ☒ above 1 GHz, the measurement shall be made up to 5th harmonic of the highest frequency or 40 GHz, whichever is lower.
Adapter Information	/

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

4.2. Description of accessory device

Description	Manufacturer	Model	Note
Adapter	HUAWEI	C0137	☐ Applicant ☒ CTB


External I/O Cable

Cable Description	Shielded Type	Ferrite Core	Length(m)	Note
USB Cable	☐ Shielded ☒ Non-shielded	☐ Yes ☒ No	0.6	☒ Applicant ☐ CTB

4.3. Test conditions

Temperature: 15-25°C
 Relative Humidity: 30-60 %
 Atmospheric pressure: 800hPa-1060hPa

4.4. Block diagram of EUT configuration



4.5. Operating condition of EUT

The test system was pre-tested based on the consideration of all possible combinations of EUT operation modes according to test plan. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively. All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, (*)the worst data were recorded and reported.

Pretest Test Mode	Description	Test Voltage
Mode 1*	Charging+Working	AC 120V/60Hz

Conducted emission test		
Final Test Mode	Description	Test Voltage
Mode 1*	Charging+Working	AC 120V/60Hz

Radiated emission test		
Final Test Mode	Description	Test Voltage
Mode 1*	Charging+Working	AC 120V/60Hz

5. List of Test and Measurement Instruments

No.1 Continuous disturbance						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2027/6/21
2	AMN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/6/30
3	Pulse limiter	ROHDE&SCHWARZ	ESH3-Z2	357881052	/	2025/6/28
4	EMI TEST RECEIVER	R&S	ESCI	100428	V4.42.SP3	2025/6/30
5	Coaxial cable	Agilent	UCE500-SMNM-1.5M	/	/	2025/6/30
6	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/30
7	ISN	Schwarzbeck	CAT5 8158	00473	/	2025/6/23
8	Voltage Probe	Schwarzbeck	TK 9420	01189	/	2024/11/16
9	EZ-EMC	Frad	Ver/ EMC-con3A1/1	/	/	/
10	Current Probe	FCC	F-52B	199453	/	2025/5/27

Radiated emission(No.1 Chamber)						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2027/6/21
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2025/7/06
3	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/29
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/30
5	Amplifier	HP	8447E	2945A02747	/	2025/6/28
6	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/29
7	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESPI	100362	RF_ATTEN_7 (104489/003)	2025/6/28
8	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
9	Coaxial cable	ETS	RFC-SNS-100-N MS-80	/	/	2025/6/28
10	Coaxial cable	ETS	RFC-SN-100-NM S-20	/	/	2025/6/28
11	Coaxial cable	ETS	RFC-SNS-100-S MS-20	/	/	2025/6/28
12	Coaxial cable	ETS	RFC-NNS-100-N MS-300	/	/	2025/6/28
13	EMI test software	Frad	EZ-EMC	Ver/ FA-03A2 RE	/	/

Radiated emission(No.2 Chamber)						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2026/11/14
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2026/7/07
3	Broadband Antenna	Schwarzbeck	VULB 9168	1471	/	2025/7/06
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/30
5	Preamplifier	Schwarzbeck	BBV 9743 B	00500	/	2025/5/23
6	EMI TEST RECEIVER	R&S	ESC17	100861	/	2024/11/27
7	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
8	EMI test software	Farad	EZ-EMC	/	Ver. FARAD-3A1+	/
9	Coaxial cable	Rosenberg	8m	/	/	2024/11/27
10	Coaxial cable	Times	2m	/	/	2024/11/27
11	Coaxial cable	Times	2m	/	/	2024/11/27
12	Coaxial cable	Times	1m	/	/	2024/11/27
13	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/29

6. Conducted Emission

6.1. Limit

Except for Class A devices:


Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Note: Decreases with the logarithm of the frequency.

For Class A devices:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	79	66
0.5-30	73	60

6.2. Test setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

The setup of EUT is according with ANSI C63.4 measurement procedure. Specification used with FCC Part 15 limits.

6.3. EMI test receiver setup


Frequency Range	9kHz-30MHz
Resolution Bandwidth	200Hz (9kHz-150kHz) 9kHz (150kHz-30MHz)

6.4. Test procedure

1. Measurement was performed in shielded room, and instruments used were followed clause 4 of ANSI C63.4.
2. Detailed test procedure was following clause 7 of ANSI C63.4.
3. Frequency range 150kHz – 30MHz was checked and EMI receiver measurement bandwidth was set to 9 kHz.

6.5. Test results

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.3580	22.89	10.60	33.49	58.77	-25.28	QP
2		0.3580	9.40	10.60	20.00	48.77	-28.77	AVG
3		0.6780	24.08	10.70	34.78	56.00	-21.22	QP
4	*	0.6780	14.23	10.70	24.93	46.00	-21.07	AVG
5		1.3500	16.99	11.17	28.16	56.00	-27.84	QP
6		1.3500	4.76	11.17	15.93	46.00	-30.07	AVG
7		2.5579	13.96	11.70	25.66	56.00	-30.34	QP
8		2.5579	2.20	11.70	13.90	46.00	-32.10	AVG
9		5.3379	11.97	12.36	24.33	60.00	-35.67	QP
10		5.3379	0.47	12.36	12.83	50.00	-37.17	AVG
11		16.0138	8.35	13.39	21.74	60.00	-38.26	QP
12		16.0138	-4.21	13.39	9.18	50.00	-40.82	AVG

Note: Result=Reading + Factor

Over Limit=Result - Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.3580	23.83	10.60	34.43	58.77	-24.34	QP
2		0.3580	8.97	10.60	19.57	48.77	-29.20	AVG
3		0.6860	25.81	10.70	36.51	56.00	-19.49	QP
4	*	0.6860	16.54	10.70	27.24	46.00	-18.76	AVG
5		1.3740	16.78	11.19	27.97	56.00	-28.03	QP
6		1.3740	5.72	11.19	16.91	46.00	-29.09	AVG
7		2.5820	14.36	11.71	26.07	56.00	-29.93	QP
8		2.5820	4.33	11.71	16.04	46.00	-29.96	AVG
9		4.2900	12.59	12.08	24.67	56.00	-31.33	QP
10		4.2900	2.60	12.08	14.68	46.00	-31.32	AVG
11		7.4259	11.37	12.98	24.35	60.00	-35.65	QP
12		7.4259	0.76	12.98	13.74	50.00	-36.26	AVG

Note: Result=Reading + Factor
Over Limit=Result – Limit

7. Radiated emissions

7.1. Limit

Except for Class A devices (at 3m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

For Class A devices (at 10m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	90	39
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

7.2. Test setup

Radiated Emission Test Set-Up Frequency Below 1 GHz



Radiated Emission Test Set-Up Frequency Above 1GHz



The radiated tests were performed in 3 meter Chamber test site, using the setup accordance with the ANSI C63.4:2014.

7.3. EMI test receiver setup and spectrum analyzer setup

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz-1000MHz	100kHz	300kHz	120kHz	QP
Above 1GHz	1MHz	3MHz	/	PK
	1MHz	10Hz	/	AVG

7.4. Test procedure

1. The measurement was performed in a semi-anechoic chamber, and instruments used were followed clause 4 of ANSI C63.4
2. Detailed test procedure was following clause 8 of ANSI C63.4.

7.5. Corrected Amplitude & Margin Calculation

1. The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$


2. The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

7.6. Test results

Up to 1GHz


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.5757	28.21	-12.65	15.56	40.00	-24.44	QP
2	58.6126	27.24	-14.64	12.60	40.00	-27.40	QP
3 *	119.0180	39.23	-16.05	23.18	43.50	-20.32	QP
4	213.7634	37.49	-16.87	20.62	43.50	-22.88	QP
5	302.4812	33.45	-13.75	19.70	46.00	-26.30	QP
6	570.6100	25.58	-7.30	18.28	46.00	-27.72	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	39.5757	41.80	-12.65	29.15	40.00	-10.85	QP
2	58.8185	37.55	-14.64	22.91	40.00	-17.09	QP
3	85.2980	39.36	-18.42	20.94	40.00	-19.06	QP
4	102.3597	44.73	-17.81	26.92	43.50	-16.58	QP
5	125.0066	42.12	-15.51	26.61	43.50	-16.89	QP
6	213.0151	35.98	-16.89	19.09	43.50	-24.41	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

Above 1GHz


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		1290.882	44.54	-0.82	43.72	74.00	-30.28	QP
2		1290.882	33.41	-0.82	32.59	54.00	-21.41	AVG
3		1838.956	44.61	0.64	45.25	74.00	-28.75	QP
4	*	1838.956	33.77	0.64	34.41	54.00	-19.59	AVG
5		2249.642	41.23	1.99	43.22	74.00	-30.78	QP
6		2249.642	30.04	1.99	32.03	54.00	-21.97	AVG
7		3023.489	39.43	4.62	44.05	74.00	-29.95	QP
8		3023.489	26.83	4.62	31.45	54.00	-22.55	AVG
9		4345.943	37.23	5.52	42.75	74.00	-31.25	QP
10		4345.943	25.63	5.52	31.15	54.00	-22.85	AVG
11		6000.000	33.21	12.24	45.45	74.00	-28.55	QP
12		6000.000	21.93	12.24	34.17	54.00	-19.83	AVG

Note: Result=Reading+Factor
Over Limit=Result-Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		1098.634	44.43	-1.70	42.73	74.00	-31.27	QP
2		1098.634	34.52	-1.70	32.82	54.00	-21.18	AVG
3		1386.796	44.65	-0.60	44.05	74.00	-29.95	QP
4		1386.796	34.02	-0.60	33.42	54.00	-20.58	AVG
5		2122.382	43.95	1.55	45.50	74.00	-28.50	QP
6		2122.382	32.37	1.55	33.92	54.00	-20.08	AVG
7		3023.489	41.79	4.62	46.41	74.00	-27.59	QP
8	*	3023.489	31.32	4.62	35.94	54.00	-18.06	AVG
9		4345.943	38.26	5.52	43.78	74.00	-30.22	QP
10		4345.943	28.63	5.52	34.15	54.00	-19.85	AVG
11		5893.452	32.36	11.25	43.61	74.00	-30.39	QP
12		5893.452	22.80	11.25	34.05	54.00	-19.95	AVG


Note: Result=Reading+Factor
Over Limit=Result-Limit

8. Photographs of test setup

RE up to 1GHz



RE above 1GHz



CE



9. Photographs of EUT


EUT photo 1




EUT photo 2



EUT photo 3



EUT photo 4



EUT photo 5



EUT photo 6



EUT photo 7



End of report