



EMC TEST REPORT

Test item description: RADIO

FCC ID: 2BR4H-PL-520

Trademark(s): TECSUN

Model/Type reference: PL-520

S/N: /

Report No.: CTB26031904601E01

Applicant's name: Kaito Electronics, Inc.

Address: 5185 Cliffwood Drive, Montclair, CA 91763, USA

Manufacturer: TECSUN GENERAL ELECTRIC MANUFACTURER CO., LTD.

Address: NO.58 DONGCHENG SECTION, GUANCHANG ROAD, DONGCHENG STREET, DONGGUAN, GUANGDONG, CHINA.

Prepared by: Shenzhen CTB Testing Technology Co., Ltd.

Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt: Mar. 19, 2026

Date of Test(s): Mar. 19, 2026 ~ Mar. 28, 2026

Date of Issue: Mar. 28, 2026

Test Standard(s): CFR47, FCC Part 15 Subpart B, ANSI C63.4: 2014

Test Result: Pass

In the configuration tested, the EUT complied with the standards specified above.

Compiled by:

Reviewed by:

Approved by:

Blake cai

Bin Mei

Rita Xiao

Black cai

Bin Mei

Rita Xiao

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "★" indicates the testing items were fulfilled by subcontracted lab. "×" indicates the items are not in CNAS accreditation scope.

Table of Contents

1.	Description of version	3
2.	Test summary.....	4
3.	Measurement uncertainty	5
4.	General information.....	6
4.1.	Description of EUT	6
4.2.	Description of accessory device	6
4.3.	Test conditions	6
4.4.	Block diagram of EUT configuration	6
4.5.	Operating condition of EUT	6
5.	List of Test and Measurement Instruments	7
6.	Conducted Emission	9
6.1.	Limit.....	9
6.2.	Test setup	9
6.3.	EMI test receiver setup	9
6.4.	Test procedure	9
6.5.	Test results	10
7.	Radiated emissions.....	12
7.1.	Limit.....	12
7.2.	Test setup	12
7.3.	EMI test receiver setup and spectrum analyzer setup	13
7.4.	Test procedure	13
7.5.	Corrected Amplitude & Margin Calculation	13
7.6.	Test results	14
8.	Photographs of test setup	18

1. Description of version

Report No.	Issue Date	Description	Approved
CTB26031904601E01	Mar. 28, 2026	Original	Valid

2. Test summary

Test procedures according to the technical standards:

Standard	Test Item	Test Result
§15.107	Conducted Emission	PASS
§15.109	Radiated Emission	PASS

3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

Test Item	Frequency	Expanded Uncertainty (U_{Lab})
Conducted Emission	150 kHz to 30 MHz	± 3.1 dB
Radiated Emission	30 MHz to 1000 MHz	± 4.1 dB
Radiated Emission	1000 MHz to 6000 MHz	± 4.8 dB

4. General information

4.1. Description of EUT

Test item description:	RADIO
Trademark(s):	TECSUN
Model/Type reference:	PL-520
Serial Model No.	N/A
Model Difference	N/A
Configuration	☒ Table-top ☐ Floor-standing
The highest frequency of the internal sources of the EUT	☐ below 1.705 MHz, the measurement shall only be made up to 30 MHz. ☒ between 1.705 MHz and 108 MHz, the measurement shall only be made up to 1 GHz. ☐ between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. ☐ between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. ☐ above 1 GHz, the measurement shall be made up to 5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

4.2. Description of accessory device

No.	Device Type	Brand	Model	Specification	Note
1	Adapter	JIYIN	JY-05100C	/	AE


4.3. Test conditions

Temperature: 15-25°C

Relative Humidity: 30-60 %

Atmospheric pressure: 800hPa-1060hPa

4.4. Block diagram of EUT configuration



4.5. Operating condition of EUT

Operating condition	Mode 1	Working	Test Voltage	/
Note: This test covers all possible operating modes of the device, only the worst data are list in report. The worst data are shows (*) is the nearest standard limit which were recorded in this report.				

5. List of Test and Measurement Instruments

Continuous disturbance							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated Date	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2024/6/22	2027/6/21
2	LISN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/5/22	2026/5/21
3	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/5/22	2026/5/21
4	Coaxial cable	ZDECL	Z302S	18091904	/	2025/5/22	2026/5/21
5	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/18	2026/6/17
6	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2025/9/19	2026/9/18
7	EZ-EMC	Frad	EMC-con3A1.1	/	/	/	/
8	Current Probe	FCC	F-52B	199453	/	2025/5/24	2026/5/23
9	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/5/23	2026/5/22
10	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

Radiated emission(No.1 Chamber)							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2024/6/23	2027/6/22
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2025/6/1	2026/5/31
3	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/29	2026/6/28
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/3	2026/6/2
5	Amplifier	HP	8447E	2945A02747	/	2025/5/23	2026/5/22
6	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/2	2026/6/1
7	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESPI	100362	RF_ATTEN_7 (104489/003)	2025/5/23	2026/5/22
8	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/5/23	2026/5/22
9	Coaxial cable	ETS	RFC-SNS-100-NMS-80	/	/	2025/5/24	2026/5/23
10	Coaxial cable	ETS	RFC-SN-100-NMS-20	/	/	2025/5/24	2026/5/23
11	Coaxial cable	ETS	RFC-SNS-100-SMS-20	/	/	2025/5/24	2026/5/23
12	Coaxial cable	ETS	RFC-NNS-100-NMS-300	/	/	2025/5/24	2026/5/23

13	EMI test software	Frad	EZ-EMC	Ver/ FA-03A2 RE	/	/	/
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/5/23	2026/5/22
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

6. Conducted Emission

6.1. Limit

Except for Class A devices:


Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Note: Decreases with the logarithm of the frequency.

For Class A devices:

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	79	66
0.5-30	73	60

6.2. Test setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

The setup of EUT is according with ANSI C63.4 measurement procedure. Specification used with FCC Part 15 limits.

6.3. EMI test receiver setup


Frequency Range	9kHz-30MHz
Resolution Bandwidth	200Hz (9kHz-150kHz) 9kHz (150kHz-30MHz)

6.4. Test procedure

1. Measurement was performed in shielded room, and instruments used were followed clause 4 of ANSI C63.4.
2. Detailed test procedure was following clause 7 of ANSI C63.4.
3. Frequency range 150kHz – 30MHz was checked and EMI receiver measurement bandwidth was set to 9 kHz.

6.5. Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.1780	25.94	10.08	36.02	64.58	-28.56	QP
2		0.1780	12.65	10.08	22.73	54.58	-31.85	AVG
3		0.2860	21.47	10.08	31.55	60.64	-29.09	QP
4		0.2860	8.74	10.08	18.82	50.64	-31.82	AVG
5	*	0.6380	27.64	10.10	37.74	56.00	-18.26	QP
6		0.6380	12.75	10.10	22.85	46.00	-23.15	AVG
7		1.7020	24.24	10.16	34.40	56.00	-21.60	QP
8		1.7020	7.75	10.16	17.91	46.00	-28.09	AVG
9		5.3100	16.24	10.30	26.54	60.00	-33.46	QP
10		5.3100	3.90	10.30	14.20	50.00	-35.80	AVG
11		17.6660	26.68	10.85	37.53	60.00	-22.47	QP
12		17.6660	7.67	10.85	18.52	50.00	-31.48	AVG

Note: Result=Reading + Factor
Over Limit=Result - Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.1819	26.98	10.08	37.06	64.40	-27.34	QP
2		0.1819	13.70	10.08	23.78	54.40	-30.62	AVG
3		0.3220	24.48	10.08	34.56	59.66	-25.10	QP
4		0.3220	12.75	10.08	22.83	49.66	-26.83	AVG
5	*	0.6340	29.62	10.10	39.72	56.00	-16.28	QP
6		0.6340	16.79	10.10	26.89	46.00	-19.11	AVG
7		1.6260	22.71	10.15	32.86	56.00	-23.14	QP
8		1.6260	8.59	10.15	18.74	46.00	-27.26	AVG
9		5.3220	17.13	10.30	27.43	60.00	-32.57	QP
10		5.3220	7.00	10.30	17.30	50.00	-32.70	AVG
11		17.7220	25.56	10.86	36.42	60.00	-23.58	QP
12		17.7220	10.63	10.86	21.49	50.00	-28.51	AVG

Note: Result=Reading + Factor
Over Limit=Result – Limit

7. Radiated emissions

7.1. Limit

Except for Class A devices (at 3m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

For Class A devices (at 10m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	90	39
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

7.2. Test setup

Radiated Emission Test Set-Up Frequency Below 1 GHz



Radiated Emission Test Set-Up Frequency Above 1GHz



The radiated tests were performed in 3 meter Chamber test site, using the setup accordance with the ANSI C63.4:2014.

7.3. EMI test receiver setup and spectrum analyzer setup

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz-1000MHz	100kHz	300kHz	120kHz	QP
Above 1GHz	1MHz	3MHz	/	PK
	1MHz	10Hz	/	AVG

7.4. Test procedure

1. The measurement was performed in a semi-anechoic chamber, and instruments used were followed clause 4 of ANSI C63.4
2. Detailed test procedure was following clause 8 of ANSI C63.4.

7.5. Corrected Amplitude & Margin Calculation

1. The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:


$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

2. The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

7.6. Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	42.2281	26.24	-5.99	20.25	40.00	-19.75	QP
2	74.6569	26.83	-8.32	18.51	40.00	-21.49	QP
3	155.9101	26.13	-3.83	22.30	43.50	-21.20	QP
4	306.2164	26.27	-2.42	23.85	46.00	-22.15	QP
5	628.3745	24.63	4.67	29.30	46.00	-16.70	QP
6 *	775.5169	29.71	8.03	37.74	46.00	-8.26	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	38.6839	26.76	-6.03	20.73	40.00	-19.27	QP
2	91.3346	25.53	-7.89	17.64	43.50	-25.86	QP
3	173.2051	26.24	-3.66	22.58	43.50	-20.92	QP
4	308.9126	26.87	-2.38	24.49	46.00	-21.51	QP
5	377.9211	25.78	-1.26	24.52	46.00	-21.48	QP
6 *	710.4268	25.83	6.61	32.44	46.00	-13.56	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

Above 1GHz:


Temperature:	24°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		1133.628	40.57	-3.75	36.82	74.00	-37.18	peak
2		1133.628	29.58	-3.75	25.83	54.00	-28.17	AVG
3		1503.244	41.05	-2.05	39.00	74.00	-35.00	peak
4		1503.244	30.70	-2.05	28.65	54.00	-25.35	AVG
5		2170.453	42.28	2.82	45.10	74.00	-28.90	peak
6		2170.453	31.15	2.82	33.97	54.00	-20.03	AVG
7		2619.729	39.38	4.90	44.28	74.00	-29.72	peak
8		2619.729	28.60	4.90	33.50	54.00	-20.50	AVG
9		3396.943	43.58	8.09	51.67	74.00	-22.33	peak
10		3396.943	33.02	8.09	41.11	54.00	-12.89	AVG
11		5535.214	41.72	15.91	57.63	74.00	-16.37	peak
12	*	5535.214	31.21	15.91	47.12	54.00	-6.88	AVG

Note: Result=Reading+Factor
Over Limit=Result-Limit

Temperature:	24°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		1088.835	36.38	-3.93	32.45	74.00	-41.55	peak
2		1088.835	26.16	-3.93	22.23	54.00	-31.77	AVG
3		1418.207	37.56	-2.40	35.16	74.00	-38.84	peak
4		1418.207	26.43	-2.40	24.03	54.00	-29.97	AVG
5		2180.197	42.04	2.86	44.90	74.00	-29.10	peak
6		2180.197	31.04	2.86	33.90	54.00	-20.10	AVG
7		3233.621	41.43	7.50	48.93	74.00	-25.07	peak
8		3233.621	31.65	7.50	39.15	54.00	-14.85	AVG
9		4365.454	40.33	11.84	52.17	74.00	-21.83	peak
10		4365.454	29.65	11.84	41.49	54.00	-12.51	AVG
11		5635.286	42.19	16.16	58.35	74.00	-15.65	peak
12	*	5635.286	30.34	16.16	46.50	54.00	-7.50	AVG

Note: Result=Reading+Factor
Over Limit=Result-Limit

8. Photographs of test setup

Radiated Emission



Radiated Emission Above 1GHz





End of report