


Test report No: 4937111.56

TEST REPORT

Radio Spectrum Matters (RF)

Identification of item tested	Module
Trademark	LEMAX
Model and /or type reference	AC6956C
FCC ID	2BR5R58000
Features	3 Vdc
Applicant's name / address	LIC LIMITED UNIT 3106, TOWER 1, ENTERPRISE SQUARE FIVE, NO. 38 WANG CHIU ROAD, KOWLOON BAY, KOWLOON, HONG KONG.
Test method requested, standard	FCC CFR Title 47 Part15 Subpart C Section 15.247; KDB558074 D01v05r02;
Verdict Summary	COMPLIANCE
Tested by (name & signature)	 Johnny Bo
Approved by (name & signature)	 Tim Yan
Date of issue	2026-01-05
Report template No	TRF_EMC 2017-06- FCC_Part15C_247

INDEX

	page
General conditions	4
Uncertainty	4
Environmental conditions	4
Possible test case verdicts	4
Definition of symbols used in this test report	5
Abbreviations	5
Document History	5
Remarks and Comments	5
1 General Information	6
1.1 General Description of the Item(s)	6
1.2 Test data	7
1.3 The environment(s) in which the EUT is intended to be used	7
1.4 Channel List	8
2 Description of Test Setup	9
2.1 Operating mode(s) used for tests	9
2.2 Support / Auxiliary equipment / unit / software for the EUT	9
2.3 Test Configuration / Block diagram used for tests	9
2.4 Measurement procedure	10
3 Verdict summary section	11
3.1 Standards	11
3.2 Deviation(s) from the Standard(s) / Test Specification(s)	11
3.3 Overview of results	11
4 Transmitter Test Results	12
4.1 AC Power Line Conducted Emission	12
4.2 Emissions in non-restricted frequency bands	15
4.3 Emissions in restricted frequency bands	26
4.4 Band Edge	33
4.5 Duty cycle	36
4.6 DTS Bandwidth	38
4.7 Fundamental emission output power	43
4.8 Power Density	46
5 Identification of the Equipment Under Test	49
Annex 1 – Measurement Uncertainty	50
Annex 2 - Used Equipment	51



Annex 3 - Test Photos53

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	-40 °C – 105 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not tested	N/T

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

☒ Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
☐ Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	☐	Comma (,)	☒ Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report nr.	Date	Description
4937111.56	2026-01-05	First release.

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item	Module
Trademark.....	LEMAX
Model / Type number	AC6956C
FCC ID	2BR5R58000
Hardware	N/A
Software.....	N/A
Firmware	N/A
Ratings.....	3 Vdc
Manufacturer.....	Same as applicant
Factory	Same as applicant

Based on customer description: The characteristics of radio module are:

Operating frequency range(s).....	2402 MHz – 2480 MHz
Type of Modulation	GFSK
Maximum RF output power(EIRP)...	0.52 dBm
Antenna type.....	Integral Antenna
Antenna gain.....	2.92 dBi
Adaptivity	Non-Adaptive
Number of channel	79
Operating Temperature Range.....	-20 - +70°C

Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 3 V					
	☐	Battery:					
Mounting position.....	☒	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☐	Hand-held equipment					
	☐	Other: Built-in					

Intended use of the Equipment Under Test (EUT)
The apparatus as supplied for the test is module intended for residential use and the product contains electronic control circuitry.
Model AC6956C was chosen for full test.

Copy of marking plate:
No provide.

1.2 Test data

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324;
Date of receipt of test item	2025-04-25
Date (s) of performance of tests	2025-04-25 to 2025-08-28
Test sample	Normal sample: AC6956C (lab on.4937111-1) RF conducted sample: AC6956C (lab on.4937111-2) RF radiated sample: AC6956C (lab on.4937111-3)

1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

☒	Residential (domestic) environment.
☒	Commercial and light-industrial environment.
☐	Industrial environment.

1.4 Channel List

The radio module (BT) operating channels are:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	28	2429	55	2456
2	2403	29	2430	56	2457
3	2404	30	2431	57	2458
4	2405	31	2432	58	2459
5	2406	32	2433	59	2460
6	2407	33	2434	60	2461
7	2408	34	2435	61	2462
8	2409	35	2436	62	2463
9	2410	36	2437	63	2464
10	2411	37	2438	64	2465
11	2412	38	2439	65	2466
12	2413	39	2440	66	2467
13	2414	40	2441	67	2468
14	2415	41	2442	68	2469
15	2416	42	2443	69	2470
16	2417	43	2444	70	2471
17	2418	44	2445	71	2472
18	2419	45	2446	72	2473
19	2420	46	2447	73	2474
20	2421	47	2448	74	2475
21	2422	48	2449	75	2476
22	2423	49	2450	76	2477
23	2424	50	2451	77	2478
24	2425	51	2452	78	2479
25	2426	52	2453	79	2480
26	2427	53	2454	-	
27	2428	54	2455	-	

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methos	
		Conducted	Radiated
1	Transmitting at BLE	☒	☒
2			
3			
4			
Supplemental information: ---			

2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
Laptop	Latitude 5488	DELL	DEKRA
Supplemental information: ---			

2.3 Test Configuration / Block diagram used for tests

Refer to Annex 3.

2.4 Measurement procedure

The EUT was controlled by a serial PCB which provided by manufacturer which connected to laptop through the com port. After connected, run the software “FCC_assist_1.0.2.2” to control the EUT work in required test mode as below table.

Mode	Frequency (MHz)	Power setting
BLE	2402	10
	2440	10
	2480	10

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
FCC CFR Title 47 Part 15 Subpart C Section 15.247	2025	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
KDB 558074 D01 v05r02	2019	Guidance for performing compliance measurements on Digital Transmission System (DTS) operating under section 15.247
ANSI C63.10	2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

3.3 Overview of results

FCC measurement			
Requirement – Test case	Basic standard(s)	Verdict	Remark
AC Power Line Conducted Emission	FCC 15.207	PASS	---
Emissions in non-restricted frequency bands	FCC 15.247(d), FCC 15.209	PASS	---
Emissions in restricted frequency bands	FCC 15.247(b)(3)	PASS	---
Duty cycle	ANSI C63.10:2020	PASS	---
Band Edge	FCC 15.247(d)	PASS	---
Fundamental emission output power	FCC 15.247(d), FCC 15.209	PASS	---
DTS Bandwidth	FCC 15.247(a)(2)	PASS	---
Power Spectral Density	FCC 15.247(e)	PASS	---
Antenna Requirement	FCC 15.203	PASS	---
<u>Supplementary information:</u>			

The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to calculate the uncertainty associated with the measurement result.

4 TRANSMITTER TEST RESULTS


4.1 AC Power Line Conducted Emission	VERDICT: PASS
---	----------------------

Limits

FCC Part 15 Subpart C Paragraph 15.207				
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾]	Limit: AV [dB(μV) ¹⁾]	IF BW	Detector(s)
0.15 - 0.50	66 - 56 ²⁾	56 - 46 ²⁾	9 KHz	QP, AV
0.50 - 5.0	56	46	9 KHz	QP, AV
5.0 - 30	60	50	9 KHz	QP, AV

¹⁾ At the transition frequency, the lower limit applies.
²⁾ The limit decreases linearly with the logarithm of the frequency.


Test Configuration



Performed measurements

Port under test		Terminal							
☒	AC mains input power	☒	N	☒	L1	☐	L2	☐	L3
☐	DC input power	☐	Positive (+)			☐	Negative (-)		
Test method applied		☒	Artificial mains network						
		☐	Voltage probe						
Test setup		☒	Table top	☐	Artificial hand applied				
		☐	Floor standing	☐	Other:				
		Refer to the Annex 2 for test setup photo(s).							
Envirment condition (temperature; humidiry)		23,0 °C; 45,0 %							
Remark		---							

Measurement data		Port under test	AC mains input power
Operating mode / voltage / frequency used during the test			Mode 1/3 Vdc
Live			
		RBW9 kHz MT1 s PREAMP OFF	
Att 10 dB			
dBµV 80 70 60 50 40 30 20 10 0 150 kHz 30 MHz 1 PK MAXH 2 AV MAXH FCCBQ FCCBA			




4.2	Emissions in non-restricted frequency bands	VERDICT: PASS
------------	--	----------------------

Emissions Limit 15.209(a)			
Frequency (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).


Test Configuration



Performed measurements

Port under test	Enclosure port	
Test method applied	☐	Conducted measurement
	☒	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1	
Remark	1)The test frequency range, 9kHz~30MHz, 18GHz~26GHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report. 2)The EUT are tested in three orientations. The record is the worst orientation which refer to the Annex 3 for test setup photo(s).	

Results of 30 – 1000 MHz

Measurement data						
Operating mode / voltage / frequency used during the test				Mode 1 / 3 Vdc		
Horizontal						
						
Freq	Reading	C.F	Result	Limit	Margin	Remark
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
42.60	4.94	20.32	25.26	40.00	14.74	QP
56.00	5.21	20.44	25.65	40.00	14.35	QP
158.11	6.40	20.86	27.26	43.50	16.24	QP
191.75	13.09	18.08	31.17	43.50	12.33	QP
629.48	2.30	29.57	31.87	46.00	14.13	QP
929.01	2.23	33.64	35.87	46.00	10.13	QP


Margin=limit-result

Remarks:

1) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

2) Result = Reading + C.F (Correction Factor)

No other significant emissions were measured at the frequency range of interest employing the QP detector.


Measurement data						
Operating mode / voltage / frequency used during the test				Mode 1 / 3 Vdc		
Vertical						
						
Freq	Reading	C.F	Result	Limit	Margin	Remark
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
31.62	13.81	19.12	32.93	40.00	7.07	QP
33.21	13.40	19.48	32.88	40.00	7.12	QP
133.62	11.54	19.74	31.28	43.50	12.22	QP
147.92	14.20	20.61	34.81	43.50	8.69	QP
156.46	10.92	20.85	31.77	43.50	11.73	QP
560.69	5.80	27.81	33.61	46.00	12.39	QP
Margin=limit-result Remarks: 1) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain 2) Result = Reading + C.F (Correction Factor) No other significant emissions were measured at the frequency range of interest employing the QP detector.						
Remark						

Results of 1 – 18 GHz

Model	AC6956C
Operation Mode	Mode 1 @2402 MHz
Test voltage	3 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	AC6956C
Operation Mode	Mode 1 @2440 MHz
Test voltage	3 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	AC6956C
Operation Mode	Mode 1 @2480 MHz
Test voltage	3 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

4.3	Emissions in restricted frequency bands	VERDICT: PASS
------------	--	----------------------

Restricted Bands of operation of FCC			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			
Restricted Bands of operation for IC			
0.090 - 0.110	13.36 - 13.41	960 - 1427	9.0 - 9.2
0.495 - 0.505	16.42 - 16.423	1435 - 1626.5	9.3 - 9.5
2.1735 - 2.1905	16.69475 - 16.69525	1645.5 - 1646.5	10.6 - 12.7
3.020 - 3.026	16.80425 - 16.80475	1660 - 1710	13.25 - 13.4
4.125 - 4.128	25.5 - 25.67	1718.8 - 1722.2	14.47 - 14.5
4.17725 - 4.17775	37.5 - 38.25	2200 - 2300	15.35 - 16.2
4.20725 - 4.20775	73 - 74.6	2310 - 2390	17.7 - 21.4
5.677 - 5.683	74.8 - 75.2	2483.5 - 2500	22.01 - 23.12
6.215 - 6.218	108 - 138	2655 - 2900	23.6 - 24.0
6.26775 - 6.26825	149.9 - 150.05	3260 - 3267	31.2 - 31.8
6.31175 - 6.31225	156.52475 - 156.52525	3332 - 3339	36.43 - 36.5
8.291 - 8.294	156.7 - 156.9	3345.8 - 3358	Above 38.6
8.362 - 8.366	162.0125 - 167.17	3500 - 4400	
8.37625 - 8.38675	167.72 - 173.2	4500 - 5150	
8.41425 - 8.41475	240 - 285	5350 - 5460	
12.29 - 12.293	322 - 335.4	7250 - 7750	
12.51975 - 12.52025	399.9 - 410	8025 - 8500	
12.57675 - 12.57725	608 - 614	--	


Restricted Band Emissions Limit

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.49	$2400/F(\text{kHz})$	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	$24000/F(\text{kHz})$	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

Test Configuration




Performed measurements

Port under test	Enclosure port	
Test method applied	☐	Conducted measurement
	☒	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1	
Remark	---	

Model	AC6956C
Operation Mode	Mode 1 @2402 MHz
Test voltage	3 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	AC6956C
Operation Mode	Mode 1 @2480 MHz
Test voltage	3 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

4.4 Band Edge	VERDICT: PASS
----------------------	----------------------

Standard	FCC Part 15 Subpart C Paragraph 15.247(d)
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)
Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD by level in 100 kHz (i.e., 30 dBc). Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD by level in 100 kHz (i.e., 20 dBc).	


Test Configuration



Performed measurements

Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1	
Remark	---	

Results for mode 1 @2402 MHz



Inband Peak


Frequency (MHz)	Level (dBm)
2402.0000	

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.025000	-46.2	22.2	-24.0	PASS
2398.875000	-46.5	22.4	-24.0	PASS
2399.175000	-46.7	22.6	-24.0	PASS
2399.075000	-46.8	22.8	-24.0	PASS
2398.825000	-47.0	23.0	-24.0	PASS
2399.225000	-47.1	23.1	-24.0	PASS
2398.975000	-47.2	23.2	-24.0	PASS
2398.925000	-47.8	23.7	-24.0	PASS
2399.125000	-48.3	24.2	-24.0	PASS
2398.725000	-49.7	25.7	-24.0	PASS
2399.375000	-49.8	25.8	-24.0	PASS
2399.275000	-49.9	25.8	-24.0	PASS
2398.675000	-49.9	25.9	-24.0	PASS
2399.325000	-49.9	25.9	-24.0	PASS
2398.425000	-50.1	26.1	-24.0	PASS

Results for mode 1 @2480 MHz

Band Edge



Inband Peak


Frequency (MHz)	Level (dBm)
2480.0000	

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2497.575000	-54.7	31.1	-23.6	PASS
2496.025000	-54.9	31.3	-23.6	PASS
2497.625000	-55.0	31.4	-23.6	PASS
2495.975000	-55.1	31.5	-23.6	PASS
2497.525000	-55.1	31.5	-23.6	PASS
2498.475000	-55.4	31.8	-23.6	PASS
2498.525000	-55.4	31.8	-23.6	PASS
2498.375000	-55.4	31.9	-23.6	PASS
2499.475000	-55.7	32.1	-23.6	PASS
2499.525000	-55.8	32.2	-23.6	PASS
2496.075000	-55.9	32.3	-23.6	PASS
2498.325000	-56.0	32.5	-23.6	PASS
2496.325000	-56.1	32.5	-23.6	PASS
2496.425000	-56.1	32.6	-23.6	PASS
2483.525000	-56.2	32.6	-23.6	PASS

4.5	Duty cycle	VERDICT: PASS
------------	-------------------	----------------------

Test Configuration



Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1	
Remark	---	

Test Mode	Tx On (ms)	Tx On + Tx Off (ms)	Duty Cycle
Mode 1	---	---	77.640%

Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control Level for the tested mode of operation.

Note 2: According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set: VBW $\geq 1/T$ will be used.


Gated Trace



4.6 DTS Bandwidth	VERDICT: PASS
--------------------------	----------------------

Standard	FCC Part 15 Subpart C Paragraph 15.247 (a)(2)
Systems using digital modulation techniques operate in the 2400-2483.5 MHz .The minimum 6 dB bandwidth shall be at by least 500 kHz	

Test Configuration



Performed measurements

Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1	
Remark	---	


Results

Mode	CH.	Test Freq. (MHz)	6dB Occupied Bandwidth (MHz)	Limit (kHz)	Result
1	1	2402	0.891	>500	Pass
	39	2440	0.891	>500	Pass
	79	2480	0.891	>500	Pass

6dB Occupied Bandwidth


Mode 1 / CH1 (2402MHz)


6 dB Bandwidth



Mode 1 / CH39 (2440MHz)

6 dB Bandwidth






Result

Mode	CH.	Test Freq. (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
1	1	2402	1.165	Within frequency range	Pass
	39	2440	1.170	Within frequency range	Pass
	79	2480	1.165	Within frequency range	Pass

99% Occupied Bandwidth


Mode 1 / CH1 (2402 MHz)

99 % Bandwidth




Mode 1 / CH39 (2440 MHz)

99 % Bandwidth



Mode 1 / CH79 (2480 MHz)


99 % Bandwidth



4.7	Fundamental emission output power	VERDICT: PASS
------------	--	----------------------

Standard		FCC Part 15 Subpart C Paragraph 15.247 (b)(3)
☒	GTX <6dBi	Pout≤30dBm
☐	GTX >6dBi	
☐	Non-Fix point-point	Pout≤30-(GTX -6)
☐	Fix point-point	Pout≤30-[(GTX-6)]/3
☐	Point-to-multipoint	Pout≤30-(GTX-6)
☐	Overlap Beams	Pout≤30-[(GTX-6)]/3
☐	Aggregate power transmitted simultaneously on all beams	Pout≤30-[(GTX-6)]/3
☐	single LE directional beam	Pout≤30-[(GTX-6)]/3+8dB
Note 1 : GTX directional gain of transmitting antennas.		
Note 2 : Pout is maximum peak conducted output power .		

Test Configuration



Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1	
Remark	---	

Results for 125 KHz

Mode	Channel	Test Frequency (MHz)	Power Output (dBm)	Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)	Result
BLE	1	2402	-3.0	≤30	-1.92	≤36	Pass
	39	2440	-2.6	≤30	-1.52	≤36	Pass
	79	2480	-2.4	≤30	-1.32	≤36	Pass


Data of 2402MHz

Peak Power




Data of 2440MHz

Peak Power



Data of 2480MHz


Peak Power



4.8 Power Density	VERDICT: PASS
--------------------------	----------------------

Standard	FCC Part 15 Subpart C Paragraph 15.247 (b)(3)
Power Spectral Density $\leq 8 \text{ dBm/3kHz}$	

Test Configuration



Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1	
Remark	---	

Results for 125 KHz

Mode	Channel	Test Frequency (MHz)	PSD (dBm)	Limit (dBm/3kHz)	Result
1	1	2402	-9.618	≤ 8	Pass
	39	2440	-9.349	≤ 8	Pass
	79	2480	-9.259	≤ 8	Pass


Data of 2402MHz

Peak Power Spectral Density




Data of 2440MHz

Peak Power Spectral Density



Data of 2480MHz
Peak Power Spectral Density



5 IDENTIFICATION OF THE EQUIPMENT UNDER TEST

The photographs show the tested device.

Refer to documents External photo and Internal photo.

ANNEX 1 – MEASUREMENT UNCERTAINTY

Test Item	Uncertainty
Occupied Channel Bandwidth	$\pm 0.7\%$
RF Output power, conducted	$\pm 0.6\text{dB}$
Power Spectral Density, Conducted	$\pm 0.6\text{dB}$
Unwanted Emissions, Conducted	$\pm 0.7\text{dB}$
Spurious (30-1000MHz)	$\pm 4.4\text{dB}$
Spurious (1-18GHz)	$\pm 4.4\text{dB}$

ANNEX 2 - USED EQUIPMENT

For Radiated Emission (30MHz-1000MHz)

Instrumentation	Manufacturer	Model No.	Serial No.	DEKRA No.	Cal. Last date	Cal. Due date
3m Chamber	ETS	FACT3-2.0	CT000344-1100	G/L856	2025/03/11	2028/03/10
EMI receiver	R&S	ESCI	101205	G/L858	2025/05/14	2026/05/13
Antenna (30MHz-2GHz)	SCHWARZBECK	VULB9168	01229	GZ2018	2025/03/17	2026/03/16
Test software	AUDIX	e3	Version 6.130520	---	-	---

For Radiated Emission (1GHz-40GHz)

Instrumentation	Manufacturer	Model No.	Serial No.	DEKRA No.	Cal. Last date	Cal. Due date
3m Chamber	ETS	FACT3-2.0	CT000344-1100	G/L856	2025/03/12	2026/03/11
Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA 9120D	02408	GZ2019	2025/01/17	2026/01/16
Horn antenna preamplifier	EMC Instruments corporation	EMC051845 SE	980778	GZ2009	2024/11/14	2025/11/13
Antenna (18GHz-26.5GHz)	ETS	3160-09	00164643	G/L1237	2025/01/17	2026/01/16
Horn antenna preamplifier	SCHWARZBECK	SCU-26D	1879064	G/L1237-1	2025/01/13	2026/01/12
Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	00908	GZ1901	2025/06/22	2026/06/21
Horn antenna preamplifier	EMCI	EMC264045 SE	980679	GZ1901-1	2025/06/06	2026/06/05
Spectrum analyzer	R&S	FSV	SN101012	G/L1235	2024/12/02	2025/12/01

FOR RF

Instrumentation	Manufacturer	Model	Serial no.	DEKRA No.	Cal. Last date	Cal Due date
Spectrum analyzer	R&S	FSV	SN101012	G/L1235	2024/12/02	2025/12/01
Chamber	ETS	/	/	G/L856	2025/03/13	2026/03/12
Horn antenna (1GHz-18GHz)	R&S	HF907	102306	G/L1236	2025/05/28	2026/05/27
Horn antenna preamplifier	Schwarzbeek	SCU-18	102234	G/L1236-1	2025/01/08	2026/01/07
Horn antenna (18GHz-26.5GHz)	ETS	3160-09	00164643	G/L1237	2025/01/17	2026/01/16
Horn antenna preamplifier	/	SCU-26D	1879064	G/L1237-1	2025/01/13	2026/01/12
EMI receiver	R&S	ESCI	101205	G/L857	2025/05/14	2026/05/13
Antenna (30MHz-3GHz)	SCHWARZBECK	VULB9163	506	G/L864	2025/07/17	2026/07/16
OSP	R&S	OSP 150	101907	GZ1893	2025/01/08	2026/01/07
Signal generator	R&S	SMB 100A	181317	GZ1895	2025/01/08	2026/01/07
Vector signal	R&S	SMBV100A	263671	GZ1896	2025/01/08	2026/01/07

generator						
Wireless connectivity tester	R&S	CMW 270	100990	GZ1894	2025/01/08	2026/01/07
Band filter	HX Microwave	HXLBQ-DZA219	23080804-1	GZ2464	2025/07/15	2026/07/14
RMI artificial antenna	/	/	/	GZ1988	2025/03/14	2026/03/13
Programmable Temperature & Humidity Chamber	ASTUOD	TT-5166	52689	GZ2209	2025/03/14	2026/03/13
Test software	R&S	EMC32	Version 11.30.00	---	-	-

ANNEX 3 - TEST PHOTOS

Refer to document Test setup.

--- END ---