

**ELEMENT WASHINGTON DC LLC**

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>**RF EXPOSURE EVALUATION
Maximum Permissible Exposure (MPE)****Applicant Name:**

Eridan Communications Inc.
400 W California Ave.
Sunnyvale, CA 94086
United States

Date of Testing:

8/4/2025 - 9/30/2025

Test Report Issue Date:

11/5/2025

Test Site/Location:

Element lab., Columbia, MD, USA

Test Report Serial No.:

1M2508040072-04.2BR8Z

FCC ID:**2BR8Z-ER2035A****APPLICANT:****Eridan Communications, Inc.****Application Type:**

Certification

Model:

ER2035

EUT Type:

Small Cell Radio Unit

FCC Classification:

Category A and B Citizens Broadband Radio Service Devices (CBSD)

FCC Rule Part:

FCC Part 1 (§1.1310) and Part 2 (§2.1091)

Test Procedure(s):

KDB 447498 D01 v06

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC KDB 447498 D01. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: 2BR8Z-ER2035A		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2508040072-04.2BR8Z	Test Dates: 8/4/2025 – 9/30/2025	EUT Type: Small Cell Radio Unit		Page 1 of 7

© 2025 ELEMENT

V 11.3 5/14/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Rev. No.	Report S/N	Description	Issue Date
-	1M2508040072-04.2BR8Z	Initial Release	11/5/2025

FCC ID: 2BR8Z-ER2035A	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2508040072-04.2BR8Z	Test Dates: 8/4/2025 – 9/30/2025	EUT Type: Small Cell Radio Unit	Page 2 of 7

TABLE OF CONTENTS

1.0 Introduction 4

1.1 Scope.....4

1.2 Element Test Location4

1.3 Test Facility / Accreditations4

2.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE) 5

2.1 Scope.....5

2.2 EUT Description.....5

2.3 Procedure6

3.0 CONCLUSION 7

FCC ID: 2BR8Z-ER2035A	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2508040072-04.2BR8Z	Test Dates: 8/4/2025 – 9/30/2025	EUT Type: Small Cell Radio Unit	Page 3 of 7

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4:2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered test laboratory with the site description on file with ISED (Wireless Test Lab number 2451B) and FCC (Designation Number US1113).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: 2BR8Z-ER2035A	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2508040072-04.2BR8Z	Test Dates: 8/4/2025 – 9/30/2025	EUT Type: Small Cell Radio Unit	Page 4 of 7

2.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

2.1 Scope

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 2-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 2-1. Limits for Maximum Permissible Exposure (MPE)

2.2 EUT Description

The **Eridan FCC ID: 2BR8Z-ER2035A** is a Citizens Broadband Radio Services (CBRS) small cell radio unit which transmits 5G NR on n48. The radio is a 2x2 MIMO system utilizing 2 cross polarized antennas. The EUT as a Category B CBSD with a maximum antenna gain of 19dBi.

Model Number	Antenna Type	Gain [dBi]	CBSD Category
KP-3DOMA-13	Omni +/- 45 pol	13	B
KP-3DP120S-45-V2	120 deg Sector, +/- 45 pol	15.5	B
HG3342DP-090-NF	90 deg Sector, +/- 45 pol	16.5	B
KPPA-3GHZDP90S-45-PMP	90 deg Sector, +/- 45 pol	16.7	B
KP-3DP65S-45	65 deg Sector, +/- 45 pol	18	B
KP-3DP33S-45	33 deg Sector, +/- 45 pol	19	B

Table 2-2. Approved Antennas

FCC ID: 2BR8Z-ER2035A	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2508040072-04.2BR8Z	Test Dates: 8/4/2025 – 9/30/2025	EUT Type: Small Cell Radio Unit	Page 5 of 7

2.3 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a spectrum analyzer and the powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at a distance of 20cm.

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

P_d = Power Density (mW/cm²)

π = 3.1416

P_{out} = output power to antenna (mW)

r = distance between observation point and center of the radiator (cm)

G = gain of antenna in linear scale

Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 2-1.

There is no co-location between the electric fields of any two transmitters therefore following power densities are calculated for each individual transmitter by frequency at 20cm spacing:

Frequency	3625	MHz
FCC Limit	1.000	mW/cm ²
EIRP Limit	47.00	dBm/10MHz
ISED Limit	7.089	W/m ²
Max Power	23.50	dBm
Duty Cycle	100.00	%
Power	223.87	mW
Max FCC Tx Ant Gain	19.00	dBi
Time-Averaged EIRP	42.50	dBm
Time-Averaged EIRP	17782.79	mW
Minimum Distance	37.62	cm

Table 2-3. Calculated MPE Data for CBRS Band – Category B

FCC ID: 2BR8Z-ER2035A	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2508040072-04.2BR8Z	Test Dates: 8/4/2025 – 9/30/2025	EUT Type: Small Cell Radio Unit	Page 6 of 7

3.0 CONCLUSION

The device meets the mobile RF exposure limit at a 37.62cm separation distance for category B operation as specified in §2.1091 of the FCC Rules and Regulations. An appropriate RF exposure compliance statement will be placed in the user's manual.

- END OF TEST REPORT -

FCC ID: 2BR8Z-ER2035A	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2508040072-04.2BR8Z	Test Dates: 8/4/2025 – 9/30/2025	EUT Type: Small Cell Radio Unit	Page 7 of 7