

TEST REPORT

Applicant: BASICS CO.,LTD

Address: 17, Tongil-ro 214beon-gil, Deogyang-gu, Goyang-si, Gyeonggi-do,
Republic of Korea

Product Name: Laptop computer

FCC ID: 2BRTE-BB1422SS-N

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: 2502V37588E-RF-00C

Report Date: 2025/12/18

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Pedro Yun

Reviewed By: Alice Tan

Approved By: Pedro Yun

Title: RF Engineer

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL ▲	5
1.4 EQUIPMENT MODIFICATIONS	5
2. SUMMARY OF TEST RESULTS	6
3. DESCRIPTION OF TEST CONFIGURATION	7
3.1 OPERATION FREQUENCY DETAIL	7
3.2 EUT OPERATION CONDITION	7
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	8
3.4 SUPPORT CABLE LIST AND DETAILS	8
3.5 BLOCK DIAGRAM OF TEST SETUP	9
3.6 TEST FACILITY	11
3.7 MEASUREMENT UNCERTAINTY	11
4. REQUIREMENTS AND TEST PROCEDURES	12
4.1 AC LINE CONDUCTED EMISSIONS	12
4.1.1 Applicable Standard	12
4.1.2 EUT Setup	13
4.1.3 EMI Test Receiver Setup	13
4.1.4 Test Procedure	14
4.1.5 Corrected Amplitude & Margin Calculation	14
4.1.6 Test Result	14
4.2 RADIATION SPURIOUS EMISSIONS	15
4.2.1 Applicable Standard	15
4.2.2 EUT Setup	15
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	17
4.2.4 Test Procedure	18
4.2.5 Corrected Result & Margin Calculation	18
4.2.6 Test Result	18
4.3 MINIMUM 6 DB EMISSION BANDWIDTH	19
4.3.1 Applicable Standard	19
4.3.2 EUT Setup	19
4.3.3 Test Procedure	19
4.3.4 Test Result	19
4.4 99% OCCUPIED BANDWIDTH	20
4.4.1 EUT Setup	20
4.4.2 Test Procedure	20
4.4.3 Test Result	20
4.5 MAXIMUM CONDUCTED OUTPUT POWER	21
4.5.1 Applicable Standard	21
4.5.2 EUT Setup	21
4.5.3 Test Procedure	21

4.5.4 Test Result	21
4.6 MAXIMUM POWER SPECTRAL DENSITY	22
4.6.1 Applicable Standard	22
4.6.2 EUT Setup	22
4.6.3 Test Procedure	22
4.6.4 Test Result	22
4.7 CONDUCTED SPURIOUS EMISSION	23
4.7.1 Applicable Standard	23
4.7.2 EUT Setup	23
4.7.3 Test Procedure	23
4.7.4 Test Result	23
4.8 DUTY CYCLE	24
4.8.1 EUT Setup	24
4.8.2 Test Procedure	24
4.8.3 Judgment	24
4.9 ANTENNA REQUIREMENT	25
4.9.1 Applicable Standard	25
4.9.2 Judgment	25
5. TEST DATA AND RESULTS	26
5.1 AC LINE CONDUCTED EMISSIONS	26
5.2 RADIATION SPURIOUS EMISSIONS	29
5.3 6dB EMISSION BANDWIDTH	52
5.4 99% OCCUPIED BANDWIDTH	55
5.5 MAXIMUM CONDUCTED OUTPUT POWER	58
5.6 POWER SPECTRAL DENSITY	59
5.7 CONDUCTED SPURIOUS EMISSION	62
5.8 DUTY CYCLE	68
EXHIBIT A - EUT PHOTOGRAPHS	70
EXHIBIT B - TEST SETUP PHOTOGRAPHS	71

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2502V37588E-RF-00C	Original Report	2025/12/18

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Laptop computer
EUT Model:	BB1422SS-N
Operation Frequency:	2412-2462MHz (802.11b/g/n ht20) 2422-2452MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	21.64dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n: OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 7.6V from Battery or DC 12V from Adapter
Serial Number:	For RF Conducted test: 37QT-2 For Radiated Spurious Emission and AC Line Conducted Emissions test: 37QT-1
EUT Received Date:	2025/7/30
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter	Shenzhen Jiuzhou Power Technology Co.,Ltd	J302-1203000UX	Input:100-240Vac~50/60Hz 1.5A Output:12.0Vdc 3.0A 36.0W

1.3 Antenna Information Detail▲

Antenna Type	input impedance (Ohm)	Frequency Range (MHz)	Antenna Gain (dBi)
FPC	50	2400~2490	2.2
The design of compliance with §15.203:			
☒ Unit uses a permanently attached antenna. ☐ Unit uses a unique coupling to the intentional radiator. ☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.			

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Conducted Spurious Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
Note 1: For AC line conducted emissions, the maximum peak output power mode and channel was tested. Note 2: For Radiated Spurious Emissions 9kHz~1GHz and 18~25GHz, the maximum peak output power mode and channel was tested.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:		MT7922 QA.exe		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲ :				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	40	40	40
802.11g	6Mbps	45	45	45
802.11n ht20	MCS0	45	45	45
802.11n ht40	MCS0	45	45	45
The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.				

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
PHILIPS	Keyboard	SPK6234	K234210510744
PHILIPS	Mouse	SPK7214	M214BQ210411115
DELL	Monitor	P2721Q	CN-0XJ46C-FCC00-135-AA8L-A03
SANDisk	USB Flash Disk	16G	BL201026115 B
IPRO	Earphone	Phonenix 5.0s	EMZBEP21103002B
SanDisk	TF Card	32 GB	Unknown
Epik	Phone	K500	SZ180322001SA

3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Keyboard Cable	NO	NO	1.5	EUT	Keyboard
Mouse Cable	NO	NO	1.5	EUT	Mouse
DC Cable	NO	NO	2	Adapter	EUT
Earphone Cable	NO	NO	1.2	EUT	Earphone
USB Cable	NO	NO	1	EUT	Phone
HDMI Cable	NO	NO	1.2	EUT	Monitor


3.5 Block Diagram of Test Setup

AC line conducted emissions:




Spurious Emissions:

Below 1G:



Above 1G:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz: 5.47 dB, 26.5GHz~40GHz: 5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground[protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor=attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions


4.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2.2 EUT Setup


9kHz~30MHz:




30MHz~1GHz:



1-18GHz:



18-25GHz:



The radiated emissions were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	120 kHz	500 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 25GHz:

Pre-scan:

Frequency Range	Measurement	RBW	Video B/W	Detector
Above 1 GHz	Peak	1MHz	3 MHz	PK
	AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

For Radiated 18-25GHz test, which was performed at 1.0 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.0m
Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.0m]})$ dB= 9.54 dB

4.2.5 Corrected Result& Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in μ V/m

E_{Log} is the field strength of the emission, in dB μ V/m

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10} (d_{\text{standard}}/d_{\text{measure}})$$

The basic equation except 18-25GHz test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For Radiated 18-25GHz test:

Factor = Antenna Factor + Cable Loss- Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.


4.3 Minimum 6 dB Emission Bandwidth

4.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

4.3.2 EUT Setup



4.3.3 Test Procedure

According to ANSI C63.10-2020 Section 11.8


- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

4.3.4 Test Result

Please refer to section 5.3.

4.4 99% Occupied Bandwidth

4.4.1 EUT Setup



4.4.2 Test Procedure

According to ANSI C63.10-2020 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.4.3 Test Result

Please refer to section 5.4.


4.5 Maximum Conducted Output Power

4.5.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.5.3 Test Procedure

According to ANSI C63.10-2020 Section 11.9.1.2

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- Set the EUT in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- Add a correction factor to the display.
- Set the power meter to test peak output power, record the result.

According to ANSI C63.10-2020 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.5.4 Test Result

Please refer to section 5.5.


4.6 Maximum Power Spectral Density

4.6.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

4.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.6.3 Test Procedure

According to ANSI C63.10-2020 Section 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span >1.5 times the DTS bandwidth.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

4.6.4 Test Result

Please refer to section 5.6.


4.7 Conducted Spurious Emission

4.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.7.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.7.3 Test Procedure

According to ANSI C63.10-2020 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

4.7.4 Test Result

Please refer to section 5.7.

4.8 Duty Cycle

4.8.1 EUT Setup



4.8.2 Test Procedure

According to ANSI C63.10-2020 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.8.3 Judgment

Report Only. Please refer to section 5.8.

4.9 Antenna Requirement

4.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. TEST DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	37QT-1	Test Date:	2025/8/14
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yukin Qiu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27.6	Relative Humidity: (%)	63	ATM Pressure: (kPa)	100.2
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2024/9/5	2025/9/4
Unknown	Coaxial Cable	RG 142	C-0200-05	2025/5/6	2026/5/5
R&S	EMI Test Receiver	ESCI	100224	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below plots.

Note: 802.11n20 Low channel was tested.

Project No.: 2502V37588E-RF
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV


Serial No.: 37QT-1
Tester: Yukin Qiu
Note: 2.4G



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	1.988	36.77	11.30	48.07	56.00	7.93	QP
2	1.988	19.55	11.30	30.85	46.00	15.15	Average
3	4.098	38.90	10.72	49.62	56.00	6.38	QP
4	4.098	24.99	10.72	35.71	46.00	10.29	Average
5	4.377	37.74	10.79	48.53	56.00	7.47	QP
6	4.377	20.80	10.79	31.59	46.00	14.41	Average
7	4.763	39.72	10.87	50.59	56.00	5.41	QP
8	4.763	25.47	10.87	36.34	46.00	9.66	Average
9	5.145	39.37	10.95	50.32	60.00	9.68	QP
10	5.145	24.39	10.95	35.34	50.00	14.66	Average
11	5.696	40.34	11.07	51.41	60.00	8.59	QP
12	5.696	24.78	11.07	35.85	50.00	14.15	Average
13	5.858	39.62	11.10	50.72	60.00	9.28	QP
14	5.858	24.79	11.10	35.89	50.00	14.11	Average

Project No.: 2502V37588E-RF
Port: neutral
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 37QT-1
Tester: Yukin Qiu
Note: 2.4G



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	3.112	33.65	10.99	44.64	56.00	11.36	QP
2	3.112	17.75	10.99	28.74	46.00	17.26	Average
3	3.638	33.81	10.87	44.68	56.00	11.32	QP
4	3.638	17.39	10.87	28.26	46.00	17.74	Average
5	3.899	32.35	10.82	43.17	56.00	12.83	QP
6	3.899	15.50	10.82	26.32	46.00	19.68	Average
7	4.695	34.81	10.83	45.64	56.00	10.36	QP
8	4.695	21.96	10.83	32.79	46.00	13.21	Average
9	5.213	35.45	10.86	46.31	60.00	13.69	QP
10	5.213	21.57	10.86	32.43	50.00	17.57	Average
11	5.736	36.82	10.89	47.71	60.00	12.29	QP
12	5.736	21.75	10.89	32.64	50.00	17.36	Average

5.2 Radiation Spurious Emissions

1)9kHz - 1GHz

Serial Number:	37QT-1	Test Date:	2025/8/23
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Ethan Wu	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	26.1	Relative Humidity: (%)	40	ATM Pressure: (kPa)	101.1

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Hybrid Antenna	JB3	A060611-2	2024/4/16	2027/4/15
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2025/7/1	2026/6/30
Sonoma	Amplifier	310N	372193	2025/7/30	2026/7/29
R&S	EMI Test Receiver	ESCI	100035	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.


Note: 802.11n20 Low channel was tested.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 2.4G WIFI
RBW:120kHz,VBW:500kHz


Serial No.: 37QT-1
Tester: Ethan Wu



Project No.: 2502V37588E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 2.4G WIFI
RBW:9kHz,VBW:30kHz

Serial No.: 37QT-1
Tester: Ethan Wu

Date: 2025-08-23




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.173	70.78	-13.50	57.28	102.86	45.58	Peak
2	0.223	64.77	-16.49	48.28	100.63	52.35	Peak
3	0.414	62.66	-23.11	39.55	95.26	55.71	Peak
4	6.175	64.47	-34.57	29.90	69.54	39.64	Peak
5	12.296	58.38	-33.92	24.46	69.54	45.08	Peak
6	26.984	66.39	-34.27	32.12	69.54	37.42	Peak

30MHz-1GHz

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 2.4G WIFI
RBW:120kHz,VBW:500kHz

Serial No.: 37QT-1
Tester: Ethan Wu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	67.18	51.11	-16.57	34.54	40.00	5.46	QP
2	138.32	42.13	-10.86	31.27	43.50	12.23	Peak
3	287.05	44.16	-9.46	34.70	46.00	11.30	Peak
4	308.07	47.20	-8.42	38.78	46.00	7.22	QP
5	461.65	37.90	-4.43	33.47	46.00	12.53	QP
6	961.20	34.75	6.30	41.05	54.00	12.95	Peak

Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 2.4G WIFI
RBW:120kHz,VBW:500kHz

Serial No.: 37QT-1
Tester: Ethan Wu

Date: 2025-08-23



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	42.93	47.01	-12.99	34.02	40.00	5.98	QP
2	67.18	52.72	-16.57	36.15	40.00	3.85	QP
3	89.82	55.08	-16.87	38.21	43.50	5.29	QP
4	536.02	42.45	-2.83	39.62	46.00	6.38	Peak
5	616.85	41.31	-1.17	40.14	46.00	5.86	QP
6	922.40	33.02	5.44	38.46	46.00	7.54	QP

2) 1-25GHz:

Serial Number:	37QT-1	Test Date:	2025/8/21
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Willem Qiu	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	25.2	Relative Humidity: (%)	54	ATM Pressure: (kPa)	101.1

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2024/11/17	2025/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2024/12/9	2025/12/8
AH	Preamplifier	PAM-0118P	469	2025/4/11	2026/4/10
AH	Preamplifier	PAM-1840VH	191	2024/9/5	2025/9/4
R&S	Spectrum Analyzer	FSV40	101944	2024/9/6	2025/9/5
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set& Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2024/8/27	2025/8/26

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below plots.
After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.




1-18GHz:




802.11b middle channel Horizontal






802.11b middle channel Vertical




802.11b high channel Horizontal






802.11b high channel Vertical




802.11g low channel Horizontal






802.11g low channel Vertical




802.11g middle channel Horizontal






802.11g middle channel Vertical




802.11g high channel Horizontal






802.11g high channel Vertical




802.11n20 low channel Horizontal






802.11n20 low channel Vertical




802.11n20 middle channel Horizontal






802.11n20 middle channel Vertical




802.11n20 high channel Horizontal






802.11n20 high channel Vertical



802.11n40 low channel Horizontal




802.11n40 low channel Vertical



802.11n40 middle channel Horizontal

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 37QT-1
Tester: Willem Qiu



802.11n40 middle channel Vertical


Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 37QT-1
Tester: Willem Qiu




Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 37QT-1
Tester: Willem Qiu




Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz




Serial No.: 37QT-1
Tester: Willem Qiu



802.11n40 high channel Horizontal



802.11n40 high channel Vertical



18-25GHz:

No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.

Project No.: 2502V37588E-RF

Polarization: Horizontal

Test Mode: Transmitting

Note: 2.4G WIFI


Peak: RBW:1MHz, VBW:3MHz

Serial No.: 37QT-1

Tester: Willem Qiu

Level (dBuV/m)

Date: 2025-08-21



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	19265.60	46.21	0.13	46.34	74.00	27.66	Peak

Project No.: 2502V37588E-RF

Polarization: Vertical

Test Mode: Transmitting

Note: 2.4G WIFI


Peak: RBW:1MHz, VBW:3MHz

Serial No.: 37QT-1

Tester: Willem Qiu

Level (dBuV/m)

Date: 2025-08-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	19867.60	46.24	0.20	46.44	74.00	27.56	Peak

Bandedge:

802.11b low channel Bandedge Horizontal

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2386.09	50.27	-0.47	49.80	74.00	24.20	Peak
2	2390.00	47.69	-0.47	47.22	74.00	26.78	Peak

802.11b low channel Bandedge Vertical

Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2360.01	48.78	-0.50	48.28	74.00	25.72	Peak
2	2390.00	46.10	-0.47	45.63	74.00	28.37	Peak

802.11b high channel Bandedge Horizontal

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	46.25	-0.30	45.95	74.00	28.05	Peak
2	2487.48	49.56	-0.30	49.26	74.00	24.74	Peak

802.11b high channel Bandedge Vertical

Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	46.67	-0.30	46.37	74.00	27.63	Peak
2	2517.86	49.05	-0.18	48.87	74.00	25.13	Peak

802.11g low channel Bandedge Horizontal

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2390.00	54.27	-0.47	53.80	74.00	20.20	Peak
2	2390.00	39.74	-0.47	39.27	54.00	14.73	Average

802.11g low channel Bandedge Vertical

Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2386.58	48.57	-0.48	48.09	74.00	25.91	Peak
2	2390.00	48.16	-0.47	47.69	74.00	26.31	Peak
3	2390.00	35.68	-0.47	35.21	54.00	18.79	Average

802.11g high channel Bandedge Horizontal

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	52.77	-0.30	52.47	74.00	21.53	Peak
2	2483.68	53.85	-0.30	53.55	74.00	20.45	Peak

802.11g high channel Bandedge Vertical

Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 370T-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	47.60	-0.30	47.30	74.00	26.70	Peak
2	2501.10	48.46	-0.27	48.19	74.00	25.81	Peak

802.11n20 low channel Bandedge Horizontal

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 37QT-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2390.00	58.70	-0.47	58.23	74.00	15.77	Peak
2	2390.00	41.04	-0.47	40.57	54.00	13.43	Average

802.11n20 low channel Bandedge Vertical

Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 37QT-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2390.00	49.41	-0.47	48.94	74.00	25.06	Peak
2	2390.00	36.70	-0.47	36.23	54.00	17.77	Average

802.11n20 high channel Bandedge Horizontal

Project No.: 2502V37588E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 37QT-1
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	54.88	-0.30	54.58	74.00	19.42	Peak
2	2483.50	40.80	-0.30	40.50	54.00	13.50	Average

802.11n20 high channel Bandedge Vertical

Project No.: 2502V37588E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz


Serial No.: 37QT-1
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	49.02	-0.30	48.72	74.00	25.28	Peak
2	2483.50	37.13	-0.30	36.83	54.00	17.17	Average
3	2484.78	51.25	-0.30	50.95	74.00	23.05	Peak

802.11n40 low channel Bandedge Horizontal


Project No.: 2502V37588E-RF Serial No.: 370T-1
Polarization: Horizontal Tester: Willem Qiu
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2388.89	58.66	-0.48	58.18	74.00	15.82	Peak
2	2388.89	42.57	-0.48	42.09	54.00	11.91	Average
3	2390.00	54.77	-0.47	54.30	74.00	19.70	Peak
4	2390.00	42.82	-0.47	42.35	54.00	11.65	Average

802.11n40 low channel Bandedge Vertical


Project No.: 2502V37588E-RF Serial No.: 370T-1
Polarization: Vertical Tester: Willem Qiu
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2388.77	53.92	-0.48	53.44	74.00	20.56	Peak
2	2388.77	37.03	-0.48	36.55	54.00	17.45	Average
3	2390.00	52.38	-0.47	51.91	74.00	22.09	Peak
4	2390.00	37.20	-0.47	36.73	54.00	17.27	Average

802.11n40 high channel Bandedge Horizontal


Project No.: 2502V37588E-RF Serial No.: 370T-1
Polarization: Horizontal Tester: Willem Qiu
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	56.83	-0.30	56.53	74.00	17.47	Peak
2	2483.50	44.89	-0.30	44.59	54.00	9.41	Average
3	2487.79	59.85	-0.30	59.55	74.00	14.45	Peak
4	2487.79	44.59	-0.30	44.29	54.00	9.71	Average

802.11n40 high channel Bandedge Vertical

Project No.: 2502V37588E-RF Serial No.: 370T-1
Polarization: Vertical Tester: Willem Qiu
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	50.10	-0.30	49.80	74.00	24.20	Peak
2	2483.50	38.86	-0.30	38.56	54.00	15.44	Average
3	2487.89	53.31	-0.30	53.01	74.00	20.99	Peak
4	2487.89	38.58	-0.30	38.28	54.00	15.72	Average

5.3 6dB Emission Bandwidth

Test Information:

Serial No.:	37QT-2	Test Date:	2025/12/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.1	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.4
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/06/13	2026/06/12
R&S	Spectrum Analyzer	FSV40	101947	2025/07/28	2026/07/27

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11b	2412	10.250	≥0.5	Pass
	2437	10.250	≥0.5	Pass
	2462	10.210	≥0.5	Pass
802.11g	2412	16.457	≥0.5	Pass
	2437	16.416	≥0.5	Pass
	2462	16.416	≥0.5	Pass
802.11n20	2412	17.458	≥0.5	Pass
	2437	17.458	≥0.5	Pass
	2462	17.458	≥0.5	Pass
802.11n40	2422	36.276	≥0.5	Pass
	2437	36.356	≥0.5	Pass
	2452	36.276	≥0.5	Pass

802.11b_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 14:55:19

802.11b_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:04:52

802.11b_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:07:48

802.11g_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:11:33

802.11g_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:15:20

802.11g_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:18:33

802.11n20_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:22:19

802.11n20_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:26:04

802.11n20_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:30:43

802.11n40_2422MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:34:08

802.11n40_2437MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:38:17

802.11n40_2452MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:42:04

5.4 99% Occupied Bandwidth

Test Information:

Serial No.:	37QT-2	Test Date:	2025/12/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	24.1	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.4
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/06/13	2026/06/12
R&S	Spectrum Analyzer	FSV40	101947	2025/07/28	2026/07/27

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11b	2412	15
	2437	15
	2462	15
802.11g	2412	16.560
	2437	16.520
	2462	16.520
802.11n20	2412	17.680
	2437	17.680
	2462	17.680
802.11n40	2422	36.400
	2437	36.400
	2452	36.400

802.11b_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 14:55:38

802.11b_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:05:10

802.11b_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:08:07

802.11g_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:11:52

802.11g_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:15:38

802.11g_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:18:51

802.11n20_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:22:39

802.11n20_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:26:22

802.11n20_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:31:00

802.11n40_2422MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:34:24

802.11n40_2437MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:38:31

802.11n40_2452MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:42:17

5.5 Maximum Conducted Output Power

Test Information:

Serial No.:	37QT-2	Test Date:	2025/12/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.1	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.4
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM504	2025/06/06	2026/06/05
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2025/06/11	2026/06/10

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Mode	Test Frequency (MHz)	Peak Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Verdict
802.11b	2412	18.89	16.38	30	Pass
	2437	18.55	16.06	30	Pass
	2462	18.22	15.71	30	Pass
802.11g	2412	21.48	14.50	30	Pass
	2437	21.16	14.11	30	Pass
	2462	20.72	13.75	30	Pass
802.11n20	2412	21.64	14.40	30	Pass
	2437	21.31	14.04	30	Pass
	2462	21.05	13.72	30	Pass
802.11n40	2422	21.58	14.47	30	Pass
	2437	21.43	14.31	30	Pass
	2452	21.12	14.11	30	Pass

5.6 Power Spectral Density

Test Information:

Serial No.:	37QT-2	Test Date:	2025/12/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.1	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.4
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/06/13	2026/06/12
R&S	Spectrum Analyzer	FSV40	101947	2025/07/28	2026/07/27

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Test Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	2412	1.59	8	Pass
	2437	1.30	8	Pass
	2462	0.95	8	Pass
802.11g	2412	1.79	8	Pass
	2437	1.44	8	Pass
	2462	1.13	8	Pass
802.11n20	2412	1.81	8	Pass
	2437	1.46	8	Pass
	2462	1.15	8	Pass
802.11n40	2422	1.64	8	Pass
	2437	1.44	8	Pass
	2452	1.25	8	Pass

802.11b_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 14:57:52

802.11b_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:06:52

802.11b_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:10:22

802.11g_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:14:27

802.11g_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:17:42

802.11g_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:21:17

802.11n20_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:25:19

802.11n20_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:28:28

802.11n20_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:33:31

802.11n40_2422MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:37:34

802.11n40_2437MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:41:13

802.11n40_2452MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:45:19

5.7 Conducted Spurious Emission

Test Information:

Serial No.:	37QT-2	Test Date:	2025/12/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.1	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.4
----------------------	------	------------------------------	----	------------------------	-------



Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2025/06/06	2026/06/05
R&S	Spectrum Analyzer	FSV40	101947	2025/07/28	2026/07/27


* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Note: The maximum path attenuation of 30MHz-25GHz was added into the offset.




802.11b_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 14:57:19

802.11b_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:05:51

802.11b_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:06:19

802.11b_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:08:53

802.11b_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:09:21

802.11b_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:09:48

802.11g_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:12:43

802.11g_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:13:11

802.11g_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:13:37

802.11g_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:16:23

802.11g_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:16:51

802.11g_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:19:34

802.11g_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:20:02

802.11g_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:20:27

802.11n20_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:23:32

802.11n20_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:24:02

802.11n20_2412MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:24:27

802.11n20_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:27:07

802.11n20_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:27:35

802.11n20_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:31:44

802.11n20_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:32:11

802.11n20_2462MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:32:37

802.11n40_2422MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:34:57

802.11n40_2422MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:35:26

802.11n40_2422MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:35:52

802.11n40_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:39:03

802.11n40_2437MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:39:31

802.11n40_2452MHz




ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:42:48

802.11n40_2452MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:43:15

802.11n40_2452MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 15:43:39

5.8 Duty Cycle

Test Information:

Serial No.:	37QT-2	Test Date:	2025/12/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	24.1	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.4
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Coaxial Attenuator	10dB	F-08-EM512	2025/06/13	2026/06/12
R&S	Spectrum Analyzer	FSV40	101947	2025/07/28	2026/07/27


* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	1/Ton (Hz)	VBW Setting (kHz)
802.11b	2437	100	100	100	NA	0.010
802.11g	2437	100	100	100	NA	0.010
802.11n20	2437	100	100	100	NA	0.010
802.11n40	2437	100	100	100	NA	0.010


Duty Cycle = $\text{Ton}/(\text{Ton}+\text{Toff}) \times 100\%$

802.11g 2437MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18 DEC 2025 14:44:21

802.11n40 2437MHz



ProjectNo.:2502V37588E-RF Tester:Jeff Wei
Date: 18.DEC.2025 14:45:13

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2502V37588E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2502V37588E-RF-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2502V37588E-RF-00A-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******